



# RF EXPOSURE REPORT

**REPORT NO.:** SA971218L07

**MODEL NO.:** WL-343v2 001 / RNX-EasyN1 / WUA-0613  
US70A / HNW300NU2 / EUB-9703

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Senao Networks Inc.

**ADDRESS:** 3F, No. 529, Chung Cheng Rd., Hsintien, Taipei,  
Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan,  
R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2412	24.490
High	2462	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	10.20	10.471
EIRP Power	13.20	20.892

**\*Note:** The antenna is Printed antenna with 3dBi gain

Threshold for no SAR evaluation is 24.490mW

Transmitter power is 20.892mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold