

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

Design Specification  
Radio Frequency Identification Board

Department: R&D Richmond

Document#: 301010xxxx

Authors:  
Kevin Deane-Freeman  
Yanchun Zhang  
Darren Rafferty

Current Revision: 4

Revision	Description	Author	Date
1	Initial Need/Want documentation	Kevin Deane-Freeman Yan chun Zhang, Darren Rafferty	27/02/07 10/05/07
2	Added RF Output plots, revised features table	Kevin Deane-Freeman	19/06/07
3	Simply some logic implementation	Yan chun Zhang, Darren Rafferty	09/07/07
4	Add Functional Description and Block Diagram	Kevin Deane-Freeman	14/07/09

Océ Display Graphics Systems

Richmond Office  
13231 Delf Place, #501  
Richmond, BC  
V6V 2C3  
Canada  
Phone: 604-232-2310 or  
604-232-2328

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

<b>1.1 Functional Description .....</b>	<b>4</b>
<b>1.2 Addressing.....</b>	<b>5</b>
<b>1.2.1     RFID Board PCI Shadow Memory Address Map .....</b>	<b>5</b>
<b>1.3 Hardware Capabilities .....</b>	<b>6</b>
<b>1.3.1     Planned Features.....</b>	<b>6</b>
<b>1.3.2     Standards Compliance.....</b>	<b>6</b>
<b>1.3.3     RF Output Characteristics .....</b>	<b>7</b>
<b>2.1 Hardware Control.....</b>	<b>8</b>
<b>2.1.1 I. CODE1 Label IC Memory Definition .....</b>	<b>9</b>
<b>2.1.2 Register Definition .....</b>	<b>9</b>
<b>2.1.3 Registers Initialization for Communication.....</b>	<b>10</b>
<b>2.1.4 Access the Reader Internal Registers .....</b>	<b>11</b>
<b>2.1.5 I.CODE1 Commands.....</b>	<b>11</b>
<b>2.1.6 Access Label IC memory.....</b>	<b>12</b>
<b>2.2. Appendix.....</b>	<b>15</b>

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY


<b>Figure 1.1 Block Diagram (Antenna 1 shown selected).....</b>	<b>4</b>
<b>Figure 1.2 RFID PCI Address Map.....</b>	<b>5</b>
<b>Figure 1.3 Features Table .....</b>	<b>6</b>
<b>Figure 1.4 TX1 Output, No Load .....</b>	<b>7</b>
<b>Figure 1.5 TX2 Output, No Load .....</b>	<b>8</b>
<b>Figure 2.1 I.CODE1 Label ICs EEPROM Memory .....</b>	<b>9</b>
<b>Figure 2.2 Reader Registers Initialization.....</b>	<b>11</b>

## 1.1 Functional Description

The design is based on the CL RC 632 Multi-Protocol reader IC from NXP. The reader is able to access up to 8 antennas using an Intersil DG411 SPST analog switch for each antenna. Antenna selection is enabled by a CPLD that, based on the state of the SPI Chip Select signal, either sets one of the eight switch control lines or passes the SPI communication through to the reader IC.

Each antenna has its own passive impedance matching circuit and EMI filter leading into the analog switch.

A block diagram is shown below.



## 1.2 Addressing

### 1.2.1 RFID Board PCI Shadow Memory Address Map

HEAD (15-11)	BID 8-6	MODULE SEL (BIT5-2)		REGISTER SEL (BIT1-0)		WR	RD	PCI OFFSET	ID
10101/ 10110	101	0000	PCI INTERFACE	00	BID WRITE	X		680	
				01	RESERVED			682	
				10	RESET / WATCHDOG	X		684	
				11	LINK ACK CNTRL	X	X	686	
#1	101	0001	RFID WRITE MEMORY ACCESS	00	BLOCK ADDR REG	X		688	
				01	IRQ MASK	X		68A	
				10	WR DATA(L)	X		68C	
				11	WR DATA(H)	X		68E	
	101	0010	RFID REGISTER CONTROL	00	CONTROL REG	X		690	
				01	READ ADDR REG	X		692	
				10	WRITE ADDR REG	X		694	
				11	WRITE DATA REG	X		696	
	101	0011	RFID DATA READ	00	REGISTER DATA		X	698	
				01	INTERNAL EEPROM		RFU*	69A	
				10	MEM DATA (L)		X	69C	
				11	MEM DATA (H)		X	69E	
	101	0100	RFID READ MEMORY ACCESS	00	READ MEM ADDR	X		6A0	
				01	BLOCK NUMBER	X		6A2	
				10	READ DATA REQ	X		6A4	
				11	SPI BUSY FLAG (RFU)		X	6A6	
	101	0101	RFID READ STATUS	00	MEM DATA READY	X	X	6A8	
				01	BMEM UPDATED	X	X	6AA	
				10	ANTENNA SELECT	X		6AC	
				11	MEM WRITE DONE	X	X	6AE	
	101	0110	RFU	00			X	6B0	
				01			X	6B2	
				10			X	6B4	
				11			X	6B6	
	101	0111	RFU	00			X	6B8	
				01			X	6BA	
				10			X	6BC	
				11			X	6BE	
	101	1000	RFU	00			X	6C0	
				01			X	6C2	
				10			X	6C4	
				11			X	6C6	
	101	1001	RFU	00			X	6C8	
				01			X	6CA	
				10			X	6CC	
				11			X	6CE	
	101	1010	RFU	00			X	6D0	
				01			X	6D2	
				10			X	6D4	
				11			X	6D6	
	101	1011	RFU	00				X	6D8
				01				X	6DA
				10				X	6DC
				11				X	6DE
	101	1100	RFU	00				X	6E0
				01				X	6E2
				10				X	6E4
				11				X	6E6
	101	1101	RFU	00				X	6E8
				01				X	6EA
				10				X	6EC
				11				X	6EE
	101	1110	RFU	00				X	6F0
				01				X	6F2
				10				X	6F4
				11				X	6F6
	101	1111	RFU	00				X	6F8
				01					6FA
				10				X	6FC
				11				X	6FE

Figure 1.2 RFID PCI Address Map

\*Reserved for future use

### 1.3 Hardware Capabilities

#### 1.3.1 Planned Features

Feature	Minimum Required	Desired/Future Performance
Reader Channels	5	6
Polling speed	1 channel per second	1 channel per < 200ms
Ch. Read Range	1.25"	2"
Ch. Write Range	As above	As above
Write/Verify	No	Yes
Antenna Spacing	78mm	78mm

Figure 1.3 Features Table

#### 1.3.2 Standards Compliance

The product is intended for a worldwide market. ODGS will test to FCC and EU standards for CE mark. Operational companies will test to local standards. Compliance with the following standards should meet the requirements of all markets:

Equipment Tested                   RFID2 Radio Module  
PMN:                                RFID Reader 2  
HVIN:                               3010120604  
Model Number:                    3010120604  
FCC ID:                           U2P-3010120604  
IC Certification Number:       6947A-3010120604  
Manufacturer:                    Océ Display Graphics Systems

Generic Industrial Immunity:  
EN61000-6-2: 2005

Emissions:

47 CFR Part 15 – Radio Frequency Devices, Subpart C – Intentional Radiator

15.209: Radiated emission limits; general requirements

15.225: Operation within the band 13.110-14.010 MHz

RSS-210 Issue 9 – License-exempt Radio Apparatus (All Frequency Bands): Category I Equipment

Annex A2.6: Band 13.110-14010 MHz

RSS-Gen Issue 4 – General Requirements and Information for the Certification of Radio Apparatus

ETSI EN300300-1: 2010

ETSI EN300330-2: 2010

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

Warnings for FCC:

FCC Part 15

This device complies with FCC Rules Part 15 operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Changes or modifications to this device, not expressly approved by XXXX, could void the user's authority to operate the equipment.

Warnings from RSS-Gen Issue 4 Section 8.4 and RSP-100 Issue 11 Section 4:

This device complies with Industry Canada's license-exempt RSSs. Operation is subject to the following two conditions:

- (1) This device may not cause interference; and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

### 1.3.3 RF Output Characteristics




Figure 1.4 TX1 Output, No Load

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY




Figure 1.5 TX2 Output, No Load

## 2.1 Hardware Control

CL RC 632 is a new family of highly integrated reader ICs for contactless communication at 13.56MHz, which includes 64 registers (8bits/each), 64 byte FIFO, as well as 32\*16 byte EEPROM. I.CODE1 Label IC is a dedicated 512 bit memory chip for electronic label applications such as detecting the presence of ink bag. RFID system operates in a so called “reader talks first” principle. The reader sends a command first, and the labels execute the instruction and send back their response to the buffer of the reader.

Based on current Calgary structure, a RFID PCB board is designed to communicate with the Data Relay Card using the fourth SPI generic port. It is eventually intended to replace the third party board Smart RFID Multiplex Reader Board. There is only one single reader with five antennas and one CPLD on the PCB board. Due to current specific SPI interface is designed for the RFID board, the fourth SPI port cannot be used as a generic SPI communication port any more. CPLD is used to select which antenna will be communicated with the Reader. Serial data clock is 4.16MHz. The bit decoding of Label IC is fast mode with a 13.56MHz carrier: each command consists of a start pulse (18.88us modulation), followed by one 8-bit instruction byte, five 8-bit parameter bytes, and two CRC bytes (16-bit CRC).

The basic rules for software accessing Label IC is that software is required to first select antenna, switch on the RF, enable CRC16, force the RFID reader state machine back to idle, clear the reader buffer, and finally to set block start address and block numbers which software needs read/write data from/to the Label IC. Once software gets data back from the Label IC, software may need to issue a switch off RF command so as to reduce the interference from RFID board, except when software needs to hold the Label IC in selected condition.

While the protocol allows for communication with multiple tags, collision detection and selection is not implemented. The reader will expect to communicate with the first tag that responds on each channel.

### 2.1.1 I. CODE1 Label IC Memory Definition

The 512 bit EEPROM memory is divided into 16 blocks. A block is the smallest access unit. Each block consists of 4 bytes. Bit 0 in each byte represents the LSB (least significant bit) and bit 7 the MSB (most significant bit). The following table shows the definition for each block.

	Byte0	Byte1	Byte2	Byte3	
Block 0	SNR0	SNR1	SNR2	SNR3	Serial Number
Block 1	SNR4	SNR5	SNR6	SNR7	Write Access Conditions
Block 2	F0	FF	FF	FF	Special Functions (EAS/QUIET)
Block 3	x	x	x	x	
Block 4	x	x	x	x	User Data
Block 5	x	x	x	x	.
Block 6	x	x	x	x	.
Block 7	x	x	x	x	.
Block 8	x	x	x	x	.
Block 9	x	x	x	x	.
Block 10	x	x	x	x	.
Block 11	x	x	x	x	.
Block 12	x	x	x	x	.
Block 13	x	x	x	x	.
Block 14	x	x	x	x	.
Block 15	x	x	x	x	User Data

**Figure 2.1 I.CODE1 Label ICs EEPROM Memory**

### 2.1.2 Register Definition

#### 1. Antenna Select Register

There is only one single reader with five antennas (five Label ICs) on the PCB RFID board; hence the defined antenna select register is used to select which antenna will be communicated with data relay card (only one bit for each command is allowed to be active). Allow 1ms for switch settling time.

Antenna Select Register						
Bit	7~5	4	3	2	1	0
	RFU	Antenna 5	Antenna 4	Antenna 3	Antenna 2	Antenna 1

#### 2. Reader Internal Registers

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

The RFID register control (Module Sel Addr:0010) used in this module include:

CONTROL REG (12 bits): Command Register

WRITE ADDR REG (6 bits): Write register address

READ ADDR REG (6 bits): Read register address

WRITE DATA REG (8 bits): Write data register

Control Register

Bit	11	10	9	8	7~5	4	3	2	1	0
	TX Start	Rst Quiet	Unsel Rd	EAS Test	RFU	Sel En	Reg Wr	Reg Rd	Mem Wr	Mem Sel Rd

Bit0 (Mem Sel Rd): Label IC Memory Selected Read  
 Bit1 (Mem Wr): Label IC Memory Write Block X  
 Bit2 (Reg Rd): Reader Register Read  
 Bit3 (Reg Wr): Reader Register Write  
 Bit4 (Mem Sel Rd): Label IC Anticollision/Select  
 Bit 5~7 (RFU): Reserved for future use  
 Bit8 (EAS Test): Label IC EAS test  
 Bit9 (Unsel Rd): Label IC unselected memory read  
 Bit10 (Rst Quiet): Label IC Reset QUIET Bit  
 Bit11 (TX Start): Transmit Start, default should be set to high. It is used for debugging, and once this bit is set to zero, the data in reader buffer cannot be transmitted.

### 2.1.3 Registers Initialization for Communication

In order to enable the I.CODE1 functionality, the following table lists the reader register initial values. Some of them may need change according to requirements with different RFID boards.

Register Name	Register Address	Value
Page	10	00
TxControl	11	58
CWConductance	12	3F
ModConductance	13	01
CoderControl	14	35
ModWidth	15	3F
ModWidthSOF	16	73
TypeBFrameing	17	00
Page	18	00
RxControl1	19	8B
DecoderControl	1A	00
BitPhase	1B	54
RxThreshold	1C	68
BPSKDemControl	1D	00
RXControl2	1E	41
ClockQControl	1F	00
Page	20	00
RxWait	21	08

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

ChannelRedundancy	22	0C
CRCPresetLSB	23	FE
CRCPresetMSB	24	FF
TimeSlotPeriod	25	00
MFOUTSelect	26	00
PreSet27	27	00
Page	28	00
FIFOLevel	29	3E
TimerClock	2A	0B
TimerControl	2B	02
TimerReload	2C	00
IRQPinConfig	2D	02
PreSet2E	2E	00
PreSet2F	2F	00

**Figure 2.2 Reader Registers Initialization**

#### **2.1.4 Access the Reader Internal Registers**

(1). When writing data to the reader internal register, the following three data packets should be sent:

First data packet: write 694 to register address

Second data packet: write 696 to register data

Third data packet: write 690 to 08 (write command)

(2). When reading data from Reader internal register, the following three data packets should be sent:

First data packet: write 692 to register address

Second data packet: write 690 to 04 (read command)

Third data packet: read register data from address 698

#### **2.1.5 I.CODE1 Commands**

A selection of the Label IC is necessary for valid execution of the following commands:

- Selected Read
- Write
- Halt (Reserved for future use)

Once an I.CODE1 Label IC is selected, it does not respond to the following command:

- Anticollision/Select
- Unselected Read

The following commands work for both the selected and unselected states:

- EAS
- Reset QUIET Bit

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

After the Label IC has been selected, if the unselected command should be issued, you need to re-enter Label IC or switch off the RF.

### 2.1.6 Access Label IC memory

Communication normally begins with the software sending a command and the Label IC responding. Commands always initiate a response except Reset Quiet Bit command. Some commands have prerequisite parameters such as memory read/write.

Current RFID firmware code supports the following commands:

- Reset QUIET Bit
- Unselected Read
- Anticollision/Select
- Write Block X
- Selected Read
- EAS Test

Manufacturer delivers the Label IC with the following configuration:

- (1) Serial number (block 0 and block 1) is unique, read only.
- (2) Write Access Conditions determine if blocks 3 through 15 can be accessed for writing.  
For Byte 0 in block 2:  
If set bit5 and bit4 to 1|1: Write access enabled.  
If set bit5 and bit4 to 0|0: Write access disabled.  
Be aware that writing of bit pairs 1|0 or 0|1 to block 2 is not allowed! Also the label must not be moved out of the communication field of the antenna during writing operation!
- (3) EAS test mode default setting is not defined. If you want to do an EAS test, you have to enable EAS test first by writing 1|1 to bit1 and bit0 in byte 0 of block 3.
- (4) Quiet mode default setting is not defined at delivery. Reset Quiet Bit command should be executed on the Label IC first, otherwise the Label IC does not respond to any command (except EAS command if the EAS mode is enabled) if the two bits (bit2 and bit3 in byte0 of block 3) are set to one (quiet mode is enabled).
- (5) Family Code/Application Identifier and User data memory is not defined.

In order to implement the above commands, an antenna select command should be issued first by software so that hardware knows which antenna should be communicated, and the data packages (See appendix) should be sent by sequence. Since the internal register setting of the reader is similar for each command, firmware FPGA will implement these setting packages (A, B, C, D, E, F, J/I) automatically when it receives a command as described below from software.

Also be aware that before you send a memory write command or an anticollision/select command, set Unselected Read command first, as the second byte of the serial number is used to calculate a quit value as a result of critical timing issue with SPI interface, this quit value is required when issuing an anticollision/select or memory write command.

#### (1) Reset QUIET Bit

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

**Action:** QUIET bits are cleared for all I.CODE1 Label ICs in the antenna field, which are in QUIT mode.

**Parameters:** None

**Commands:** N package

**Response:** None

**(2) Unselected Read**

Before issuing an **unselected** read command, software needs to set read block start address and the number of blocks first. The Label IC will respond with its required data bytes, which are stored to the buffer of the reader.

**Action:** Each of the unselected I.CODE1 Label ICs responds with the requested number of block

**Parameters:** Required block start address of data to be read  
Required number of blocks to be read

**Commands:** G, K package

**Response:** Data bits of X blocks, 16 bit CRC

There are 16\*32bit dual port block memory locations for latching the data read from the reader memory. After sending these packages, software needs to read the busy flag status from the PCI shadow memory address 6A8. Once this bit has been set to one, software needs to send a read data command (6A4) and immediately clear the busy flag. The read data command definition is as follows:

Reading IC buffer data command (6A4)

Bit	4	3-0
	Read Command	Block number

Once this command has been sent, the firmware will read 32 bits word data from internal block memory to PCI shadow memory responding to this command.

When PCI shadow memory address 6AA (BMEM UPDATED) has been set to one, software can get the 32bits data from PCI shadow memory address 69C, and also software is required to clear this bit (BMEM UPDATED) as well.

For whole memory data read requires at least 25ms.

**(3) Anticollision/Select**

When firmware receives the serial numbers after issuing an Anticollision/Select command, it will transmit a QUIT byte immediately. The Label IC will remain in the timeslot chosen at this command for all further commands, such as memory write and selected read, until it leaves (and re-enters) the RF field.

**Action:** Each of the unselected the Label IC responds with its 64 bits serial number in different timeslots

**Parameters:** None

**Commands:** M package

**Response:** 64 bit SNR (Serial Number), 16 bit CRC

#### (4) Write Block X

Remember that this command is required to a selection of the Label IC (Anticollision>Select). Before issuing a write command, software needs to set the block address and 4 bytes of data. Once each of the selected Label IC responds with its 64 bit serial number, firmware will send a quit value immediately so that the given 4 bytes of data are written to the address block if Label IC receives a QUIT from the reader in its timeslot.

**Action:** Given 4 bytes of data are written to the address block if Label IC receives a QUIT from the reader in its timeslot.

**Parameters:** Required block address of data to be written  
Required 4 bytes data to be written

**Commands:** H, O package

**Response:** 64 bit SNR (Serial Number), 16 bit CRC

In addition, a minimum delay time of 4852.16  $\mu$ s (included in 'total time\*') is required before the starting of a new command or switching off the RF due to EEPROM programming in Label IC. After software issuing a memory write command, firmware will send memory write done flag (6AE) to inform software, this flag means that firmware already finished sending a QUIT value to Label IC, therefore, the waiting time should be considered by software.

*Total time:  $18.88 + 2416.64 + n * (325.68 + 3020.8 + 269.04 + 311.52) + 4852.16 = 7287.68 + n * 3927.04 \mu$ s*  
*Here, n = number of timeslots*

#### (5) Selected Read

The operation is similar to the Unselected Read except this command is required to a selection of the Label IC (Anticollision>Select).

Each Label IC has his own antenna, and also the space between any two antennas is big enough to prevent from the interference among them, therefore this command is no necessary for current application.

**Action:** Each of the **selected** the Label IC responds with the given number of blocks in its timeslot at which the Label IC was fixed with the Anticollision/ Select command

**Parameters:** Required block start address of data to be read  
Required number of blocks to be read

**Commands:** G, P package

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

**Response:** Data bits of X blocks, 16 bit CRC

**(6) EAS Test**

Once again, EAS test mode default setting is not defined by manufacturer. Enable EAS test is required by writing 1|1 to bit1 and bit0 in byte 0 of block 3 before issuing EAS test.

**Action:** I.CODE1 Label IC responds with a special predefined EAS pattern (256bits)

**Parameters:** None

**Commands:** **Q** package

**Response:** 256 bit special EAS response

After Label IC receives this command, the corresponding 32 bytes in hexadecimal notation as follows:

2F B3 62 70 D5 A7 90 7F  
E8 B1 80 38 D2 81 49 76  
82 DA 9A 86 6F AF 8B B0  
F1 9C D1 12 A5 72 37 EF

## 2.2. Appendix

Antenna select should be issued first by software before the following package commands:

**A package: switching on RF**

Addr Data  
694 11 (16bits); Tx Control register address  
696 4B (16bits);  
690 08 (16bits); Write command

**B package: Enable 16bits CRC**

Addr Data  
694 22 (16bits);  
696 0C (16bits);  
690 08 (16bits);

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

**C package: Preset LSB for the CRC register**

Addr Data  
694 23 (16bits);  
696 FE (16bits);  
690 08 (16bits);

**D package: Preset MSB for the CRC register**

Addr Data  
694 24 (16bits);  
696 FF (16bits);  
690 08 (16bits);

**E package: Force Reader back to idle state**

Addr Data  
694 01 (16bits)  
696 00 (16bits)  
690 08 (16bits)

**F package: Clear buffer**

Addr Data  
694 09 (16bits)  
696 01 (16bits)  
690 08 (16bits)

**G package: Set memory read start address and block numbers**

Addr Data  
6A0 X (16bits); Set memory start block address (x-1=0...15)  
6A2 y (16bits); Set number of blocks (0...15)

**H package: Set memory write address and data**

Addr Data  
688 x (16bits); Set memory block address (0...15)  
68C x (32bits); Set writing data to Label IC

**I package: Set time slot period**

Addr Data  
694 25 (16bits);  
696 5F (16bits);  
690 08 (16bits);

**J package: clear time slot period**

Addr Data  
694 25 (16bits);  
696 00 (16bits);  
690 08 (16bits);

**K package: Sending unselected read command**

Addr Data  
690 A0016bits);

**L package: Switching off RF (preventing from interference)**

Addr Data  
694 11 (16bits);

ENGINEERING SPECIFICATION DOCUMENT  
Project: CALGARY

696 58 (16bits);  
690 08 (16bits);

***M package: Sending Anticollision>Select command***

Addr Data  
690 810(16bits);

***N package: Sending Reset Quiet Bit command (Respond, None)***

Addr Data  
690 C00 (16bits);

***O package: Sending write block x command***

Addr Data  
690 802 (16bits);

***P package: Sending selected read memory command (Responds memory data of numbers of blocks)***

Addr Data  
690 801 (16bits);

***Q package: Sending EAS test command (Corresponding 32 bytes data in hexadecimal)***

Addr Data  
690 900 (16bits);