



# FCC TEST REPORT

For

**Door Window Sensor**

**Model Number: ZW6305**

**FCC ID: U2ZZW6305**

**Report Number : WT188001793**

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection  
National Digital Electronic Product Testing Center

Site Location : No.4 TongFa Road, Xili Town, Nanshan District,  
Shenzhen, China

Tel : 0086-755-86009898

Fax : 0086-755-86009898-31396

Web : [www.smq.com.cn](http://www.smq.com.cn)



## Test report declaration

Applicant : SHEENWAY ASIA LTD.

Address : Room1313, 13/F., AustinTower, 22-26AustinAvenu, TsimSha Tsui, Kowloon. Hong Kong. China

Manufacturer : SHEENWAY ASIA LTD.

Address : Room1313, 13/F., AustinTower, 22-26AustinAvenu, TsimSha Tsui, Kowloon. Hong Kong. China

EUT Description : Door Window Sensor

Model No : ZW6305

FCC ID : U2ZZW6305

Test Standards:

**FCC Part 15 (October 1, 2017 Edition)**

**ANSI C63.10-2013**

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 15.249.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:  Date: Apr.28,2018  
(Chen Qichun)

Checked by:  Date: Apr.28,2018  
(Lin Yixiang)

Approved by:  Date: Apr.28,2018  
(Lin Bin)



## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION .....</b>	<b>2</b>
1. <b>TEST RESULTS SUMMARY .....</b>	<b>5</b>
2. <b>GENERAL INFORMATION .....</b>	<b>6</b>
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer .....	6
2.3. Measurement Uncertainty .....	7
3. <b>PRODUCT DESCRIPTION .....</b>	<b>8</b>
3.1. EUT Description.....	8
3.1. Block Diagram of EUT Configuration .....	8
3.2. Operating Condition of EUT.....	8
3.3. Operating Condition of EUT.....	9
3.4. Special Accessories.....	9
3.5. Equipment Modifications .....	9
3.6. Support Equipment List .....	9
3.7. Test Conditions .....	9
4. <b>TEST EQUIPMENT USED .....</b>	<b>10</b>
5. <b>CONDUCTED DISTURBANCE TEST .....</b>	<b>11</b>
5.1. Test Standard and Limit .....	11
5.2. Test Procedure .....	11
5.3. Test Arrangement.....	11
6. <b>RADIATED DISTURBANCE TEST .....</b>	<b>12</b>
6.1. Test Standard and Limit .....	12
6.2. Test Procedure .....	12
6.3. Test Arrangement.....	12
6.4. Test Data .....	13
7. <b>OCCUPIED BANDWIDTH .....</b>	<b>23</b>
7.1. Test Standard and Limit .....	23
7.2. Test Procedure .....	23
7.3. Test Arrangement.....	23



7.4. Test Data .....	23
<b>8. BAND EDGE .....</b>	<b>25</b>
8.1. Test Standard and Limit .....	25
8.2. Band Edge FCC 15.249(d) Limit.....	25
8.3. Test Procedure .....	25
8.4. Test Arrangement.....	25
8.5. Test Data .....	25
<b>9. ANTENNA REQUIREMENT .....</b>	<b>27</b>



## 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
Conducted Disturbance	15.207	Pass
Radiated disturbance	15.249	Pass
Occupied Bandwidth	15.215	Pass
Band Edges	15.249	Pass
Antenna Requirement	15.203	Pass

Remark: "N/A" means "Not applicable."



## 2. GENERAL INFORMATION

### 2.1. Report information

- 2.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 2.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 2.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

### 2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at No.4 TongFa Road, Xili Town, Nanshan District, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is 11177A-1.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is UA 50303686.



### 2.3. Measurement Uncertainty

#### Conducted Emission

9kHz~30MHz 3.5dB

#### Radiated Emission

30MHz~1000MHz 4.5dB

1GHz~18GHz 4.6dB




### 3. PRODUCT DESCRIPTION

#### 3.1. EUT Description

Description : Door Window Sensor  
Manufacturer : SHEENWAY ASIA LTD.  
Model Number : ZW6305  
Rated Input : DC 3V, CR2450 battery  
Power supply : DC 3V, CR2450 battery  
Operate Frequency : 908.4MHz, 916MHz  
Modulation : 908.4MHz: FSK, 916MHz: GFSK  
Antenna Designation : Integrated

#### 3.1. Block Diagram of EUT Configuration



Test Setup

#### 3.2. Operating Condition of EUT

- Mode 1: Transmitting at 908.4MHz
- Mode 2: Transmitting at 916MHz
- Mode 3: ON, Receiving



### 3.3. Operating Condition of EUT

Mode 1: Transmitting at 908.4MHz

Mode 2: Transmitting at 916MHz

Mode 3: ON, Receiving

### 3.4. Special Accessories

Not available for this EUT intended for grant.

### 3.5. Equipment Modifications

Not available for this EUT intended for grant.

### 3.6. Support Equipment List

Table 2 Support Equipment List

Name	Model No	S/N	Manufacturer
--	--	--	--

### 3.7. Test Conditions

Date of test: Apr.16, 2018 - Apr.20, 2018

Date of EUT Receive: Apr.04, 2018

Temperature: (21-23) °C

Relative Humidity: (47-55)%



#### 4. TEST EQUIPMENT USED

Table 3 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	Mar.20, 2018	1 Year
SB3955	Broadband antenna	SCHWARZBECK	VULB9163	Mar.05, 2018	1 Year
SB8501/01	Horn Antenna	Rohde & Schwarz	HF907	Mar.08, 2018	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Mar.05, 2018	1 Year



## 5. CONDUCTED DISTURBANCE TEST

### 5.1. Test Standard and Limit

#### 5.1.1. Test Standard

FCC Part 15 15.207

#### 5.1.2. Test Limit

Table 4 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

\*Decreasing linearly with logarithm of the frequency

\*The lower limit shall apply at the transition frequency.

### 5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). An EMI test receiver is used to test the emissions from both sides of AC line. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9 kHz.

### 5.3. Test Arrangement

The EUT is power supply by batteries, Therefore this test is not applicable.



## 6. RADIATED DISTURBANCE TEST

### 6.1. Test Standard and Limit

#### 6.1.1. Test Standard

FCC Part 15 15.249

#### 6.1.2. Test Limit

Table 5 Radiated Disturbance Test Limit

FREQUENCY MHz	FIELD STRENGTHS LIMITS ( $\mu$ V/m)	FIELD STRENGTHS LIMITS dB ( $\mu$ V/m)
Fundamental	50000	94.0
Harmonics	500	54.0
30 ~ 88	100	40.0
88 ~ 216	150	43.5
216 ~ 960	200	46.0
960 ~	500	54.0

\* The lower limit shall apply at the transition frequency.

\* The test distance is 3m.

### 6.2. Test Procedure

Radiated emission test below 1 GHz, test at SAC, the EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down to find out the maximum emission level. Radiated emission test above 1 GHz, test at FAR, the EUT is placed on a non-conductive table, which is 1.5 meter above ground. Broadband antenna is used as a receiving antenna at frequency range 30MHz to 1000MHz, Horn antenna is used as a receiving antenna at frequency range above 1GHz. Both horizontal and vertical polarization of the antenna is set on test, in order to find out the max emission, the relative positions of this EUT was rotated through three orthogonal axes.

The RBW of the EMI test receiver is:

30~1000MHz 120KHz  
1-18GHz 1MHz

### 6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture. The EUT shall be measured in the XYZ three positions, and the test data which was shown in the follow was the worst case.



## 6.4. Test Data

Table 6 Radiated Disturbance Test Data

Model No.: ZW6305								
Test mode: 1								
Frequency (MHz)	Polarization	Correction Factor (dB)	Antenna Factor (dB/m)	Reading Value (dB $\mu$ V)	Emission Level dB ( $\mu$ V/m)	Limits dB ( $\mu$ V/m)	EUT axes	Note
40.265	Horizontal	0.7	13.6	-3.0	11.3	40.0	X	QP
53.691	Horizontal	0.7	13.3	-2.3	11.7	40.0	X	QP
101.595	Horizontal	1.1	13.2	-1.4	12.9	43.5	X	QP
908.400	Horizontal	3.9	21.1	53.4	78.4	94	X	Fundamental QP
1825.547	Horizontal	-40.5	26.9	53.7	40.1	74	X	Harmonics PK
1825.547	Horizontal	-40.5	26.9	40.3	26.7	54	X	Harmonics AV
2725.274	Horizontal	-39.8	29.6	56.1	45.9	74	X	Harmonics PK
2725.274	Horizontal	-39.8	29.6	51.1	40.9	54	X	Harmonics AV
4541.983	Horizontal	-39.4	33.7	51.6	45.9	74	X	Harmonics PK
4541.983	Horizontal	-39.4	33.7	43.1	37.4	54	X	Harmonics AV
6358.759	Horizontal	-35.1	34.7	51.4	51.0	74	X	Harmonics PK
6358.759	Horizontal	-35.1	34.7	41.8	41.4	54	X	Harmonics AV
8175.529	Horizontal	-37.7	36.1	55.4	53.8	74	X	Harmonics PK
8175.529	Horizontal	-37.7	36.1	47.2	45.6	54	X	Harmonics AV
41.115	Vertical	0.7	13.6	-3.0	11.3	40.0	X	QP
54.784	Vertical	0.8	13.3	-2.5	11.6	40.0	X	QP
102.548	Vertical	1.1	13.2	-1.2	13.1	43.5	X	QP
908.400	Vertical	3.9	21.1	40.4	65.4	94	X	Fundamental QP
1316.223	Vertical	-40.8	24.3	59.7	43.2	74	X	PK
1316.223	Vertical	-40.8	24.3	40.0	23.5	54	X	AV
1826.009	Vertical	-40.5	26.9	57.4	43.8	74	X	Harmonics PK
1826.009	Vertical	-40.5	26.9	43.5	29.9	54	X	Harmonics AV
2725.149	Vertical	-39.8	29.6	52.8	42.6	74	X	Harmonics PK
2725.149	Vertical	-39.8	29.6	42.9	32.7	54	X	Harmonics AV
8175.639	Vertical	-37.7	36.1	44.8	43.2	74	X	Harmonics PK
8175.639	Vertical	-37.7	36.1	25.1	23.5	54	X	Harmonics AV



Table 7 Radiated Disturbance Test Data

Model No.: ZW6305								
Test mode: 2								
Frequency (MHz)	Polarization	Correction Factor (dB)	Antenna Factor (dB/m)	Reading Value (dB $\mu$ V)	Emission Level dB ( $\mu$ V/m)	Limits dB ( $\mu$ V/m)	EUT axes	Note
36.824	Horizontal	0.6	12.3	-2.0	10.9	40.0	X	QP
57.782	Horizontal	0.8	13.0	-2.4	11.4	40.0	X	QP
101.059	Horizontal	1.1	13.2	-1.6	12.7	43.5	X	QP
916.000	Horizontal	3.9	21.1	45.2	70.2	94	X	Fundamental QP
1239.948	Horizontal	-41.0	24.3	68.5	51.8	74	X	PK
1239.948	Horizontal	-41.0	24.3	54.9	38.2	54	X	AV
2748.068	Horizontal	-39.8	29.6	54.8	44.6	74	X	Harmonics PK
2748.068	Horizontal	-39.8	29.6	48.3	38.1	54	X	Harmonics AV
4579.948	Horizontal	-39.2	33.7	51.8	46.3	74	X	Harmonics PK
4579.948	Horizontal	-39.2	33.7	43.8	38.3	54	X	Harmonics AV
6411.822	Horizontal	-34.5	34.8	50.5	50.8	74	X	Harmonics PK
6411.822	Horizontal	-34.5	34.8	39.9	40.2	54	X	Harmonics AV
8243.740	Horizontal	-37.6	36.5	54.2	53.1	74	X	Harmonics PK
8243.740	Horizontal	-37.6	36.5	44.9	43.8	54	X	Harmonics AV
38.223	Vertical	0.7	12.3	-2.5	10.5	40.0	X	QP
55.015	Vertical	0.8	13.0	-2.5	11.3	40.0	X	QP
103.716	Vertical	1.2	13.2	-1.7	12.7	40.0	X	QP
916.000	Vertical	3.9	21.1	32.7	57.7	94	X	Fundamental QP
1825.623	Vertical	-40.5	26.9	54.6	41.0	74	X	Harmonics PK
1825.623	Vertical	-40.5	26.9	40.5	26.9	54	X	Harmonics AV
2748.180	Vertical	-39.8	29.6	52.5	42.3	74	X	Harmonics PK
2748.180	Vertical	-39.8	29.6	41.2	31.0	54	X	Harmonics AV
8243.869	Vertical	-37.6	36.5	54.3	53.2	74	X	Harmonics PK
8243.869	Vertical	-37.6	36.5	45.8	44.7	54	X	Harmonics AV



Table 8 Radiated Disturbance Test Data

Model No.: ZW6305								
Test mode: 3								
Frequency (MHz)	Polarization	Correction Factor (dB)	Antenna Factor (dB/m)	Reading Value (dB $\mu$ V)	Emission Level dB ( $\mu$ V/m)	Limits dB ( $\mu$ V/m)	EUT axes	Note
39.290	Horizontal	0.6	12.3	-2.0	10.9	40.0	X	QP
60.072	Horizontal	1.0	12.7	-2.2	11.5	40.0	X	QP
93.100	Horizontal	1.1	11.9	-1.3	11.7	43.5	X	QP
101.226	Horizontal	1.1	13.2	-1.5	12.8	43.5	X	QP
1821.105	Horizontal	-40.5	26.9	50.1	36.5	74	X	PK
1821.105	Horizontal	-40.5	26.9	36.6	23.0	54	X	AV
3164.100	Horizontal	-39.1	30.4	49.5	40.8	74	X	PK
3164.100	Horizontal	-39.1	30.4	36.2	27.5	54	X	AV
35.975	Vertical	0.6	12.3	-2.3	10.6	40.0	X	QP
51.214	Vertical	0.8	13.3	-2.4	11.7	40.0	X	QP
63.410	Vertical	0.9	12.7	-3.0	10.6	40.0	X	QP
101.937	Vertical	1.1	13.2	-1.1	13.2	43.5	X	QP
1825.641	Vertical	-40.5	26.9	59.4	45.8	74	X	PK
1825.641	Vertical	-40.5	26.9	48.1	34.5	54	X	AV
4923.600	Vertical	-39.6	34.0	50.8	45.2	74	X	PK
4923.600	Vertical	-39.6	34.0	36.6	31.0	54	X	AV
9598.611	Vertical	-36.6	37.2	49.5	50.1	74	X	PK
9598.611	Vertical	-36.6	37.2	35.6	36.2	54	X	AV

Note: 1. Emission level(dBuV/m)=Reading Value(dBuV) + Correction Factor(dB)+Antenna Factor (dB/m)

2. Correction Factor(dB) = Cable Factor (dB)+Amplifier Factor(dB)

3. No other spurious and harmonic emissions were reported greater than listed emissions above table.




Table 9 Restricted Band Radiated Emission Data


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	
6.31175 - 6.31225	123 - 138	2200 - 2300	
8.291 - 8.294	149.9 - 150.05	2310 - 2390	
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	
12.29 - 12.293	167.72 - 173.2	3332 - 3339	
12.51975	- 240 - 285	3345.8 - 3358	
12.52025	322 - 335.4	3600 - 4400	
12.57675	-		
12.57725			
13.36 - 13.41			

All the emission levels of the above band were less than the limit 20dB.

### Test mode 1, below 1GHz, Vertical




### Test mode 1, below 1GHz, Horizontal




Test mode 1, above 1GHz, Vertical

FCC Electric Field Strength 1-18GHz operate on 900MHz




Test mode 1, above 1GHz, Horizontal


FCC Electric Field Strength 1-18GHz operate on 900MHz



### Test mode 2, below 1GHz, Vertical




### Test mode 2, below 1GHz, Horizontal




Test mode 2, above 1GHz, Vertical

FCC Electric Field Strength 1-18GHz operate on 900MHz




Test mode 2, above 1GHz, Horizontal


FCC Electric Field Strength 1-18GHz operate on 900MHz



### Test mode 3, below 1GHz, Vertical




### Test mode 3, below 1GHz, Horizontal




Test mode 3, above 1GHz, Vertical

FCC Electric Field Strength 1-18 GHz



Test mode 3, above 1GHz, Horizontal

FCC Electric Field Strength 1-18 GHz



## 7. OCCUPIED BANDWIDTH

### 7.1. Test Standard and Limit

#### 7.1.1. Test Standard

FCC Part 15 15.215

### 7.2. Test Procedure


1. Set EUT as normal operation
2. Set EMI test receiver Center Frequency = fundamental frequency, RBW=1% to 5% of the OBW, VBW=3 times of RBW, Span=Wide enough to capture the complete power envelope.
3. Set EMI test receiver Max hold. Mark peak, -20dB.

### 7.3. Test Arrangement


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 7.4. Test Data

Transmitting at 908.4MHz: 20dB bandwidth =97.4 kHz



Transmitting at 916MHz: 20dB bandwidth =146.1 kHz





## 8. BAND EDGE

### 8.1. Test Standard and Limit

#### 8.1.1. Test Standard

FCC Part 15 15.249

### 8.2. Band Edge FCC 15.249(d) Limit

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation

### 8.3. Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instruments. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Measure the highest amplitude appearing on spectral display and set it as reference level. Plot the graph with marking the highest point and edge frequency.
4. Repeat above procedures until all measured frequencies were complete.


### 8.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.


### 8.5. Test Data

All the emission outside 902 to 928 is lower than 46 dB ( $\mu$  V/m). The detailed information refers to test picture.

## Transmitting at 908.4MHz



## Transmitting at 916MHz





## 9. ANTENNA REQUIREMENT

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The EUT has a built in antenna which is integrated inside the enclosure, this is permanently attached antenna and meets the requirements of this section.