

RG-06-91271-2A - AA / CHB

EVALUATION OF HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

According to standard:

EN 50364:2001

Equipment under test:

ON BOARD banknote card reloader BBR415

Company:

ACS-INC

Diffusion: Mrs DEJOUX (Company: ACS-INC)

Number of pages: 8 including 1 annex

Ed.	Date	Modified page(s)	Written by Name Visa	Technical verification Name Visa	Quality approval Name Visa
0	29-Jan-07	Creation	Augustin ALVAREZ	Régis GONZALEZ	Olivier HEYER

Duplication of this report is only permitted for an integral photographic facsimile. It includes the number of pages referenced above. This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole production of the item tested.

Document électronique : Seule la version papier fait foi



RG-06-91271-2A Ed.0 PAGE : 2

NAME OF THE EQUIPMENT UNDER TEST (E.U.T): ON BOARD banknote card reloader BBR415

Serial number: Proto 1

Part number: None

Software Version: None

MANUFACTURER'S NAME: ACS-INC

APPLICANT'S ADRESS:

Company: ACS-INC

Adress: Rue Claude Chappe

BP 345

07500 GUILHERAND-GRANGES

FRANCE

Person present during the tests: Mr VILLERET

Responsible: Mrs DEJOUX

DATES OF TESTS: From 11th to 15th of December, 2006

TESTS LOCATION: Emitech Grand Sud Laboratory in Vendargues (34)

TESTS OPERATOR: Augustin ALVAREZ

PAGE: 3

CONTENTS

1.	INTRODUCTION	4
2.	REFERENCE DOCUMENTS	4
3.	EQUIPMENT UNDER TEST CONFIGURATION AND DESCRIPTION	4
4.	SUMMARY OF TEST RESULTS	4
5.	AVERAGED SPATIAL MEASUREMENT	5
6.	LIMB AND CONTACT CURRENTS MEASUREMENTS	6
ΑN	INEX: EMF BOARD	7

RG-06-91271-2A Ed.0 PAGE : 4

1. INTRODUCTION

This report presents the results of the measurements performed on BBR 415 in order to verify the compliance of this product with the European standard EN 50364 (01) which requirements are derived from the European recommendation 99/519/EC

2. REFERENCE DOCUMENTS

EN 50364:2001 Limitation of human exposure to electromagnetic fields from devices operating in

the frequency range 0 Hz to 10 GHz, used in Electronic Article Surveillance (EAS),

Radio Frequency Identification (RFID) and similar applications.

EN 50357:2001 Evaluation of human exposure to electromagnetic fields from devices used in

Electronic Article Surveillance (EAS), Radio Frequency Identification (RFID) and

similar applications.

Recommendation Limitation of exposure of the general public to electromagnetic fields 99/519/EC of

12 july 1999

3. EQUIPMENT UNDER TEST CONFIGURATION AND DESCRIPTION

Equipment under test description (E.U.T): BBR 415

Cycle and operating mode during emission tests: Modulated permanent emission

4. SUMMARY OF TEST RESULTS

Results satisfying?	Comments
YES	
YES	
	satisfying? YES

N.P.: Not Performed. N.A.: Not Applicable.

• <u>In emission</u>: Sample subject to the test complies with prescriptions of the standard EN 50364:2001 according to limits specified in this test report.

PAGE: 5

5. AVERAGED SPATIAL MEASUREMENT

The Derived Reference Levels are based on spatially averaged values over the entire body of the exposed individual. The measurement was performed to verify the compliance of the EUT with the derived reference levels in the frequencies of interest.

The fundamental frequency of emission of EUT is 13.56MHz. The compliance with radio standard EN 300 330 imposes that harmonics are low and spurious much lower, in consequence all the records are performed at fundamental frequency.

Moreover the type of tested equipment emits a near field inductive field and electric component of the electromagnetic field is lower than in plane wave.

So only H field is taken into account in the measurements and the SAR* calculated with this value will be an overvaluation of the actual SAR* (see § 4.2.2 of the EN 50357).

The limit defined for H field is 73 mA/m at 13.56 MHz.

(*) Specific absorption rate

Test configuration according to table 1 of the standard: 2h

Test apparatus list:

CATEGORY	BRAND	MODEL NUMBER	N° EMITECH
Spectrum Analyzer	Hewlett Packard	HP 8590L	2001
Antenna	Loop	Loop 7.5 CM	2464

Climatic Conditions:

Date	Temperature (°C)	Humidity (%HR)	Pressure (hPa)
12/12/06	20	30	1019

E.U.T mode: Permanent modulated emission

Results: See Board in annexe: H= 0.77 mA/m

<u>Test Conclusion</u>: Sample subject to the test complies with prescriptions of the standard according to limits specified in this test report.

RG-06-91271-2A Ed.0 PAGE : 6

6. LIMB AND CONTACT CURRENTS MEASUREMENTS

Body current measurements under consideration are those defined by ICNIRP with frequencies up to 110 MHz.

Two types of current are mentioned:

- -limb current
- -contact current.

Both limb and contact current arise from a person touching a metallic object isolated from the ground and charged by electromagnetic field or a charged person isolated from the ground and touching a grounded metallic object.

The limb current is set to prevent excessive SAR* in the wrists, elbows, ankle and knees. The limit is 45 mA for the relevant frequency.

The contact current is set to prevent the risk of shock, or burn from light contact of the fingers with the external object. The limit of contact current is 20 mA for the relevant frequency.

The limb and contact current assume different contact impedance.

(*) Specific absorption rate

Test apparatus list:

CATEGORY	BRAND	MODEL NUMBER	N° EMITECH	
Measurement clamp	FCC	F-80	2535	
Spectrum Analyzer	Hewlett Packard	HP 8590L	2001	

Climatic Conditions:

Date	Temperature (°C)	Humidity (%HR)	Pressure (hPa)
12/12/06	20	30	1019

E.U.T mode: Permanent modulated emission

Results: See Board in annexe: H (max) = 0.46 mA

<u>Test Conclusion</u>: Sample subject to the test complies with prescriptions of the standard according to limits specified in this test report.

☐☐☐ End of report – 1 annex to be forwarded ☐☐☐

ANNEX: EMF BOARD



custome	r : ACS-INC configuration : 2	2h		: BBR 415	4		OG-06-91271 X:0,2m 0,15 m		T Hr	12/12/06 20 30
	EUT height		100cm						Pa operator: A	1019 A/CB/EV
point 1 2 3 4 5 6 7 8		48.8 54.9 52.7 41.7 44.0 43.0 36.4 36.3 36.3	85cm	field (mA/m)	0.7 1.5 1.2 0.3 0.4 0.4 0.2 0.2		8	5	2 1	EUT
	neasure height		100cm	annana ana ara-			9	6	3	
point 1 2 3 4 5 6 7 8 9		51.6 60.0 58.9 42.6 46.2 45.2 35.6 37.3 36.6		field (mA/m)	1.0 2.7 2.4 0.4 0.5 0.5 0.2 0.2		7	5	1	
	neasure height	00.0	115cm		0.2		9	6	3	
point 1 2 3 4 5 6 7 8 9	measure (dBuV)	47.0 55.5 53.9 40.0 42.6 42.5 33.0 34.4 34.6		field (mA/m)	0.6 1.6 1.3 0.3 0.4 0.4 0.1 0.1		8 7	5	2	
r	neasure height		130cm				9	6	3	
point 1 2 3 4 5 6 7 8 9	measure (dBuV)	44.1 50.8 48.1 37.5 41.0 41.0 31.3 33.9 34.0		field (mA/m)	0.4 0.9 0.7 0.2 0.3 0.3 0.1 0.1		7	5 4	1	
	neasure height		145cm	5-1-1 (A ()			9	6	3	
point 1 2 3 4 5 6 7 8 9	measure (dBuV)	39.0 42.9 41.9 34.7 37.5 36.4 29.3 31.0 31.6		field (mA/m)	0.2 0.4 0.3 0.1 0.2 0.2 0.1 0.1		7	5	1	
	averaged measu					mA/m	limits 73 mA/m			
1 2	on harm		measure 67.2 56.9	e (dBµV)			current (m 0.4	A) 6 mA 4 mA	limits (mA) 45 45	
measure in front o	at 1cm f antenna		measure 102.8	e (dBµV)		in front of	field at 1cm antenna (for		369.9 m/	A/m 1/1