

# **Technical Note**

Subject: Ampy 5252 Meter RF Exposure Levels

Date: 01 May 2008 Document ref: 6RT189 01

# 1 Summary

This document outlines RF radiation exposure level calculations for the AMPY 5252 Meter. Levels are specified as a power density.

Limits are those defined in FCC § 1.1310 Radio frequency radiation exposure limits.

In summary, the RF radiation exposure levels at a distance of 20 cm are below the specified FCC limits.

# 2 FCC § 1.1310 Limits

### 2.1 Limits for General Population/Uncontrolled Exposure

This is appropriate for the meter since it is typically deployed on the side of residential property.

Limit:

$$PD_{\text{lim}} = \frac{f}{1500}$$
 mW/cm<sup>2</sup>, where f is the frequency in MHz.

At 902 MHz, the limit is 0.601 mW/cm<sup>2</sup>.

# 3 RF Radiated Exposure Calculations

### 3.1 Power Density Expression

The power density, PD, at a range R from the transmitter with an effective isotropic radiated power EIRP, is given by:

$$PD = \frac{EIRP}{4\pi R^2}.$$

To calculate the closest range at which the power density reaches the FCC limits, the following expression is used.

$$R = \sqrt{\frac{EIRP}{4\pi PD_{\lim}}} \ .$$

### 3.2 5252 Meter

#### 3.2.1 Power Density at 20 cm

A worst case EIRP of 400 mW is assumed for the outstation. At 20 cm, the power density is  $0.080 \text{ mW/cm}^2$ , which is below the FCC limit of  $0.601 \text{ mW/cm}^2$ . This is based on a duty cycle of 100%.

6RT189 01 01 May 2008 Page 1 of 2

### COMMERCIAL IN CONFIDENCE



However, during normal operation, the transmit duty cycle will typically be less than 1% when averaged over a 30 minute period which will mean that in practice the averaged power density will be much lower than the above calculated value.