




CURTIS-STRAUS

Test Report

Report No	EH0043-3
Client	Ohio Willow Wood 15441 Scioto Darby Rd. Mt. Sterling, OH 43143
Phone	800-553-3445
FRN	0016158792
Model	OWWCO Transceiver Module PN.6221020 V1.1X
FCC ID	U3V6221020
Equipment Type	Low Power Communications Device Transceiver
Equipment Code	DXT
Results	As detailed within this report
Prepared by	 Evan Gould – Compliance Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	12/11/07
Conditions of issue	This Test Report is issued subject to the conditions stated in 'terms and conditions' section of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

Curtis-Straus LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Table Of Contents

<i>Summary</i>	3
<i>Statement of Conformity</i>	3
<i>Test Methodology</i>	3
<i>EUT Configuration</i>	4
<i>Test Equipment Used</i>	4
<i>Conducted Emissions Measurements</i>	5
<i>Measurement Uncertainty</i>	6
<i>Conditions Of Testing</i>	7
<i>A2LA Accreditation</i>	9

Summary

This test report supports a Class II Permissive Change of a transmitter operating with a Limited Modular Approval pursuant to 47 CFR 15.249. The original approval of the Ohio Willow Wood Radio Module (Model 6221020 V1.1X) contained the following statement:

“According to the applicant the device [EUT] will always be powered by a device deriving power from a battery, therefore AC line conducted testing is not required.”

This implies that the module's status of approval is conditional upon limiting its installation to battery powered devices. That condition of implementation must be removed from the Limited Modular Approval.

AC Line Conducted Emissions testing was performed on the Ohio Willow Wood Four Hole Vacuum Pump, which contains FCC ID U3V6221020.

Statement of Conformity

The Ohio Willow Wood Radio Module (Model 6221020 V1.1X) has been found to comply with the line conducted emissions limits specified in 47 CFR 15.207.

Test Methodology

Conducted emission testing was performed according to the procedures in ANSI C63.4 (2003). The testing was performed using a 50 μ H/50 Ω Line Impedance Stabilization Network. The device's performance was investigated in the range 0.15 – 30 MHz.

EUT Configuration

EUT Configuration

Work Order: H0043

Company: Ohio Willow Wood Co

Company Address: 15441 Scioto Darby Rd.
Mt. Sterling, OH 43143

Contact: Mike Haynes

Person Present: Mike Haynes

MN

SN

EUT: 6221020 V1.1X

1

EUT Description: OWWCO Radio Module

EUT Max Frequency: 2.40-2.48GHz

Support Equipment:

MN

SN

Four Hole Vacuum Pump LLV-01040 732952260

Charge Indicator LLV-01010 PN-1988-B

GlobTek Inc Medical p/s GTM41060-1505 WR9QA2600A00-N-MED

EUT Cables:

Qty

Shielded?

Length

Ferrites

Indicator to Vacuum 1 No 1.5ft None

Adaptor to Indicator 1 No 26ft 1 Molded

Unpopulated EUT Ports:

Qty

Reason

None

Software / Operating Mode Description:

2.4GHz Direct Sequence Hopping Low Power Radio Transceiver.

Test Equipment Used

REV. 26-NOV-2007

REV. 20-NOV-2007							
SPECTRUM ANALYZERS / RECEIVERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
YELLOW	9kHz-2.9GHz	8594E	Agilent	3523A01958	00100	I	08-JUN-2008
LISNs/MEASUREMENT PROBES	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
YELLOW-BLACK	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	0411657	00248	I	24-MAY-2008
CONDUCTED TEST SITES (MAINS / TELCO)	FCC CODE	IC CODE	VCCI CODE		CAT	CALIBRATION DUE	
EMI 1	93448	N/A	C-1801, T-268		III	NA	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Conducted Emissions Measurements**LIMIT**

Frequency of emission (MHz)	Quasi-peak limit (dB μ V)	Average limit (dB μ V)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*decreases with the logarithm of frequency.

Note: If peak measurements meet the Average limit, then Average measurements are not required.

MEASUREMENTS

AC Mains Conducted Emissions										Curtis-Straus LLC									
Date: 29-Nov-07		Company: Ohio Willow Wood				Work Order: H0043													
Engineer: Evan Gould		EUT Desc: OWWCO Radio Module				Test Site: EMI 1													
Notes: Module is in TX Mode, installed in the Four Hole Vacuum Pump, model LLV-01040, s/n: 732952260																			
Measurement Device: Yellow-Black LISN		EUT Operating Voltage/Frequency:																	
Range: 0.15-30MHz		Spectrum Analyzer: Yellow																	
Frequency (MHz)	Q.P. Readings		Ave. Readings		Impedance Factor (dB)	---		FCC/CISPR B		FCC/CISPR B		Overall Result (Pass/Fail)							
	QP1 (dB μ V)	QP2 (dB μ V)	AV1 (dB μ V)	AV2 (dB μ V)		Limit (dB μ V)	Margin dB	qp Limit (dB μ V)	qp Margin dB	AVE Limit (dB μ V)	AVE Margin dB								
0.15	29.8	31.3	29.8	31.3	20.6	---	---	66.0	-14.1	56.0	-4.1	Pass							
4.33	5.1	4.0	5.1	4.0	20.1	---	---	56.0	-30.8	46.0	-20.8	Pass							
9.48	6.0	2.4	6.0	2.4	20.1	---	---	60.0	-33.9	50.0	-23.9	Pass							
13.80	9.3	1.4	9.3	1.4	20.1	---	---	60.0	-30.6	50.0	-20.6	Pass							
17.50	12.0	4.1	12.0	4.1	20.2	---	---	60.0	-27.8	50.0	-17.8	Pass							
23.10	8.3	4.3	8.3	4.3	20.3	---	---	60.0	-31.4	50.0	-21.4	Pass							
Table Result:		Pass	by	-4.10 dB							Worst Freq:	0.15 MHz							

Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty (ETSI)
Radiated Emissions (30-1000MHz)	5.6dB	N/A
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions	3.9dB	N/A
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency	8.2×10^{-8}	1×10^{-7}
RF power, conducted	0.7dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency	• 1.2%	• 5%
• Within 6kHz and 25kHz of audio frequency	• 0.1dB	• 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	0.7dB	3dB
Conducted emission of receivers	0.7dB	1dB
Radiated emission of transmitter, valid up to 26.5GHz	5.6dB	6dB
Radiated emission of transmitter, valid up to 80GHz	5.6dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	5.6dB	6dB
Radiated emission of receiver, valid up to 80GHz	5.6dB	6dB
RF level uncertainty for a given BER	0.7dB	1dB
Humidity	2.31%	5%
Temperature	0.6°C	1.0°C
Time	0.8%	10%
RF Power Density, Conducted	2.2dB	3dB
DC and low frequency voltages	1.29%	3%
Voltage (AC, <10kHz)	1.29%	2%
Voltage (DC)	0.23%	1%
The above reflects a 95% confidence level		

Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS", "MTL", "ACTS", "MTL-ACTS" and CURTIS-STRAUS (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS

AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B)NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

Rev.160009121(2)_#684340 v13CS

A2LA Accreditation

<p>SCOPE OF ACCREDITATION TO ISO/IEC 17025-1999</p> <p>CURTIS-STRAUS¹ 527 Great Road Littleton, MA 01460 Barry Quinlan Phone: 978-486-8880 ELECTRICAL</p> <p>Valid until: November 30, 2007</p> <p>Certificate Number: 1627.01</p>																																					
<p>In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Telecommunications, and Product Safety tests:</p> <p>Electromagnetic Compatibility (EMC)</p> <p>Radiated emissions testing (electric and magnetic fields)*; Conducted emissions testing (voltage and current)*; Electrostatic Discharge testing*; Electrical Fast Transient testing*; Radiated Immunity testing*; Conducted Immunity testing*; Lightning Immunity testing*; Voltage Dips*, Interrupts and Voltage Variations testing*; Magnetic Immunity testing*; RF Power measurements*; Frequency Stability Measurements*; Longitudinal Induction measurements*; Harmonic emissions testing*; Light flicker testing*; Low frequency disturbance voltage testing*; Disturbance Power measurements*; Power Cross Overvoltage testing*;</p> <table border="1"> <thead> <tr> <th>Test Type</th><th>Test Method(s)</th></tr> </thead> <tbody> <tr> <td colspan="2">Emissions</td></tr> <tr> <td>Radiated and Conducted Emissions</td><td>FCC 47 CFR Parts 15 & 18; C63.4; CISPR 22; EN55022; SABS CISPR 22; AS/NZS CISPR 22; AS/NZS 3548; Canada ICES-003; CNS13438; KN 22 (RRL No. 2005-82, September 29, 2005); CISPR 11; EN 55011; SABS CISPR 11; AS/NZS CISPR 11; AS/NZS 2064; Canada ICES-001; CNS13803; CISPR 13; EN 55013; SABS CISPR 13; AS/NZS CISPR 13; AS/NZS 1053; CISPR 14-1; EN 55014-1; SABS CISPR 14; AS/NZS CISPR 14; AS/NZS 1044; CNS 13439; CISPR 15; EN 55015; GR-1089-CORE; CSA C108.8-M1983;</td></tr> <tr> <td>Harmonics</td><td>EN 61000-3-2; AS/NZS 61000.3.2</td></tr> <tr> <td>Flicker</td><td>EN 61000-3-3; AS/NZS 61000.3.3</td></tr> </tbody> </table> <p>1 Note: This accreditation covers testing performed at the laboratory listed above and the satellite facility located at 168 Ayer Rd, Littleton, MA 01460 and, for test types marked with an asterisk, at other sites as defined in "A2LA specific criteria for the accreditation of site testing and site calibration laboratories."</p>		Test Type	Test Method(s)	Emissions		Radiated and Conducted Emissions	FCC 47 CFR Parts 15 & 18; C63.4; CISPR 22; EN55022; SABS CISPR 22; AS/NZS CISPR 22; AS/NZS 3548; Canada ICES-003; CNS13438; KN 22 (RRL No. 2005-82, September 29, 2005); CISPR 11; EN 55011; SABS CISPR 11; AS/NZS CISPR 11; AS/NZS 2064; Canada ICES-001; CNS13803; CISPR 13; EN 55013; SABS CISPR 13; AS/NZS CISPR 13; AS/NZS 1053; CISPR 14-1; EN 55014-1; SABS CISPR 14; AS/NZS CISPR 14; AS/NZS 1044; CNS 13439; CISPR 15; EN 55015; GR-1089-CORE; CSA C108.8-M1983;	Harmonics	EN 61000-3-2; AS/NZS 61000.3.2	Flicker	EN 61000-3-3; AS/NZS 61000.3.3																										
Test Type	Test Method(s)																																				
Emissions																																					
Radiated and Conducted Emissions	FCC 47 CFR Parts 15 & 18; C63.4; CISPR 22; EN55022; SABS CISPR 22; AS/NZS CISPR 22; AS/NZS 3548; Canada ICES-003; CNS13438; KN 22 (RRL No. 2005-82, September 29, 2005); CISPR 11; EN 55011; SABS CISPR 11; AS/NZS CISPR 11; AS/NZS 2064; Canada ICES-001; CNS13803; CISPR 13; EN 55013; SABS CISPR 13; AS/NZS CISPR 13; AS/NZS 1053; CISPR 14-1; EN 55014-1; SABS CISPR 14; AS/NZS CISPR 14; AS/NZS 1044; CNS 13439; CISPR 15; EN 55015; GR-1089-CORE; CSA C108.8-M1983;																																				
Harmonics	EN 61000-3-2; AS/NZS 61000.3.2																																				
Flicker	EN 61000-3-3; AS/NZS 61000.3.3																																				
(A2LA Cert. No. 1627.01) 3/27/06		Page 1 of 10																																			
<p>Other Radio Standards</p> <p>FCC Standards and Test methods Support TCB Status--</p> <p>FCC Scope A – Unlicensed Radio Frequency Devices</p> <table border="1"> <tbody> <tr> <td>A1</td><td>1. 47 CFR Parts 11, 15 and 18 2. FCC MP-5. 3. ANSI C63.4-2003.</td></tr> <tr> <td>A2</td><td>1. 47 CFR Part 15. 2. ANSI C63.4-2003.</td></tr> <tr> <td>A3</td><td>1. 47 CFR Part 15. 2. ANSI C63.17-1998. 3. ANSI C63.4-2003.</td></tr> <tr> <td>A4</td><td>1. 47 CFR Part 15. 2. ANSI C63.4-2003.</td></tr> </tbody> </table> <p>FCC Scope B – Licensed Radio Service Equipment</p> <table border="1"> <tbody> <tr> <td>B1</td><td>1. 47 CFR Parts 2, 22, 24, 25, and 27 2. ANSI/TIA-603-C (2004)</td></tr> <tr> <td>B2</td><td>1. 47 CFR Parts 2, 22, 74, 90, 95, and 97 2. ANSI/TIA-603-C (2004)</td></tr> <tr> <td>B3</td><td>1. 47 CFR Parts 2, 80, and 87 2. ANSI/TIA-603-C (2004)</td></tr> <tr> <td>B4</td><td>1. 47 CFR Parts 2, 21, 74, and 101 2. ANSI/TIA-603-C (2004)</td></tr> </tbody> </table> <p>Country Specific Standards and Other</p> <table border="1"> <tbody> <tr> <td>ITU EMC Standards</td><td>K.20; K.21; K.41; K.44</td></tr> <tr> <td>Swedish EMC Standards</td><td>BAKOM 3336.3</td></tr> <tr> <td>South African EMC Standards other then CISPR equivalents</td><td>SABS 1718-1; SANS 211/SABS CISPR 11; SANS 224/SABS CISPR 24; SANS 213/SABS CISPR 13; SANS 2200; SANS214-1/SABS CISPR 14-1; SANS214-2/SABS CISPR 14-2; SANS 215/SABS CISPR 15; SANS 222/SABS CISPR 22</td></tr> <tr> <td>Hong Kong EMC Standards</td><td>HKTA 1006; HKTA 1007; HKTA 1008; HKTA 1010; HKTA 1015; HKTA 1026; HKTA 1035; HKTA 1039; HKTA 1041; HKTA 1042; HKTA 1045</td></tr> <tr> <td>Singapore EMC Standards</td><td>IDA TS SRD; IDA TS EMC</td></tr> <tr> <td>Japanese VCCI Standards</td><td>VCCI V-3, VCCI V-4</td></tr> </tbody> </table>		A1	1. 47 CFR Parts 11, 15 and 18 2. FCC MP-5. 3. ANSI C63.4-2003.	A2	1. 47 CFR Part 15. 2. ANSI C63.4-2003.	A3	1. 47 CFR Part 15. 2. ANSI C63.17-1998. 3. ANSI C63.4-2003.	A4	1. 47 CFR Part 15. 2. ANSI C63.4-2003.	B1	1. 47 CFR Parts 2, 22, 24, 25, and 27 2. ANSI/TIA-603-C (2004)	B2	1. 47 CFR Parts 2, 22, 74, 90, 95, and 97 2. ANSI/TIA-603-C (2004)	B3	1. 47 CFR Parts 2, 80, and 87 2. ANSI/TIA-603-C (2004)	B4	1. 47 CFR Parts 2, 21, 74, and 101 2. ANSI/TIA-603-C (2004)	ITU EMC Standards	K.20; K.21; K.41; K.44	Swedish EMC Standards	BAKOM 3336.3	South African EMC Standards other then CISPR equivalents	SABS 1718-1; SANS 211/SABS CISPR 11; SANS 224/SABS CISPR 24; SANS 213/SABS CISPR 13; SANS 2200; SANS214-1/SABS CISPR 14-1; SANS214-2/SABS CISPR 14-2; SANS 215/SABS CISPR 15; SANS 222/SABS CISPR 22	Hong Kong EMC Standards	HKTA 1006; HKTA 1007; HKTA 1008; HKTA 1010; HKTA 1015; HKTA 1026; HKTA 1035; HKTA 1039; HKTA 1041; HKTA 1042; HKTA 1045	Singapore EMC Standards	IDA TS SRD; IDA TS EMC	Japanese VCCI Standards	VCCI V-3, VCCI V-4								
A1	1. 47 CFR Parts 11, 15 and 18 2. FCC MP-5. 3. ANSI C63.4-2003.																																				
A2	1. 47 CFR Part 15. 2. ANSI C63.4-2003.																																				
A3	1. 47 CFR Part 15. 2. ANSI C63.17-1998. 3. ANSI C63.4-2003.																																				
A4	1. 47 CFR Part 15. 2. ANSI C63.4-2003.																																				
B1	1. 47 CFR Parts 2, 22, 24, 25, and 27 2. ANSI/TIA-603-C (2004)																																				
B2	1. 47 CFR Parts 2, 22, 74, 90, 95, and 97 2. ANSI/TIA-603-C (2004)																																				
B3	1. 47 CFR Parts 2, 80, and 87 2. ANSI/TIA-603-C (2004)																																				
B4	1. 47 CFR Parts 2, 21, 74, and 101 2. ANSI/TIA-603-C (2004)																																				
ITU EMC Standards	K.20; K.21; K.41; K.44																																				
Swedish EMC Standards	BAKOM 3336.3																																				
South African EMC Standards other then CISPR equivalents	SABS 1718-1; SANS 211/SABS CISPR 11; SANS 224/SABS CISPR 24; SANS 213/SABS CISPR 13; SANS 2200; SANS214-1/SABS CISPR 14-1; SANS214-2/SABS CISPR 14-2; SANS 215/SABS CISPR 15; SANS 222/SABS CISPR 22																																				
Hong Kong EMC Standards	HKTA 1006; HKTA 1007; HKTA 1008; HKTA 1010; HKTA 1015; HKTA 1026; HKTA 1035; HKTA 1039; HKTA 1041; HKTA 1042; HKTA 1045																																				
Singapore EMC Standards	IDA TS SRD; IDA TS EMC																																				
Japanese VCCI Standards	VCCI V-3, VCCI V-4																																				
(A2LA Cert. No. 1627.01) 3/27/06		Page 3 of 10																																			
<table border="1"> <tbody> <tr> <td>Immunity</td><td>RRL No. 2005-130 (December 27, 2005)</td></tr> <tr> <td>Electrostatic Discharge (ESD)</td><td>EN 61000-4-2; AS/NZS 61000.4.2; KN61000-4-2</td></tr> <tr> <td>Radiated Immunity (RFI)</td><td>EN 61000-4-3; AS/NZS 61000.4.3; KN61000-4-3</td></tr> <tr> <td>Electrical Fast Transient Bursts (EFT)</td><td>EN 61000-4-4; AS/NZS 61000.4.4; KN61000-4-4</td></tr> <tr> <td>Surge</td><td>EN 61000-4-5; AS/NZS 61000.4.5; KN61000-4-5</td></tr> <tr> <td>Conducted Immunity</td><td>EN 61000-4-6; AS/NZS 61000.4.6; KN61000-4-6</td></tr> <tr> <td>Magnetic Immunity</td><td>EN 61000-4-8; AS/NZS 61000.4.8; KN61000-4-8</td></tr> <tr> <td>Voltage Dips and Interrupts</td><td>EN 61000-4-11; KN61000-4-11</td></tr> <tr> <td>Low Frequency Conducted Disturbances</td><td>EN 61000-2-2</td></tr> </tbody> </table>		Immunity	RRL No. 2005-130 (December 27, 2005)	Electrostatic Discharge (ESD)	EN 61000-4-2; AS/NZS 61000.4.2; KN61000-4-2	Radiated Immunity (RFI)	EN 61000-4-3; AS/NZS 61000.4.3; KN61000-4-3	Electrical Fast Transient Bursts (EFT)	EN 61000-4-4; AS/NZS 61000.4.4; KN61000-4-4	Surge	EN 61000-4-5; AS/NZS 61000.4.5; KN61000-4-5	Conducted Immunity	EN 61000-4-6; AS/NZS 61000.4.6; KN61000-4-6	Magnetic Immunity	EN 61000-4-8; AS/NZS 61000.4.8; KN61000-4-8	Voltage Dips and Interrupts	EN 61000-4-11; KN61000-4-11	Low Frequency Conducted Disturbances	EN 61000-2-2																		
Immunity	RRL No. 2005-130 (December 27, 2005)																																				
Electrostatic Discharge (ESD)	EN 61000-4-2; AS/NZS 61000.4.2; KN61000-4-2																																				
Radiated Immunity (RFI)	EN 61000-4-3; AS/NZS 61000.4.3; KN61000-4-3																																				
Electrical Fast Transient Bursts (EFT)	EN 61000-4-4; AS/NZS 61000.4.4; KN61000-4-4																																				
Surge	EN 61000-4-5; AS/NZS 61000.4.5; KN61000-4-5																																				
Conducted Immunity	EN 61000-4-6; AS/NZS 61000.4.6; KN61000-4-6																																				
Magnetic Immunity	EN 61000-4-8; AS/NZS 61000.4.8; KN61000-4-8																																				
Voltage Dips and Interrupts	EN 61000-4-11; KN61000-4-11																																				
Low Frequency Conducted Disturbances	EN 61000-2-2																																				
<table border="1"> <tbody> <tr> <td>Family Product or Industry Specific Specifications including emissions and/or immunity</td><td>GR-1089-CORE; GR-78-CORE (ESD) EN50081-1; EN50081-2; EN50082-1; EN50082-1; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 50091-2; EN 55024; CISPR 24 EN 55103-1; EN 55103-2; EN 61326; EN 61547; EN 50130-4; EN 50083-2; EN 60601-1-2; EN 60601-2-2; EN 60601-2-24; EN 60601-2-32; EN 60601-2-38; EN 60601-2-47; IEC 1800-3; EN 61800-3; EN 55020; CISPR 20; EN 60555 Part 2; EN 60555 Part 3; ETS 300 386-1; EN 300 386-2; EN 301 386; ETS 300 132-1; ETS 300 132-2; EN 6069-2-1; AS/NZS 3200.1.2; CNS 13783-1; ETR 283; C62.41</td></tr> <tr> <td>Radiocommunications</td><td>EU R&TTE Radio Standards; EN 300 220-1; EN 300 220-3; EN 300 330-1; EN 300 330-2; EN 300 440-1; EN 300 440-2; EN 300 328; EN 300 385; EN 301 893</td></tr> <tr> <td>EU R&TTE EMC Standards</td><td>EN 301 339; EN 301 489-01; EN 301 489-03; EN 301 489-17</td></tr> <tr> <td>Canada Radio Standards</td><td>RSS-102; RSS-117; RSS-118; RSS-119; RSS-123; RSS-125; RSS-128; RSS-129; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-136; RSS-137; RSS-138; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-187; RSS-188; RSS-191; RSS-192; RSS-193; RSS-195; RSS-210; RSS-212; RSS-213; RSS-215; RSS-243; RSS-GEN; RSS-310; GL-36</td></tr> <tr> <td>Australia/New Zealand Radio Standards</td><td>AS/NZS 4268; AS/NZS 4771; RFS29; Radiocommunications (Data Transmission Equipment Using Spread Spectrum Modulation Techniques); Radiocommunications (Spread Spectrum Devices); Radiocommunications (Short Range Devices); Radiocommunications (Low Interference Potential Devices);</td></tr> </tbody> </table>		Family Product or Industry Specific Specifications including emissions and/or immunity	GR-1089-CORE; GR-78-CORE (ESD) EN50081-1; EN50081-2; EN50082-1; EN50082-1; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 50091-2; EN 55024; CISPR 24 EN 55103-1; EN 55103-2; EN 61326; EN 61547; EN 50130-4; EN 50083-2; EN 60601-1-2; EN 60601-2-2; EN 60601-2-24; EN 60601-2-32; EN 60601-2-38; EN 60601-2-47; IEC 1800-3; EN 61800-3; EN 55020; CISPR 20; EN 60555 Part 2; EN 60555 Part 3; ETS 300 386-1; EN 300 386-2; EN 301 386; ETS 300 132-1; ETS 300 132-2; EN 6069-2-1; AS/NZS 3200.1.2; CNS 13783-1; ETR 283; C62.41	Radiocommunications	EU R&TTE Radio Standards; EN 300 220-1; EN 300 220-3; EN 300 330-1; EN 300 330-2; EN 300 440-1; EN 300 440-2; EN 300 328; EN 300 385; EN 301 893	EU R&TTE EMC Standards	EN 301 339; EN 301 489-01; EN 301 489-03; EN 301 489-17	Canada Radio Standards	RSS-102; RSS-117; RSS-118; RSS-119; RSS-123; RSS-125; RSS-128; RSS-129; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-136; RSS-137; RSS-138; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-187; RSS-188; RSS-191; RSS-192; RSS-193; RSS-195; RSS-210; RSS-212; RSS-213; RSS-215; RSS-243; RSS-GEN; RSS-310; GL-36	Australia/New Zealand Radio Standards	AS/NZS 4268; AS/NZS 4771; RFS29; Radiocommunications (Data Transmission Equipment Using Spread Spectrum Modulation Techniques); Radiocommunications (Spread Spectrum Devices); Radiocommunications (Short Range Devices); Radiocommunications (Low Interference Potential Devices);																										
Family Product or Industry Specific Specifications including emissions and/or immunity	GR-1089-CORE; GR-78-CORE (ESD) EN50081-1; EN50081-2; EN50082-1; EN50082-1; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 50091-2; EN 55024; CISPR 24 EN 55103-1; EN 55103-2; EN 61326; EN 61547; EN 50130-4; EN 50083-2; EN 60601-1-2; EN 60601-2-2; EN 60601-2-24; EN 60601-2-32; EN 60601-2-38; EN 60601-2-47; IEC 1800-3; EN 61800-3; EN 55020; CISPR 20; EN 60555 Part 2; EN 60555 Part 3; ETS 300 386-1; EN 300 386-2; EN 301 386; ETS 300 132-1; ETS 300 132-2; EN 6069-2-1; AS/NZS 3200.1.2; CNS 13783-1; ETR 283; C62.41																																				
Radiocommunications	EU R&TTE Radio Standards; EN 300 220-1; EN 300 220-3; EN 300 330-1; EN 300 330-2; EN 300 440-1; EN 300 440-2; EN 300 328; EN 300 385; EN 301 893																																				
EU R&TTE EMC Standards	EN 301 339; EN 301 489-01; EN 301 489-03; EN 301 489-17																																				
Canada Radio Standards	RSS-102; RSS-117; RSS-118; RSS-119; RSS-123; RSS-125; RSS-128; RSS-129; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-136; RSS-137; RSS-138; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-187; RSS-188; RSS-191; RSS-192; RSS-193; RSS-195; RSS-210; RSS-212; RSS-213; RSS-215; RSS-243; RSS-GEN; RSS-310; GL-36																																				
Australia/New Zealand Radio Standards	AS/NZS 4268; AS/NZS 4771; RFS29; Radiocommunications (Data Transmission Equipment Using Spread Spectrum Modulation Techniques); Radiocommunications (Spread Spectrum Devices); Radiocommunications (Short Range Devices); Radiocommunications (Low Interference Potential Devices);																																				
(A2LA Cert. No. 1627.01) 3/27/06		Page 2 of 10																																			
<p>Telecommunications</p> <p>Telecommunications Registration; General test methods; Lightning surge*; Drop testing*; Balance testing*; Signal power (metallic and longitudinal)*; Frequency measurements*; Pulse templates*; Leakage testing*; Impedance testing*; Hearing Aid Compatibility testing (excluding volume control)*; Protocol analysis* and Jitter testing*.</p> <table border="1"> <thead> <tr> <th>Telecom Standards</th><th>Title</th></tr> </thead> <tbody> <tr> <td>North American standards</td><td>North American standards</td></tr> <tr> <td>FCC 47 CFR Part 68 Telephone Terminal Equipment CS-03 Issue 9</td><td>Specification for terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.</td></tr> <tr> <td>TIA/EIA TSB31-B 1998</td><td>Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)</td></tr> <tr> <td>TIA-968-A, A1, A2, A3</td><td>Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network</td></tr> <tr> <td>T1.TRQ.6-2001</td><td>Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry</td></tr> <tr> <td>Australia standards</td><td>Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network</td></tr> <tr> <td>AS/ACIF S002-2001</td><td>Requirements for Customer Equipment for connection to hierarchical digital interfaces</td></tr> <tr> <td>AS/ACIF S031-2001</td><td>Requirements for ISDN Basic Access Interface</td></tr> <tr> <td>AS/ACIF S038-2001</td><td>Requirements for ISDN Primary Rate Access Interface</td></tr> <tr> <td>AS/ACIF S043-2001</td><td>Requirements for Customer Equipment for Connection to a Metallic Local Loop Interface of a Telecommunications Network —</td></tr> <tr> <td>Part 1: General</td><td>Part 1: General</td></tr> <tr> <td>Part 2: Broadband</td><td>Part 2: Broadband</td></tr> <tr> <td>Part 3: DC, Low Frequency AC and Voice band</td><td>Part 3: DC, Low Frequency AC and Voice band</td></tr> <tr> <td>International standards</td><td>Physical/electrical characteristics of hierarchical Digital interfaces</td></tr> <tr> <td>ITU-T G.703</td><td>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Direct Exchange Lines (DEL) of the Public Switched Telephone Network (PSTN) in Hong Kong</td></tr> <tr> <td>Hong Kong standards</td><td>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations</td></tr> <tr> <td>HKTA 2014</td><td>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations</td></tr> </tbody> </table>		Telecom Standards	Title	North American standards	North American standards	FCC 47 CFR Part 68 Telephone Terminal Equipment CS-03 Issue 9	Specification for terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.	TIA/EIA TSB31-B 1998	Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)	TIA-968-A, A1, A2, A3	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network	T1.TRQ.6-2001	Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry	Australia standards	Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network	AS/ACIF S002-2001	Requirements for Customer Equipment for connection to hierarchical digital interfaces	AS/ACIF S031-2001	Requirements for ISDN Basic Access Interface	AS/ACIF S038-2001	Requirements for ISDN Primary Rate Access Interface	AS/ACIF S043-2001	Requirements for Customer Equipment for Connection to a Metallic Local Loop Interface of a Telecommunications Network —	Part 1: General	Part 1: General	Part 2: Broadband	Part 2: Broadband	Part 3: DC, Low Frequency AC and Voice band	Part 3: DC, Low Frequency AC and Voice band	International standards	Physical/electrical characteristics of hierarchical Digital interfaces	ITU-T G.703	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Direct Exchange Lines (DEL) of the Public Switched Telephone Network (PSTN) in Hong Kong	Hong Kong standards	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations	HKTA 2014	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations
Telecom Standards	Title																																				
North American standards	North American standards																																				
FCC 47 CFR Part 68 Telephone Terminal Equipment CS-03 Issue 9	Specification for terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.																																				
TIA/EIA TSB31-B 1998	Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)																																				
TIA-968-A, A1, A2, A3	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network																																				
T1.TRQ.6-2001	Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry																																				
Australia standards	Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network																																				
AS/ACIF S002-2001	Requirements for Customer Equipment for connection to hierarchical digital interfaces																																				
AS/ACIF S031-2001	Requirements for ISDN Basic Access Interface																																				
AS/ACIF S038-2001	Requirements for ISDN Primary Rate Access Interface																																				
AS/ACIF S043-2001	Requirements for Customer Equipment for Connection to a Metallic Local Loop Interface of a Telecommunications Network —																																				
Part 1: General	Part 1: General																																				
Part 2: Broadband	Part 2: Broadband																																				
Part 3: DC, Low Frequency AC and Voice band	Part 3: DC, Low Frequency AC and Voice band																																				
International standards	Physical/electrical characteristics of hierarchical Digital interfaces																																				
ITU-T G.703	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Direct Exchange Lines (DEL) of the Public Switched Telephone Network (PSTN) in Hong Kong																																				
Hong Kong standards	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations																																				
HKTA 2014	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations																																				
(A2LA Cert. No. 1627.01) 3/27/06		Page 4 of 10																																			

REPORT: EH0043-3

FCC ID: U3V6221020

Telecom Standards	Title Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 1544 kbit/s	European standards (cont'd) TBR 21: 1998	Terminal Equipment (TE); Attachment requirements for pan-European approval for connection to the Analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signaling
HKTA 2028			Business TeleCommunications (BTC); 34 Mbit/s Digital Unstructured and structured leased lines (D34U and D34S); Attachment requirements for Terminal equipment interface
HKTA 2029			
HKTA 2030			
HKTA 2031			
HKTA 2032			
HKTA 2033			
European standards TBR 1: 1995			
	Attachment requirements for terminal equipment to Be connected to circuit switched data networks and Leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including, 1 984 kbit/s Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations X.21 and X.21 bit Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U); Attachment requirements for terminal equipment		
TBR 2: 1997			
TBR 3: 1995 + Amdt : 1997			
TBR 4: 1995 + Amdt : 1997			
TBR 012: 1993 + Amdt : 1996			
TBR 013: 1996			
(A2LA Cert. No. 1627.01) 3/27/06	Page 5 of 10	(A2LA Cert. No. 1627.01) 3/27/06	Page 6 of 10
Product Safety			
General test methods:			
Power input*, Permanence of marking*, Accessibility*, Permissibly limits*, Energy hazard measurement*, SELV circuits*, TNV limits*, Limited current*, Capacitor Discharge / voltage limitation*, Ring signal*, Humidity conditioning*, Creepage / Clearance / Distance thru Insulation (excluding CTI)*, Limited power measurement*, Ground Bond/Earthing*, Ground continuity*, Temperature*, Stability*, Applied force*, Steel sphere impact*, Mold stress*, Battery reverse current*, Ball pressure*, Leakage current*, Component abnormal*, Electrical strength*, Impulse*, Overvoltage*, Acoustic sound pressure*, 130mm / 20mm flame*, Needle flame*, Hot flaming oil*, Locked rotor/motor armature*, Vibration, Bump, Drop*, Strain relief*, Torque*, Insulation resistance*, Sound level*, Handle loading*, Liquid overflow*, Spillage*, Liquid leakage*, Transformer shorts/overloads*, Rain test*, Wall mount*, Laser radiation (excluding x-ray)*, Voltage surge*, Functionality*, Protective impedance abnormal*, Capacitor short circuit abnormal*, Output abnormal*, Multi-supply abnormal*, Cooling abnormal*, Heating device abnormal*, Interlock abnormal*, Rigidity*, Cleaning*			
Product Safety Standards	Title	Product Safety Standards	Title
<i>Specific Product Safety Standards</i>		<i>IEC 60825-1 2001</i> <i>IEC 60825-2 2000-5</i>	<i>Classification, requirements and user's guide.</i> <i>Safety of laser products – Part 2: Safety of optical communication systems</i>
UL 60950 2000	Safety of information technology equipment	IEC 60825-4 1997-11 21 CFR 1040.10	<i>Safety of laser products – Part 4: Laser guards</i>
IEC 60950 1999	Safety of information technology equipment	IEC 60335-1 1995 <i>Including AM2 – 1997 & AM 12 – 1997</i>	<i>Performance standard for laser products</i>
EN 60950 2000	Safety of information technology equipment, including Electrical business equipment.	EN 60335-1 2001 UL 60335-1 1998 CAN/CSA E335-1 1994	<i>Safety of household and similar electrical appliances</i>
IEC 60950-1 2001		UL 61010A-1: 2002	<i>Part 1: General requirements</i>
UL 60950-1 2003			
CSA C22.2 No. 60950-00		EN 61010-1: 2001	
CSA C22.2 No. 60950-1 03		AS/NZS 60950: 2000 EN 60950-1: 2001	<i>Electrical equipment for laboratory use; part 1: General requirements</i>
IEC 61010-1 1993		AS/NZS 60950.1: 2003	<i>Safety requirements for electrical equipment for measurement, control and laboratory use - Part 1: General requirements</i>
IEC 61010-1 2001		UL 61010-1: 2004	<i>Information Technology Equipment – Safety – Part 1: General Requirements</i>
UL 61010B-1 2003		UL 60601-1: 2003	<i>Information Technology Equipment – Safety – General requirements</i>
CAN/CSA 1010-1 1999 (<i>Including AM 2</i>)		IEC 60601-1-1: 2000	<i>Electrical Equipment for Measurement, Control and Laboratory Use; Part 1: General Requirements</i>
IEC 60601-1 1995		EN 60601-1-1: 2001	<i>Medical Electrical Equipment; Part 1: General Requirements for Safety</i>
EN 60601-1 1995 (<i>Including AM 2</i>)		UL 60065: 2003	<i>Medical Electrical Equipment - Part 1: General Requirements For Safety; 1: Collateral Standard: Safety Requirements For Medical Electrical Systems</i>
UL 2601-1 1997		CSA 60065: 2003	<i>Medical Electrical Equipment - Part 1: General Requirements For Safety - Section 1-1. Collateral Standard: Safety Requirements For Medical Electrical Systems</i>
IEC 60065 1998, 2000		IEC 60065: 2001	<i>Audio, Video and Similar Electronic Apparatus – Safety Requirements</i>
ANSI/UL 6500: 1998		EN 60065: 2002	<i>Audio, Video and Similar Electronic Apparatus – Safety Requirements</i>
CAN/CSA 60065-00		EN 60204 - 1: 1998	<i>Safety of Machinery – Electrical Equipment of Machines – Part 1: Specification for General Requirements</i>
AS/NZS 60065 2000		HKTA 2001	<i>Compliance Test Specification – Safety and Electrical Protection Requirements for Subscriber Equipment Connected to the Public Telecommunications Networks In Hong Kong</i>
Canadian C22.2 No. 1-94 (1-98) 1994, 1998			
EN 60065 1994			
IEC 60825 1990			
EN 60825-1 1994			
(A2LA Cert. No. 1627.01) 3/27/06	Page 7 of 10	(A2LA Cert. No. 1627.01) 3/27/06	Page 8 of 10



Environmental Simulation

Test Technology	Test Standard	Supporting Standards	
Accessibility*	IEC 60529	IP-0x thru IP-6x	
Acoustic Noise*	GR-63-CORE Sec 4.6		
Airborne Contaminants	GR-63-CORE Sec 4.5	MFG & Hygroscopic Dust	
Altitude	GR-63-CORE Sec 4.1.3		
Cold Start*	ETS 300 019	IEC 60068-2-1	
Drip	IEC 60529	IP-x1 & IP-x2	
Drops*	ETS 300 019	IEC 60068-2-32	
Dust	GR-63-CORE Sec 4.3		
Firearms Resistance Testing	IEC 60529	IP-5x & IP-6x	
Fire Resistance	GR-487		
Heat Dissipation*	ANSI T1.319		
Illumination	GR-63-CORE Sec 4.2	Fire & Needle Flame	
Operational Temperature & Humidity (OpTH)*	GR-63-CORE Sec 4.1.4		
	GR-63-CORE Sec 4.7		
	ETS 300 019	IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-56	
	GR-63-CORE Sec 4.1.2		
Salt Fog & Spray	ASTM B117		
Spatial*	GR-63-CORE Sec 2.0 & 3.0		
Spraying-Splashing	IEC 60529	IP-x3 & IP-x4	
Storage (Temperature & Humidity)*	ETS 300 019	IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-56	
Vibration	GR-63-CORE Sec 4.1.1		
	ETS 300 019	IEC 60068-2-6 IEC 60068-2-27 IEC 60068-2-29 IEC 60068-2-32 IEC 60068-2-57 IEC 60068-2-64 Earthquake, Office & Transportation	
Water Immersion	GR-63-CORE Sec 4.4	IP-x7 & IP-x8	
Water Jet	IEC 60529	IP-x5 & IP-x6	

(A2LA Cert. No. 1627.01) 3/27/06

Page 9 of 10

Note 1. For standards or methods listed on the scope of accreditation without a revision date, laboratories are expected to be competent in the use of the current version within one year of the date of publication of the standard test method or upon the date specified by the standard test method originator when the originator has implementation authority. When a superseded standard or method is required for an accredited test, the scope will include the superseded date/version. For those that support the TCB/CB status of the organization acting as a certifier on behalf of the FCC or IC the expectation is currency within 30 days of Federal Register publication of changes for FCC and 30 days after IC website update. This note shall not be construed as an Accreditation Body implication to adopt a more current standard than is required in a regulation or code (i.e. the legal requirement) which is adopted by the lab under their responsibility.

* On-site test service is available for this technology, test, or method.

(A2LA Cert. No. 1627.01) 3/27/06

Page 10 of 10