

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-194-RWD-019

AGR No. : A192A-095R

Applicant : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, 22013, South Korea

Manufacturer : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, 22013, South Korea

Type of Equipment : Bluetooth Earbud

FCC ID. : U3WBCST90

Model Name : BCS-T90

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : March 18, 2019

Date of issue : April 03, 2019

#### **SUMMARY**

The equipment complies with the regulation; FCC PART 15 SUBPART C Section 15.247

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Ki-Hong, Nam / Chief Engineer ONETECH Corp. Approved by:

Keun-Young, Choi / Vice President

Report No.: OT-194-RWD-019

ONETECH Corp.





## **CONTENTS**

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.	5
3. EUT MODIFICATIONS	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 RF Exposure Calculation	
4.2 EUT DESCRIPTION	6
4.3 CALCULATED MPE SAFE DISTANCE.	7





**Revision History** 

Report No.: OT-194-RWD-019

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-194-RWD-019	April 03, 2019	Initial Release	All





#### 1. VERIFICATION OF COMPLIANCE

Applicant : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, 22013, South Korea

Contact Person: Ki-eok, Park / Principal Engineer

Telephone No. : +82-32-8100-582 FCC ID : U3WBCST90

Model Name : BCS-T90

Brand Name : Serial Number : N/A

Date : April 03, 2019

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Bluetooth Earbud
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	
AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED	FCC DART 15 GUDDART C G 15 247
UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve	N
Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

<sup>-.</sup> The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



#### 2. GENERAL INFORMATION

#### 2.1 Product Description

The BLUECOM Co., Ltd., Model BCS-T90 (referred to as the EUT in this report) is a Bluetooth Earbud. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Bluetooth Earbud			
Temperature Range	-10 °C ~ 50 °C			
OPERATING EDECAMENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz		
OPERATING FREQUENCY	Bluetooth	2 402 MHz ~ 2 480 MHz		
MODAL ATTOM TWO	Bluetooth LE	GFSK		
MODULATION TYPE	Bluetooth GFSK for 1Mbps, π/4-DQPSK for 2Mbps, 8-DPS		ps, π/4-DQPSK for 2Mbps, 8-DPSK for 3Mbps	
	Bluetooth LE	9.80 dBm		
RF OUTPUT POWER'	Bluetooth	1 Mbps	9.36 dBm	
		2 Mbps	9.20 dBm	
		3 Mbps	9.55 dBm	
ANTENNA TYPE	FPCB Antenna			
ANTENNA GAIN	3.00 dBi			
List of each Osc. or crystal  Freq.(Freq. >= 1 MHz)	32 MHz			
RATED SUPPLY VOLTAGE	DC 3.6 V			

## 2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

#### 3. EUT MODIFICATIONS

-. None



#### 4. MAXIMUM PERMISSIBLE EXPOSURE

#### **4.1 RF Exposure Calculation**

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are f/1500 mW/cm<sup>2</sup> for the frequency range between 300 MHz and 1.00 mW/cm<sup>2</sup> for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm<sup>2</sup> exposure is calculated as follows:

$$E = \sqrt{(30 * P * G)} / d$$
, and  $S = E^2 / Z = E^2 / 377$ , because 1 mW/cm<sup>2</sup> = 10 W/m<sup>2</sup>

Where

S = Power density in mW/cm<sup>2</sup>, Z = Impedance of free space, 377  $\Omega$ 

E = Electric filed strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combing equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P(mW) = P(W) / 1000, d(cm) = 0.01 \* d(m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm<sup>2</sup>

**4.2 EUT Description** 

Kind of EUT	Bluetooth Earbud		
	☐ Portable (< 20 cm separation)		
Device Category	☐ Mobile (> 20 cm separation)		
	■ Others		
_	■ MPE		
Exposure Evaluation Applied	□ SAR		
	□ N/A		





**4.3 Calculated MPE Safe Distance** 

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is [(Max. Power of channel, including tune-up tolerance, mW)/(Mim. test separation distance, mm)] X [  $\sqrt{f(GHz)}$ ] < 3 = (9.55/5) X  $\sqrt{2.402}$  = 2.96

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and are excluded from SAR Test.

Mode	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
1 Mbps	2 402.00	$9.30 \pm 0.5$	9.80	9.55	5.00	2.96
2 Mbps	2 402.00	$9.30 \pm 0.5$	9.80	9.55	5.00	2.96
3 Mbps	2 402.00	$9.30 \pm 0.5$	9.80	9.55	5.00	2.96
BLE	2 402.00	9.30 ± 0.5	9.80	9.55	5.00	2.96

Tested by: Hyung-Kwon, Oh / Assistant Manager

Report No.: OT-194-RWD-019