## ANSI/IEEE Std. C95.1-1992

In accordance with the requirements of FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C

## **FCC SAR TEST REPORT**

For Mobile phone

Model No.: G10

Trade Name: Zonda

**Test Report Number:** KS100315B01

Prepared for

## TeleEpoch Limited.

2/F, R2-A North Gate, Shenzhen High-Tech Industria Nanshan District, Shenzhen, Guang Dong, China

Issued by

Compliance Certification Services (Kunshan) Inc. No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, PRC.

TEL: 86-512-57355888 FAX: 86-512-57370818 http://www.ccsrf.com







**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

1.	CERTIFICATE OF COMPLIANCE (SAR EVALUATION)	
2. 3.	EUT DESCRIPTION REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC	4
3. 4.	Applied Standards	
5.	Test Configuration	5
6.	DOSIMETRIC ASSESSMENT SETUP	5
	6.1 MEASUREMENT SYSTEM DIAGRAM	7
	6.2 SYSTEM COMPONENTS	
7.	EVALUATION PROCEDURES	
8. 9.	MEASUREMENT UNCERTAINTY EXPOSURE LIMIT	
9. 10.		
	10.1ANTHROPOMORPHIC HEAD PHANTOM	16
	10.2DEFINITION OF THE "CHEEK/TOUCH" POSITION	17
	10.3DEFINITION OF THE "TILTED" POSITION	
11.	MEASUREMENT RESULTS	19
	11.1TEST LIQUIDS CONFIRMATION	19
	11.2SYSTEM PERFORMANCE CHECK	20
	11.3EUT TUNE-UP PROCEDURES AND TEST MODE	22
	11.4RF POWER OUTPUT FOR UMTS REL99	23
	11.5RF POWER OUTPUT FOR UMTS REL 5 HSDPA	23
	11.6EUT SETUP PHOTOS	25
	11.7SAR MEASUREMENT RESULTS	
12. 13.	EUT PHOTO	
13. 14.	EQUIPMENT LIST & CALIBRATION STATUSFACILITIES	
1 <del>5</del> .	REFERENCES	
16.	ATTACHMENTS	

**TABLE OF CONTENTS** 

# 1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

**Applicant:** TeleEpoch Limited.

Address: 2/F, R2-A North Gate, Shenzhen High-Tech Industria Nanshan

District, Shenzhen, Guang Dong, China

Date of Issue: March 17, 2010

**Equipment Under Test:** Mobile Phone

Trade Name: Zonda

Model Number: G10

No Oll

Date of Test: March 16, 2010

Report Number: KS100315B01

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

APPLICABLE STANDARDS							
STANDARD	TEST RESULT						
FCC OET 65 Supplement C	No non-compliance noted						
Deviation from Applicable Standard							
None							

The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in OET Bulletin 65 Supplement C(Edition 01-01). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by: Reviewed by:

Miro Chueh Lin Zhang

EMC Manager EMC Section Manager

Compliance Certification Services Inc. Compliance Certification Services Inc.

Page 3 Rev. 00

# 2. EUT DESCRIPTION

Product	Mobile phone					
Model Number	G10					
Trade Name	Zonda					
Model Discrepancy	N/A					
Frequency Range	GSM / GPRS / EGPRS 850: 824.2 ~ 848.8 MHz WCDMA / HSDPA band V: 826.4 ~ 846.6 MHz					
Transmit Power(Average)	GSM850 Band: GSM 850: 32.89 dBm GPRS 850: 32.88 dBm EDGE850:32.89.76 dBm WCDMA Band V: WCDMA band V: 24.53 dBm HSDPA band V: 22.49 dBm					
Max. SAR :	GSM 850: 0.901 W/kg WCDMA band V: 0.897 W/kg					
Modulation Technique	GSM/GPRS :GMSK; EDGE:8PSK; WCDMA:QPSK; HSDPA:QPSK/16QAM;					
Accessories	Battery: model number: Ion de Litio 3.7Vcc 800mAh					

Date of Issue: March 17, 2010

Page 4 Rev. 00

#### 3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

Date of Issue: March 17, 2010

#### 4. APPLIED STANDARDS

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in
accordance with the following standards:
□ 47 CFR Part 2 ( 2.1093)
□ IEEE C95.1-1999
☐ KDB 941225 D01 v02
□ KDB 447498 D02 v01
□ OET Bulletin 65 Supplement C (Edition 01-01)
☐ Preliminary Guidance for Reviewing Applications for Certification of 3G Device. May 2006.

#### 5. TEST CONFIGURATION

The device was controlled by using a base station emulator R&S CMU200. Communication between the device and the emulator was established by air link. The distance between the DUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of DUT. The DUT was set from the emulator to radiate maximum output power during all tests.

Measurements were performed on the lowest, middle, and highest channel for each testing position.

For SAR testing, EUT is in GPRS/EDGE or WCDMA/HSDPA link mode. In GPRS/EDGE link mode, its crest factor is 2, because EUT is set in GPRS/EDGE multi-slot class 12 with 4 uplink slots. In WCDMA/HSDPA link mode, its crest factor is 1.

#### 6. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system OPENSAR from ATTENNESSA. The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EP100 1109 (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than ±10%. The spherical isotropy was evaluated with the procedure described in [8] and found to be better than ±0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEE P1528 and CENELEC EN50361.

Page 5 Rev. 00


The Tissue simulation liquid used for each test is in according with the FCC OET65 supplement C as listed below.

Date of Issue: March 17, 2010

Ingredients	Frequency (MHz)									
(% by weight)	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Page 6 Rev. 00

#### **6.1 MEASUREMENT SYSTEM DIAGRAM**



Date of Issue: March 17, 2010

# The OPENSAR system for performing compliance tests consist of the following items:

- 1. A standard high precision 6-axis robot (KUKA) with controller and software.
- 2. KUKA Control Panel (KCP).
- 3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- 4. The functions of the PC plug-in card are to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
- 5. A computer operating Windows 95.
- 6. OPENSAR software.
- 7. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
- 8. The SAM phantom enabling testing left-hand right-hand and body usage.
- 9. The Position device for handheld EUT.
- 10. Tissue simulating liquid mixed according to the given recipes (see Application Note). System validation dipoles to validate the proper functioning of the system.

Page 7 Rev. 00

#### **6.2 SYSTEM COMPONENTS**

#### SN11/09 EP100 Probe Specification

Construction Symmetrical design with triangular core Built-in optical fiber for surface detection System

Built-in shielding against static charges

Calibration in air from 100 MHz to 2.5 GHz

In brain and muscle simulating tissue at frequencies of 835 MHz, 897MHz, 1747 MHz, 1880 MHz, 1950 MHz and 1.8 GHz (accuracy of  $\pm$  8%)

Frequency 100 MHz to > 30GHz; Linearity: ± 0.25 dB (100 MHz to 30 GHz)

Directivity  $\pm$  0.25 dB in brain tissue (rotation around probe axis)

± 0.5 dB in brain tissue (rotation normal probe axis)

Dynamic 0.001W/kg to > 100 W/kg;

Range Linearity: ± 0.25 dB

Surface  $\pm$  0.2 mm repeatability in air and clear liquids

Detection over diffuse reflecting surfaces Dimensions Overall length: 330 mm

Tip length: 16 mm Body diameter: 8 mm Tip diameter: 6.5 mm


Distance from probe tip to dipole centers: <2.7 mm

Application General dosimetric up to 3 GHz

Compliance tests of mobile phones

Fast automatic scanning in arbitrary phantoms

The SAR measurements were conducted with the dosimetric probe SN11/09 EP100designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique, with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the KRC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the





Inside View of SN11/09 EP100 E-field Probe

reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The OPENSAR software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.

> Page 8 Total Page: 41

## **E-Field Probe Calibration Process**

Each probe is calibrated according to a dosimetric assessment procedure described in [6] with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in [7] and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in dielectric medium. For temperature correlation calibration a

RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

#### **SAM Phantom**

The SAM Phantom SAM29 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1. The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness: 2 ± 0.2 mm Filling Volume: Approx. 25 liters

Dimensions (H x L x W): 810 x 1000 x 500 mm



Date of Issue: March 17, 2010

#### **Device Holder for Transmitters**

In combination with the Generic Twin Phantom V3.0, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

**Note:** A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations [10]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Page 9 Rev. 00

## 7. EVALUATION PROCEDURES

#### **DATA EVALUATION**

The OPENSAR4 post processing software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Date of Issue: March 17, 2010

Probe parameters: - Sensitivity Norm<sub>i</sub>,  $a_{i0}$ ,  $a_{i1}$ ,  $a_{i2}$ 

Conversion factor ConvF<sub>i</sub>
 Diode compression point dcp<sub>i</sub>

Device parameters: - Frequency f

- Crest factor cf

Media parameters: - Conductivity  $\sigma$ 

- Density ho

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the OPENSAR components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = Compensated signal of channel i (i = x, y, z)

 $U_i$  = Input signal of channel i (i = x, y, z)

cf = Crest factor of exciting field (OPENSAR parameter) dcp<sub>i</sub> = Diode compression point (OPENSAR parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:  $E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$ 

H-field probes:  $H_i = \sqrt{Vi} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$ 

with  $V_i$  = Compensated signal of channel i (i = x, y, z)

 $Norm_i$  = Sensor sensitivity of channel i (i = x, y, z)

μV/(V/m)<sup>2</sup> for E0field Probes

ConvF= Sensitivity enhancement in solution

aij = Sensor sensitivity factors for H-field probes

f = Carrier frequency (GHz)

Ei = Electric field strength of channel i in V/mHi = Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$\boldsymbol{E}_{tot} = \sqrt{\boldsymbol{E}_{x}^{2} + \boldsymbol{E}_{y}^{2} + \boldsymbol{E}_{z}^{2}}$$

The primary field data are used to calculate the derived field units.

Page 10 Rev. 00

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

 $E_{tot}$  = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [Siemens/m]

 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$
 or  $P_{pwe} = H_{tot}^2 \cdot 37.7$ 

with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>

 $E_{tot}$  = total electric field strength in V/m

 $H_{tot}$  = total magnetic field strength in A/m

Page 11 Rev. 00

Date of Issue: March 17, 2010

#### **SAR EVALUATION PROCEDURES**

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

#### Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

Date of Issue: March 17, 2010

#### Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in OPENSAR software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

#### Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures  $5 \times 5 \times 7$  points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

#### Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

Page 12 Rev. 00

#### SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The OPENSAR4 system allows evaluations that combine measured data and robot positions, such as:

Date of Issue: March 17, 2010

- · maximum search
- extrapolation
- · boundary correction
- · peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

#### **Extrapolation**

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

#### **Boundary effect**

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b exp(-\frac{z}{a})cos(\pi \frac{z}{\lambda})$$

Since the decay of the boundary effect dominates for small probes ( $a << \lambda$ ), the cos-term can be omitted. Factors Sb (parameter Alpha in the OPENSAR software) and a (parameter Delta in the OPENSAR software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30\_ to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a OPENSAR system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.

Page 13 Rev. 00

# 8. MEASUREMENT UNCERTAINTY

UNCERTAINTY EV	ALUA	ATIO	V F	OR I	HANE	SET	SAR	TES	T
a	b	С	d	e= f(d,k)	f	g	h= cxf/e	i= cxg/e	k
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> (1 g)	c <sub>i</sub> (10 g)	1 g u <sub>i</sub> (± %)	10 g u <sub>i</sub> (± %)	Vi
Measurement System							[ (± 70)	(± 70)	¥Ι
Probe Calibration	E.2.1.	7	N	1 1	1	1	7	7	
	E.2.2.	2,5	R	√3	$(1-c_p)^{1/2}$	/4 = \1/2	1.00000	1,02062	
Axial Isotropy						$(1-c_p)^{1/2}$		<u> </u>	_
Hemispherical Isotropy	E.2.2.	4	R	√3	√Cp	√Cp		1,63299	
Boundary Effect	E.2.3.	1	R	√3	1	1		0,57735	
Linearity	E.2.4.	5	R	√3	1	1		2,88675	
System Detection Limits	E.2.5.	1	R	√3	1	1		0,57735	
Readout Electronics	E.2.6.	0,02	N	1 /-	1	1	0,02	0,02	
Response Time	E.2.7.	3	R	√3	1	1	_	1,73205	_
Integration Time	E.2.8.	2	R	√3	1	1	1,1547	1,1547	
RF Ambient Conditions	E.6.1.	3	R	√3	1	1	1,73205	1,73205	
Probe Positioner Mechanical									
Tolerance	E.6.2.	2	R	√3	1	1	1,1547	1,1547	
Probe Positioning with respect to									
Phantom Shell	E.6.3.	0,05	R	√3	1	1	0,02887	0,02887	00
Extrapolation, interpolation and									
Integration Algorithms for Max. SAR		_							
Evaluation	E.5.2.	5	R	√3	1	1	2,88675	2,88675	ω
Test sample Related									
Test Sample Positioning	E.4.2.1.	0,03	N	1	1	1	0,03	0,03	
Device Holder Uncertainty	E.4.1.1.	5	N	1	1	1	5	5	N-1
Output Power Variation - SAR drift							4 70005	4 70005	
measurement	6.6.2.	3	R	√3	1	1	1,/3205	1,73205	
Phantom and Tissue Parameters	I			Г	Π				Г
Phantom Uncertainty (shape and		0.05			_	_	0.00007	0.00007	
thickness tolerances)	E.3.1.	0,05	R	√3	1	1	0,02887	0,02887	
Liquid Conductivity - deviation from		_		l ./a	0.04	0.40	4 04750	4 2442	
target values	E.3.2.	5	R	√3	0,64	0,43	1,84752	1,2413	·
Liquid Conductivity - measurement	E22	5	, NI	1	0.64	0.42		2 45	
uncertainty Liquid Permittivity - deviation from	E.3.3.	5	N		0,64	0,43	3,2	2,15	IM
	E22	3	R	√3	n e	0.40	1,03923   1,03923	0.0407	_
target values Liquid Permittivity - measurement	E.3.2.		R	73	0,6	0,49	1,03923	0,8487	100
	E22	40	NI NI	4	ne l	0.40		4.0	l <sub>M</sub>
uncertainty	E.3.3.	10	N	1	0,6	0,49	6	4,9	IM
Combined Standard Uncertainty			RSS				   11,1265	10,5799	
Expanded Uncertainty			1,00				11,1200	10,0100	
(95% CONFIDENCE INTERVAL)			k=2				21,8079	00.7000	

Date of Issue: March 17, 2010

9. EXPOSURE LIMIT

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

**Note:** Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 1 grams of tissue defined as a tissue volume in the shape of a cube.

<u>Population/Uncontrolled Environments</u> are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

<u>Occupational/Controlled Environments</u> are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg

Page 15 Rev. 00

Date of Issue: March 17, 2010

Report No: KS100315B01

Date of Issue: March 17, 2010

#### 10. **EUT ARRANGEMENT**

Please refer to IEEE P1528 illustration below.

#### 10.1 ANTHROPOMORPHIC HEAD PHANTOM

Figure 7-1a shows the front, back and side views of SAM. The point "M" is the reference point for the center of mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERPs are 15 mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 7-1b. The plane passing through the two ear reference points and M is defined as the Reference Plane. The line N-F (Neck-Front) perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 7-1c). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines should be marked on the external phantom shell to facilitate handset positioning. Posterior to the N-F line, the thickness of the phantom shell with the shape of an ear is a flat surface 6 mm thick at the ERPs. Anterior to the N-F line, the ear is truncated as illustrated in Figure 7-1b. The ear truncation is introduced to avoid the handset from touching the ear lobe, which can cause unstable handset positioning at the cheek.

> Figure 7-1a Front, back and side view of SAM (model for the phantom shell)



Figure 7-1b Close up side view of phantom showing the ear region




Figure 7-1b Close up side view of phantom showing the ear region

Figure 7-1c Side view of the phantom showing relevant markings and the 7 cross sectional plane locations




Figure 7-1c Side view of the phantom showing relevant markings and the 7 cross sectional plane locations

Page 16 Rev. 00

## 10.2 DEFINITION OF THE "CHEEK/TOUCH" POSITION

The "cheek" or "touch" position is defined as follows:

a. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover. (If the handset can also be used with the cover closed both configurations must be tested.)

Date of Issue: March 17, 2010

- b. Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width wt of the handset at the level of the acoustic output (point A on Figures 7-2a and 7-2b), and the midpoint of the width wb of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 7-2a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 7-2b), especially for clamshell handsets, handsets with flip pieces, and other irregularly-shaped handsets.
- c. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 7-2c), such that the plane defined by the vertical center line and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
- d. Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the pinna.
- e. e) While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
- f. Rotate the handset around the vertical centerline until the handset (horizontal line) is symmetrical with respect to the line NF.
- g. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the handset contact with the pinna, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the pinna (cheek). See Figure 7-2c. The physical angles of rotation should be noted.





Figure 7.2c

Phone "cheek" or "touch" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for handset positioning, are indicated.

Page 17 Rev. 00






Figure 7.2a Figure 7.2b

#### 10.3 DEFINITION OF THE "TILTED" POSITION

The "tilted" position is defined as follows:

- a. Repeat steps (a) (g) of 7.2 to place the device in the "cheek position."
- b. While maintaining the orientation of the handset move the handset away from the pinna along the line passing through RE and LE in order to enable a rotation of the handset by 15 degrees.
- c. Rotate the handset around the horizontal line by 15 degrees.
- d. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna (e.g., the antenna with the back of the phantom head), the angle of the handset should be reduced. In this case, the tilted position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is contact with the phantom (e.g., the antenna with the back of the head).




Figure 7-3
Phone "tilted" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for handset positioning, are indicated.

Page 18 Rev. 00

# 11. MEASUREMENT RESULTS

#### 11.1 TEST LIQUIDS CONFIRMATION

#### SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION

The dielectric parameters were checked prior to assessment using the HP85070C dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

Date of Issue: March 17, 2010

#### IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and

extrapolated according to the head parameters specified in P1528

Target Frequency	He	ead	Body		
(MHz)	ε <sub>r</sub> σ (S/m)		$\epsilon_{\rm r}$	σ (S/m)	
150	52.3	0.76	61.9	0.80	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	0.98	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800-2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	45.3	5.27	48.2	6.00	

(ε<sub>r</sub> = relative permittivity, σ = conductivity and ρ = 1000 kg/m<sup>3</sup>)

Page 19 Rev. 00

## LIQUID MEASUREMENT RESULTS

#### Ambient condition:

Temperature: 21 °C Relative humidity: 58%

Date: March 16, 2010

Head Simulatinf Liquid		Parameters	Target	Measured	Deviation[%]	Limited[%]		
Frequency	Temp. [°C]	Depth [cm]	Farameters	ranget	Measureu	Deviation[%]	Limited[%]	
835 MHz	835 MHz 23.50 15.00	Permitivity:	41.5	41.047	1.09	± 5		
633 WIIIZ	23.30	13.00	Conductivity:	0.9	0.901	-0.11	± 5	

Date of Issue: March 17, 2010

#### **Ambient condition:**

Temperature: <u>21</u> °C Relative humidity: <u>58</u>%

Date: March 16, 2010

Body Simulatinf Liquid		Param eters Param eters	Target	Measured	Deviation[%]	Limited[%]		
Frequency	Temp. [°C]	Depth [cm]	1 arameters	Target	wieas ureu	Deviation[%]	Limited[%]	
835 MHz	835 MHz 23.50 15.00		Permitivity:	55.2	54.021	2.13	± 5	
033 WIIIZ	23.30	13.00	Conductivity:	0.97	0.938	3.4	± 5	

#### 11.2 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of  $\pm 10\%$ . The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

IEEE P1528 Recommended Reference Value

Frequency (MHz)	1 g SAR	10 g SAR	Local SAR at surface (Above feed point)	Local SAR at surface (y=2cm offset from feed point)
300	3.0	2.0	4.4	2.1
450	4.9	3.3	7.2	3.2
835	9.5	6.2	14.1	4.9
900	10.8	6.9	16.4	5.4
1450	29.0	16.0	50.2	6.5
1800	38.1	19.8	69.5	6.8
1900	38.8	20.4	67.6	6.6
2000	41.1	21.1	74.6	6.5
2450	52.4	24.0	104.2	7.7
3000	63.8	25.7	140.2	9.5

Page 20 Rev. 00

## SYSTEM PERFORMANCE CHECK RESULTS

Dipole: DIPOLE850 SN:SN 48/05 DIPC32

**Date:** March 16, 2010

**Ambient condition:** Temperature: <u>21</u> °C Relative humidity: <u>58</u>%

Неас	Head Simulatinf Liquid		Daramatare	Parameters Target		Deviation[%]	Limited[%]	
Frequency	Temp. [°C]	Depth [cm]	1 arameters	rarget	Measured	Deviation[%]	Limited[%]	
		Permitivity:	41.5	41.047	1.09	± 5		
835 MHz 20.00	20.00	15.00	Conductivity:	0.9	0.901	-0.11	± 5	
		1 g SAR:	9.41	9.201	2.22	± 10		

Date of Issue: March 17, 2010

Dipole: DIPOLE850 SN:SN 48/05 DIPC32

Date: March 16, 2010

**Ambient condition:** Temperature: <u>21</u> °C Relative humidity: <u>58</u>%

Body	Body Simulatinf Liquid		Param eters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth [cm]	1 arameters	rarget	wie as ureu	Deviation[/// ]	Limiteu[%]
835.00 20.00			Permitivity:	55.2	54.021	2.13	± 5
	20.00	15.00	Conductivity:	0.97	0.938	3.4	± 5
			1 g SAR:	9.79	9.745	0.46	± 10

ps. 1g SAR is equal 4x10.2(250mW forward power SAR value)

Page 21 Rev. 00

#### 11.3 EUT TUNE-UP PROCEDURES AND TEST MODE

The following procedure had been used to prepare the EUT for the SAR test.

 The client supplied a special driver to program the EUT, allowing it to continually transmit the specified maximum power and change the channel frequency.

Date of Issue: March 17, 2010

- The conducted power was measured at the high, middle and low channel frequency before and after the SAR measurement.
- o During SAR test, the highest output channel per band measured first.

**GSM 850 / GPRS 850 / EDGE 850** 

Network Support: GSM only / GPRS/EDGE

Main Service: Circuit Switched / Packet data / Packet data


Power Setting: 33dBm / 33dBm / 33dBm

Class: B

Class: 12 (4 Up / 1 Down) WCDMA Band V/ HSDPA

Network Support: WCDMA / HSDPA

o the depth of Liquid must above 15cm.



Output powers are measured as below:

Page 22 Rev. 00

#### 11.4 RF POWER OUTPUT FOR UMTS REL99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V8.5.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

Date of Issue: March 17, 2010

-	Mode	Rel99
	Subtest	-
	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	HSDPA FRC	Not Applicable
	HSUPA Test	Not Applicable
WCDMA General	Power Control Algorithm	Algorithm2
Settings	βс	Not Applicable
Settings	βd	Not Applicable
	βес	Not Applicable
	βc/βd	8/15
	βhs	Not Applicable
	βed	Not Applicable

#### **REL 99**

Band	UL Ch DL Ch		Frequency	Conducted output power (dBm)	
			, ,	Average	
	4132	4357	826.4	24.53	
UMTS850 (Band V)	4183	4407	836.4	23.57	
(200 7)	4233	4458	846.6	23.96	

#### 11.5 RF POWER OUTPUT FOR UMTS REL 5 HSDPA

The following Sub-Tests were completed according to the test requirements outlined in section 5.2A of the 3GPP TS34.121-1 V8.5.0 specification. All TX RMS and Peak power requirements for Power Class 3 were met according to table 5.2AA.5 and achieved through the outlined test procedure in section 5.2AA.4.2. A summary of these settings are illustrated below:

	Mode	Rel6 HSDPA	Rel6 HSDPA	Rel6 HSDPA	Rel6 HSDPA			
	Subtest	1	2	3	4			
	Loopback Mode	Test Mode 1						
	Rel99 RMC	12.2kbps RMC						
	HSDPA FRC	H-Set1						
	HSUPA Test	Not Applicable						
WCDMA	Power Control Algorithm	Algorithm 2						
General	βс	2/15	12/15	15/15	15/15			
Settings	βd	15/15	15/15	8/15	4/15			
	βec	-	-	-	-			
	Rel99 RMC	12/15	15/8	15/4				
	βhs	4/15	2 3 12/15 15/15 15/15 8/15 	30/15				
	βed	Not Applicable						
	DACK	8						
	DNAK	8						
HSDPA	DCQI	8						
Specific	Ack-Nack repetition factor	3						
Settings	CQI Feedback (Table 5.2B.4)	4ms						
	CQI Repetition Factor (Table 5.2B.4)	2						
	Ahs = βhs/βc	30/15						

Page 23 Rev. 00

#### Result

#### **REL 5 HSDPA only**

Band	Subtest	UL Ch	DL Ch	Frequency	Conducted output power (dBm)  Average
		4132	4357	826.4	22.49
	1	4183	4407	836.4	22.47
		4233	4458		22.43
	2	4132	4357	826.4	22.35
		4183	4407	836.4	22.38
UMTS850		4233	4458	846.6	22.34
(Band V)		4132	4357	826.4	21.92
	3	4183	4407	836.4	21.88
		4233	4458	846.6	21.85
		4132	4357	826.4	21.87
	4	4183	4407	836.4	21.86
		4233	4458	846.6	21.82

The respectively maximum output powers of each RF modes are as below:

Conducted output power (Average)(dBm)

<u> </u>	Solidatica output power (Average)(abin)										
GSM		GSM	mode		mode S 4Up)	EDGE (GPRS	mode S 4Up)				
		before	after	before	after	before	after				
	Ch 128	32.89	32.87	32.88	32.87	32.89	32.87				
GSM850	Ch 180	32.57	32.56	32.55	32.54	32.54	32.53				
	Ch 251	31.47	31.45	31.45	31.44	31.43	31.42				

Conducted output power (Average)(dBm)

WCDMA		WCDM	A mode	HSDPA mode		
		before	after	before	after	
Band V	Ch 4132	24.53	24.49	22.49	22.45	
	Ch 4183	23.57	23.53	22.47	22.43	
	Ch 4233	23.96	23.92	22.43	22.40	

**Notice:** Due to this EUT operates with 3GPP Release 5 function, according to the KDB 941225, we have to submit a Permit-But-Ask to FCC before we perform any SAR tests. According to the KDB Tracking Number 902030(for WCDMA/HSDPA/HSUPA), FCC administrator approves our PBA and SAR exclusion for HSPA in this EUT.


Page 24 Rev. 00

Date of Issue: March 17, 2010

# **11.6 EUT SETUP PHOTOS**


# **EUT Setup Configuration 1**

the back side of the EUT in body position with GSM



# **EUT Setup Configuration 2**

Cheek device with head phantom.



Page 25 Rev. 00



Report No: KS100315B01


Date of Issue: March 17, 2010

# **EUT Setup Configuration 3**

Tilt device with head phantom.



<u>EUT Setup Configuration 4</u> the back side of the EUT in body position with GPRS



Page 26 Rev. 00

## 11.7 SAR MEASUREMENT RESULTS

Date of Measurement: March 16, 2010

SAR Measurement G	;SM	850
-------------------	-----	-----

Crest Factor: <u>8</u> (Duty cycle: <u>12.5%</u>) Depth of Liquid: <u>15.0</u> cm

# **EUT Configuration 1**

EUT Setup Condition		Frequer	ncv		ed Power	Liquid	SAR(1g)	Limit
Condi	tion	n (dBm)		Bm)	Temp		Limit	
Position	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
Flat (1.5cm)		128	824.2	32.89	32.87	20.0	0.254	
	Fixed	180	836.6	32.57	32.56	20.0	0.276	1.6
		251	848.8	31.47	31.45	20.0	0.319	

# **EUT Configuration 2**

	UT S Condi	•	Frequer	псу	Conducted Power (dBm)		Liquid Temp	<b>SAR</b> (1g)	Limit
Position	on	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
	ad	ad	128	824.2	32.89	32.87	20.0	0.827	
	Righthead Signature Signat	Fixed	180	836.6	32.57	32.56	20.0	0.841	
cheek			251	848.8	31.47	31.45	20.0	0.813	1.6
CHECK	head		128	824.2	32.89	32.87	20.0	0.901	1.0
I I I	Fixed	180	836.6	32.57	32.56	20.0	0.821		
	Left		251	848.8	31.47	31.45	20.0	0.815	

# **EUT Configuration 3**

	EUT Setup Condition Frequency		псу		ed Power 3m)	Liquid Temp	<b>SAR</b> (1g)	Limit	
Positi	on	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
	ad	Righthead Pexid	128	824.2	32.89	32.87	20.0	0.572	
	hthe		180	836.6	32.57	32.56	20.0	0.639	1.6
tilt	Rig		251	848.8	31.47	31.45	20.0	0.598	
""	ad		128	824.2	32.89	32.87	20.0	0.456	1.0
		Fixed	180	836.6	32.57	32.56	20.0	0.524	
	Left		251	848.8	31.47	31.45	20.0	0.539	

Page 27 Rev. 00

Date of Measurement: March 16, 2010

SAR Measurement	GPRS 850 Class 12
-----------------	-------------------

Crest Factor: <u>2</u> (Duty cycle: <u>50%</u>) Depth of Liquid: <u>15.0</u> cm

# **EUT Configuration 4**

EUT S Cond	•	Frequency		Conducted Power (dBm)		Liquid Temp	SAR(1g)	Limit
Position	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
	128	824.2	32.88	32.87	20.0	0.287		
<b>Flat</b> (1.5cm)	Fixed	180	836.6	32.55	32.54	20.0	0.312	1.6
(1.5611)		251	848.8	31.45	31.44	20.0	0.323	

SAR Measurement EDGE 850 Class 12

Crest Factor: <u>2</u> (Duty cycle: <u>50%</u>) Depth of Liquid: <u>15.0</u> cm

EUT Configuration 4								
EUT S Cond	•	Frequency		Conducted Power (dBm)		Liquid Temp	SAR(1g) (W/kg)	Limit
Position	Antenna	Channel	MHz	Before	After	[°C]	(vv/kg)	(W/kg)
Flat (1.5cm) Fixed	128	824.2	32.89	32.87	20.0	0.285		
	180	836.6	32.54	32.53	20.0	0.314	1.6	
		251	848.8	31.43	31.42	20.0	0.324	

Page 28 Rev. 00

	SAR Measurement	WCDMA band V
--	-----------------	--------------

Crest Factor: <u>1</u> (Duty cycle: <u>100%</u>) Depth of Liquid: <u>15.0</u> cm

# **EUT Configuration 1**

	EUT Setup Condition Frequen		псу	y Conducted Power (dBm)		Liquid Temp	SAR(1g)	Limit
Position	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
Flat (1.5cm)	Fixed	4132	826.4	24.53	24.49	20.0	0.199	
		4183	836.4	23.57	23.53	20.0	0.215	1.6
		4233	846.6	23.96	23.92	20.0	0.246	

# **EUT Configuration 2**

	UT S Condi	•	Frequency		Conducted Power (dBm)		Liquid Temp	SAR(1g)	Limit
Position	on	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
	ad		4132	826.4	24.53	24.49	20.0	0.826	
	Righthead	Fixed	4183	836.4	23.57	23.53	20.0	0.842	
cheek	Rig		4233	846.6	23.96	23.92	20.0	0.811	1.6
Oncor	head		4132	826.4	24.53	24.49	20.0	0.897	1.0
	Left_he		4183	836.4	23.57	23.53	20.0	0.820	
			4233	846.6	23.96	23.92	20.0	0.813	

# **EUT Configuration 3**

	UT S Condi	•	Frequency		Conducted Power (dBm)		Liquid Temp	SAR(1g)	Limit
Positi	on	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
	∓ Righthead		4132	826.4	24.53	24.49	20.0	0.571	
		Fixed	4183	836.4	23.57	23.53	20.0	0.637	
tilt			4233	846.6	23.96	23.92	20.0	0.593	1.6
	ad		4132	826.4	24.53	24.49	20.0	0.455	1.0
	Fixed	4183	836.4	23.57	23.53	20.0	0.522		
	Left		4233	846.6	23.96	23.92	20.0	0.538	

Page 29 Rev. 00

SAR Measurement HSD	OPA band V
---------------------	------------

Crest Factor: <u>1</u> (Duty cycle: <u>100%</u>) Depth of Liquid: <u>15.0</u> cm

# **EUT Configuration 4**

EUT S Cond	•	Frequency		Conducted Power (dBm)		Liquid Temp	SAR(1g)	Limit
Position	Antenna	Channel	MHz	Before	After	[°C]	(W/kg)	(W/kg)
Flat (1.5cm) Fixed	4132	826.4	22.49	22.45	20.0	0.197		
	Fixed	4183	836.4	22.47	22.43	20.0	0.214	1.6
		4233	846.6	22.43	22.40	20.0	0.245	

Page 30 Rev. 00

#### **EUT PHOTO 12.**





Page 31 Rev. 00







Page 32 Rev. 00





Page 33 Rev. 00





Page 34 Rev. 00

Report No: KS100315B01

Date of Issue: March 17, 2010

#### **EQUIPMENT LIST & CALIBRATION STATUS** 13.

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Due
PC	HP	PV 3.06GHz	375052-AA1	N/A
Signal Generator	Agilent	E8257C	MY43321570	12/11/2010
MultiMeter	Keithley	2000	1015843	05/01/2010
S-Parameter Network Analyzer	Agilent	E5071B	MY42301382	08/07/2010
Wireless Communication Test Set	R&S	CMU200	SN:B23-03291	06/17/2010
Power Meter	Agilent	E4416A	QB41292714	07/29/2010
E-field PROBE	ANTENNESSA	EP_100	SN1109	04/16/2010
DIPOLE 835	ANTENNESSA	DIPC32	SN 48/05	12/10/2010
DIPOLE 900	ANTENNESSA	DIPD33	SN 48/05	12/10/2010
DIPOLE 1800	ANTENNESSA	DIPF34	SN 48/05	12/10/2010
DIPOLE 1900	ANTENNESSA	DIPI36	SN 48/05	12/10/2010
DIPOLE 2450	ANTENNESSA	DIPJ37	SN 48/05	12/10/2010
POSITIONING DEVICE	ANTENNESSA	MSH_14	SN 41_05	N/A
DUMMY PROBE	ANTENNESSA	DP_12	SN 39_05	N/A
SAM PHANTOM	ANTENNESSA	SAM29	SN 41_05	N/A
PHANTON WOOD TABLE	ANTENNESSA	N/A	N/A	N/A
6 AXIS ROBOT	KUKA	KR3	846428	N/A
ROBOT KRC	KUKA	KCP2	01436	N/A
CHANELS SCAN CARD	KEITHLEY	2000	2000-172-01B	N/A
PROBE/ROBOT POSITIONING DEVICE	ANTENNESSA	MSH14	SN 41_05	N/A
LIQUID CALIBRATION KIT	ANTENNESSA	41/05 OCP9	00425167	N/A

Page 35 Rev. 00

## 14. FACILITIES

All measurement facilities used to collect the measurement data are located at

Date of Issue: March 17, 2010

No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, PRC.

## 15. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, O\_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-\_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph K.astle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-\_eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_ 97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-\_eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

Page 36 Rev. 00

# 16. ATTACHMENTS

Exhibit	Content
1	System Validation Plots
2	SAR Test Plots
3	Dipole calibration report (850MHz/1900MHz)
4	E-field calibration report

Date of Issue: March 17, 2010

# **END OF REPORT**

Page 37 Rev. 00