



FCC RF Test Report

APPLICANT : Datalogic S.r.l.
EQUIPMENT : MOBILE COMPUTER/BARCODE
READER
BRAND NAME : DATALOGIC
MODEL NAME : AELNRNA
FCC ID : U4G-AELNRNA
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Nov. 21, 2024 ~ Jan. 28, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	19
3.5 Radiated Band Edges and Spurious Emission Measurement	20
3.6 AC Conducted Emission Measurement.....	24
3.7 Antenna Requirements.....	26
4 LIST OF MEASURING EQUIPMENT	27
5 MEASUREMENT UNCERTAINTY	28
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4N0543C	Rev. 01	Initial issue of report	Feb. 24, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.22 dB at 2483.50 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.21 dB at 0.620 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Datalogic S.r.l.

Via San Vitalino 13 CALDERARA DI RENO, BO 40012 Italy

1.2 Manufacturer

Datalogic S.r.l.

Via San Vitalino 13 CALDERARA DI RENO, BO 40012 Italy

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	MOBILE COMPUTER/BARCODE READER
Brand Name	DATALOGIC
Model Name	AELNRNA
FCC ID	U4G-AELNRNA
IMEI Code	Conducted: 356616170008422 Conduction: 356616170010147/356616170010154 Radiation: 004400152020000
HW Version	V3
SW Version	1.18.001.20241225
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	<MIMO Ant. 8+9> 802.11b : 25.11 dBm (0.3243 W) 802.11g : 27.42 dBm (0.5521 W) 802.11n HT20 : 27.17 dBm (0.5212 W) 802.11n HT40 : 27.38 dBm (0.5470 W) 802.11ac VHT20 : 27.12 dBm (0.5152 W) 802.11ac VHT40 : 27.32 dBm (0.5395 W) 802.11ax HE20 : 28.66 dBm (0.7345 W) 802.11ax HE40 : 27.55 dBm (0.5689 W)
99% Occupied Bandwidth	802.11b : 12.947MHz 802.11g : 16.503MHz 802.11n HT20 : 17.702MHz 802.11n HT40 : 36.044MHz 802.11ax HE20 : 18.941MHz 802.11ax HE40 : 37.802MHz
Antenna Type / Gain	<Ant. 8> : LDS Antenna type with gain -1.00 dBi <Ant. 9> : LDS Antenna type with gain -0.50 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

Note:

1. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal output power.
2. For 802.11n/ac & 802.11ax mode, the whole testing have assessed only 802.11ax HE20/40 by referring to the higher output power.
3. 802.11ax support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power, the full RU power/PSD > partial RU, therefore the full RU perform full, and partial RU verify bandedge/spurious.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH06-KS TH01-KS	CN1257	314309

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO02-SZ	CN1256	421272

Note: Test data subcontracted: Conduction test case in section 3.6 of this report

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO02-SZ	AUDIX	E3	6.120613b



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z for Adapter mode, Cradle mode and Earphone mode. The worst cases (X plane-Adapter mode) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

MIMO Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS8
802.11n HT40	MCS8
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :BT Link+ WLAN Link(2.4G)+ USB Cable(Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performed with Adapter and USB Cable.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,2.7m with Core
2.	Bluetooth Earphone	Samsung	EO-MG900	N/A	N/A	N/A
3.	Notebook	Lenovo	E540	FCC DoC	N/A	Unshielded,1.8m
4.	Adapter	N/A	N/A	N/A	N/A	N/A
5.	USB Cable	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.25 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.25 + 20 = 22.25 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

2.4GHz Band MIMO																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	
11b	1Mbps	2	1	2412	22.52	21.64	25.11	30.00		-0.50		24.61		36.00		Pass
11b	1Mbps	2	6	2437	22.31	21.66	25.01	30.00		-0.50		24.51		36.00		Pass
11b	1Mbps	2	11	2462	22.36	21.67	25.04	30.00		-0.50		24.54		36.00		Pass
11g	6Mbps	2	1	2412	24.52	24.19	27.37	30.00		-0.50		26.87		36.00		Pass
11g	6Mbps	2	6	2437	24.33	24.15	27.25	30.00		-0.50		26.75		36.00		Pass
11g	6Mbps	2	11	2462	24.47	24.34	27.42	30.00		-0.50		26.92		36.00		Pass
HT20	MCS8	2	1	2412	24.31	23.97	27.15	30.00		-0.50		26.65		36.00		Pass
HT20	MCS8	2	6	2437	24.09	24.04	27.08	30.00		-0.50		26.58		36.00		Pass
HT20	MCS8	2	11	2462	24.23	24.08	27.17	30.00		-0.50		26.67		36.00		Pass
HT40	MCS8	2	3	2422	24.22	24.11	27.18	30.00		-0.50		26.68		36.00		Pass
HT40	MCS8	2	6	2437	24.27	24.24	27.27	30.00		-0.50		26.77		36.00		Pass
HT40	MCS8	2	9	2452	24.42	24.32	27.38	30.00		-0.50		26.88		36.00		Pass
VHT20	MCS0	2	1	2412	24.28	23.82	27.07	30.00		-0.50		26.57		36.00		Pass
VHT20	MCS0	2	6	2437	24.02	24.00	27.02	30.00		-0.50		26.52		36.00		Pass
VHT20	MCS0	2	11	2462	24.19	24.02	27.12	30.00		-0.50		26.62		36.00		Pass
VHT40	MCS0	2	3	2422	24.17	24.05	27.12	30.00		-0.50		26.62		36.00		Pass
VHT40	MCS0	2	6	2437	24.21	24.06	27.15	30.00		-0.50		26.65		36.00		Pass
VHT40	MCS0	2	9	2452	24.34	24.27	27.32	30.00		-0.50		26.82		36.00		Pass

2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	
HE20	MCS0	2	1	2412	Full	25.66	25.39	28.54	30.00		-0.50		28.04		36.00		Pass
HE20	MCS0	2	1	2412	26/0	21.14	20.97	24.07	30.00		-0.50		23.57		36.00		Pass
HE20	MCS0	2	1	2412	52/37	23.08	22.49	25.81	30.00		-0.50		25.31		36.00		Pass
HE20	MCS0	2	1	2412	106/53	25.95	24.27	28.20	30.00		-0.50		27.70		36.00		Pass
HE20	MCS0	2	6	2437	Full	25.45	25.24	28.36	30.00		-0.50		27.86		36.00		Pass
HE20	MCS0	2	6	2437	26/0	21.09	20.64	23.88	30.00		-0.50		23.38		36.00		Pass
HE20	MCS0	2	6	2437	52/37	23.38	22.99	26.20	30.00		-0.50		25.70		36.00		Pass
HE20	MCS0	2	6	2437	106/53	25.50	24.67	28.12	30.00		-0.50		27.62		36.00		Pass



HE20	MCS0	2	11	2462	Full	25.53	25.77	28.66	30.00	-0.50	28.16	36.00	Pass
HE20	MCS0	2	11	2462	26/8	21.52	19.98	23.83	30.00	-0.50	23.33	36.00	Pass
HE20	MCS0	2	11	2462	52/40	24.55	24.11	27.35	30.00	-0.50	26.85	36.00	Pass
HE20	MCS0	2	11	2462	106/54	25.53	25.77	28.66	30.00	-0.50	28.16	36.00	Pass
HE40	MCS0	2	3	2422	Full	24.47	24.23	27.36	30.00	-0.50	26.86	36.00	Pass
HE40	MCS0	2	6	2437	Full	24.45	24.38	27.43	30.00	-0.50	26.93	36.00	Pass
HE40	MCS0	2	9	2452	Full	24.61	24.47	27.55	30.00	-0.50	27.05	36.00	Pass

3.2.6 Test Result of Average Output Power (Reporting Only)

2.4GHz Band MIMO																				
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	Setting	
					Ant8	Ant9	Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9		Ant8	Ant9
11b	1Mbps	2	1	2412	0.00	0.00	19.95	19.18	22.59	30.00		-0.50		22.09		36.00		Pass	19.00	
11b	1Mbps	2	6	2437	0.00	0.00	19.71	19.12	22.44	30.00		-0.50		21.94		36.00		Pass	19.00	
11b	1Mbps	2	11	2462	0.00	0.00	19.78	19.15	22.49	30.00		-0.50		21.99		36.00		Pass	19.00	
11g	6Mbps	2	1	2412	0.03	0.03	18.20	17.97	21.10	30.00		-0.50		20.60		36.00		Pass	18.00	
11g	6Mbps	2	6	2437	0.03	0.03	18.08	17.90	21.00	30.00		-0.50		20.50		36.00		Pass	18.00	
11g	6Mbps	2	11	2462	0.03	0.03	18.18	18.00	21.10	30.00		-0.50		20.60		36.00		Pass	18.00	
HT20	MCS8	2	1	2412	0.00	0.00	17.81	17.49	20.66	30.00		-0.50		20.16		36.00		Pass	18.00	
HT20	MCS8	2	6	2437	0.00	0.00	17.69	17.57	20.64	30.00		-0.50		20.14		36.00		Pass	18.00	
HT20	MCS8	2	11	2462	0.00	0.00	17.75	17.64	20.71	30.00		-0.50		20.21		36.00		Pass	18.00	
HT40	MCS8	2	3	2422	0.00	0.00	17.41	17.12	20.28	30.00		-0.50		19.78		36.00		Pass	18.00	
HT40	MCS8	2	6	2437	0.00	0.00	17.39	17.16	20.29	30.00		-0.50		19.79		36.00		Pass	18.00	
HT40	MCS8	2	9	2452	0.00	0.00	17.49	17.35	20.43	30.00		-0.50		19.93		36.00		Pass	18.00	
VHT20	MCS0	2	1	2412	0.00	0.00	17.74	17.43	20.60	30.00		-0.50		20.10		36.00		Pass	18.00	
VHT20	MCS0	2	6	2437	0.00	0.00	17.65	17.55	20.61	30.00		-0.50		20.11		36.00		Pass	18.00	
VHT20	MCS0	2	11	2462	0.00	0.00	17.71	17.62	20.68	30.00		-0.50		20.18		36.00		Pass	18.00	
VHT40	MCS0	2	3	2422	0.00	0.00	17.38	17.09	20.25	30.00		-0.50		19.75		36.00		Pass	18.00	
VHT40	MCS0	2	6	2437	0.00	0.00	17.31	17.13	20.23	30.00		-0.50		19.73		36.00		Pass	18.00	
VHT40	MCS0	2	9	2452	0.00	0.00	17.44	17.32	20.39	30.00		-0.50		19.89		36.00		Pass	18.00	



2.4GHz Band MIMO																					
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	Setting	
						Ant8	Ant9	Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9		Ant8	Ant9
HE20	MCS0	2	1	2412	Full	0.00	0.00	18.03	17.73	20.89	30.00		-0.50		20.39		36.00		Pass	18.00	
HE20	MCS0	2	1	2412	26/0	0.00	0.00	10.24	9.61	12.95	30.00		-0.50		12.45		36.00		Pass	9.50	
HE20	MCS0	2	1	2412	52/37	0.00	0.00	12.44	11.52	15.01	30.00		-0.50		14.51		36.00		Pass	12.00	
HE20	MCS0	2	1	2412	106/53	0.00	0.00	15.02	14.35	17.71	30.00		-0.50		17.21		36.00		Pass	14.50	
HE20	MCS0	2	6	2437	Full	0.00	0.00	17.83	17.71	20.78	30.00		-0.50		20.28		36.00		Pass	18.00	
HE20	MCS0	2	6	2437	26/0	0.00	0.00	10.41	9.59	13.03	30.00		-0.50		12.53		36.00		Pass	9.50	
HE20	MCS0	2	6	2437	52/37	0.00	0.00	12.96	12.07	15.55	30.00		-0.50		15.05		36.00		Pass	12.50	
HE20	MCS0	2	6	2437	106/53	0.00	0.00	15.04	14.41	17.75	30.00		-0.50		17.25		36.00		Pass	14.50	
HE20	MCS0	2	11	2462	Full	0.00	0.00	17.96	17.79	20.89	30.00		-0.50		20.39		36.00		Pass	18.00	
HE20	MCS0	2	11	2462	26/8	0.00	0.00	10.62	10.45	13.55	30.00		-0.50		13.05		36.00		Pass	10.00	
HE20	MCS0	2	11	2462	52/40	0.00	0.00	13.33	12.89	16.13	30.00		-0.50		15.63		36.00		Pass	13.00	
HE20	MCS0	2	11	2462	106/54	0.00	0.00	15.66	15.41	18.55	30.00		-0.50		18.05		36.00		Pass	15.50	
HE40	MCS0	2	3	2422	Full	0.00	0.00	17.42	17.14	20.29	30.00		-0.50		19.79		36.00		Pass	18.00	
HE40	MCS0	2	6	2437	Full	0.00	0.00	17.41	17.18	20.31	30.00		-0.50		19.81		36.00		Pass	18.00	
HE40	MCS0	2	9	2452	Full	0.00	0.00	17.51	17.38	20.46	30.00		-0.50		19.96		36.00		Pass	18.00	

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01:

Method (b): Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<STBC Modes>

For completely uncorrelated transmissions, directional gain is calculated as,

Directional gain = $G_{ANT\ MAX}(\text{Ant.1 Gain, Ant.2 Gain,...})$, as following table

<STBC Modes>						
			DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
	Ant. 8 (dBi)	Ant. 9 (dBi)				
2.4 GHz	-1.00	-0.50	-0.50	-0.50	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$

This device supports STBC mode, not support CDD (Cyclic Delay Diversity) mode which controlled by Qualcomm chipset software. This chipset support WIFI MIMO(2*2), and support STBC mode by manufacturer declared.

Space time block coding (STBC) transmits multiple copies of one data flow in wireless communication. STBC uses two antennas (Ant 8 and Ant 9) to produce multiple receive versions of data, improving data transmission reliability. Among these data copies, optimal copies are combined to provide most reliable data. This redundancy increases the chance of using one or more copies of received data to correctly decode the received data. STBC combines all the copies of received signals to produce the useful data.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Nov. 21, 2024~Dec. 04, 2024	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 03, 2024	Nov. 21, 2024~Dec. 04, 2024	Jan. 02, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 03, 2024	Nov. 21, 2024~Dec. 04, 2024	Jan. 02, 2025	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max 30dBm	Jan. 03, 2025	Jan. 28, 2025	Jan. 02, 2026	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz~44GHz	Jul. 04, 2024	Jan. 28, 2025	Jul. 03, 2025	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jan. 28, 2025	Sep. 07, 2025	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz~1GHz	Sep. 03, 2024	Jan. 28, 2025	Sep. 02, 2025	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 11, 2024	Jan. 28, 2025	Apr. 10, 2025	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jan. 28, 2025	Oct. 21, 2025	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 04, 2024	Jan. 28, 2025	Jul. 03, 2025	Radiation (03CH06-KS)
Amplifier	EM	EM18G40GA	060728	18~40GHz	Jan. 03, 2025	Jan. 28, 2025	Jan. 02, 2026	Radiation (03CH06-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz~18Ghz	Jan. 03, 2025	Jan. 28, 2025	Jan. 02, 2026	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY57280119	500MHz~26.5GHz	Oct. 09, 2024	Jan. 28, 2025	Oct. 08, 2025	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 28, 2025	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 28, 2025	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 28, 2025	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 03, 2024	Dec. 11, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2024	Dec. 11, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002470	100Vac~250Vac	Dec. 26, 2023	Dec. 11, 2024	Dec. 25, 2024	Conduction (CO02-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.06dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.18dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.38dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results




DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant8	2412	7.56	2408.00	2415.56	0.5	PASS
	Ant9	2412	7.56	2408.48	2416.04	0.5	PASS
	Ant8	2437	7.60	2432.96	2440.56	0.5	PASS
	Ant9	2437	7.08	2433.48	2440.56	0.5	PASS
	Ant8	2462	7.12	2458.44	2465.56	0.5	PASS
	Ant9	2462	7.60	2458.44	2466.04	0.5	PASS
11G	Ant8	2412	13.80	2405.76	2419.56	0.5	PASS
	Ant9	2412	15.12	2404.44	2419.56	0.5	PASS
	Ant8	2437	15.52	2429.24	2444.76	0.5	PASS
	Ant9	2437	14.44	2429.48	2443.92	0.5	PASS
	Ant8	2462	15.32	2454.24	2469.56	0.5	PASS
	Ant9	2462	16.32	2453.84	2470.16	0.5	PASS
11N20MIMO	Ant8	2412	15.44	2404.44	2419.88	0.5	PASS
	Ant9	2412	16.52	2403.88	2420.40	0.5	PASS
	Ant8	2437	15.12	2429.44	2444.56	0.5	PASS
	Ant9	2437	16.32	2428.84	2445.16	0.5	PASS
	Ant8	2462	17.16	2453.24	2470.40	0.5	PASS
	Ant9	2462	17.60	2453.20	2470.80	0.5	PASS
11N40MIMO	Ant8	2422	35.12	2404.48	2439.60	0.5	PASS
	Ant9	2422	35.12	2404.48	2439.60	0.5	PASS
	Ant8	2437	35.04	2419.48	2454.52	0.5	PASS
	Ant9	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant8	2452	35.12	2434.48	2469.60	0.5	PASS
	Ant9	2452	35.12	2434.48	2469.60	0.5	PASS
11AX20MIMO	Ant8	2412	17.88	2403.04	2420.92	0.5	PASS
	Ant9	2412	17.84	2403.56	2421.40	0.5	PASS
	Ant8	2437	16.76	2428.68	2445.44	0.5	PASS
	Ant9	2437	15.44	2428.60	2444.04	0.5	PASS
	Ant8	2462	17.56	2452.76	2470.32	0.5	PASS
	Ant9	2462	18.52	2452.72	2471.24	0.5	PASS
11AX40MIMO	Ant8	2422	35.36	2404.24	2439.60	0.5	PASS
	Ant9	2422	35.44	2404.48	2439.92	0.5	PASS
	Ant8	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant9	2437	33.84	2420.68	2454.52	0.5	PASS
	Ant8	2452	36.08	2433.52	2469.60	0.5	PASS
	Ant9	2452	35.12	2434.48	2469.60	0.5	PASS




Test Graphs






11B_Ant8_2437




11B_Ant9_2437






11B_Ant8_2462



Date: 21.NOV.2024 23:19:32


11B_Ant9_2462




Date: 21.NOV.2024 23:21:12



11G_Ant8_2412




11G_Ant9_2412






11G_Ant8_2437




11G_Ant9_2437






11G_Ant8_2462



Date: 21.NOV.2024 23:34:28


11G_Ant9_2462



Date: 21.NOV.2024 23:36:08




11N20MIMO_Ant8_2412



Date: 21.NOV.2024 23:39:23


11N20MIMO_Ant9_2412



Date: 21.NOV.2024 23:41:03




11N20MIMO_Ant8_2437



Date: 21.NOV.2024 23:49:27


11N20MIMO_Ant9_2437



Date: 21.NOV.2024 23:50:49




11N20MIMO_Ant8_2462



Date: 21.NOV.2024 23:53:08


11N20MIMO_Ant9_2462



Date: 21.NOV.2024 23:54:48




11N40MIMO_Ant8_2422



Date: 21.NOV.2024 23:57:09


11N40MIMO_Ant9_2422




Date: 21.NOV.2024 23:58:50



11N40MIMO_Ant8_2437




11N40MIMO_Ant9_2437






11N40MIMO_Ant8_2452




11N40MIMO_Ant9_2452






11AX20MIMO_Ant8_2412




11AX20MIMO_Ant9_2412






11AX20MIMO_Ant8_2437




11AX20MIMO_Ant9_2437






11AX20MIMO_Ant8_2462




11AX20MIMO_Ant9_2462






11AX40MIMO_Ant8_2422




11AX40MIMO_Ant9_2422






11AX40MIMO_Ant8_2437




11AX40MIMO_Ant9_2437






11AX40MIMO_Ant8_2452



11AX40MIMO_Ant9_2452






Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant8	2412	12.907	2405.5664	2418.4735	---	---
	Ant9	2412	12.947	2405.6064	2418.5534	---	---
	Ant8	2437	12.867	2430.5664	2443.4336	---	---
	Ant9	2437	12.907	2430.5664	2443.4735	---	---
	Ant8	2462	12.907	2455.4865	2468.3936	---	---
	Ant9	2462	12.867	2455.5664	2468.4336	---	---
11G	Ant8	2412	16.464	2403.7682	2420.2318	---	---
	Ant9	2412	16.464	2403.8082	2420.2717	---	---
	Ant8	2437	16.503	2428.7283	2445.2318	---	---
	Ant9	2437	16.503	2428.7682	2445.2717	---	---
	Ant8	2462	16.464	2453.7283	2470.1918	---	---
	Ant9	2462	16.503	2453.7682	2470.2717	---	---
11N20MIMO	Ant8	2412	17.662	2403.1688	2420.8312	---	---
	Ant9	2412	17.662	2403.2088	2420.8711	---	---
	Ant8	2437	17.702	2428.1289	2445.8312	---	---
	Ant9	2437	17.662	2428.1688	2445.8312	---	---
	Ant8	2462	17.702	2453.0889	2470.7912	---	---
	Ant9	2462	17.662	2453.1688	2470.8312	---	---
11N40MIMO	Ant8	2422	35.964	2404.0180	2439.9820	---	---
	Ant9	2422	36.044	2404.0180	2440.0619	---	---
	Ant8	2437	35.964	2419.0180	2454.9820	---	---
	Ant9	2437	35.964	2419.0180	2454.9820	---	---
	Ant8	2452	35.964	2433.9381	2469.9021	---	---
	Ant9	2452	35.964	2433.9381	2469.9021	---	---
11AX20MIMO	Ant8	2412	18.901	2402.5694	2421.4705	---	---
	Ant9	2412	18.901	2402.5694	2421.4705	---	---
	Ant8	2437	18.941	2427.5295	2446.4705	---	---
	Ant9	2437	18.861	2427.5694	2446.4306	---	---
	Ant8	2462	18.901	2452.5295	2471.4306	---	---
	Ant9	2462	18.941	2452.5295	2471.4705	---	---
11AX40MIMO	Ant8	2422	37.722	2403.1389	2440.8611	---	---
	Ant9	2422	37.802	2403.1389	2440.9411	---	---
	Ant8	2437	37.642	2418.1389	2455.7812	---	---
	Ant9	2437	37.642	2418.1389	2455.7812	---	---
	Ant8	2452	37.642	2433.1389	2470.7812	---	---
	Ant9	2452	37.722	2433.1389	2470.8611	---	---




Test Graphs






11B_Ant8_2437




11B_Ant9_2437






11B_Ant8_2462



Date: 21.NOV.2024 23:19:43


11B_Ant9_2462




Date: 21.NOV.2024 23:21:23



11G_Ant8_2412




11G_Ant9_2412






11G_Ant8_2437




11G_Ant9_2437






11G_Ant8_2462




11G_Ant9_2462






11N20MIMO_Ant8_2412




11N20MIMO_Ant9_2412






11N20MIMO_Ant8_2437



Date: 21.NOV.2024 23:49:38


11N20MIMO_Ant9_2437




Date: 21.NOV.2024 23:51:00



11N20MIMO_Ant8_2462




11N20MIMO_Ant9_2462






11N40MIMO_Ant8_2422




11N40MIMO_Ant9_2422






11N40MIMO_Ant8_2437




11N40MIMO_Ant9_2437






11N40MIMO_Ant8_2452




11N40MIMO_Ant9_2452






11AX20MIMO_Ant8_2412




11AX20MIMO_Ant9_2412






11AX20MIMO_Ant8_2437




11AX20MIMO_Ant9_2437






11AX20MIMO_Ant8_2462



Date: 22.NOV.2024 00:17:04


11AX20MIMO_Ant9_2462




Date: 22.NOV.2024 00:18:44



11AX40MIMO_Ant8_2422




11AX40MIMO_Ant9_2422






11AX40MIMO_Ant8_2437




11AX40MIMO_Ant9_2437






11AX40MIMO_Ant8_2452



11AX40MIMO_Ant9_2452





Maximum power spectral density

Test Result


TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant8	2412	-2.74	≤8.00	PASS
	Ant9	2412	-3.23	≤8.00	PASS
	total	2412	0.03	≤8.00	PASS
	Ant8	2437	-2.73	≤8.00	PASS
	Ant9	2437	-2.89	≤8.00	PASS
	total	2437	0.20	≤8.00	PASS
	Ant8	2462	-2.81	≤8.00	PASS
	Ant9	2462	-3.09	≤8.00	PASS
	total	2462	0.06	≤8.00	PASS
11G	Ant8	2412	-6.63	≤8.00	PASS
	Ant9	2412	-6.54	≤8.00	PASS
	total	2412	-3.57	≤8.00	PASS
	Ant8	2437	-6.92	≤8.00	PASS
	Ant9	2437	-7.27	≤8.00	PASS
	total	2437	-4.08	≤8.00	PASS
	Ant8	2462	-5.92	≤8.00	PASS
	Ant9	2462	-7.22	≤8.00	PASS
	total	2462	-3.51	≤8.00	PASS
11N20MIMO	Ant8	2412	-5.67	≤8.00	PASS
	Ant9	2412	-6.15	≤8.00	PASS
	total	2412	-2.89	≤8.00	PASS
	Ant8	2437	-5.90	≤8.00	PASS
	Ant9	2437	-6.82	≤8.00	PASS
	total	2437	-3.33	≤8.00	PASS
	Ant8	2462	-6.07	≤8.00	PASS
	Ant9	2462	-7.19	≤8.00	PASS
	total	2462	-3.58	≤8.00	PASS
11N40MIMO	Ant8	2422	-9.03	≤8.00	PASS
	Ant9	2422	-9.42	≤8.00	PASS
	total	2422	-6.21	≤8.00	PASS
	Ant8	2437	-9.37	≤8.00	PASS
	Ant9	2437	-9.42	≤8.00	PASS
	total	2437	-6.38	≤8.00	PASS
	Ant8	2452	-9.02	≤8.00	PASS
	Ant9	2452	-9.83	≤8.00	PASS
	total	2452	-6.40	≤8.00	PASS
11AX20MIMO	Ant8	2412	-6.37	≤8.00	PASS
	Ant9	2412	-6.75	≤8.00	PASS
	total	2412	-3.55	≤8.00	PASS
	Ant8	2437	-7.24	≤8.00	PASS
	Ant9	2437	-6.25	≤8.00	PASS



	total	2437	-3.71	≤8.00	PASS
	Ant8	2462	-6.12	≤8.00	PASS
	Ant9	2462	-7.85	≤8.00	PASS
	total	2462	-3.89	≤8.00	PASS
11AX40MIMO	Ant8	2422	-10.30	≤8.00	PASS
	Ant9	2422	-10.49	≤8.00	PASS
	total	2422	-7.38	≤8.00	PASS
	Ant8	2437	-10.17	≤8.00	PASS
	Ant9	2437	-10.47	≤8.00	PASS
	total	2437	-7.31	≤8.00	PASS
	Ant8	2452	-9.80	≤8.00	PASS
	Ant9	2452	-9.91	≤8.00	PASS
	total	2452	-6.84	≤8.00	PASS




Test Graphs





11B_Ant8_2437



11B_Ant9_2437

