
Measurement Protocol

Measurement Object	LTE Band 30_10M_QPSK_1RB_0Offset_EVS NB 24.4kbps_Ch27710_8N
--------------------	---

Project	4N0543
Report Generation Date	24/12/25 19:49
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay NB	Done	Delay (Cross) [ms]	115.3	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.1a Receive Volume Control Performance 8N NB	Ok	Speech Level [dB[SPL]]	90.81	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 400 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	30.08	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 500 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	34.34	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 630 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	37.25	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 800 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	31.37	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 1000 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	40.91	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 1250 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	24.34	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 1600 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	43.93	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 2000 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	46.24	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 2500 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	42.99	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.2 RCV Distortion and Noise - 3150 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	43.69	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
Report - Receive Distortion and Noise (Conversational Gain)	Ok	Minimum SDNR [dB], (occured at 1250Hz)	24.34	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.3 Frequency Response 8N FF HANB	Ok	Min. dist. to tolerance scheme [dB], 1948.0 Hz	1.83	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N
5.3 Frequency Response 8N DF HANB	Ok	Min. dist. to tolerance scheme [dB], 2057.5 Hz	2.25	LTE Band 30_10M_QPSK_1RB_0Offset_EV S NB 24.4kbps_Ch27710_8N


ACQUA Report
30_10M_QPSK_1RB_0Offset_EVS NB 24.4kbps_Ch27710_8N

Title: LTE Band

Overall Receive Delay NB	5
5.1a Receive Volume Control Performance 8N NB	6
5.2 RCV Distortion and Noise - 400 Hz NB	7
5.2 RCV Distortion and Noise - 500 Hz NB	8
5.2 RCV Distortion and Noise - 630 Hz NB	9
5.2 RCV Distortion and Noise - 800 Hz NB	10
5.2 RCV Distortion and Noise - 1000 Hz NB	11
5.2 RCV Distortion and Noise - 1250 Hz NB	12
5.2 RCV Distortion and Noise - 1600 Hz NB	13
5.2 RCV Distortion and Noise - 2000 Hz NB	14
5.2 RCV Distortion and Noise - 2500 Hz NB	15
5.2 RCV Distortion and Noise - 3150 Hz NB	16
Report - Receive Distortion and Noise (Conversational Gain)	17
5.3 Frequency Response 8N FF HANB	18
5.3 Frequency Response 8N DF HANB	19

Overall Receive Delay NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ Preparation - Delay measurement




Delay (Cross): 115.3 ms

24/12/25 19:33 ACQUA 5.1.200

5.1a Receive Volume Control Performance 8N NB

TIA-5050 (2018-01) \ Measurements \ Narrowband




Speech Level RCV: 90.81 dB[SPL], Act.: 80.31% Ok

Ok

24/12/25 19:33 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 400 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 30.08 dB (3.13%) Ok

Ok

24/12/25 19:34 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 500 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 34.34 dB (1.92%) Ok

Ok

24/12/25 19:34 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 630 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 37.25 dB (1.37%) Ok

Ok

24/12/25 19:35 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 800 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 31.37 dB (2.70%) Ok

Ok

24/12/25 19:35 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1000 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 40.91 dB (0.90%) Ok

Ok

24/12/25 19:35 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1250 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 24.34 dB (6.07%) Ok

Ok

24/12/25 19:36 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1600 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 43.93 dB (0.64%) Ok

Ok

24/12/25 19:36 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2000 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 46.24 dB (0.49%) Ok

Ok

24/12/25 19:39 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2500 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 42.99 dB (0.71%) Ok

Ok

24/12/25 19:37 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 3150 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N



Distortion (Noise) RCV (packed): 43.69 dB (0.65%) Ok

Ok

24/12/25 19:38 ACQUA 5.1.200

Report - Receive Distortion and Noise (Conversational Gain)

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N

Region	Frequency	SDNR
1	400Hz	30.08 dB
2	500Hz	34.34 dB
3	630Hz	37.25 dB
4	800Hz	31.37 dB
5	1000Hz	40.91 dB
6	1250Hz	24.34 dB
7	1600Hz	43.93 dB
8	2500Hz	42.99 dB
9	3150Hz	43.69 dB
10	2000Hz	46.24 dB


All SDNRs were greater than 20.0 dB, requirement was met.

Smallest SDNR was 24.34dB at 1250Hz.

24/12/25 19:39 ACQUA

5.3 Frequency Response 8N FF HANB

TIA-5050 (2018-01) \ Measurements \ Narrowband




Absolute minimal distance
1.83 dB at 1948.0 Hz Ok

Ok

24/12/25 19:38 ACQUA 5.1.200

5.3 Frequency Response 8N DF HANB

TIA-5050 (2018-01) \ Measurements \ Narrowband



Absolute minimal distance
2.25 dB at 2057.5 Hz Ok

Ok

24/12/25 19:38 ACQUA 5.1.200

ACQUA Report
WB 128kbps_Ch349000_2N

Title: 02_FR1 n66_20M_QPSK_1RB_1Offset_EVS

Measurement Protocol

Measurement Object	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
--------------------	---

Project	4N0543
Report Generation Date	24/12/20 11:17
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	267.2	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	84.43	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 250 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	27.55	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 315 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	29.37	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 400 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	32.45	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 500 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	38.18	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 630 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	41.73	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 800 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	44.93	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 1000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	47.78	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 1250 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	33.75	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 1600 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	56.18	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 2000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	55.71	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 2500 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	48.99	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N

ACQUA Report
WB 128kbps_Ch349000_2N

Title: FR1 n66_20M_QPSK_1RB_1Offset_EVS

				EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 3150 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	49.36	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 4000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	51.67	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.2 RCV Distortion and Noise - 5000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	48.61	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
Report - Receive Distortion and Noise (Conversational Gain)	Ok	Minimum SDNR [dB], (occured at 250Hz)	27.55	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.3 Frequency Response 2N FF	Ok	Min. dist. to tolerance scheme [dB], 7764.8 Hz	2.12	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N
5.3 Frequency Response 2N DF	Ok	Min. dist. to tolerance scheme [dB], 2177.4 Hz	2.02	FR1 n66_20M_QPSK_1RB_1Offset_EVS WB 128kbps_Ch349000_2N


ACQUA Report
WB 128kbps_Ch349000_2N

Title: FR1 n66_20M_QPSK_1RB_1Offset_EVS

Overall Receive Delay WB	6
5.1b Receive Volume Control Performance 2N WB	7
5.2 RCV Distortion and Noise - 250 Hz WB	8
5.2 RCV Distortion and Noise - 315 Hz WB	9
5.2 RCV Distortion and Noise - 400 Hz WB	10
5.2 RCV Distortion and Noise - 500 Hz WB	11
5.2 RCV Distortion and Noise - 630 Hz WB	12
5.2 RCV Distortion and Noise - 800 Hz WB	13
5.2 RCV Distortion and Noise - 1000 Hz WB	14
5.2 RCV Distortion and Noise - 1250 Hz WB	15
5.2 RCV Distortion and Noise - 1600 Hz WB	16
5.2 RCV Distortion and Noise - 2000 Hz WB	17
5.2 RCV Distortion and Noise - 2500 Hz WB	18
5.2 RCV Distortion and Noise - 3150 Hz WB	19
5.2 RCV Distortion and Noise - 4000 Hz WB	20
5.2 RCV Distortion and Noise - 5000 Hz WB	21
Report - Receive Distortion and Noise (Conversational Gain)	22
5.3 Frequency Response 2N FF	23
5.3 Frequency Response 2N DF	24

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 267.2 ms

24/12/20 11:09 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband




Speech Level RCV: 84.43 dB[SPL], Act.: 82.79% Ok

Ok

24/12/20 11:09 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 250 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 27.55 dB (4.19%) Ok

Ok

24/12/20 11:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 315 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 29.37 dB (3.40%) Ok

Ok

24/12/20 11:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 400 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 32.45 dB (2.38%) Ok

Ok

24/12/20 11:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 500 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 38.18 dB (1.23%) Ok

Ok

24/12/20 11:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 630 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 41.73 dB (0.82%) Ok

Ok

24/12/20 11:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 800 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 44.93 dB (0.57%) Ok

Ok

24/12/20 11:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 47.78 dB (0.41%) Ok

Ok

24/12/20 11:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1250 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 33.75 dB (2.05%) Ok

Ok

24/12/20 11:13 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1600 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 56.18 dB (0.16%) Ok

Ok

24/12/20 11:13 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 55.71 dB (0.16%) Ok

Ok

24/12/20 11:14 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2500 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 48.99 dB (0.36%) Ok

Ok

24/12/20 11:14 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 3150 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 49.36 dB (0.34%) Ok

Ok

24/12/20 11:15 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 4000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 51.67 dB (0.26%) Ok

Ok

24/12/20 11:15 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 5000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N



Distortion (Noise) RCV (packed): 48.61 dB (0.37%) Ok

Ok

24/12/20 11:15 ACQUA 5.1.200

Report - Receive Distortion and Noise (Conversational Gain)

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N

Region	Frequency	SDNR
1	250Hz	27.55 dB
2	315Hz	29.37 dB
3	400Hz	32.45 dB
4	500Hz	38.18 dB
5	630Hz	41.73 dB
6	800Hz	44.93 dB
7	1000Hz	47.78 dB
8	1250Hz	33.75 dB
9	1600Hz	56.18 dB
10	2000Hz	55.71 dB
11	2500Hz	48.99 dB
12	3150Hz	49.36 dB
13	4000Hz	51.67 dB
14	5000Hz	48.61 dB


All SDNRs were greater than 20.0 dB, requirement was met.

Smallest SDNR was 27.55dB at 250Hz.

24/12/20 11:16 ACQUA

5.3 Frequency Response 2N FF

TIA-5050 (2018-01) \ Measurements \ Wideband




Absolute minimal distance
2.12 dB at 7764.8 Hz Ok

Ok

24/12/20 11:16 ACQUA 5.1.200

5.3 Frequency Response 2N DF

TIA-5050 (2018-01) \ Measurements \ Wideband



Absolute minimal distance
2.02 dB at 2177.4 Hz Ok

Ok

24/12/20 11:16 ACQUA 5.1.200

Measurement Protocol

Measurement Object	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24.4kbps_Ch6_8N
--------------------	---

Project	4N0543
Report Generation Date	24/12/26 10:27
Responsible Person	AC01-KS


Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay NB	Done	Delay (Cross) [ms]	198.6	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.1a Receive Volume Control Performance 8N NB	Ok	Speech Level [dB[SPL]]	91.46	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 400 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	30.17	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 500 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	30.66	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 630 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	32.63	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 800 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	31.71	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 1000 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	32.18	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 1250 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	21.07	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 1600 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	32.25	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 2000 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	33.57	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 2500 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	32.59	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.2 RCV Distortion and Noise - 3150 Hz NB	Ok	Distortion (Noise) [dB], 0.0 dB	34.86	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
Report - Receive Distortion and Noise (Conversational Gain)	Ok	Minimum SDNR [dB], (occured at 1250Hz)	21.07	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.3 Frequency Response 8N FF HANB	Ok	Min. dist. to tolerance scheme [dB], 1948.0 Hz	1.28	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N
5.3 Frequency Response 8N DF HANB	Ok	Min. dist. to tolerance scheme [dB], 305.9 Hz	0.99	WLAN2.4GHz_802.11b 1Mbps_EVS NB 24. 4kbps_Ch6_8N

Overall Receive Delay NB	5
5.1a Receive Volume Control Performance 8N NB	6
5.2 RCV Distortion and Noise - 400 Hz NB	7
5.2 RCV Distortion and Noise - 500 Hz NB	8
5.2 RCV Distortion and Noise - 630 Hz NB	9
5.2 RCV Distortion and Noise - 800 Hz NB	10
5.2 RCV Distortion and Noise - 1000 Hz NB	11
5.2 RCV Distortion and Noise - 1250 Hz NB	12
5.2 RCV Distortion and Noise - 1600 Hz NB	13
5.2 RCV Distortion and Noise - 2000 Hz NB	14
5.2 RCV Distortion and Noise - 2500 Hz NB	15
5.2 RCV Distortion and Noise - 3150 Hz NB	16
Report - Receive Distortion and Noise (Conversational Gain)	17
5.3 Frequency Response 8N FF HANB	18
5.3 Frequency Response 8N DF HANB	19

Overall Receive Delay NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ Preparation - Delay measurement




Delay (Cross): 198.6 ms

24/12/26 10:09 ACQUA 5.1.200

5.1a Receive Volume Control Performance 8N NB

TIA-5050 (2018-01) \ Measurements \ Narrowband




Speech Level RCV: 91.46 dB[SPL], Act.: 80.40% Ok

Ok

24/12/26 10:09 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 400 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 30.17 dB (3.10%) Ok

Ok

24/12/26 10:09 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 500 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 30.66 dB (2.93%) Ok

Ok

24/12/26 10:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 630 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 32.63 dB (2.34%) Ok

Ok

24/12/26 10:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 800 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 31.71 dB (2.60%) Ok

Ok

24/12/26 10:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1000 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 32.18 dB (2.46%) Ok

Ok

24/12/26 10:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1250 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 21.07 dB (8.84%) Ok

Ok

24/12/26 10:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1600 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 32.25 dB (2.44%) Ok

Ok

24/12/26 10:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2000 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 33.57 dB (2.10%) Ok

Ok

24/12/26 10:13 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2500 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N




Distortion (Noise) RCV (packed): 32.59 dB (2.35%) Ok

Ok

24/12/26 10:13 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 3150 Hz NB

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N



Distortion (Noise) RCV (packed): 34.86 dB (1.81%) Ok

Ok

24/12/26 10:14 ACQUA 5.1.200

Report - Receive Distortion and Noise (Conversational Gain)

TIA-5050 (2018-01) \ Measurements \ Narrowband \ 5.2 Receive Distortion and Noise 8N

Region	Frequency	SDNR
1	400Hz	30.17 dB
2	500Hz	30.66 dB
3	630Hz	32.63 dB
4	800Hz	31.71 dB
5	1000Hz	32.18 dB
6	1250Hz	21.07 dB
7	1600Hz	32.25 dB
8	2000Hz	33.57 dB
9	2500Hz	32.59 dB
10	3150Hz	34.86 dB


All SDNRs were greater than 20.0 dB, requirement was met.

Smallest SDNR was 21.07dB at 1250Hz.

24/12/26 10:14 ACQUA

5.3 Frequency Response 8N FF HANB

TIA-5050 (2018-01) \ Measurements \ Narrowband




Absolute minimal distance
1.28 dB at 1948.0 Hz Ok

Ok

24/12/26 10:14 ACQUA 5.1.200

5.3 Frequency Response 8N DF HANB

TIA-5050 (2018-01) \ Measurements \ Narrowband



Absolute minimal distance
0.99 dB at 305.9 Hz Ok

Ok

24/12/26 10:14 ACQUA 5.1.200

Measurement Protocol

Measurement Object	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
--------------------	---

Project	4N0543
Report Generation Date	24/12/26 13:15
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	277.9	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	85.30	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 250 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	29.40	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 315 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	30.47	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 400 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	27.92	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 500 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	34.72	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 630 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	34.42	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 800 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	31.03	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 1000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	31.27	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 1250 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	22.04	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 1600 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	30.30	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 2000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	32.58	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 2500 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	32.45	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 3150 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	31.49	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 4000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	36.82	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.2 RCV Distortion and Noise - 5000 Hz WB	Ok	Distortion (Noise) [dB], 0.0 dB	36.98	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
Report - Receive Distortion	Ok	Minimum SDNR [dB],	22.04	WLAN5GHz_802.11a

ACQUA Report
128kbps_Ch60_2N


Title: WLAN5GHz_802.11a 6Mbps_EVS WB

and Noise (Conversational Gain)		(occured at 1250Hz)		6Mbps_EVS WB 128kbps_Ch60_2N
5.3 Frequency Response 2N FF	Ok	Min. dist. to tolerance scheme [dB], 7764.8 Hz	1.02	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N
5.3 Frequency Response 2N DF	Ok	Min. dist. to tolerance scheme [dB], 2057.5 Hz	0.94	WLAN5GHz_802.11a 6Mbps_EVS WB 128kbps_Ch60_2N

Overall Receive Delay WB	6
5.1b Receive Volume Control Performance 2N WB	7
5.2 RCV Distortion and Noise - 250 Hz WB	8
5.2 RCV Distortion and Noise - 315 Hz WB	9
5.2 RCV Distortion and Noise - 400 Hz WB	10
5.2 RCV Distortion and Noise - 500 Hz WB	11
5.2 RCV Distortion and Noise - 630 Hz WB	12
5.2 RCV Distortion and Noise - 800 Hz WB	13
5.2 RCV Distortion and Noise - 1000 Hz WB	14
5.2 RCV Distortion and Noise - 1250 Hz WB	15
5.2 RCV Distortion and Noise - 1600 Hz WB	16
5.2 RCV Distortion and Noise - 2000 Hz WB	17
5.2 RCV Distortion and Noise - 2500 Hz WB	18
5.2 RCV Distortion and Noise - 3150 Hz WB	19
5.2 RCV Distortion and Noise - 4000 Hz WB	20
5.2 RCV Distortion and Noise - 5000 Hz WB	21
Report - Receive Distortion and Noise (Conversational Gain)	22
5.3 Frequency Response 2N FF	23
5.3 Frequency Response 2N DF	24

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 277.9 ms

24/12/26 13:06 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband




Speech Level RCV: 85.30 dB[SPL], Act.: 80.86% Ok

Ok

24/12/26 13:07 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 250 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 29.40 dB (3.39%) Ok

Ok

24/12/26 13:07 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 315 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 30.47 dB (3.00%) Ok

Ok

24/12/26 13:08 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 400 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 27.92 dB (4.02%) Ok

Ok

24/12/26 13:08 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 500 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 34.72 dB (1.84%) Ok

Ok

24/12/26 13:09 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 630 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 34.42 dB (1.90%) Ok

Ok

24/12/26 13:09 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 800 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 31.03 dB (2.81%) Ok

Ok

24/12/26 13:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 31.27 dB (2.73%) Ok

Ok

24/12/26 13:10 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1250 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 22.04 dB (7.90%) Ok

Ok

24/12/26 13:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 1600 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 30.30 dB (3.06%) Ok

Ok

24/12/26 13:11 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 32.58 dB (2.35%) Ok

Ok

24/12/26 13:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 2500 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 32.45 dB (2.38%) Ok

Ok

24/12/26 13:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 3150 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 31.49 dB (2.66%) Ok

Ok

24/12/26 13:12 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 4000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N




Distortion (Noise) RCV (packed): 36.82 dB (1.44%) Ok

Ok

24/12/26 13:13 ACQUA 5.1.200

5.2 RCV Distortion and Noise - 5000 Hz WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N



Distortion (Noise) RCV (packed): 36.98 dB (1.42%) Ok

Ok

24/12/26 13:13 ACQUA 5.1.200

Report - Receive Distortion and Noise (Conversational Gain)

TIA-5050 (2018-01) \ Measurements \ Wideband \ 5.2 Receive Distortion and Noise 2N

Region	Frequency	SDNR
1	250Hz	29.40 dB
2	315Hz	30.47 dB
3	400Hz	27.92 dB
4	500Hz	34.72 dB
5	630Hz	34.42 dB
6	800Hz	31.03 dB
7	1000Hz	31.27 dB
8	1250Hz	22.04 dB
9	1600Hz	30.30 dB
10	2000Hz	32.58 dB
11	2500Hz	32.45 dB
12	3150Hz	31.49 dB
13	4000Hz	36.82 dB
14	5000Hz	36.98 dB


All SDNRs were greater than 20.0 dB, requirement was met.

Smallest SDNR was 22.04dB at 1250Hz.

24/12/26 13:14 ACQUA

5.3 Frequency Response 2N FF

TIA-5050 (2018-01) \ Measurements \ Wideband




Absolute minimal distance
1.02 dB at 7764.8 Hz Ok

Ok

24/12/26 13:14 ACQUA 5.1.200

5.3 Frequency Response 2N DF

TIA-5050 (2018-01) \ Measurements \ Wideband



Absolute minimal distance
0.94 dB at 2057.5 Hz Ok

Ok

24/12/26 13:14 ACQUA 5.1.200

Measurement Protocol

Measurement Object	WCDMA II_Voice_AMR WB 6.60kbps_Ch9400_2N
--------------------	--

Project	4N0543
Report Generation Date	24/12/26 15:39
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	183.2	WCDMA II_Voice_AMR WB 6. 60kbps_Ch9400_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	83.97	WCDMA II_Voice_AMR WB 6. 60kbps_Ch9400_2N


ACQUA Report
60kbps_Ch9400_2N

Title: WCDMA II_Voice_AMR WB 6.

Overall Receive Delay WB	5
5.1b Receive Volume Control Performance 2N WB	6

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 183.2 ms

24/12/26 15:39 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband



Speech Level RCV: 83.97 dB[SPL], Act.: 79.70% Ok

Ok

24/12/26 15:39 ACQUA 5.1.200

Measurement Protocol

Measurement Object	LTE Band 30_10M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch27710_8N
--------------------	--

Project	4N0543
Report Generation Date	25/01/03 11:48
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	152.0	LTE Band 30_10M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch27710_8N
5.1a Receive Volume Control Performance 8N WB	Ok	Speech Level [dB[SPL]]	88.40	LTE Band 30_10M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch27710_8N


ACQUA Report
30_10M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch27710_8N

Title: LTE Band

Overall Receive Delay WB	5
5.1a Receive Volume Control Performance 8N WB	6

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 152.0 ms

25/01/03 11:48 ACQUA 5.1.200

5.1a Receive Volume Control Performance 8N WB

TIA-5050 (2018-01) \ Measurements \ Wideband



Speech Level RCV: 88.40 dB[SPL], Act.: 80.18% Ok

Ok

25/01/03 11:48 ACQUA 5.1.200

Measurement Protocol

Measurement Object	LTE Band 42 Part 27Q_20M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch42590_2N
--------------------	---

Project	4N0543
Report Generation Date	25/01/02 14:01
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	149.8	LTE Band 42 Part 27Q_20M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch42590_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	83.32	LTE Band 42 Part 27Q_20M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch42590_2N


ACQUA Report
27Q_20M_QPSK_1RB_0Offset_EVS WB 5.9kbps_Ch42590_2N

Title: LTE Band 42 Part

Overall Receive Delay WB	5
5.1b Receive Volume Control Performance 2N WB	6

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 149.8 ms

25/01/02 14:00 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband



Speech Level RCV: 83.32 dB[SPL], Act.: 80.68% Ok

Ok

25/01/02 14:01 ACQUA 5.1.200

Measurement Protocol

Measurement Object	FR1 n30_10M_QPSK_1RB_1Offset_EVS WB 5.9kbps_Ch462000_2N
--------------------	---

Project	4N0543
Report Generation Date	24/12/31 15:33
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	266.6	FR1 n30_10M_QPSK_1RB_1Offset_EVS WB 5.9kbps_Ch462000_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	83.41	FR1 n30_10M_QPSK_1RB_1Offset_EVS WB 5.9kbps_Ch462000_2N


ACQUA Report
WB 5.9kbps_Ch462000_2N

Title: FR1 n30_10M_QPSK_1RB_1Offset_EVS

Overall Receive Delay WB	5
5.1b Receive Volume Control Performance 2N WB	6

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 266.6 ms

24/12/31 15:30 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband



Speech Level RCV: 83.41 dB[SPL], Act.: 80.10% Ok

Ok

24/12/31 15:31 ACQUA 5.1.200

Measurement Protocol

Measurement Object	WLAN5GHz_802.11a 6Mbps_EVS WB 5.9kbps_Ch40_2N
--------------------	---

Project	4N0543
Report Generation Date	25/01/01 15:43
Responsible Person	AC01-KS

Status Overview

SMD	Status	Single Value Description	Single Value	Object
Overall Receive Delay WB	Done	Delay (Cross) [ms]	179.7	WLAN5GHz_802.11a 6Mbps_EVS WB 5.9kbps_Ch40_2N
5.1b Receive Volume Control Performance 2N WB	Ok	Speech Level [dB[SPL]]	83.59	WLAN5GHz_802.11a 6Mbps_EVS WB 5.9kbps_Ch40_2N


ACQUA Report
9kbps_Ch40_2N

Title: WLAN5GHz_802.11a 6Mbps_EVS WB 5.

Overall Receive Delay WB	5
5.1b Receive Volume Control Performance 2N WB	6

Overall Receive Delay WB

TIA-5050 (2018-01) \ Measurements \ Wideband \ Preparation - Delay measurement




Delay (Cross): 179.7 ms

25/01/01 15:42 ACQUA 5.1.200

5.1b Receive Volume Control Performance 2N WB

TIA-5050 (2018-01) \ Measurements \ Wideband



Speech Level RCV: 83.59 dB[SPL], Act.: 81.97% Ok

Ok

25/01/01 15:42 ACQUA 5.1.200