

FCC RF Test Report

APPLICANT : Datalogic S.r.l.
EQUIPMENT : MOBILE COMPUTER/BARCODE READER
BRAND NAME : DATALOGIC
MODEL NAME : AELNRNA
FCC ID : U4G-AELNRNA
STANDARD : 47 CFR Part 27 Subpart Q
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Dec. 01, 2024 ~ Jan. 19, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Maximum EIRP Power and Emission Designator	6
1.7 Testing Site	6
1.8 Test Software.....	6
1.9 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode	8
2.2 Connection Diagram of Test System.....	9
2.3 Support Unit used in test configuration and system	9
2.4 Measurement Results Explanation Example.....	9
2.5 Frequency List of Low/Middle/High Channels	10
3 CONDUCTED TEST ITEMS	11
3.1 Measuring Instruments	11
3.2 Test Setup	11
3.3 Test Result of Conducted Test	11
3.4 Conducted Output Power Measurement	12
3.5 Peak-to-Average Ratio	13
3.6 EIRP	14
3.7 Occupied Bandwidth.....	15
3.8 Conducted Band Edge Measurement	16
3.9 Conducted Spurious Emission Measurement	17
3.10 Frequency Stability Measurement.....	18
4 RADIATED TEST ITEMS	19
4.1 Measuring Instruments	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test	20
4.4 Radiated Spurious Emission Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 MEASUREMENT UNCERTAINTY	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG4N0543F	Rev. 01	Initial issue of report	Feb. 24, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 45.3 dB at 13800.000 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Datalogic S.r.l.

Via San Vitalino 13 CALDERARA DI RENO, BO 40012 Italy

1.2 Manufacturer

Datalogic S.r.l.

Via San Vitalino 13 CALDERARA DI RENO, BO 40012 Italy

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	MOBILE COMPUTER/BARCODE READER
Brand Name	DATALOGIC
Model Name	AELNRNA
FCC ID	U4G-AELNRNA
IMEI/SN Code	Conducted: 356616170009222 Radiation: X24N00016
HW Version	V3
SW Version	1.18.001.20241225
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx/Rx Frequency	LTE Band 42: 3450 MHz ~ 3550 MHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	<Ant.2> LTE Band 42 : 23.59 dBm <Ant.3> LTE Band 42 : 21.85 dBm <Ant.5> LTE Band 42 : 23.10 dBm <Ant.6> LTE Band 42 : 24.52 dBm
Antenna Gain	<Ant.2> LTE Band 42 : -4.0 dBi <Ant.3> LTE Band 42 : -4.0 dBi <Ant.5> LTE Band 42 : -4.0 dBi <Ant.6> LTE Band 42 : -4.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Note: The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP of Ant.6 for LTE Band 42 is shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP Power and Emission Designator

LTE Band 42		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	3452.5 ~ 3547.5	0.1102	4M50G7D	0.0863	4M50W7D
10	3455 ~ 3545	0.1104	9M07G7D	0.0865	9M03W7D
15	3457.5 ~ 3542.5	0.1117	13M5G7D	0.0881	13M5W7D
20	3460 ~ 3540	0.1127	17M9G7D	0.0887	17M9W7D

1.7 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
2.	03CH04-KS	AUDIX	E3	210616

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 27 Subpart Q
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z for Adapter mode, Cradle mode and Earphone mode.. The worst cases (X-Plane-Adapter mode) were recorded in this report.

Test Cases	Band	Bandwidth (MHz)	Modulation	RB #	Test Channel
		eg. 5M, 10M, 15M, 20M	eg. QPSK, 16QAM, 64QAM	1RB, Partial RB, Full RB	L/M/H
Max. Output Power	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM, 256QAM	1RB, Partial RB, Full RB	L, M, H
Peak-to-Average Ratio	LTE Band 42	20M	QPSK, 16QAM, 64QAM, 256QAM	Full RB	M
E.I.R.P	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM, 256QAM	1RB, Partial RB, Full RB	L, M, H
26dB and 99% Bandwidth	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM	Full RB	M
Conducted Band Edge	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM, 256QAM	1RB, Full RB	L, H
Conducted Spurious Emission	LTE Band 42	5M, 10M, 15M, 20M	QPSK	1RB	L, M, H
Frequency Stability	LTE Band 42	5M	QPSK	1RB	M
Radiated Spurious Emission	LTE Band 42	Worst case from maximum power			L, M, H

Note:
The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Adapter	N/A	N/A	N/A	N/A	N/A
4.	USB Cable	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss

$$\text{Offset} = \text{RF cable loss}$$

Following shows an offset computation example with cable loss 6.5 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 6.5 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

LTE Band 42 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	42190	42590	42990
	Frequency	3460	3500	3540
15	Channel	42165	42590	43015
	Frequency	3457.5	3500	3542.5
10	Channel	42140	42590	43040
	Frequency	3455	3500	3545
5	Channel	42115	42590	43065
	Frequency	3452.5	3500	3547.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP Limit

§ 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. $EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where
 P_T = transmitter output power in dBm
 G_T = gain of the transmitting antenna in dBi
 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

§ 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW ≥ 500 KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. Offset has included the duty factor for LTE Band 42. Duty factor $= 10 \log (1/x)$, where x is the measured duty cycle
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Offset has included the duty factor for LTE Band 42. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle
9. Taking the record of maximum spurious emission.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. Checked that all the results comply with the emission limit line.

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Dec. 01, 2024~Jan. 09, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Dec. 01, 2024~Jan. 09, 2025	NCR	Conducted (TH01-KS)
Temperature & humidity	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2024	Dec. 01, 2024~Jan. 09, 2025	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44G,MAX 30dB	Oct. 11, 2024	Jan. 19, 2025	Oct. 10, 2025	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jan. 19, 2025	Sep. 07, 2025	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Nov. 23, 2024	Jan. 19, 2025	Nov. 22, 2025	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 16, 2024	Jan. 19, 2025	Aug. 15, 2025	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jan. 19, 2025	Oct. 21, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 03, 2024	Jan. 19, 2025	Jul. 02, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060852	18~40GHz	Jan. 03, 2025	Jan. 19, 2025	Jan. 02, 2026	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz~18Ghz	Oct. 09, 2024	Jan. 19, 2025	Oct. 08, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz~18Ghz	Oct. 09, 2024	Jan. 19, 2025	Oct. 08, 2025	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 19, 2025	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 19, 2025	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 19, 2025	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Peak to Average Ratio	±0.50 dB
Frequency Stability	±0.04 ppm

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82 dB
---	---------

----- THE END -----

Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and EIRP

LTE Band 42 <Ant.6>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP	EIRP	EIRP
Channel				42190	42590	42990	42190	42590	42990
Frequency (MHz)				3460	3500	3540	3460	3500	3540
20	QPSK	1	0	24.34	24.52	24.47	0.1081	0.1127	0.1114
20	QPSK	1	49	24.29	24.39	24.43	0.1069	0.1094	0.1104
20	QPSK	1	99	24.36	24.30	24.36	0.1086	0.1072	0.1086
20	QPSK	50	0	23.40	23.63	23.57	0.0871	0.0918	0.0906
20	QPSK	50	24	23.39	23.52	23.45	0.0869	0.0895	0.0881
20	QPSK	50	50	23.34	23.52	23.53	0.0859	0.0895	0.0897
20	QPSK	100	0	23.36	23.59	23.41	0.0863	0.0910	0.0873
20	16QAM	1	0	23.41	23.48	23.43	0.0873	0.0887	0.0877
20	16QAM	1	49	23.23	23.33	23.33	0.0838	0.0857	0.0857
20	16QAM	1	99	23.20	23.31	23.38	0.0832	0.0853	0.0867
20	16QAM	50	0	22.42	22.48	22.48	0.0695	0.0705	0.0705
20	16QAM	50	24	22.41	22.43	22.53	0.0693	0.0697	0.0713
20	16QAM	50	50	22.37	22.51	22.43	0.0687	0.0710	0.0697
20	16QAM	100	0	22.28	22.43	22.36	0.0673	0.0697	0.0685
20	64QAM	1	0	22.47	22.67	22.63	0.0703	0.0736	0.0729
20	64QAM	1	49	22.40	22.44	22.55	0.0692	0.0698	0.0716
20	64QAM	1	99	22.50	22.52	22.55	0.0708	0.0711	0.0716
20	64QAM	50	0	21.48	21.51	21.63	0.0560	0.0564	0.0579
20	64QAM	50	24	21.32	21.49	21.40	0.0540	0.0561	0.0550
20	64QAM	50	50	21.32	21.50	21.31	0.0540	0.0562	0.0538
20	64QAM	100	0	21.39	21.49	21.49	0.0548	0.0561	0.0561
20	256QAM	1	0	19.22	19.31	19.27	0.0333	0.0340	0.0337



20	256QAM	1	49	19.18	19.27	19.38	0.0330	0.0337	0.0345
20	256QAM	1	99	19.15	19.23	19.27	0.0327	0.0333	0.0337
20	256QAM	50	0	19.39	19.43	19.36	0.0346	0.0349	0.0344
20	256QAM	50	24	19.38	19.34	19.34	0.0345	0.0342	0.0342
20	256QAM	50	50	19.28	19.46	19.47	0.0337	0.0352	0.0352
20	256QAM	100	0	19.26	19.39	19.34	0.0336	0.0346	0.0342
Channel				42165	42590	43015	42165	42590	43015
Frequency (MHz)				3457.5	3500	3542.5	3457.5	3500	3542.5
15	QPSK	1	0	24.21	24.48	24.39	0.1050	0.1117	0.1094
15	QPSK	1	37	24.24	24.29	24.37	0.1057	0.1069	0.1089
15	QPSK	1	74	24.25	24.18	24.28	0.1059	0.1042	0.1067
15	QPSK	36	0	23.28	23.57	23.44	0.0847	0.0906	0.0879
15	QPSK	36	20	23.31	23.42	23.34	0.0853	0.0875	0.0859
15	QPSK	36	39	23.21	23.48	23.49	0.0834	0.0887	0.0889
15	QPSK	75	0	23.26	23.52	23.34	0.0843	0.0895	0.0859
15	16QAM	1	0	23.34	23.45	23.30	0.0859	0.0881	0.0851
15	16QAM	1	37	23.16	23.26	23.28	0.0824	0.0843	0.0847
15	16QAM	1	74	23.10	23.21	23.31	0.0813	0.0834	0.0853
15	16QAM	36	0	22.35	22.37	22.45	0.0684	0.0687	0.0700
15	16QAM	36	20	22.34	22.38	22.46	0.0682	0.0689	0.0701
15	16QAM	36	39	22.28	22.39	22.36	0.0673	0.0690	0.0685
15	16QAM	75	0	22.21	22.37	22.28	0.0662	0.0687	0.0673
15	64QAM	1	0	22.43	22.59	22.52	0.0697	0.0723	0.0711
15	64QAM	1	37	22.28	22.38	22.42	0.0673	0.0689	0.0695
15	64QAM	1	74	22.42	22.48	22.45	0.0695	0.0705	0.0700
15	64QAM	36	0	21.42	21.41	21.60	0.0552	0.0551	0.0575
15	64QAM	36	20	21.23	21.41	21.33	0.0528	0.0551	0.0541
15	64QAM	36	39	21.25	21.41	21.22	0.0531	0.0551	0.0527
15	64QAM	75	0	21.36	21.40	21.39	0.0545	0.0550	0.0548
15	256QAM	1	0	19.14	19.21	19.16	0.0327	0.0332	0.0328
15	256QAM	1	37	19.07	19.15	19.28	0.0321	0.0327	0.0337
15	256QAM	1	74	19.11	19.15	19.22	0.0324	0.0327	0.0333
15	256QAM	36	0	19.27	19.32	19.23	0.0337	0.0340	0.0333
15	256QAM	36	20	19.28	19.26	19.25	0.0337	0.0336	0.0335
15	256QAM	36	39	19.17	19.37	19.35	0.0329	0.0344	0.0343




15	256QAM	75	0	19.20	19.31	19.26	0.0331	0.0340	0.0336
Channel				42140	42590	43040	42140	42590	43040
Frequency (MHz)				3455	3500	3545	3455	3500	3545
10	QPSK	1	0	24.25	24.43	24.35	0.1059	0.1104	0.1084
10	QPSK	1	25	24.16	24.32	24.36	0.1038	0.1076	0.1086
10	QPSK	1	49	24.27	24.24	24.24	0.1064	0.1057	0.1057
10	QPSK	25	0	23.33	23.53	23.45	0.0857	0.0897	0.0881
10	QPSK	25	12	23.34	23.40	23.36	0.0859	0.0871	0.0863
10	QPSK	25	25	23.31	23.41	23.46	0.0853	0.0873	0.0883
10	QPSK	50	0	23.32	23.49	23.30	0.0855	0.0889	0.0851
10	16QAM	1	0	23.33	23.37	23.31	0.0857	0.0865	0.0853
10	16QAM	1	25	23.18	23.24	23.27	0.0828	0.0839	0.0845
10	16QAM	1	49	23.15	23.27	23.27	0.0822	0.0845	0.0845
10	16QAM	25	0	22.33	22.36	22.42	0.0681	0.0685	0.0695
10	16QAM	25	12	22.37	22.34	22.42	0.0687	0.0682	0.0695
10	16QAM	25	25	22.30	22.47	22.31	0.0676	0.0703	0.0678
10	16QAM	50	0	22.21	22.39	22.31	0.0662	0.0690	0.0678
10	64QAM	1	0	22.40	22.63	22.59	0.0692	0.0729	0.0723
10	64QAM	1	25	22.36	22.34	22.46	0.0685	0.0682	0.0701
10	64QAM	1	49	22.47	22.43	22.49	0.0703	0.0697	0.0706
10	64QAM	25	0	21.41	21.40	21.55	0.0551	0.0550	0.0569
10	64QAM	25	12	21.28	21.40	21.30	0.0535	0.0550	0.0537
10	64QAM	25	25	21.28	21.42	21.20	0.0535	0.0552	0.0525
10	64QAM	50	0	21.30	21.45	21.36	0.0537	0.0556	0.0545
10	256QAM	1	0	19.13	19.19	19.24	0.0326	0.0330	0.0334
10	256QAM	1	25	19.06	19.15	19.27	0.0321	0.0327	0.0337
10	256QAM	1	49	19.11	19.14	19.24	0.0324	0.0327	0.0334
10	256QAM	25	0	19.29	19.35	19.24	0.0338	0.0343	0.0334
10	256QAM	25	12	19.31	19.21	19.24	0.0340	0.0332	0.0334
10	256QAM	25	25	19.16	19.39	19.40	0.0328	0.0346	0.0347
10	256QAM	50	0	19.14	19.31	19.30	0.0327	0.0340	0.0339
Channel				42115	42590	43065	42115	42590	43065
Frequency (MHz)				3452.5	3500	3547.5	3452.5	3500	3547.5
5	QPSK	1	0	24.28	24.42	24.38	0.1067	0.1102	0.1091
5	QPSK	1	12	24.22	24.31	24.36	0.1052	0.1074	0.1086

5	QPSK	1	24	24.25	24.19	24.25	0.1059	0.1045	0.1059
5	QPSK	12	0	23.36	23.52	23.47	0.0863	0.0895	0.0885
5	QPSK	12	7	23.28	23.41	23.34	0.0847	0.0873	0.0859
5	QPSK	12	13	23.23	23.40	23.42	0.0838	0.0871	0.0875
5	QPSK	25	0	23.25	23.47	23.30	0.0841	0.0885	0.0851
5	16QAM	1	0	23.31	23.36	23.32	0.0853	0.0863	0.0855
5	16QAM	1	12	23.10	23.26	23.22	0.0813	0.0843	0.0836
5	16QAM	1	24	23.12	23.27	23.32	0.0817	0.0845	0.0855
5	16QAM	12	0	22.34	22.35	22.38	0.0682	0.0684	0.0689
5	16QAM	12	7	22.37	22.30	22.41	0.0687	0.0676	0.0693
5	16QAM	12	13	22.28	22.44	22.33	0.0673	0.0698	0.0681
5	16QAM	25	0	22.16	22.33	22.26	0.0655	0.0681	0.0670
5	64QAM	1	0	22.42	22.56	22.50	0.0695	0.0718	0.0708
5	64QAM	1	12	22.30	22.32	22.48	0.0676	0.0679	0.0705
5	64QAM	1	24	22.38	22.49	22.45	0.0689	0.0706	0.0700
5	64QAM	12	0	21.41	21.38	21.51	0.0551	0.0547	0.0564
5	64QAM	12	7	21.22	21.43	21.28	0.0527	0.0553	0.0535
5	64QAM	12	13	21.23	21.42	21.25	0.0528	0.0552	0.0531
5	64QAM	25	0	21.32	21.41	21.38	0.0540	0.0551	0.0547
5	256QAM	1	0	19.16	19.26	19.21	0.0328	0.0336	0.0332
5	256QAM	1	12	19.07	19.21	19.35	0.0321	0.0332	0.0343
5	256QAM	1	24	19.09	19.19	19.21	0.0323	0.0330	0.0332
5	256QAM	12	0	19.33	19.39	19.27	0.0341	0.0346	0.0337
5	256QAM	12	7	19.30	19.23	19.26	0.0339	0.0333	0.0336
5	256QAM	12	13	19.21	19.39	19.42	0.0332	0.0346	0.0348
5	256QAM	25	0	19.20	19.34	19.24	0.0331	0.0342	0.0334

LTE Band 42


Peak-to-Average Ratio

Mode	LTE Band 42 / 20MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB				Result
Middle CH	7.39	6.52	7.16	7.39	PASS




26dB Bandwidth

Mode	LTE Band 42 : 26dB BW(MHz)							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.73	4.95	9.71	9.63	14.36	14.33	19.26	19.34




LTE Band 42 / Middle channel / Full RB/15M

QPSK




16QAM




LTE Band 42 / Middle channel / Full RB/20M

QPSK




16QAM




Occupied Bandwidth

Mode	LTE Band 42 : 99%OBW(MHz)							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.50	4.50	9.07	9.03	13.49	13.52	17.94	17.90




LTE Band 42 / Middle channel / Full RB/15M

QPSK




16QAM




LTE Band 42 / Middle channel / Full RB/20M

QPSK




16QAM





Conducted Band Edge






LTE Band 42 / 5MHz


16QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:13:08




Date: 1.DEC.2024 01:22:07

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 01:17:38



Date: 1.DEC.2024 02:48:19





LTE Band 42 / 5MHz

64QAM



Lowest Channel / 1RB0

Highest Channel / 1RBmax



Lowest Channel / FullRB

Highest Channel / FullRB







LTE Band 42 / 5MHz

256QAM



Lowest Channel / 1RB0

Highest Channel / 1RBmax



Lowest Channel / FullRB

Highest Channel / FullRB






LTE Band 42 / 10MHz


QPSK

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:37:36




Date: 1.DEC.2024 01:46:38

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 01:42:07



Date: 1.DEC.2024 01:51:08




LTE Band 42 / 10MHz


16QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:38:43




Date: 1.DEC.2024 01:47:45

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 01:43:14



Date: 1.DEC.2024 01:52:15




LTE Band 42 / 10MHz


64QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:39:50




Date: 1.DEC.2024 01:48:51

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 01:44:21



Date: 1.DEC.2024 01:53:22




LTE Band 42 / 10MHz


256QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:40:58




Date: 1.DEC.2024 01:49:58

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 01:45:28



Date: 1.DEC.2024 01:54:29




LTE Band 42 / 15MHz


QPSK

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:56:26




Date: 1.DEC.2024 02:05:26

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 02:00:56




Date: 1.DEC.2024 02:09:56




LTE Band 42 / 15MHz

16QAM


Lowest Channel / 1RB0




Highest Channel / 1RBmax



Lowest Channel / FullRB



Highest Channel / FullRB






LTE Band 42 / 15MHz


64QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:58:40




Date: 1.DEC.2024 02:07:40

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 02:03:10



Date: 1.DEC.2024 02:12:09




LTE Band 42 / 15MHz


256QAM

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 01:59:46




Date: 1.DEC.2024 02:08:46

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 02:04:16



Date: 1.DEC.2024 02:13:16




LTE Band 42 / 20MHz


QPSK

Lowest Channel / 1RB0

Highest Channel / 1RBmax




Date: 1.DEC.2024 02:17:00




Date: 1.DEC.2024 02:25:57

Lowest Channel / FullRB

Highest Channel / FullRB



Date: 1.DEC.2024 02:21:30



Date: 1.DEC.2024 02:30:27