

## Datalogic S.r.l.

Via San Vitalino 13  
40012 Calderara di Reno (BO)  
Italy  
Tel. +39 051 3147011  
Fax +39 051 3147205

### ©2024 Datalogic S.p.A. and/or its affiliates

All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates.

Owners of Datalogic products are hereby granted a non-exclusive, revocable license to reproduce and transmit this documentation for the purchaser's own internal business purposes. Purchaser shall not remove or alter any proprietary notices, including copyright notices, contained in this documentation and shall ensure that all notices appear on any reproductions of the documentation.

Electronic versions of this document may be downloaded from the Datalogic website ([www.datalogic.com](http://www.datalogic.com)). If you visit our website and would like to make comments or suggestions about this or other Datalogic publications, please let us know via the "Contact" page.

### Disclaimer

Datalogic has taken reasonable measures to provide information in this manual that is complete and accurate, however, Datalogic shall not be liable for technical or editorial errors or omissions contained herein, nor for incidental or consequential damages resulting from the use of this material. Datalogic reserves the right to change any specification at any time without prior notice.

### Trademarks


Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S.A. and the E.U.

Memor is a trademark of Datalogic S.p.A. and/or its affiliates. All other brand and product names may be trademarks of their respective owners.

## Support Through the Website

Datalogic provides several services as well as technical support through its website.

Log on to [www.datalogic.com](http://www.datalogic.com).

For quick access, from the home page click on the search icon  , and type in the name of the product you're looking for. This allows you access to download Data Sheets, Manuals, Software & Utilities, and Drawings.

Hover over the Support & Service menu for access to Services and Technical Support.

# MEMOR™ 3X

## QUICK START GUIDE



VEHICLE DOCK (WLC)

MODEL: SGVVSD

### ©2024 Datalogic S.p.A. and/or its affiliates

• All rights reserved • Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U.

[www.datalogic.com](http://www.datalogic.com)



822004620 (Rev. A) February 2024

## OUT OF THE BOX

The package contains:

- Vehicle Dock (Model: SGVVSD)
- Two M5x10 screws
- Quick Start Guide
- Safety & Regulatory Addendum.

Remove all the components from their packaging; check their integrity and compare them with all the packing documents.



**CAUTION: Keep the original packaging for use when sending products to the technical assistance center. Damage caused by improper packaging is not covered under the warranty.**

## GENERAL VIEW

### Vehicle Dock



## POWER THE DOCK

1. Unfasten the two screws on the back of the dock to remove the USB cover and access the USB port.



2. Insert the USB power cable into the USB port.



3. Insert the USB cover and fasten the screws.



4. Plug in the cigarette lighter adapter into your vehicle's cigarette lighter.
5. Connect the vehicle dock's USB cable to the USB connector of the CLA.



**CAUTION:** Make sure your vehicle's power source is between 10 to 30 VDC, and is capable of supporting a 3000mA current drain. If you have any concerns regarding this, refer to your vehicle owner's manual.



**CAUTION:** The cigarette lighter adapter must not be used if the battery car is fully depleted.



**NOTE:** To reduce quiescent current and extend battery life, disconnect the dock when the car is not powered.

## CHARGE THE MEMOR 3X

To insert the Memor 3X into the dock, the rubber boot is needed.

The rubber boot provides additional protection to the device and is available as optional accessory.

Insert the Memor 3X with the rubber boot into the dock with the screen facing front and the head facing up.



**CAUTION:** Make sure there is nothing between the dock and the device. Do not put any foreign object such as, but not limited to, coins, paper clips, stickers inside the slot of any of the docks.

Do not apply any sticker to the Memor 3X (see the examples below).



**WARNING:** Do not attempt to charge any other device different from the Memor 3X devices.



**CAUTION:** Do not use the Memor 3X while driving. The user is responsible for driving safely.

## TECHNICAL SPECIFICATIONS

Mechanical Features	
Dimensions	208 x 97.7 x 58 mm / 8.2 x 3.8 x 2.3 in
Weight	310 g / 10.9 oz
Eletrical Features	
Power supply	Max. 9.4V, Typ. 9V, Min. 7.5V
Environmental Features	
Working Temperature	0° to 40°C
Operating Temperature	-20° to 50°C
Storage Temperature	-30°C to 70°C
Humidity	5-95% non-condensing
Vibration Resistance	EN60068-2-64
Shock Resistance	EN60068-2-27