

# **FCC C2PC Test Report**

FCC ID : U4G004W

Equipment : 802.11ag Mlni Compact Flash Module

Model No. : DL-MSD30AG

Brand Name : Datalogic

Applicant : Datalogic ADC S.r.l.

Address : Via San Vitalino no. 13, Calderara di Reno -

40012 (Bologna) Bologna

Standard : 47 CFR FCC Part 15.407

Received Date : Jul. 09, 2015

Tested Date : Jul. 16 ~ Jul. 30, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Iac-MRA



Report No.: FR570901-01 Report Version: Rev. 01 Page: 1 of 31



## **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	The Equipment List	7
1.5	Testing Applied Standards	8
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION	9
2.1	Testing Condition	9
2.2	The Worst Test Modes and Channel Details	9
3	TRANSMITTER TEST RESULTS	10
3.1	Conducted Emissions	10
3.2	Emission Bandwidth	13
3.3	RF Output Power	15
3.4	Peak Power Spectral Density	16
3.5	Transmitter Radiated and Band Edge Emissions	18
3.6	Frequency Stability	29
4	TEST LABORATORY INFORMATION	31



## **Release Record**

Report No.	Version	Description	Issued Date
FR570901-01	Rev. 01	Initial issue	May 25, 2016

Report No.: FR570901-01 Page : 3 of 31



## **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.574MHz 36.35 (Margin -9.65dB) - AV	Pass
15.407(b)(4) 15.209	Radiated Emissions	[dBuV/m at 3m]: 214.30MHz 40.66 (Margin -2.84dB) - PK	Pass
15.407(a)(5)	Emission Bandwidth	Meet the requirement of limit	Pass
15.407(a)(3)	RF Output Power	Max Power [dBm]: 11.42	Pass
15.407(a)(3)	Peak Power Spectral Density	Meet the requirement of limit	Pass
15.407(e)	6dB Bandwidth	Meet the requirement of limit	Pass
15.407(g)	Frequency Stability	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR570901-01 Page: 4 of 31



## 1 General Description

#### 1.1 Information

This report is issued as a FCC Class II Permissive Change for complying with New U-NII rule requirement. Only test results of U-NII band 3 are recorded in this report. There is no test result of U-NII band 1/2A/2C in this report since

- 1) Output power of U-NII band 1 is not changed.
- 2) Requirement of U-NII band 2A/2C is not changed.
- 3) Device keeps all conditions of U-NII band 1/2A/2C as grant.

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS		
5725-5850	а	5745-5805	149-161 [4]	1	6-54 Mbps		

Note 1: RF output power specifies that Maximum Conducted Output Power.

Note 2: 802.11a uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

Note 3: NO MIMO and diversity function is supported for the device.

#### 1.1.2 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Gain (dBi)
1	Radiall Larsen	R380.500.314	Dipole	RP-TNC plug	5

## 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type 3.3Vdc from host	
------------------------------------	--

#### 1.1.4 Accessories

N/A

#### 1.1.5 Channel List

802.11 a			
Channel	Frequency(MHz)		
149	5745		
153	5765		
157	5785		
161	5805		

Report No.: FR570901-01 Page : 5 of 31



## 1.1.6 Test Tool and Duty Cycle

Test Tool	SRU, Version:3.3.10				
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)		
Duty Cycle and Duty Factor	11a	100 %	0		

## 1.1.7 Power Setting


Modulation Mode	Test Frequency (MHz)	Power Set
11a	5745	70%
11a	5785	75%
11a	5805	75%

## 1.2 Local Support Equipment List

	Support Equipment List								
No.	Equipment	Signal cable / Length (m)							
1	PDA	HP	HSTNH-L05C-BT						
2	AC Adapter for PDA		3A-041WE05						

Note: No. 1~2 were supplied by applicant.

## 1.3 Test Setup Chart



Report No.: FR570901-01 Page: 6 of 31



## 1.4 The Equipment List

Test Item	Conducted Emission	Conducted Emission						
Test Site	Conduction room 1 / (	Conduction room 1 / (CO01-WS)						
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Unti						
EMC Receiver	R&S	ESCS 30	100169	Oct. 17, 2014	Oct. 16, 2015			
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 17, 2014	Nov. 16, 2015			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 31, 2014	Dec. 30, 2015			
Measurement Software   AUDIX   e3   6.120210k   NA   NA								
Note: Calibration Inte	rval of instruments liste	d above is one year.						

Test Item	Radiated Emission							
Test Site	966 chamber1 / (03CH01-WS)							
Instrument	Manufacturer							
Spectrum Analyzer	R&S	FSV40	101498	Dec. 09, 2014	Dec. 08, 2015			
Receiver	R&S	ESR3	101658	Nov. 10, 2014	Nov. 09, 2015			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Sep. 05, 2014	Sep. 04, 2015			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 11, 2014	Dec. 10, 2015			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015			
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 10, 2014	Nov. 09, 2015			
Preamplifier	Burgeon	BPA-530	SN:100219	Sep. 09, 2014	Sep. 08, 2015			
Preamplifier	Agilent	83017A	MY39501308	Oct. 09, 2014	Oct. 08, 2015			
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 15, 2014	Dec. 14, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 15, 2014	Dec. 14, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 15, 2014	Dec. 14, 2015			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 15, 2014	Dec. 14, 2015			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 15, 2014	Dec. 14, 2015			
Measurement Software	AUDIX	e3	6.120210g	NA	NA			
Note: Calibration Inter	rval of instruments listed	d above is one year.						

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Dec. 03, 2014	Dec. 02, 2015
Power Meter	Anritsu	ML2495A	1241002	Sep. 29, 2014	Sep. 28, 2015
Power Sensor	Anritsu	MA2411B	1207366	Sep. 29, 2014	Sep. 28, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Report No.: FR570901-01 Page: 7 of 31



## 1.5 Testing Applied Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01

FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Bandwidth	±34.134 Hz				
Conducted power	±0.808 dB				
Frequency error	±34.134 Hz				
Power density	±0.463 dB				
Conducted emission	±2.670 dB				
AC conducted emission	±2.92 dB				
Radiated emission ≤ 1GHz	±3.72 dB				
Radiated emission > 1GHz	±5.65 dB				
Time	±0.1%				
Temperature	±0.6 °C				

Report No.: FR570901-01 Page: 8 of 31



## 2 Test Configuration

## 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 60%	Kevin Ma
Radiated Emissions	03CH01-WS	24-26°C / 66%	Aska Huang
RF Conducted	TH01-WS	25°C / 63%	Felix Sung

FCC site registration No.: 657002IC site registration No.: 10807A-1

### 2.2 The Worst Test Modes and Channel Details

	For Frequency band 5725-5850 MHz								
Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuratio n					
Conducted Emissions	11a	5785	6 Mbps						
Radiated Emissions ≤1GHz	11a	5785	6 Mbps						
RF Output Power	11a	5745 / 5785 / 5805	6 Mbps						
Radiated Emissions >1GHz Emission Bandwidth 6dB bandwidth Peak Power Spectral Density	11a	5745 / 5785 / 5805	6 Mbps						
Frequency Stability	Un-modulation	5785							

#### NOTE:

Report No.: FR570901-01 Page: 9 of 31

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.



### 3 Transmitter Test Results

#### 3.1 Conducted Emissions


#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit							
Frequency Emission (MHz) Quasi-Peak Average							
0.15-0.5	66 - 56 *	56 - 46 *					
0.5-5	56	46					
5-30 60 50							
Note 1: * Decreases with the logarithm of the frequency.							

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR570901-01 Page: 10 of 31




#### 3.1.4 Test Result of Conducted Emissions



Report No.: FR570901-01 Page: 11 of 31





2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV).

Report No.: FR570901-01 Page: 12 of 31



#### 3.2 Emission Bandwidth

#### 3.2.1 Limit of Emission Bandwidth

The minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

#### 3.2.2 Test Procedures


#### **Occupied Bandwidth**

- 1. Set RBW = 1 % to 5 % of the OBW
- 2. Set VBW ≥ 3 RBW
- 3. Sample detection and single sweep mode shall be used
- 4. Use the 99 % power bandwidth function of the instrument

#### 6dB Bandwidth

- 1. Set RBW = 100 kHz, video bandwidth = 300 kHz
- 2. Detector = Peak, Trace mode = max hold, Sweep = auto couple, Allow the trace to stabilize
- 3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 3.2.3 Test Setup




Report No.: FR570901-01 Page: 13 of 31



### 3.2.4 Test Result of Emission Bandwidth

	Emission Bandwidth										
				OBW Bandwidth (MHz)				6dB Bandwidth (MHz)			
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Chain 0	Chain 1	Chain 2	Chain 3	6dB BW Limit (MHz)
11a	1	5745	16.98				16.29				0.5
11a	1	5785	16.99				16.35				0.5
11a	1	5805	17.07				16.35				0.5



Report No.: FR570901-01 Page: 14 of 31



## 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power


The maximum conducted output power over the frequency band of operation shall not exceed 1 W

#### 3.3.2 Test Procedures

#### Method PM-G (Measurement using a gated RF average power meter)

Measurements may is performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

#### 3.3.3 Test Setup



#### 3.3.4 Test Result of Maximum Conducted Output Power

Mode	N <sub>TX</sub>	Freq. (MHz)	Condu		age) output Bm)	power	Total Power	Total Power	Limit
			Chain 0	Chain 1	Chain 2	Chain 3	(mW)	(dBm)	(dBm)
11a	1	5745	10.47				11.143	10.47	30.00
11a	1	5785	11.42				13.868	11.42	30.00
11a	1	5805	11.36				13.677	11.36	30.00

Report No.: FR570901-01 Page: 15 of 31



### 3.4 Peak Power Spectral Density


### 3.4.1 Limit of Peak Power Spectral Density

The maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

#### 3.4.2 Test Procedures

- Method SA-1
  - 1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
  - 2. Trace average 100 traces.
  - 3. Use the peak marker function to determine the maximum amplitude level.
- ☐ Method SA-2
  - 1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
  - 2. Trace average at 100 traces
  - 3. Use the peak marker function to determine the maximum amplitude level.
  - 4. Add 10  $\log(1/x)$ , where x is the duty cycle
- ☐ Method SA-2 Alternative (VHT80 only)
  - 1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = RMS.
  - 2. Set sweep time ≥ 10 \* (number of points in sweep) \* (total on/off period of the transmitted signal).
  - 3. Perform a single sweep.
  - 4. Use the peak marker function to determine the maximum amplitude level.
  - 5. Add 10 log(1/x), where x is the duty cycle.

#### 3.4.3 Test Setup




Report No.: FR570901-01 Page: 16 of 31



## 3.4.4 Test Result of Peak Power Spectral Density

For Frequency band 5725-5850 MHz								
Condition Peak Power Spectral Density (dBm/500kHz)								
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	PPSD w/o D.F (dBm/500kHz)	PPSD Limit (dBm/500kHz)				
11a	1	5745	-4.12	0.00	-4.12	30.00		
11a	1	5785	-3.16	0.00	-3.16	30.00		
11a	1	5805	-3.22	0.00	-3.22	30.00		

Note: D.F is duty factor.



Report No.: FR570901-01 Page: 17 of 31



### 3.5 Transmitter Radiated and Band Edge Emissions

#### 3.5.1 Limit of Transmitter Radiated and Band Edge Emissions

Restricted Band Emissions Limit						
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)			
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300			
0.490~1.705	24000/F(kHz)	33.8 - 23	30			
1.705~30.0	30	29	30			
30~88	100	40	3			
88~216	150	43.5	3			
216~960	200	46	3			
Above 960	500	54	3			

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

	Un-restricted band emissions above 1GHz Limit					
Operating Band	Limit					
5.15 - 5.25 GHz	e.i.r.p27 dBm [68.2 dBuV/m@3m]					
5.725 - 5.850 GHz	15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.					
	15.407(b)(4)(ii) ,compliance with the emission limits in § 15.247(d) Shall be at least 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power,. Attenuation below the general limits specified in §15.209(a) is not required. In addition,radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see § 15.205(c))					

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Report No.: FR570901-01 Page: 18 of 31



#### 3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR570901-01 Page: 19 of 31




## 3.5.3 Test Setup



Report No.: FR570901-01 Page: 20 of 31



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR570901-01 Page: 21 of 31





\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR570901-01 Page: 22 of 31



### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 23 of 31






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 24 of 31






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 25 of 31






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 26 of 31






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 27 of 31





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR570901-01 Page: 28 of 31



## 3.6 Frequency Stability


#### 3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

#### 3.6.2 Test Procedures

- 1. The EUT is installed in an environment test chamber with external power source.
- Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT.
- 3. A sufficient stabilization period at each temperature is used prior to each frequency measurement.
- 4. When temperature is stabled, measure the frequency stability.
- 5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.

#### 3.6.3 Test Setup



Report No.: FR570901-01 Page: 29 of 31



## 3.6.4 Test Result of Frequency Stability

Frequency: 5785 MHz		Frequency Drift (ppm)					
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes			
T20°CVmax	5.64	6.06	6.08	6.37			
T20°CVmin	4.89	4.41	5.60	5.39			
T50°CVnom	5.14	4.48	5.14	4.39			
T40°CVnom	3.73	4.31	3.82	4.29			
T30°CVnom	4.64	4.69	4.50	4.65			
T20°CVnom	3.52	3.45	3.57	4.09			
T10°CVnom	4.15	3.89	3.35	3.29			
T0°CVnom	2.90	3.50	3.26	3.59			
T-10°CVnom	1.77	1.66	1.14	2.01			
T-20°CVnom	2.12	1.73	1.89	1.32			
T-30°CVnom	2.20	2.32	2.17	2.34			
Vnom [Vac]: 120		Vmax [Vac]: 138	Vmin [Vac]: 1	Vmin [Vac]: 102			
Tnom [°C]: 20		Tmax [°C]: 50	Tmin [°C]: -30	)			

Report No.: FR570901-01 Page: 30 of 31



## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan

Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan

Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

<u>==END</u>==

Report No.: FR570901-01 Page: 31 of 31