



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	LANCOM Systems GmbH
Applicant Address	Adenauerstrasse 20/B2 52146, Wuerselen Germany
FCC ID	U4Y-ESLREVC2
Manufacturer's company	LANCOM Systems GmbH
Manufacturer Address	Adenauerstrasse 20/B2 52146, Wuerselen Germany

Product Name	Dual RF Transceiver
Brand Name	LANCOM
Model Name	ESL Rev. C2
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2402 ~ 2480MHz
Received Date	Aug. 18, 2016
Final Test Date	Oct. 14, 2016
Submission Type	Original Equipment

### Statement

**Test result included is only for the Bluetooth LE of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C** and **KDB558074 D01 v03r05**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	4
3.4. Table for Carrier Frequencies .....	5
3.5. Table for Test Modes.....	5
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units .....	6
3.8. Table for Parameters of Test Software Setting .....	7
3.9. EUT Operation during Test .....	7
3.10. Duty Cycle.....	7
3.11. Test Configurations .....	8
<b>4. TEST RESULT .....</b>	<b>10</b>
4.1. AC Power Line Conducted Emissions Measurement.....	10
4.2. Maximum Conducted Output Power Measurement.....	14
4.3. Power Spectral Density Measurement .....	16
4.4. 6dB Spectrum Bandwidth Measurement .....	20
4.5. Radiated Emissions Measurement .....	24
4.6. Emissions Measurement.....	34
4.7. Antenna Requirements .....	42
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>43</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>45</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A7</b>



## History of This Test Report



## 1. VERIFICATION OF COMPLIANCE

Product Name : Dual RF Transceiver  
Brand Name : LANCOM  
Model No. : ESL Rev. C2  
Applicant : LANCOM Systems GmbH  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 18, 2016 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Cliff Chang  
Cliff Chang  
SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C			
Part	Rule Section	Description of Test	Result
4.1	15.207	AC Power Line Conducted Emissions	Complies
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies
4.3	15.247(e)	Power Spectral Density	Complies
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies
4.5	15.247(d)	Radiated Emissions	Complies
4.6	15.247(d)	Band Edge Emissions	Complies
4.7	15.203	Antenna Requirements	Complies

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Power Type	From host system
Modulation	DSSS
Data Rate (Mbps)	GFSK: 1
Frequency Range	2402 ~ 2480MHz
Channel Number	40 (37 hopping + 3 advertising channel)
Channel Bandwidth (99%)	1.17 MHz
Maximum Conducted Output Power	7.28 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

#### 3.2. Accessories

N/A

### 3.3. Table for Filed Antenna

Ant.	Antenna board	Brand Holder	P/N	Antenna Type	Connector	Gain (dBi)
1	3	Tyco Electronics Corporation	1513164-1	Dipole Antenna	U.FL	4
2	4	Tyco Electronics Corporation	1513164-1	Dipole Antenna	U.FL	4


Note: The EUT has two antennas.

**For IEEE bluetooth function (1TX/1RX):**

Only Ant. 1 can be used as transmitting/receiving antenna.

**For IEEE electronic shelf label function (1TX/1RX):**

Only Ant. 2 can be used as transmitting/receiving antenna.



### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	0	2402 MHz	20	2442 MHz
	1	2404 MHz	:	:
	2	2406 MHz	37	2476 MHz
	:	:	38	2478 MHz
	18	2438 MHz	39	2480 MHz
	19	2440 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	GFSK	1 Mbps	0/20/39	1
Power Spectral Density				
6dB Spectrum Bandwidth	GFSK	1 Mbps	0/20/39	1
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	GFSK	1 Mbps	0/20/39	1
Band Edge Emissions	GFSK	1 Mbps	0/20/39	1

The following test modes were performed for all tests:

**For Conducted Emission test:**

Mode 1. EUT - CTX

**For Radiated Emission below 1GHz test:**

Mode 1 generated the worst test result for Radiated emission above 1GHz test, thus the measurement for Radiated emission below 1GHz test will follow this same test configuration.

**For Radiated Emission above 1GHz test:**

The EUT was performed at X axis, Y axis and Z axis position for Radiated emission above 1GHz test, and the worst case was found at Z axis. So the measurement will follow this same test configuration.

Mode 1. EUT in Z axis

**For Co-location MPE:**

The EUT could be applied with bluetooth function and electronic shelf label function; therefore Co-location Maximum Permissible Exposure (Please refer to FA681137) is added for simultaneously transmit between bluetooth function and electronic shelf label function.

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D
CO02-CB	Conduction	Hsin Chu	TW0006	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Supporting Units

For Test Site No: 03CH01-CB and TH01-CB

Support Unit	Brand	Model	FCC ID
LCD TV	SONY	KLV-32U300A	DoC
Mouse	Logitech	M-U0026	DoC
Keyboard	iCooky	SK068	DoC
AP	LANCOM	L-151E	DoC
Raspberry Pi	LANCOM	N/A	DoC
Test Fixture	LANCOM	400340781800002	N/A

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
LCD Monitor	DELL	1704FPT	DoC
Keyboard	iCooky	SK068	DoC
Mouse	Logitech	M-U0026	DoC
Raspberry Pi	Teleconformity	Raspb212	DoC
AP	LANCOM	LN-830E	DoC
Test Fixture	LANCOM	400340781800002	N/A

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters:

Test Software Version	LANCOM BLE		
Frequency	2402 MHz	2442 MHz	2480 MHz
Power Parameters	-2	-2	-2

### 3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

### 3.10. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
GFSK	1.000	1.000	100	0.00	0.01


### 3.11. Test Configurations

#### 3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	2m
2	Bus cable	No	0.1m
3	RJ-45 cable	No	10m
4	HDMI cable	Yes	1.8m
5	USB cable	Yes	1.8m
6	USB cable	Yes	1.8m

### 3.11.2. Radiation Emissions Test Configuration



Item	Connection	Shield	Length
1	HDMI cable	Yes	1.82m
2	RJ-45 cable	No	3m
3	Power cable	No	1.5m
4	Power cable	No	2m
5	Bus cable	No	0.1m
6	USB cable	Yes	1.8m
7	USB cable	Yes	1.8m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



## LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


## 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	59%
Test Engineer	GN Hou	Phase	Line
Configuration	CTX		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark	Pol/Phase
		Limit	Line	Level	Factor	Loss		
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1500	37.74	-18.26	56.00	27.62	9.96	0.16 Average	LINE
2	0.1500	52.99	-13.01	66.00	42.87	9.96	0.16 QP	LINE
3	0.1582	36.69	-18.87	55.56	26.57	9.96	0.16 Average	LINE
4	0.1582	49.91	-15.65	65.56	39.79	9.96	0.16 QP	LINE
5	1.7071	23.94	-22.06	46.00	13.63	10.07	0.24 Average	LINE
6	1.7071	31.52	-24.48	56.00	21.21	10.07	0.24 QP	LINE
7	3.1563	21.49	-24.51	46.00	11.09	10.10	0.30 Average	LINE
8	3.1563	29.57	-26.43	56.00	19.17	10.10	0.30 QP	LINE
9	5.0046	20.98	-29.02	50.00	10.52	10.12	0.34 Average	LINE
10	5.0046	28.44	-31.56	60.00	17.98	10.12	0.34 QP	LINE
11	7.4465	20.76	-29.24	50.00	10.26	10.14	0.36 Average	LINE
12	7.4465	28.24	-31.76	60.00	17.74	10.14	0.36 QP	LINE

<b>Temperature</b>	23°C	<b>Humidity</b>	59%
<b>Test Engineer</b>	GN Hou	<b>Phase</b>	Neutral
<b>Configuration</b>	CTX		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark	Pol/Phase
		Limit	Line	Level	Factor	Loss		
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1557	37.23	-18.46	55.69	27.11	9.96	0.16 Average	NEUTRAL
2	0.1557	51.73	-13.96	65.69	41.61	9.96	0.16 QP	NEUTRAL
3	0.1731	36.20	-18.61	54.81	26.08	9.96	0.16 Average	NEUTRAL
4	0.1731	49.46	-15.35	64.81	39.34	9.96	0.16 QP	NEUTRAL
5	0.3852	32.28	-15.89	48.17	22.11	9.97	0.20 Average	NEUTRAL
6	0.3852	39.19	-18.98	58.17	29.02	9.97	0.20 QP	NEUTRAL
7	1.5935	24.10	-21.90	46.00	13.89	9.98	0.23 Average	NEUTRAL
8	1.5935	30.88	-25.12	56.00	20.67	9.98	0.23 QP	NEUTRAL
9	1.7253	23.71	-22.29	46.00	13.48	9.99	0.24 Average	NEUTRAL
10	1.7253	30.48	-25.52	56.00	20.25	9.99	0.24 QP	NEUTRAL
11	3.1066	21.27	-24.73	46.00	10.96	10.01	0.30 Average	NEUTRAL
12	3.1066	28.17	-27.83	56.00	17.86	10.01	0.30 QP	NEUTRAL

Note: Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

The limit for output power is 30dBm.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r05 section 9.2.3.2.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	22°C	Humidity	54%
Test Engineer	Wen Chao	Configurations	GFSK
Test Date	Sep. 22, 2016 ~ Oct. 14, 2016		

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	7.28	30.00	Complies
20	2442 MHz	6.57	30.00	Complies
39	2480 MHz	6.32	30.00	Complies

## 4.3. Power Spectral Density Measurement

### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	5-30 % greater than the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

### 4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD).
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

### 4.3.4. Test Setup Layout



#### **4.3.5. Test Deviation**

There is no deviation with the original standard.

#### **4.3.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	22°C	Humidity	54%
Test Engineer	Wen Chao	Configurations	GFSK

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
0	2402 MHz	-5.04	8.00	Complies
20	2442 MHz	-6.73	8.00	Complies
39	2480 MHz	-8.11	8.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

### Power Density Plot on Configuration Bluetooth / 2402 MHz



Date: 14.OCT.2016 14:54:06

## 4.4. 6dB Spectrum Bandwidth Measurement

### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold

### 4.4.3. Test Procedures

#### For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth=> 8.1 Option 1.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 4.4.4. Test Setup Layout

#### For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.4.5. Test Deviation**

There is no deviation with the original standard.

#### **4.4.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth


Temperature	22°C	Humidity	54%
Test Engineer	Wen Chao	Configurations	GFSK

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
0	2402 MHz	0.69	1.17	500	Complies
20	2442 MHz	0.71	1.16	500	Complies
39	2480 MHz	0.71	1.17	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### 6 dB Bandwidth Plot on Configuration Bluetooth / 2402 MHz



Date: 14.OCT.2016 14:51:17

### 99% Occupied Bandwidth Plot on Configuration Bluetooth / 2402 MHz



Date: 14.OCT.2016 14:43:36

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.


#### 4.5.4. Test Setup Layout

For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



**For Radiated Emissions: Above 1GHz**

**4.5.5. Test Deviation**

There is no deviation with the original standard.

**4.5.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	CTX
Test Date	Oct. 05, 2015		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	CTX

*Horizontal*



Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
		Line	dBuV/m			dBuV	dB			dB	cm	deg	
1	39.70	35.20	40.00	-4.80	42.33	1.29	20.05	28.47	125	351	Peak	HORIZONTAL	
2	199.75	39.79	43.50	-3.71	49.70	1.86	16.00	27.77	125	258	Peak	HORIZONTAL	
3	250.19	43.53	46.00	-2.47	50.30	1.97	18.90	27.64	126	282	QP	HORIZONTAL	
4	266.68	41.68	46.00	-4.32	47.73	2.03	19.52	27.60	100	298	Peak	HORIZONTAL	
5	274.44	42.58	46.00	-3.42	48.81	2.05	19.30	27.58	150	193	Peak	HORIZONTAL	
6	299.66	41.20	46.00	-4.80	46.92	2.13	19.68	27.53	100	169	Peak	HORIZONTAL	

**Vertical**


Freq	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	Level	Line									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	31.94	35.63	40.00	-4.37	38.53	1.23	24.35	28.48	150	196 Peak	VERTICAL
2	199.75	39.29	43.50	-4.21	49.20	1.86	16.00	27.77	113	358 QP	VERTICAL
3	250.19	42.92	46.00	-3.08	49.69	1.97	18.90	27.64	125	347 Peak	VERTICAL
4	274.44	38.47	46.00	-7.53	44.70	2.05	19.30	27.58	100	269 Peak	VERTICAL
5	886.51	40.73	46.00	-5.27	37.85	3.43	27.50	28.05	125	301 Peak	VERTICAL
6	894.27	42.36	46.00	-3.64	39.39	3.44	27.55	28.02	125	322 Peak	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	Channel 0
Test Date	Sep. 22, 2016		

## Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
		Line	dBuV/m			dB	dBuV			dB	dB/m		
1	4804.36	58.96	74.00	-15.04	51.24	7.77	31.10	31.15	194	312	Peak	HORIZONTAL	
2	4814.00	34.80	54.00	-19.20	27.05	7.77	31.12	31.14	194	312	Average	HORIZONTAL	

## Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
		Line	dBuV/m			dB	dBuV			dB	dB/m		
1	4794.00	34.71	54.00	-19.29	27.03	7.75	31.08	31.15	190	211	Average	VERTICAL	
2	4804.28	50.84	74.00	-23.16	43.12	7.77	31.10	31.15	190	211	Peak	VERTICAL	

Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	Channel 20
Test Date	Sep. 22, 2016		

**Horizontal**

	Freq	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4883.80	53.38	74.00	-20.62	45.40	7.86	31.23	31.11	169	61	Peak HORIZONTAL
2	4894.00	34.22	54.00	-19.78	26.22	7.88	31.23	31.11	169	61	Average HORIZONTAL

**Vertical**

	Freq	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4883.68	52.23	74.00	-21.77	44.25	7.86	31.23	31.11	184	198	Peak VERTICAL
2	4894.00	34.02	54.00	-19.98	26.02	7.88	31.23	31.11	184	198	Average VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	Channel 39
Test Date	Sep. 22, 2016		

**Horizontal**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB				
1	4959.64	39.52	54.00	-14.48	31.29	7.97	31.34	31.08	183	295	Average	HORIZONTAL
2	4959.64	47.69	74.00	-26.31	39.46	7.97	31.34	31.08	183	295	Peak	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB				
1	4958.00	46.05	74.00	-27.95	37.82	7.97	31.34	31.08	108	21	Peak	VERTICAL
2	4960.24	36.40	54.00	-17.60	28.17	7.97	31.34	31.08	108	21	Average	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

#### For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

#### For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 11.0 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

#### **4.6.4. Test Setup Layout**

##### For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

##### For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.


#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions


Temperature	22°C	Humidity	54%
Test Engineer	Zero Chen	Configurations	Channel 0, 20, 39

##### Channel 0



Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
		Line	dBuV/m									
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	
1	2363.28	58.93	74.00	-15.07	27.09	4.84	27.00	0.00	199	313	Peak	HORIZONTAL
2	2390.00	46.92	54.00	-7.08	14.98	4.89	27.05	0.00	199	313	Average	HORIZONTAL
3 @	2402.00	100.71			68.74	4.89	27.08	0.00	199	313	Average	HORIZONTAL
4 @	2402.40	101.53			69.56	4.89	27.08	0.00	199	313	Peak	HORIZONTAL


Item 3, 4 are the fundamental frequency at 2402 MHz.

**Channel 20**


Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	2378.42	46.32	54.00	-7.68	14.41	4.87	27.04	0.00	192	314 Average	HORIZONTAL
2	2384.81	57.24	74.00	-16.76	25.32	4.87	27.05	0.00	192	314 Peak	HORIZONTAL
3 @	2442.00	104.06			71.93	4.95	27.18	0.00	192	314 Average	HORIZONTAL
4 @	2442.00	104.91			72.78	4.95	27.18	0.00	192	314 Peak	HORIZONTAL
5	2491.08	59.43	74.00	-14.57	27.15	5.00	27.28	0.00	192	314 Peak	HORIZONTAL
6	2493.88	48.01	54.00	-5.99	15.73	5.00	27.28	0.00	192	314 Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2442 MHz.

## Channel 39





Freq	Level	Limit	Over	Read	Antenna		Preamp	A/Pos	T/Pos	Remark	Pol/Phase
					Line	Limit					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 @ 2479.80	103.00				70.77	4.98	27.25	0.00	109	319 Peak	HORIZONTAL
2 @ 2480.00	102.11				69.88	4.98	27.25	0.00	109	319 Average	HORIZONTAL
3 2483.50	53.03	54.00	-0.97	20.78	4.98	27.27	0.00	109	319 Average		HORIZONTAL
4 2483.79	62.75	74.00	-11.25	30.50	4.98	27.27	0.00	109	319 Peak		HORIZONTAL

Item 1, 2 are the fundamental frequency at 2480 MHz.


## Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**For Emission not in Restricted Band**
**Plot on Configuration / Reference Level**

**Plot on Configuration For Bluetooth 4.0 / Channel 0 / 30MHz~2400MHz (down 30dBc)**



### Plot on Configuration For Bluetooth 4.0 / Channel 0 / 2483.5MHz~26500MHz (down 30dBc)



### Plot on Configuration For Bluetooth 4.0 / Channel 39 / 30MHz~2400MHz (down 30dBc)



**Plot on Configuration For Bluetooth 4.0 / Channel 39 / 2483.5MHz~26500MHz (down 30dBc)**



## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 16, 2015	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 13, 2015	Conduction (CO02-CB)
EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8.4GHz	Jan. 18, 2016	Conduction (CO02-CB)
COND Cable	Woken	Cable	01	0.15MHz ~ 30MHz	Dec. 01, 2015	Conduction (CO02-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO02-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Feb. 15, 2016	Conduction (CO02-CB)
BILOG ANTENNA	TESEQ	CBL6112D	37880	20MHz ~ 2GHz	Aug. 30, 2016	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2016*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 25, 2016	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 18, 2016	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 13, 2015	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
EMI Test	R&S	ESCS	100355	9kHz ~ 2.75GHz	May 16, 2016	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-17	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
Test Software	Audix	E3	6.2009-I0-7	N/A	N/A	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 09, 2015	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2016	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 02, 2015	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

\*Calibration Interval of instruments listed above is two year.

## 6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%


## Appendix A. Test Photos

## 1. Photographs of Conducted Emissions Test Configuration


**FRONT VIEW**



**REAR VIEW**



**CLOSE-UP VIEW**



## 2. Photographs of Radiated Emissions Test Configuration

**Test Configuration: 30MHz~1GHz**


**FRONT VIEW**



**REAR VIEW**




**CLOSE-UP VIEW**



**Test Configuration: Above 1GHz**

**FRONT VIEW**



**REAR VIEW**



**CLOSE-UP VIEW**

