

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# **TEST REPORT For FCC**

FCC Standards: FCC 47CFR part 15 subpart C

iest Report No CTR-2015-01465	Гest Report No.	:	CTK-2015-01489
-------------------------------	-----------------	---	----------------

Date of Issue : 2015-11-22

FCC ID : U5MBGT-100P

Basic Model/Type No. : BGT-10\*P

Kind of Product : mPOS Thermal Printer

Applicant : BIXOLON Co., Ltd.

Applicant Address : 7th-8th FL, Miraeasset Venture Tower, 20, Pangyoyeok-ro

241beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

Manufacturer : BIXOLON Co., Ltd.

Manufacturer Address : 7th-8th FL, Miraeasset Venture Tower, 20, Pangyoyeok-ro

241beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

Contact Person : Shin Ji Sung / Assistant Manager

Telephone : +82-31-218-5582

Received Date : 2015-10-16

Test period : Start : 2015-11-02 End : 2015-11-07

The test results presented in this report relate only to the object tested.

Tested by

Y. T. Lee

Young-taek Lee Test Engineer Date: 2015-11-22 Reviewed by

Young-Joon, Park Technical Manager Date: 2015-11-22

Test Report No.: CTK-2015-01489 Page 1 of 55
Date: 2015-11-22



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# REPORT REVISION HISTORY

Date	Revision	Page No
2015-11-22	Issued (CTK-2015-01489)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

Test Report No.: CTK-2015-01489 Page 2 of 55

Date: 2015-11-22

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



# **TABLE OF CONTENTS**

REPORT	REVISION HISTORY	. 2
1.0	General Product Description	
1.1	Tested Frequency	
1.2	Tested Mode	
1.3	Model Differences	. 5
1.4	Device Modifications	. 5
1.5	Peripheral Devices	
1.6	Calibration Details of Equipment Used for Measurement	. 5
1.7	Test Facility	
1.8	Laboratory Accreditations and Listings	
2.0	Summary of tests	
2.1	Transmitter Requirements	
2.1.		
2.1.		
2.1.		
2.1.	pour our adotte our part i or	
2.1.	*** ***********************************	
2.1.	, out of the control	
2.1.		
2.1.		
APPEND	IX A – Test Equipment Used For Tests	55

Test Report No.: CTK-2015-01489 Date: 2015-11-22





# 1.0 General Product Description

Equipment model name	BGT-10*P	
Serial number	Prototype	
EUT condition	Pre-production, not damaged	
Antenna type	Chip antenna Gain -0.28 dBi	
Frequency Range	2402 MHz - 2480 MHz	
RF power	7.67 dBm Peak Conducted (GFSK) 8.72 dBm Peak Conducted (8-DPSK)	
Type of Modulation	Frequency Hopping Spread Spectrum	
Number of channels	79	
Channel Spacing	1 MHz	
Channel Access Protocol	Frequency Hopping	
Type of Modulation	GFSK(1Mbps), DQPSK(2Mbps), 8-DPSK(3Mbps)	
Power Source	DC 24 V	

# 1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

## 1.2 Tested Mode

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Tested Ch	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Test Report No.: CTK-2015-01489 Page 4 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

## 1.3 Model Differences

Remark: BGT-10\*P

'\*' means a buyer or optional function and may be alphanumeric.

## 1.4 Device Modifications

The following modifications were necessary for compliance:

Not applicable

# 1.5 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Notebook	Hewlett Packard Co.,Ltd	A3008CD10003	5CG5114KD2
AC Adapter	Hewlett Packard Co.,Ltd	PPP012D-S	WCNXF0AAR8T4UV

# 1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

# 1.7 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea.

Test Report No.: CTK-2015-01489 Page 5 of 55



# **Laboratory Accreditations and Listings**

Country	Agency	Scope of Accreditation	Registration Number	Logo
USA	FCC	FCC Part 15 & 18 EMI (Electromagnetic Interference / Emission)	805871	FC
JAPAN	VCCI	VCCI V-3 EMI (Electromagnetic Interference / Emission)	C-986 T-1843 R-3627 G-387	V€I
KOREA	MSIP	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)		

Test Report No.: CTK-2015-01489 Page 6 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# 2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz		С
15.247(a)	Number of Hopping Frequencies	> 15 hops		С
15.247(a)	20 dB Bandwidth	NA		С
15.247(a)	Dwell Time	< 0.4 seconds	Conducted	С
15.247(b)	Transmitter Output Power	< 0.125 Watts		С
15.247(d)	Conducted Spurious emission	> 20 dBc		С
15.247(d)	Band Edge	> 20 dBc		С
15.209	Field Strength of Harmonics	15.209(a)	Radiated	С
15.207	AC Conducted Emissions	15.207(a)	Line Conducted	С

The sample was tested according to the following specification:

The tests were performed according to the method of measurements prescribed in DA 00-705.

Test Report No.: CTK-2015-01489 Page 7 of 55

<sup>-</sup> FCC Part 15.247, ANSI C63.10-2013



# 2.1 Transmitter Requirements

## 2.1.1 Carrier Frequency Separation

### **Test Location**

RF Test Room

#### **Test Procedures**

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

## The spectrum analyzer is set to:

Span = 5 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz ( $\geq$  1% of the span) Sweep = auto

VBW = 100 kHz ( $\geq$  RBW) Detector function = peak

Trace = max hold




Figure 1: Measurement setup for the carrier frequency separation

#### Limit

§15.247(a)(1) Frequency hopping system operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-third of 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### **Test Results**

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	1000.0	625.0	25	Complies

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)


i cot illouc i	o bi sit, ci o i it i acite	L Type . Si I deket s	NEC . IUEI(JD	<i></i>
	Adjacent Hopping	Two-third of 20dB	Minimum	
Channel	Channel Separation	bandwidth	Bandwidth	Result
	(kHz)	(kHz)	(kHz)	
2441MHz	1010.0	833.3	25	Complies

See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-01489 Page 8 of 55

### **Carrier Frequency Separation**

### Test mode: GFSK



Date: 3.NOV.2015 14:55:04

# Test mode: 8-DPSK **8** \*RBW 30 kHz Delta 2 [T1 ] -0.55 dB \*VBW 30 kHz 1.010000000 MHz Ref 15 dBm 50 dB SWT 15 ms Att Off Marker 1 [T1 44199 0 P GH2 MUNUM JUNIV 3DB

500 kHz/

Date: 3.NOV.2015 16:29:00

Center 2.441 GHz

Test Report No.: CTK-2015-01489 Page 9 of 55

Date: 2015-11-22

Span 5 MHz



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# 2.1.2 Number of Hopping Frequencies

### **Test Location**

RF Test Room

### **Test Procedures**

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

### The spectrum analyzer is set to:


Frequency range 1: Start = 2389.5 MHz, Stop = 2439.5 MHz

2: Start = 2439.5 MHz, Stop = 2489.5 MHz

RBW = 300 kHz ( $\geq 1\% \text{ of the span}$ ) Sweep = auto

 $VBW = 300 \text{ kHz} (\geq RBW)$ Detector function = peak

Trace = max hold



#### Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.

### **Test Results**

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Total number of Hopping Channels	Result
79	Complies

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Total number of Hopping Channels	Result
79	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-01489 Page 10 of 55


Date: 2015-11-22

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)

## Number of Hopping Frequencies(GFSK)




Date: 3.NOV.2015 15:15:23




Date: 3.NOV.2015 15:16:19

Test Report No.: CTK-2015-01489 Page 11 of 55

## **Number of Hopping Frequencies(8-DPSK)**



Date: 3.NOV.2015 16:33:15



Date: 3.NOV.2015 16:36:19

Test Report No.: CTK-2015-01489

Date: 2015-11-22

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)

Page 12 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### 2.1.3 20 dB bandwidth

### **Test Location**

RF Test Room

#### **Test Procedures**

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels. After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = approximately 2 or 3 times of the 20 dB bandwidth

RBW = 30 kHz ( $\geq 1\%$  of the 20 dB bandwidth) Sweep = auto

VBW = 30 kHz (≥ RBW) Detector function = peak

Trace = max hold

EUT \_\_\_\_\_ Spectrum Analyzer

#### Limit

Limit: N/A

Test Report No.: CTK-2015-01489 Page 13 of 55 Date: 2015-11-22



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### **Test Results**

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

		, pe : : : : : : ;		
Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result	
2402	0	0.881	Complies	
2441	39	0.937	Complies	
2480	78	0.946	Complies	


Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

1 COC III OUC I O DI O	1 1011(55115)		
Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2402	0	1.234	Complies
2441	39	1.250	Complies
2480	78	1.250	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-01489 Page 14 of 55

### 20 dB Bandwidth - GFSK




Date: 3.NoV.2015 14:20:34



Date: 3.NOV.2015 14:20:07

Test Report No.: CTK-2015-01489 Page 15 of 55







Date: 3.NOV.2015 14:18:37

Test Report No.: CTK-2015-01489 Page 16 of 55 Date: 2015-11-22

### 20 dB Bandwidth - 8-DPSK




Date: 3.NOV.2015 18:55:23



Date: 3.NOV.2015 18:53:39

Test Report No.: CTK-2015-01489 Page 17 of 55





Date: 3.NOV.2015 18:52:07

Test Report No.: CTK-2015-01489 Page 18 of 55 Date: 2015-11-22



# 2.1.4 Time of Occupancy (Dwell Time)

#### **Test Location**

RF Test Room

### **Test Procedures**

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- 4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- 5. Repeat above procedures until all frequencies measured were complete.
- 6. The SPP-R200IIIa has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second.

### The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

Span = zero

RBW = 1 MHz Trace = max hold

 $VBW = 1 MHz (\ge RBW)$  Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel



## Limit

 $\S15.247(a)(1)(iii)$  For frequency hopping system operating in 2400-2483.5 MHz band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Report No.: CTK-2015-01489 Page 19 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### **Test Results**

Time of occupancy on the TX channel in 31.6 sec = time domain slot length  $\times$  hop rate  $\div$  number of hop per channel  $\times$  31.6

### Test mode: GFSK

Channel		cket Type Dwell Time (ms)	Test Results	
Frequency (MHz)	Packet Type		Time of occupancy on the TX channel in 31.6sec (ms)	Result
	DH 1	0.433	138.56	Complies
2402	DH 3	1.683	269.28	Complies
	DH 5	2.960	315.73	Complies

DH1 Dwell time =  $0.433 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 138.56 \text{ ms}$ DH3 Dwell time =  $1.683 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 269.28 \text{ ms}$ DH5 Dwell time =  $2.960 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 315.73 \text{ ms}$ 

## Test mode: 8-DPSK


	i est illoue	ic i o bi sk				
	Channel Frequency Packet Type (MHz)		Dwell Time (ms)	Test Results		
		Packet Type		Time of occupancy on the TX channel in 31.6sec (ms)	Result	
		3DH 1	0.449	143.68	Complies	
	2480	3DH 3	1.699	271.84	Complies	
		3DH 5	2.980	317.87	Complies	

DH1 Dwell time =  $0.449 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 143.68 \text{ ms}$ DH3 Dwell time =  $1.699 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 271.84 \text{ ms}$ DH5 Dwell time =  $2.980 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 317.87 \text{ ms}$ 

See next pages for actual measured spectrum plots.


Test Report No.: CTK-2015-01489 Page 20 of 55

# Time of Occupancy for PACKET Type DH1(GFSK)



Date: 3.NOV.2015 19:02:58

## Time of Occupancy for PACKET Type DH3(GFSK)




Date: 3.NOV.2015 19:01:48

Test Report No.: CTK-2015-01489 Page 21 of 55




# Time of Occupancy for PACKET Type DH5(GFSK)



Date: 3.NOV.2015 16:40:11


Test Report No.: CTK-2015-01489 Page 22 of 55 Date: 2015-11-22

# Time of Occupancy for PACKET Type 3DH1(8-DPSK)



Date: 3.NOV.2015 18:59:15


## **Time of Occupancy for PACKET Type 3DH3(8-DPSK)**



Date: 3.NOV.2015 19:00:33

Test Report No.: CTK-2015-01489 Page 23 of 55

# Time of Occupancy for PACKET Type 3DH5(8-DPSK)



Date: 3.NOV.2015 16:38:26

Test Report No.: CTK-2015-01489 Page 24 of 55 Date: 2015-11-22



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

## 2.1.5 Maximum peak Conducted Output Power

#### **Test Location**

RF Test Room

### **Test Procedures**

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

Span = approximately 5 times of the 20 dB bandwidth

RBW = 1 MHz (greater than the 20 dB bandwidth of the emission being measured)

 $VBW = 1 MHz (\ge RBW)$  Detector function = peak

Trace =  $\max$  hold Sweep = auto



#### Note:

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. The RF output of EUT was connected to the spectrum analyzer by low loss cable.

### Limit

 $\S 5.247(b)(1)$  The Maximum Peak Output Power Measurement is 0.125 Watts for frequency hopping system operating in 2400-2483.5 MHz employing at least 15 Hopping channels.

Test Report No.: CTK-2015-01489 Page 25 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### **Test Results**

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Channel No.	Peak output	Peak output	Result
(MHz) 2402	0	power(dBm) 7.67	power(mW) 5.85	Complies
2441	39	7.63	5.79	Complies
2480	78	7.67	5.85	Complies


Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

1000111100010 21014	0: 0 : 1:: : acitet : / Po : 0 = : acitet o: = 0 : = 0 = =			(
Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	8.72	7.45	Complies
2441	39	8.16	6.55	Complies
2480	78	8.23	6.65	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-01489 Page 26 of 55

## **Maximum peak Conducted Output Power - GFSK**




Date: 3.NOV.2015 14:06:21



Date: 3.NOV.2015 14:07:48

Test Report No.: CTK-2015-01489 Page 27 of 55







Date: 3.NOV.2015 14:08:23

Page 28 of 55 Test Report No.: CTK-2015-01489

## **Maximum peak Conducted Output Power - 8-DPSK**




Date: 3.NOV.2015 16:47:46



Date: 3.NOV.2015 16:47:23

Test Report No.: CTK-2015-01489 Page 29 of 55





Date: 3.NOV.2015 16:48:22

Page 30 of 55 Test Report No.: CTK-2015-01489

Date: 2015-11-22 -11-22
This Report shall not be reproduced except in full without the written approval of CTK
Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

## 2.1.6 RF Conducted Emissions

#### **Test Location**

RF Test Room

### **Test Procedures**

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

### The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz

 $VBW = 100 \text{ kHz} (\geq RBW)$ 

Span = 10 MHz Detector function = peak

Trace =  $\max$  hold Sweep = auto



### Limit

> 20 dBc


#### **Test Results**

All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest level of the inband spectral density. Therefore the applying equipment meets the requirement.


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-01489 Page 31 of 55

## Band - edge (Hopping mode) - GFSK




Date: 3.NOV.2015 14:50:54




Date: 3.NOV.2015 14:49:40

Test Report No.: CTK-2015-01489 Page 32 of 55

# Band - edge (Hopping mode) - 8-DPSK




Date: 3.NOV.2015 16:17:41




Date: 3.NOV.2015 16:20:27

Test Report No.: CTK-2015-01489 Page 33 of 55

# Band - edge (Non-Hopping mode) - GFSK




Date: 3.NOV.2015 14:47:14




Date: 3.NOV.2015 14:48:07

Test Report No.: CTK-2015-01489 Page 34 of 55

# Band - edge (Non-Hopping mode) - 8-DPSK




Date: 3.NOV.2015 16:16:27




Date: 3.NOV.2015 16:18:54

Test Report No.: CTK-2015-01489 Page 35 of 55

## Spurious (at 20 dB blow) - Low channel Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic (Test mode : GFSK)



Date: 3.NOV.2015 19:41:33




Date: 3.NOV.2015 19:41:56


Test Report No.: CTK-2015-01489

Page 36 of 55

# Spurious (at 20 dB blow) – Mid channel Frequency Range = 30 MHz $\sim 10^{th}$ harmonic (Test mode : GFSK)




Date: 3.NOV.2015 19:43:21




Date: 3.NOV.2015 19:43:40

Test Report No.: CTK-2015-01489

### Spurious (at 20 dB blow) - High channel Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic (Test mode : GFSK)



Date: 3.NOV.2015 19:44:25




Date: 3.NOV.2015 19:45:00


Test Report No.: CTK-2015-01489



# Spurious (at 20 dB blow) – Low channel Frequency Range = 30 MHz $\sim$ 10<sup>th</sup> harmonic (Test mode: 8-DPSK)




Date: 3.NOV.2015 19:49:13




Date: 3.NOV.2015 19:49:29

Test Report No.: CTK-2015-01489

# Spurious (at 20 dB blow) – Mid channel Frequency Range = 30 MHz $\sim 10^{th}$ harmonic (Test mode: 8-DPSK)




Date: 3.NOV.2015 19:50:36




Date: 3.NOV.2015 19:50:51

Test Report No.: CTK-2015-01489 Page 40 of 55

### Spurious (at 20 dB blow) - High channel Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic (Test mode: 8-DPSK)



Date: 3.NOV.2015 19:52:07



Date: 3.NOV.2015 19:52:39

Test Report No.: CTK-2015-01489



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### 2.1.7 Other requirements Frequency Hopping Spread Spectrum System

### Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidth of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. in addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Example of a 79 hopping sequence in data mode:

l	20	62	46	77		_7_	64		8	73		16	75	1_
l														
					L						J			

Test Report No.: CTK-2015-01489 Page 42 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### 2.1.8 Field Strength of Emissions

### Test Location

 $\boxtimes$  10 m SAC (test distance :  $\square$  10 m,  $\boxtimes$  3 m) □ 3 m SAC (test distance : 3 m)

#### **Test Procedures**

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency rage above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

#### The spectrum analyzer is set to:

Frequency Range = 9 kHz ~ 25 GHz (2.4 GHz 10<sup>th</sup> harmonic) RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz, 9 kHz for f < 30 MHz VBW ≥ RBW Sweep = auto

Test Report No.: CTK-2015-01489 Page 43 of 55

Date: 2015-11-22



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### Limit

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
					_
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
<sup>1</sup> 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475- 156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	<sup>2</sup> Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

<sup>&</sup>lt;sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Test Report No.: CTK-2015-01489 Page 44 of 55

<sup>&</sup>lt;sup>2</sup> Above 38.6



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency(MHz)	Field Strength	Field Strength	Deasurement
i requericy(MIIZ)	uV/m@3m	dBuV/m@3m	Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

<sup>\*\*</sup> Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

#### Note:

- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)
- 3) For measurement above 1GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 1 MHz for peak measurement and 10 Hz for average measurement.


Test Report No.: CTK-2015-01489 Page 45 of 55




(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### **Test Setup:**

1) For field strength of emissions from 9 kHz to 30 MHz



2) For field strength of emissions from 30 MHz to 1 GHz



Test Report No.: CTK-2015-01489


Date: 2015-11-22

Page 46 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

3) For field strength of emissions above 1 GHz



# Test Results 1) 9 kHz to 30 MHz

EUT	mPOS Thermal Printer	Measurement Detail				
Frequency	Range	9 kHz – 30 MHz				
Test mode	GFSK (Worst case)	Detector function	Quasi-Peak			

#### The requirements are:

Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	
-	ı	ı	See note

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

Test Report No.: CTK-2015-01489 Page 47 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### 2) 30 MHz to 1 GHz


#### Test mode: Hopping(GFSK), CFG PKT Packet Type: 15 Packet Size: 339(DH5)

	- F F S C 71	<b>/</b>	
EUT	mPOS Thermal Printer	Measurement Detail	
Frequency	Range	Below 1000MHz	
Test mode	8-DPSK (Worst case)	Detector function	Quasi-Peak

#### The requirements are:

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
266.68	43.7	2.3	Quasi-Peak

#### **Test Data**



1 1110	II Nesult								
No.	Frequency	(P)	Reading QP	o.f	Result QP	Limit QP	Margin QP	Height	Angle
	[MHz]		[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]
1	266,680	Н	53.1	-9.4	43.7	46.0	2.3	100.0	48.0
2	266,680	V	46.9	-9.4	37.5	46.0	8.5	195.0	160.0
3	533,309	V	35.8	-1.5	34.3	46.0	11.7	100.0	349.0
4	768,049	Н	29.1	3.4	32.5	46.0	13.5	100.0	309.0
5	800,059	Н	35.5	4.1	39.6	46.0	6.4	205.0	52.0
6	800,059	V	30.9	4.1	35.0	46.0	11.0	100.0	312.0
7	864.079	Н	28.5	5.7	34.2	46.0	11.8	100.0	11.0
8	933,434	Н	28.8	7.4	36.2	46.0	9.8	100.0	160.0

### Remark:

- 1. The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
- 2. Result = Reading + Correction factor
- 3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator Amp Gain

Test Report No.: CTK-2015-01489 Page 48 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

### 3) above 1 GHz

EUT	mPOS Thermal Printer	Measurement Detail	
Model	BGT-10*P	Frequency Range	1-25GHz
Channel	Channel 0	Detector function	Peak

#### Remarks

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4804	47.3	6.7	Average

#### **Test Data**

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	equency Reading H		Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak	
4804.00	34.7 45.6	Н	2.0	12.6	54.0 74.0	47.3 58.2	6.7 15.8	

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]		Pol.	Height	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
[MHz]	AV /	Peak		[m]	Antenna + Amp. Gain + Cable	AV /	<b>Peak</b>	AV ,	/ Peak	AV /	Peak
4804.00	30.9	46.4	Н	2.0	12.6	54.0	74.0	43.5	59.0	10.5	15.0

### Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	cy Reading [dBuV/m] Pol.		Height	Height Correction Factor		Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak	
2390.00	37.2 49.6	Н	2.0	3.1	54.0 74.0	40.3 52.7	13.8 21.3	
	l :				1 :	l : '		

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
2390.00	40.4 51.1	Н	2.0	3.1	54.0 74.0	43.5 54.2	10.5 19.8

Test Report No.: CTK-2015-01489 Page 49 of 55

Date: 2015-11-22

This Report shall not be reproduced except in full without the written approval of CTK



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

EUT	mPOS Thermal Printer	Measurement Detail	
Model	BGT-10*P	Frequency Range	1-25GHz
Channel	Channel 39	Detector function	Peak

#### Remarks

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

M Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4882	46.5	7.5	Average

#### **Test Data**

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4882.00	33.9 45.7	Н	2.0	12.6	54.0 74.0	46.5 58.3	7.5 15.7

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4882.00	30.9 46.6	Н	2.0	12.6	54.0 74.0	43.5 59.2	10.5 14.8

### Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading	Pol.	Height	Correction Factor		Limits	Result	Margin		
[MHz]	[dBuV/m]		[m]	Antenna	Amp. Gain	Cable	[dBuV/m]	[dBuV/m]	[dB]	
	No emissions were detected at a level greater than 20dB below limit.									

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading	Pol.	Height	Correction Factor		Limits	Result	Margin	
[MHz]	[dBuV/m]		[m]	Antenna	Amp. Gain	Cable	[dBuV/m]	[dBuV/m]	[dB]
No emissions were detected at a level greater than 20dB below limit.									

Test Report No.: CTK-2015-01489 Page 50 of 55

Date: 2015-11-22



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

EUT	mPOS Thermal Printer	Measurement Detail	
Model	BGT-10*P	Frequency Range	1-25GHz
Channel	Channel 78	Detector function	Peak

#### **Remarks**

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

□ Complies

□ complics			
Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	Keiliaik
2483.5	52.3	1.7	Average

#### **Test Data**

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4960.00	36.0 46.1	Н	2.0	12.8	54.0 74.0	48.8 58.9	5.2 15.1

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4960.00	31.0 46.8	Н	2.0	12.8	54.0 74.0	43.8 59.6	10.2 14.4

#### Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m] Pol.		Height		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]		
[MHz]	AV ,	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV	/ Peak	AV ,	/ Peak	AV /	Peak
2483.50	49.2	63.1	Н	2.0	3.1	54.0	74.0	52.3	66.2	1.7	7.8

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m] Pol.		Height		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak	
2483.50	49.1 66.6	Н	2.0	3.1	54.0 74.0	52.2 69.7	1.8 4.3	

Test Report No.: CTK-2015-01489 Page 51 of 55

Date: 2015-11-22

This Report shall not be reproduced except in full without the written approval of CTK



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

#### 2.1.9 AC Conducted Emissions

#### **Test Location**

Shielded Room

#### **Frequency Range of Measurement**

150 kHz to 30 MHz

### **Instrument Settings**

IF Band Width: 9 kHz

#### **Test Procedures**

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

#### Limit

#### - 15.207(a)

Frequency	Conducted Limit (dBuV)					
(MHz)	Quasi-peak	Average				
0.15 ~ 0.5	66 to 56*	56 to 46*				
0.5 ~ 5	56	46				
5 ~ 30	60	50				

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **Test Results**

The requirements are:

Test mode: Hopping(GFSK), CFG PKT Packet Type: 15,

Packet Size: 339(DH5)


Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	
0.150	45.2	20.8	QuasiPeak

Test Report No.: CTK-2015-01489 Page 52 of 55



## Test Data\_Hopping(GFSK)

[L1] CISPR 22 Class B\_L1



### **Final Result 1**

Frequency (MHz)	QuasiPeak (dBm)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBm)
0.150000	45.2	1000.0	9.000	On	L1	9.7	20.8	66.0
0.195000	40.0	1000.0	9.000	On	L1	9.8	23.8	63.8
0.253500	35.7	1000.0	9.000	On	L1	9.6	26.0	61.6
0.289500	32.6	1000.0	9.000	On	L1	9.7	27.9	60.5
0.370500	29.1	1000.0	9.000	On	L1	9.9	29.4	58.5
0.469500	26.2	1000.0	9.000	On	L1	9.9	30.3	56.5

### **Final Result 2**


	Juit =							
Frequency (MHz)	CAverage (dBm)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBm)
0.181500	22.2	1000.0	9.000	On	L1	9.8	32.3	54.4
0.537000	15.2	1000.0	9.000	On	L1	9.9	30.8	46.0
0.991500	12.8	1000.0	9.000	On	L1	9.7	33.2	46.0
1.108500	15.3	1000.0	9.000	On	L1	9.7	30.7	46.0
10.900500	17.7	1000.0	9.000	On	L1	9.9	32.3	50.0
24.126000	19.5	1000.0	9.000	On	L1	10.0	30.5	50.0

Page 53 of 55 Test Report No.: CTK-2015-01489



## [NEUTRAL]

CISPR 22 Class B\_N



## **Final Result 1**

Frequency (MHz)	QuasiPeak (dBm)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBm)
0.150000	45.1	1000.0	9.000	On	N	9.7	20.9	66.0
0.186000	41.0	1000.0	9.000	On	N	9.8	23.2	64.2
0.253500	35.2	1000.0	9.000	On	N	9.6	26.4	61.6
0.316500	31.0	1000.0	9.000	On	N	9.8	28.8	59.8
0.420000	26.9	1000.0	9.000	On	N	9.9	30.5	57.4
0.478500	25.4	1000.0	9.000	On	N	9.9	31.0	56.4

### **Final Result 2**

Frequency (MHz)	CAverage (dBm)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBm)
0.487500	15.5	1000.0	9.000	On	N	9.9	30.7	46.2
0.996000	17.2	1000.0	9.000	On	N	9.7	28.8	46.0
1.108500	17.9	1000.0	9.000	On	N	9.7	28.1	46.0
1.392000	14.9	1000.0	9.000	On	N	9.7	31.1	46.0
4.191000	15.3	1000.0	9.000	On	N	9.7	30.7	46.0
21.529500	20.2	1000.0	9.000	On	N	10.1	29.8	50.0

Page 54 of 55 Test Report No.: CTK-2015-01489



# **APPENDIX A – Test Equipment Used For Tests**

	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2015-11-02	2016-11-02
2	Spectrum Analyzer	Rohde & Schwarz	FSP	100401	2015-05-13	2016-05-13
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2014-12-05	2015-12-05
4	EMI Test Receiver	Rohde & Schwarz	ESCI7	100816	2014-12-05	2015-12-05
5	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2015-05-15	2016-05-15
6	Bilog Antenna	Schaffner	CBL6111C	2551	2014-05-08	2016-05-08
7	Double Ridged Guide Antenna	ETS-Lindgren	3116	00062916	2015-04-30	2017-04-30
8	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2014-05-19	2016-05-19
9	Attenuator	Rohde & Schwarz	DNF	272.4110.50-2	2015-11-04	2016-11-03
10	PREAMPLIFIER	Agilent	8449B	3008A02307	2015-10-01	2016-10-01
11	AMPLIFIER	Sonoma Instrument Co.	310	291721	2015-02-02	2016-02-02
12	Band Reject Filter	Wainwright Instruments GmbH	WRCGV 2400/2483- 2375/2505- 50/10EE	2	2015-05-14	2016-05-14
13	Signal Generator	Rohde & Schwarz	SMB100A	175528	2015-01-19	2016-01-19
14	LISN	Rohde & Schwarz	ENV216	101760	2015-02-02	2016-02-02
15	LISN	Rohde & Schwarz	ENV216	101150	2015-02-02	2016-02-02
16	DC Power Supply	Topward Electric Instruments Co.,Ltd.	6303D	666421	2015-02-03	2016-02-03
17	DC Power Supply	Agilent	E3632A	MY40011638	2015-11-02	2016-11-02

Page 55 of 55 Test Report No.: CTK-2015-01489