

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : BIXOLON Co., Ltd.

: 7th~8th FL, Miraeasset Venture Tower, 685,

Applicant Address Sampyeong-dong, Bundang-gu Seongnam-si,

Gyeonggi-do, Korea

Kind of Product : Thermal Receipt Printer

Equipment model name : SRP-35*plusIII

RF power : 14.446 dBm Peak Conducted

Antenna type : Chip antenna

Antenna Gain : -0.28 dBi

Frequency Range : 2402 MHz - 2480 MHz

Number of channels : 79 CH



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where,
EIRP = 14.446 + (-0.28) = 14.166 dBm => 26.10 mW	P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$ (dB antenna gain / 10)

 $G = Log^{-1} (-0.28/10)$

G = 0.94

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where,
$S = (26.10)/(4 * 20^2 * \pi)$	S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
S =0.005 mW/cm ²	antenna (20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm 2 . The power density at 20cm does not exceed the 1 mW/cm 2 limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where,
$R = \sqrt{(26.10 / 4\pi)}$	P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
R = 1.44 cm	antenna (20cm = limit for MPE)