

11 FCC §1.1307(b) (1) & §2.1091 - RF EXPOSURE

11.1 Applicable Standard

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

11.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Cellular Band:

Worst Case: EDGE Middle Channel 881.6 MHz

Maximum peak output power at antenna input terminal (dBm): 23.21

Maximum peak output power at antenna input terminal (mW): 209.41

Prediction distance (cm): 30

Prediction frequency (MHz): 881.6

Antenna Gain, typical (dBi): 5

Maximum Antenna Gain (numeric): 3.16

Power density at predication frequency and distance (mW/cm²): 0.0585

MPE limit for uncontrolled exposure at predication frequency (mW/cm²): 0.5877

PCS Band:

Worst Case: EDGE Middle Channel 1960 MHz

Maximum peak output power at antenna input terminal (dBm):	<u>22.26</u>
Maximum peak output power at antenna input terminal (mW):	<u>168.27</u>
Prediction distance (cm):	<u>30</u>
Prediction frequency (MHz):	<u>1960</u>
Antenna Gain, typical (dBi):	<u>5</u>
Maximum Antenna Gain (numeric):	<u>3.16</u>
Power density at predication frequency and distance (mW/cm ²):	<u>0.0470</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm ²):	<u>1.0</u>

Test Result

For Cellular Band, the highest power density level at 30 cm is 0.0585 mW/cm², which is below the uncontrolled exposure limit of 0.5877 mW/cm² at 881.6 MHz.

For PCS Band, the highest power density level at 30 cm is 0.0470 mW/cm², which is below the uncontrolled exposure limit of 1 mW/cm² at 1960 MHz.

This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 30 cm between the radiation and your body.