



RF EXPOSURE REPORT

REPORT NO.: SA960306L09

MODEL NO.: WZ-2154X (refer to page 3 for more details)

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Wizyoung Tech. Corp.

ADDRESS: 9F., No.25, Sec. 1, Nanjing E. Rd., Taipei City,
Taiwan

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.412	24.62
High	2.462	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)
Conducted Power	8.10
EIRP Power	13.10

***Note:** The antenna is Dipole antenna with 5dBi gain

Threshold for no SAR evaluation is 24.62mW

Transmitter power is 20.417mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold



The models as below are identical to each other, except for their model designation and different enclosure color due to marketing requirement.

Brand	Model	Remark
Wizyoung Tech. Corp.	WZ-2154X (X= 1~ 9, A~Z)	for different enclosure color