

CONNECT-FLX-ZNA Antennas

433.92MHz Antenna

433.92MHz antennas are PCB trace antennas of the inverted F type attached to the PCB. This antenna type has a gain of 3dBi.

908.42MHz Antenna (Z-Wave)

908.42MHz antenna is a PCB trace antenna of the inverted F type attached to the PCB. This antenna type has a gain of 3dBi.

WiFi Antenna

The WiFi antenna is integral to the ESP32-WROOM WiFi module. The gain is shown in the specification as 2 dBi.



ESP-WROOM-02 PCB Design and Module Placement Guide

1. Introduction

The ESP-WROOM-02 module is designed to be soldered to a host PCB. The placement of the module and antenna needs to adhere to our guidelines, in order to optimize the RF performance of the final product. This application note describes the recommended placement of the antenna on a host board to ensure optimal RF performance.

2. Module Placement

The PCB antenna used on ESP-WROOM-02 is a Meandered Inverted F Antenna (MIFA) for the 2.4G Wi-Fi band with an antenna [gain](#) of 2 dBi. Figure 1 shows six placement options that are commonly used; option 1 is used as a reference, and the measurements results show that option 2 and 3 have the best performances, while the other options are sub-optimal.

Cellular Antenna

The cellular antenna is a PCBA antenna, Quectel part number YC0003BA. The gain of this antenna is 3.1-3.5dBi.



The image shows a Quectel YC0003BA cellular antenna. It is a rectangular, black PCB antenna with a small red and white logo on its side. The text on the side of the antenna reads "YC0003BA" and "698-2690MHz". The background of the image is a light gray with a subtle diamond pattern. The Quectel logo is located in the top right corner of the image area.

Antenna Datasheet

Product OC (Antenna Only): YC0003BA
(Antenna + Rectangular EVB): YC0003BAEVB

Version: 3.1
Date: 2023-11-21
Status: Released

Product Name: 4G SMD Antenna
Key Features:
High efficiency, excellent performance
Frequency band: 700–960 MHz, 1710–2690 MHz
Peak efficiency: 62 % (On 120 mm × 43 mm GND)
Dimensions: 40 mm × 7 mm × 3 mm
RoHS & REACH Compliant

www.quectel.com

AVG Eff. (%)	On 120 x 43 mm GND	-	57.3	55.8	51.6	46.9	40.8	42.9
	On 110 x 43 mm GND	-	47.7	54.2	52.3	49.7	42.6	42.3
	On 100 x 43 mm GND	-	37.1	44.2	44.8	52.5	48.4	46.4
	On 90 x 43 mm GND	-	30.3	34.6	43.7	46.3	44.2	44.5
	On 80 x 43 mm GND	-	25.6	29.1	54.0	54.3	48.6	45.0
AVG Avg Gain (dB)	On 120 x 43 mm GND	-	-2.4	-2.5	-2.9	-3.3	-3.9	-3.7
	On 110 x 43 mm GND	-	-3.2	-2.7	-2.8	-3.1	-3.7	-3.8
	On 100 x 43 mm GND	-	-4.3	-3.6	-3.5	-2.8	-3.2	-3.3
	On 90 x 43 mm GND	-	-5.2	-4.6	-3.6	-3.4	-3.6	-3.6
	On 80 x 43 mm GND	-	-6.0	-5.4	-2.7	-2.7	-3.2	-3.5
Max Peak Gain (dBi)	On 120 x 43 mm GND	-	0.5	0.7	3.0	3.1	2.6	2.8
	On 110 x 43 mm GND	-	0.0	0.5	2.9	2.9	3.0	3.4
	On 100 x 43 mm GND	-	-0.9	-0.4	2.5	2.7	3.0	2.7
	On 90 x 43 mm GND	-	-1.9	-1.6	2.3	2.8	3.0	2.7
	On 80 x 43 mm GND	-	-2.0	-2.1	2.6	3.2	3.5	2.9
VSWR	On 120 x 43 mm GND					≤ 3.5		
	On 110 x 43 mm GND					≤ 3.5		
	On 100 x 43 mm GND					≤ 3.9		
	On 90 x 43 mm GND					≤ 4.3		
	On 80 x 43 mm GND					≤ 4.8		
Return Loss	On 120 x 43 mm GND					≤ -5.1 dB		
	On 110 x 43 mm GND					≤ -5.1 dB		
	On 100 x 43 mm GND					≤ -4.6 dB		
	On 90 x 43 mm GND					≤ -4.1 dB		
	On 80 x 43 mm GND					≤ -3.7 dB		
Peak Gain	On 120 x 43 mm GND					≤ 3.1 dBi		

On 110 x 43 mm GND	≤ 3.4 dBi
On 100 x 43 mm GND	≤ 3 dBi
On 90 x 43 mm GND	≤ 3 dBi
On 80 x 43 mm GND	≤ 3.5 dBi