RADIO FREQUENCY EXPOSURE REPORT

FOR THE

Device: Thermanode EZ Model: 0944

Report No.: 93248-19

Date of issue: July 23, 2012

PREPARED FOR:

SynapSense Corporation 2365 Iron Point Road, Suite 100 Folsom CA 95630

PREPARED BY:

Chuck Kendall CKC Laboratories, Inc. 5046 Sierra Pines Drive Mariposa, CA 95338

Page 1 of 8 Report No: 93248-19



Purpose:

To demonstrate compliance with United States, Canada and/or European Union RF Exposure requirements for Portable equipment (devices used ≤20cm from the body) or Mobile equipment (devices used >20cm from the body) with power output below exemption levels and Mobile equipment, where Maximum Permissible Exposure (MPE) Calculations apply.

United States Compliance Requirements (1.1310):

RF Exposure Evaluation Limits Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1	6
300-1500			f/300	6
1500-100,000			5.0	6

RF Exposure Evaluation Limits General Population / Uncontrolled Exposure

Central i opanation / Cited Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)		
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f ²)	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

^{*} Plane wave equivalent power density

Limit is calculated based on the mid-band frequency used in the operating frequency range.

Exemption Level: Power output $<60/f_{GHz}$ (mW)

Canadian Compliance Requirements (RSS-102):

RF Exposure Evaluation Limits Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m²)	Averaging Time (minutes)	
0.003-1.0	600	4.9		6	
1.0-10	600/f	4.9/f		6	
10-30	60	4.9/f		6	
30-300	60	0.163	10	6	
300-1500	3.54 f ^{0.5}	0.0094*f ^{0.5}	f/3	6	
1500-15,000	137	0.364	50	6	
15,000-150,000	137	0.364	50	616000/f ^{1.2}	

RF Exposure Evaluation Limits General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m²)	Averaging Time (minutes)
0.003-1.0	280	2.19		6
1.0-10	280/f	2.19/f		6
10-30	28	2.19/f		6
30-300	28	0.073	2	6
300-1500	1.585 * f ^{0.5}	0.0042 * f ^{0.5}	f/150	6
1500-15,000	61.4	0.163	10	6
15,000-150,000	61.4	0.163	10	616000/f ^{1.2}

^{*}Power density limit applicable >100MHz

Exemption Level:

Frequency Range (MHz)	Maximum Output Power (Conducted or EIRP)
0.003-1000	≤ 200 mW
1000-2200	≤ 100 mW
2200-3000	≤ 20 mW
3000-6000	≤ 10 mW

European Union Compliance Requirements (ICNIRP):

RF Exposure Evaluation Limits Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m²)	Averaging Time (minutes)
0.00082-0.065	610	24.4		6
0.065-1.0	610	1.6/f		
1.0-10	610/f	1.6/f		6
10-400	61	0.16	10	6
400-2000	3.0 * f ^{0.5}	0.008 * f ^{0.5}	f/40	6
2000-300,000	137	0.36	50	6

RF Exposure Evaluation Limits General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m²)	Averaging Time (minutes)
0.003-0.150	87	5.0		6
0.150-1.0	87	0.73/f		6
1.0-10	87/f ^{0.5}	0.73/f		6
10-400	28	0.073	2	6
400-2000	1.375 f ^{0.5}	0.0037*f ^{0.5}	f/200	6
2000-300,000	61	0.16	10	6

^{*}Power density limit applicable >100MHz

Exemption Level: Power output < 20mW¹

Device and Antenna Operating Configuration:

Device operating at maximum output power with continuous transmission of modulated data.

Orientated in wall mounted position as intended, the EUT is placed on the wooden table lined with Styrofoam of 10 cm thickness. The I/O cables and AC/DC power cables are routed in as designed. I/O cable are unterminated.

The EUT is set in constant transmit mode at the rated power.

The Support AC step-down transformer is remotely located.

Antenna gain = 3.3 dBi Modulation: O-QPSK, Protocol: Zigbee (802.15) Freq: 2400-2483.5MHz

Test Procedure:

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65 & ANSI C95.1 for the US and Health Canada Safety Code 6 & RSS 102 for Canada.

Other Considerations:

None or Delete "none & Insert specific

MPE Calculations

Applicability:

Limit Used	Х	General Population / Uncontrolled Exposure
Littit Osea		Occupational / Controlled Exposure
	Yes	United States
RF Exposure Exemption	Yes	Canada
	No	Europe

Equipment operational details:

Config #	Operating Frequency (MHz)	Measured Output Power (dBm)	Antenna Gain (dBi)	Antenna Type / Configuration	EIRP (dBm)
1	2445	4.7	3.3	integral	8.0

Measurements based from EMC Test Report(s): 93248-9

MPE Calculation:

PowerDensity =
$$\frac{EIRP}{4\pi d^2}$$
 Given: **EIRP** in mW or W and **d** in cm or m

		US (1.1310)		Canada ('RSS-102)	EU (IC	CNIRP)
Config	Distance	Power	Limit	Power	Limit	Power	Limit
#	(cm)	Density	(mW/cm²)	Density	(W/m^2)	Density	(W/m^2)
		(mW/cm²)		(W/m^2)		(W/m^2)	
1	20	Exempt		Exempt		Exempt	

Page 6 of 8 Report No: 93248-19

Summary:

Exemptions:

In the case the equipment meets compliance requirements by exemption the product is approved for use under mobile or portable conditions without further testing under the condition that any additional collocation or simultaneous transmission requirements (including necessary separation distances) have been met.

Page 7 of 8 Report No: 93248-19

References

- Federal Communications Commission Knowledge Database (KDB) Publication 447498, "What are the RF exposure requirements and procedures for mobile and portable devices?" As in effect on the issue date of this report.
- Federal Communications Commission Bulletin OET 65 Supplement C, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields" June 2001
- Title 47 Code of Federal Regulations, Part 1.1310, "Radiofrequency radiation exposure limits." As in effect on the issue date of this report.
- Title 47 Code of Federal Regulations, Part 2.1091, "Radiofrequency radiation exposure evaluation: mobile devices." As in effect on the issue date of this report.
- Health Canada Safety Code 6 <u>Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the</u>
 <u>Frequency Range from 3 kHz to 300 GHz</u>, 2009
- Health Canada Safety Code 6 Technical Guide, 2009
- Industry Canada RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010 (including update December, 2010)
- International Commission on Non-Ionizing Radiation Protection. Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). Health Physics 74 (4): 494-522; 1998.
- International Commission on Non-Ionizing Radiation Protection Statement on the "Guidelines for limiting exposure to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz). Health Physics 97(3):257-259; 2009.
- European Committee for Electrotechnical Standardization. European Normative, EN 50371 <u>Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz) 2002.</u>

Page 8 of 8 Report No: 93248-19