Description of Operation

The EUT is a N+ High Power Broadband Router - All Broadbands with IEEE

802.11b/g/n (2T2R) . And this device provided of transmitting speed:

IEEE 802.11b: 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps

<u>IEEE 802.11n HT20 : 65, 58.5, 52, 39, 26, 19.5, 13, 6.5 Mbps</u> <u>IEEE 802.11n HT40 : 135, 121.5, 108, 81, 54, 40.5, 27, 13.5 Mbps</u>

the device of RF carrier is CCK, DQPSK, DBPSK, 64QAM, 16QAM, QPSK and BPSK.

The device adapts <u>DSSS</u> and <u>OFDM</u> modulation. And the antennas were <u>two dipole</u> <u>antennas</u> and provided diversity function to improve the receiving function. It allows your computer to connect to a wireless network and to share resources, such as files or printers without being bound to the network wires.

And this EUT Operation in 2.4GHz <u>Direct Sequence Spread Spectrum (D.S.S.S) and</u>

Orthogonal Frequency division Multiplex (O.F.D.M) radio transmission.

In addition, its standard compliance ensures that it can communicate with any **802.11b/g/n** network.

Frequency Range	IEEE 802.11b/g, 802.11n HT20 (DTS Band):2412MHz∼2462MHz IEEE 802.11n HT40 (DTS Band):2422MHz∼2452MHz
Channel Spacing	IEEE 802.11b/g, 802.11n HT20/HT40: 5MHz
Channel Number	IEEE 802.11b/g, 802.11n HT20:11 Channels IEEE 802.11n HT40 :7 Channels

Remark: This device does not support the CDD mode.