

INVENTEC BESTA CO., LTD.
10FL., No. 36, Lane 513, Rui Guang Road, Nei Hu Dist., Taipei 114,
Taiwan, R.O.C.

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: Digital Wireless Receiver
Model No: DMR-101

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.


A safety statement concerning minimum separation distances from enclosure of the
Product : Digital Wireless Receiver
will be integrated in the user's manual to provide end-users with transmitter operating
conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21411-14612-C-1
and the accompanying calculations.

Company: INVENTEC BESTA CO., LTD.
Address: 10FL., No. 36, Lane 513, Rui Guang Road, Nei Hu Dist., Taipei 114, Taiwan,
R.O.C.

Date: 2014-11-13

Signature *Chang Yuan-young*



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21411-14612-C-1
FCC ID: U6OCA913

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain (Directional gain)

$$\text{EIRP} = 14.85 \text{ dBm} + 2.5 \text{ dBi}$$

$$= 17.35 \text{ dBm}$$

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{P G}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	30.5492	Peak value
D	dB		
AG	dBi	2.5	
G		1.77827941	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.010807597	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0