

FCC LISTED,
REGISTRATION
NUMBER: 905266



CENTRO DE
TECNOLOGÍA DE LAS
COMUNICACIONES, S.A.

Parque Tecnológico de Andalucía,
c/Severo Ochoa nº 2
29590 Campanillas/ Málaga/ España
Tel. 952 61 91 00 - Fax 952 61 91 13
MÁLAGA, C.I.F. A29 507 456
Registro Mercantil Tomo 1169 Libro 82
Folio 133 Hoja MA3729

TEST REPORT




Report No.: 25762RET

TEST NAME: FCC PART 22, PART 24

Product	: ECG Cardiograph (Recorder / Transmitter) with GSM
Trade Mark	: CardioSen'C
Model/type Ref.	: CardioSen'C
Manufacturer	: SHL Telemedicine International Ltd.
Requested by	: SHL Telemedicine International Ltd.
Other identification of the product	: FCC ID: U6VCBSENC Serial number: 08001060
Standard(s)	: FCC Part 22 & 24

This test report includes 3 annexes and therefore the total number of pages is 36

IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (AT4 WIRELESS).

Date: 2007-04-24	Test operator A. Llamas 	Revised by: Date: 2007-04-24 J.C. Soler Consultant  Centro de Tecnología de las Comunicaciones, S.A. 	Approved by: Date: 2007-04-24 J.A. Rodrigo Technical Director 	Page: 1 of 7
------------------	---	---	---	--------------

INDEX

1. COMPETENCE AND GUARANTEES	3
2. GENERAL CONDITIONS	3
3. CHARACTERISTICS OF THE TEST	3
3.1 TEST REQUESTED.....	3
3.2 REQUIREMENTS AND METHOD	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT.....	4
4.1 APPLICANT.....	4
4.2 REPRESENTATIVE.....	4
4.3 TEST SAMPLES SUPPLIER.....	5
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS	5
5.1 USAGE OF SAMPLES	5
5.2 PERIOD OF TESTING	5
5.3 ENVIROMENTAL CONDITIONS.....	6
6. TEST RESULTS	7
7. REMARKS AND COMMENTS.....	7
8. SUMMARY.....	7

ANNEXES

- ANNEX A. TEST RESULTS FOR FCC PART 22
- ANNEX B. TEST RESULTS FOR FCC PART 24
- ANNEX C. PHOTOGRAPHS

Report No.: 25762RET		Page: 2 of 7
Date: 2007-04-24		

1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (AT4 WIRELESS), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

In order to assure the traceability to other national and international laboratories, AT4 WIRELESS has a calibration and maintenance programme for its measuring equipment.

AT4 WIRELESS guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at AT4 WIRELESS at the time of execution of the test.

AT4 WIRELESS is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of AT4 WIRELESS.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of AT4 WIRELESS and the Accreditation Bodies.

3. CHARACTERISTICS OF THE TEST

3.1 TEST REQUESTED

1. Measurements for PCS 850 and PCS 1900 devices according to FCC parts 22 and 24:
 - Radiated RF output power.
 - Radiated emissions.

3.2 REQUIREMENTS AND METHOD

The test has been carried out according to the following documents and standards:

1. FCC part 22.
2. FCC part 24.

Radiated testing was performed in AT4 WIRELESS' semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002. Radiated measurements were made in accordance with the general procedures of ANSI C63.4: 2003 and substitution method according to TIA/EIA 603-C: 2004.

Report No.:		Page: 3 of 7
25762RET		
Date: 2007-04-24		

Uncertainty (factor k=2) was calculated according to the following AT4 WIRELESS' internal documents:

1. PODT000: Procedimiento para el cálculo de incertidumbres de medida

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Spectrum Analyzer Agilent E4440A.
4. Bilog antenna CHASE CBL6111.
5. Antenna tripod EMCO 11968C.
6. Antenna mast EM 1072 NMT.
7. Rotating table EM 1084-4. ON.
8. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
9. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
10. RF pre-amplifier Miteq AFS5-04001300-15-10P-6.
11. RF pre-amplifier Miteq JS4-12002600-30-5A.
12. EMI Test Receiver R&S ESIB26.
13. Universal Radio communication Tester R&S CMU200.
14. 10 dB attenuator HP 8491B.
15. Multi Device Controller EMCO 2090.
16. DC Power supply R & S NGPE 40/40.

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data in this section has been supplied by the client.

4.1 APPLICANT

Name or Company: SHL Telemedicine International Ltd.

V.A.T.: ----

Address: Ashdar Building, 90 Igal Alon St.

City: Tel Aviv

Postal code: 67891

Country: ISRAEL

Telephone: +972-3-5612212

Fax: +972-3-6242414

4.2 REPRESENTATIVE

Name: Roni Kazaz (Products Development Director)

Report No.: 25762RET		Page: 4 of 7
Date: 2007-04-24		

4.3 TEST SAMPLES SUPPLIER

Name or Company: BDR Technologies Ltd.

V.A.T.: ----

Address: Ha-Harash, 6

City: Nes Ziona

Postal code: 74106

Country: ISRAEL

Telephone: 972-8-9401718

Fax: 972-8-9401314

Samples undergoing test have been selected by: **the client.**

4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

Product: ECG Cardiograph (Recorder / Transmitter) with GSM

Trade mark: CardioSen'C **Model:** CardioSen'C

Hw version: 2.0 **SW version:** 2.0

Manufacturer: SHL Telemedicine International Ltd.

Country of manufacture: ISRAEL

Description: Cardiograph (Recorder / Transmitter) with GSM

5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

5.1 USAGE OF SAMPLES

Sample M/01 is formed by the following elements:

Control No.	Description	Model	Serial No.	Date of reception
25762/01	Cardiograph with GSM	CardioSen'C	08001060	22/02/07

1. Sample M/01 has undergone the following test(s).

Radiated measurements indicated in annex A and B.

5.2 PERIOD OF TESTING

The performed test started on 2007-02-22 and finished on the same day.

The tests as detailed in this report have been performed at AT4 WIRELESS.

Report No.: 25762RET		Page: 5 of 7
Date: 2007-04-24		

5.3 ENVIRONMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 24 °C Max. = 25 °C
Relative humidity	Min. = 51 % Max. = 51 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 25 °C Max. = 25 °C
Relative humidity	Min. = 50 % Max. = 50 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

Report No.: 25762RET		Page: 6 of 7
Date: 2007-04-24		

6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

- P** Pass
- F** Fail
- NA** not applicable
- NM** not measured

FCC PART 22 PARAGRAPH	VERDICT			
	NA	P	F	NM
Clause 22.913: RF output power	P			
Clause 22.917: Radiated emissions	P			

FCC PART 24 PARAGRAPH	VERDICT			
	NA	P	F	NM
Clause 24.232: RF output power	P			
Clause 24.238: Radiated emissions	P			

7. REMARKS AND COMMENTS

None.

8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 “TEST REQUESTED”.

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 “IDENTIFICATION OF ITEM/ITEMS TESTED” of this document, as presented for test on the date(s) declared in section 5, “USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS”.

Report No.: 25762RET		Page: 7 of 7
Date: 2007-04-24		



ANNEX A
TEST RESULTS FOR FCC PART 22

Report No: 25762RET

Report No: 25762RET		Page: 1 of 12
Date: 2007-04-24		Annex A

INDEX

	Page
TEST CONDITIONS	3
RF Output Power (E.R.P.)	4
Radiated emissions	5

Report No:
25762RET

Date: 2007-04-24

FET45_00.DOC

Page: 2 of 12

Annex A

TEST CONDITIONS

Power supply (V):

$$V_{\text{nom}} = 3 \text{ Vdc}$$

Type of power supply = 2 x type AA lithium battery 1.5 V

Type of antenna = Integral antenna

TEST FREQUENCIES:

Lowest channel (128): 824.2 MHz

Middle channel (190): 836.6 MHz

Highest channel (251): 848.8 MHz

Report No:
25762RET

Date: 2007-04-24

FET45_00.DOC

Page: 3 of 12

Annex A

RF Output Power (E.R.P.)

SPECIFICATION

§2.1046 and 22.913

The Effective Radiated Power (E.R.P.) of mobile transmitter and auxiliary test transmitter must not exceed 7 Watts (38.45 dBm).

METHOD

For radiated measurements the EUT was placed on a 1 m high non-conductive stand inside an anechoic chamber. The measuring antenna was placed at 3 m distance and the maximum field strength was measured for the three channels. The EUT was controlled via the Universal Radio Communication tester R&S CMU200 selecting maximum transmission power of the EUT and GMSK modulated signal.

The Effective Radiated Power (E.R.P.) is obtained by using the Substitution Method according to ANSI/TIA/EIA-603-C: 2004.

RESULTS

MAXIMUM EFFECTIVE RADIATED POWER E.R.P. (RADIATED).

Channel	Lowest	Middle	Highest
Maximum peak power (dBm)	11.50	10.50	8.74
Maximum peak power (W)	0.014	0.011	0.007
Measurement uncertainty (dB)	± 3.8		

Verdict: PASS

Report No: 25762RET		Page: 4 of 12
Date: 2007-04-24		Annex A

Radiated emissions

SPECIFICATION

§ 22.917

METHOD

The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment.

The EUT was placed on a 1 meter high non-conductive stand at a 3 meter distance from the measuring antenna for measurements below 1 GHz and at 1 m distance for measurements above 1 GHz.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum meter reading was recorded. The radiated emissions were measured with peak detector and 1 MHz bandwidth.

Each detected emissions were substituted by the Substitution method, in accordance with the ANSI/TIA/EIA-603-C: 2004.

Measurement Limit:

According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB, P in watts.

At P_o transmitting power, the specified minimum attenuation becomes $43 + 10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm}$$

Report No: 25762RET		Page: 5 of 12
Date: 2007-04-24		Annex A

RESULTS

Frequency range 30 MHz-1000 MHz.

The result do not depend on the operating channel selected.

Carrier level (dBm) = 8.74 (worst case)

Spurious frequency (MHz)	Level (dBm)	Polarization	Attenuation below carrier (dBc)
115.71180	-38.62	Horizontal	47.36

Frequency range 1 GHz-12.75 GHz.

1. CHANNEL: LOWEST (824.2MHz).

Carrier level (dBm) = 11.50

Spurious frequency (MHz)	Level (dBm)	Polarization	Attenuation below carrier (dBc)
2472.700	-13.47	Horizontal	24.97

2. CHANNEL: MIDDLE (836.6 MHz).

Carrier level (dBm) = 10.50

Spurious frequency (MHz)	Level (dBm)	Polarization	Attenuation below carrier (dBc)
2509.958	-17.97	Horizontal	28.47

3. CHANNEL: HIGHEST (848.8 MHz).

Carrier level (dBm) = 8.74


Spurious frequency (MHz)	Level (dBm)	Polarization	Attenuation below carrier (dBc)
1697.5870	-26.85	Horizontal	35.59
2546.382	-21.94	Horizontal	30.68

Verdict: PASS

Report No: 25762RET		Page: 6 of 12
Date: 2007-04-24		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.


CHANNEL: LOWEST (824.2 MHz)



Note: The peak above the limit is the carrier frequency.

Report No: 25762RET		Page: 7 of 12
Date: 2007-04-24		Annex A


CHANNEL: MIDDLE (836.6 MHz)



Note: The peak above the limit is the carrier frequency.

Report No: 25762RET		Page: 8 of 12
Date: 2007-04-24		Annex A

CHANNEL: HIGHEST (848.8 MHz)




Note: The peak above the limit is the carrier frequency.

Report No: 25762RET		Page: 9 of 12
Date: 2007-04-24		Annex A


FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL: LOWEST (824.2 MHz)

* Agilent




CHANNEL: MIDDLE (836.6 MHz)



Report No: 25762RET		Page: 10 of 12
Date: 2007-04-24		Annex A

CHANNEL: HIGHEST (848.8 MHz)


* Agilent



Report No: 25762RET		Page: 11 of 12
Date: 2007-04-24		Annex A

FREQUENCY RANGE 3 GHz to 12.75 GHz.

 Agilent



(This plot is valid for all three channels).

Report No: 25762RET		Page: 12 of 12
Date: 2007-04-24		Annex A



ANNEX B
TEST RESULTS FOR FCC PART 24

Report No: 25762RET

Report No: 25762RET		Page: 1 of 11
Date: 2007-04-24		Annex B

INDEX

	Page
TEST CONDITIONS	3
RF Output Power (E.I.R.P.).....	4
Radiated emissions	5

Report No: 25762RET		Page: 2 of 11
Date: 2007-04-24		Annex B

TEST CONDITIONS

Power supply (V):

$$V_{\text{nom}} = 3 \text{ Vdc}$$

Type of power supply = 2 x type AA lithium battery 1.5 V

Type of antenna = Integral antenna

TEST FREQUENCIES:

Lowest channel (512): 1850.2 MHz

Middle channel (662): 1880.2 MHz

Highest channel (810): 1909.8 MHz

Report No:
25762RET

Date: 2007-04-24

FET45_00.DOC

Page: 3 of 11

Annex B

RF Output Power (E.I.R.P.)

SPECIFICATION

§2.1046 and 24.232

Mobile/portable stations are limited to 2 Watts (33 dBm) Effective Isotropic Radiated Power (E.I.R.P.) peak power.

METHOD

For radiated measurements the EUT was placed on a 1 m high non-conductive stand inside an anechoic chamber. The measuring antenna was placed at 1 m distance and the maximum field strength was measured for the three channels. The EUT was controlled via the Universal Radio Communication tester R&S CMU200 selecting maximum transmission power of the EUT and GMSK modulated signal.

The Effective Isotropic Radiated Power (E.I.R.P.) is obtained by using the Substitution Method according to ANSI/TIA/EIA-603-C: 2004.

RESULTS

MAXIMUM EQUIVALENT ISOTROPIC RADIATED POWER E.I.R.P. (RADIATED).

Channel	Lowest	Middle	Highest
Maximum peak power (dBm)	16.88	16.95	17.64
Maximum peak power (W)	0.049	0.049	0.058
Measurement uncertainty (dB)	± 4.0		

Verdict: PASS

Report No: 25762RET		Page: 4 of 11
Date: 2007-04-24		Annex B

Radiated emissions

SPECIFICATION

§ 24.238

METHOD

The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment.

The EUT was placed on a 1 meter high non-conductive stand at a 3 meter distance from the measuring antenna for measurements below 1 GHz and at 1 m distance for measurements above 1 GHz.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum meter reading was recorded. The radiated emissions were measured with peak detector and 1 MHz bandwidth.

Each detected emissions were substituted by the Substitution method, in accordance with the ANSI/TIA/EIA-603-C: 2004.

Measurement Limit:

According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB, P in watts.

At P_o transmitting power, the specified minimum attenuation becomes $43 + 10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm}$$

Report No: 25762RET		Page: 5 of 11
Date: 2007-04-24		Annex B

RESULTS

Frequency range 30 MHz-1000 MHz.

The result do not depend on the operating channel selected.

Carrier level (dBm) = 16.88 (worst case)

Spurious frequency (MHz)	Level (dBm)	Polarization	Attenuation below carrier (dBc)
115.71180	-38.62	Horizontal	55.5

Frequency range 1 GHz-20 GHz.

1. CHANNEL: LOWEST (1850.2MHz).

No spurious signals were found in all the range.

2. CHANNEL: MIDDLE (1880.2 MHz).

No spurious signals were found in all the range.


3. CHANNEL: HIGHEST (1909.8 MHz).

No spurious signals were found in all the range.

Verdict: PASS

Report No: 25762RET		Page: 6 of 11
Date: 2007-04-24		Annex B

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels).

Report No: 25762RET		Page: 7 of 11
Date: 2007-04-24		Annex B

FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL: LOWEST (1850.2 MHz)


* Agilent



Note: The peak above the limit is the carrier frequency.

CHANNEL: MIDDLE (1880.2 MHz)

* Agilent




Note: The peak above the limit is the carrier frequency.

Report No: 25762RET		Page: 8 of 11
Date: 2007-04-24		Annex B

CHANNEL: HIGHEST (1909.8 MHz)

 Agilent



Note: The peak above the limit is the carrier frequency.

Report No:
25762RET

Date: 2007-04-24


FET45_00.DOC

Page: 9 of 11

Annex B

FREQUENCY RANGE 3 GHz to 12.75 GHz.


 Agilent



(This plot is valid for all three channels).

FREQUENCY RANGE 12.75 GHz TO 18 GHz.

 Agilent




(This plot is valid for all three channels).

Report No: 25762RET		Page: 10 of 11
Date: 2007-04-24		Annex B

FREQUENCY RANGE 18 GHz TO 20 GHz.

* Agilent



(This plot is valid for all three channels).

Report No:
25762RET

Date: 2007-04-24

FET45_00.DOC

Page: 11 of 11

Annex B

ANNEX C

PHOTOGRAPHS (Number of photographs: 5)

Report No.: 25762RET

Report No.: 25762RET		Page: 1 of 6
Date: 2007-04-24		Annex C

1. Equipment (front view)




Report No.: 25762RET		Page: 2 of 6
Date: 2007-04-24		Annex C

2. Equipment (back view)



Report No.: 25762RET		Page: 3 of 6
Date: 2007-04-24		Annex C

3. General test set-up for radiated measurements.



Report No.:
25762RET


Date: 2007-04-24

FET18_00.DOC

Page: 4 of 6

Annex C

4. Test set-up for radiated measurements below 1 GHz.



Report No.:
25762RET


Date: 2007-04-24

FET18_00.DOC

Page: 5 of 6

Annex C

5. Test set-up for radiated measurements above 1 GHz.



Report No.: 25762RET		Page: 6 of 6
Date: 2007-04-24		Annex C