

FCC Report (NFC)

Applicant: Magtek Incorporated

Address of Applicant: 1710 Apollo Court, seal beach, California 90740, United States

Manufacturer: Magtek Incorporated

Address of Manufacturer: 1710 Apollo Court, seal beach, California 90740, United States

Equipment Under Test (EUT)

Product Name: Dynawave

Model No.: 21079814

Trade Mark: MAGTEK

FCC ID: U73-21079814A0

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.225

Date of sample receipt: June 28, 2018

Date of Test: June 29, 2018-August 21, 2018

Date of report issued: August 22, 2018

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature of Robinson Lo is written over a circular blue stamp. The stamp contains the text "GTS" in the center, surrounded by "GLOBAL UNITED TECHNOLOGY SERVICES CO." and "TESTING" at the bottom, with "2018" at the bottom right.

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	August 22, 2018	Original

Prepared By:




Date:

August 22, 2018

Project Engineer

Check By:



Date:

August 22, 2018

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	6
5.3 TEST FACILITY.....	6
5.4 TEST LOCATION.....	6
5.5 DESCRIPTION OF SUPPORT UNITS.....	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	9
7.1 ANTENNA REQUIREMENT:.....	9
7.2 CONDUCTED EMISSIONS	10
7.3 FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK MEASUREMENT.....	13
7.4 RADIATED EMISSION.....	15
7.5 20DB EMISSION BANDWIDTH.....	19
7.6 FREQUENCY STABILITY MEASUREMENT	21
8 TEST SETUP PHOTO	23
9 EUT CONSTRUCTIONAL DETAILS.....	25

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field Strength of Fundamental Emissions and Mask Measurement	15.225(a)(b)(c)	Pass
Radiated Emission	15.225(d)&15.209	Pass
20dB Emission Bandwidth	15.225&15.215	Pass
Frequency Stability Measurement	15.225(e)	Pass

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Dynawave
Model No.:	21079814
Serial No.:	B416D99
Test sample(s) ID:	GTS201806000077-1
Sample(s) Status	Engineered sample
Hardware Version:	mDynamo_NFCB V004C
Software Version:	EMCdynamo_34_06_17
Operation Frequency:	13.56MHz
Channel Number:	1
Modulation:	ASK
Antenna type:	Integral Antenna
Antenna gain:	2.0dBi (declare by Applicant)
Power supply:	DC 5.0V

5.2 Test mode

Transmitter mode	Keep the EUT in continuously transmitting.					
Pre-test mode.						
GTS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:						
Axis	X	Y	Z			
Field Strength(dBuV/m)	58.05	58.48	57.69			
Final Test Mode:						
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”: Y axis (see the test setup photo)						

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number
Apple	Notebook PC	A1278	C1MN99ERDTY3
Customer to provide	CONTACTLESS card	N/A	N/A

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement:	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	

The antenna is integral antenna, the best case gain of the antenna is 2.0dBi




7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<p>* Decreases with the logarithm of the frequency.</p>																
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test results:	Pass																

Measurement data:

Line:



Freq MHz	Reading level dBuV	LISM/ISM factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.17	44.60	0.40	0.08	45.08	65.16	-20.08	QP
0.17	28.15	0.40	0.08	28.63	55.16	-26.53	Average
0.19	41.50	0.40	0.10	42.00	64.15	-22.15	QP
0.19	24.83	0.40	0.10	25.33	54.15	-28.82	Average
0.23	35.42	0.40	0.11	35.93	62.30	-26.37	QP
0.23	22.63	0.40	0.11	23.14	52.30	-29.16	Average
0.31	29.32	0.39	0.10	29.81	59.84	-30.03	QP
0.31	22.00	0.39	0.10	22.49	49.84	-27.35	Average
0.45	26.72	0.33	0.11	27.16	56.89	-29.73	QP
0.45	22.15	0.33	0.11	22.59	46.89	-24.30	Average
0.48	28.99	0.32	0.11	29.42	56.32	-26.90	QP
0.48	24.66	0.32	0.11	25.09	46.32	-21.23	Average


Neutral:


Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Limit Level dBuV	Over level dBuV	Over limit dB	Remark
0.16	46.45	0.40	0.08	46.93	65.47	-18.54	QP
0.16	29.37	0.40	0.08	29.85	55.47	-25.62	Average
0.18	42.59	0.40	0.10	43.09	64.37	-21.28	QP
0.18	24.58	0.40	0.10	25.08	54.37	-29.29	Average
0.23	35.71	0.40	0.11	36.22	62.30	-26.08	QP
0.23	22.27	0.40	0.11	22.78	52.30	-29.52	Average
0.32	29.93	0.39	0.10	30.42	59.80	-29.38	QP
0.32	22.20	0.39	0.10	22.69	49.80	-27.11	Average
0.49	26.00	0.32	0.11	26.43	56.23	-29.80	QP
0.49	18.04	0.32	0.11	18.47	46.23	-27.76	Average
1.42	23.68	0.20	0.16	24.04	56.00	-31.96	QP
1.42	19.18	0.20	0.16	19.54	46.00	-26.46	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.3 Field Strength of Fundamental Emissions and Mask Measurement


Test Requirement:	FCC Part15 C Section 15.225(a)(b)(c)		
Test Method:	ANSI C63.10:2013		
Test site:	Measurement Distance: 3m		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=Auto		
limit:	Frequency (MHz)	Field Strength (microvolts/meter) at 30m	Field Strength (dBuV/m) at 3m
	1.705~13.110	30	69.5
	13.110~13.410	106	80.5
	13.410~13.553	334	90.5
	13.553~13.567	15848	124.0
	13.567~13.710	334	90.5
	13.710~14.010	106	80.5
Test setup:	14.010~30.000	30	69.5
			
Test Procedure:	<ol style="list-style-type: none"> Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable. Power on the EUT, the turntable was rotated by 360 degrees to determine the position of the highest radiation. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength. For Fundamental emissions, use the receiver to measure QP reading. When the radiated emissions limits are expressed in terms of the average value of the emissions and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. 		

	6. Compliance with the spectrum mask is tested using a spectrum analyzer with RB set to a 1KHz for the band 13.553~13.567MHz.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement data:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark
13.56	33.27	24.70	0.51	58.48	124.00	-65.52	QP

Test plot as follows:



7.4 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.225(d) and 15.209							
Test Method:	ANSI C63.10: 2013							
Test Frequency Range:	9KHz to 1000MHz							
Test site:	Measurement Distance: 3m							
Receiver setup:	Frequency	Detector	RBW	VBW	Remark			
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value			
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value			
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value			
Limit:	All out of band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.							
	Frequency (MHz)	Field strength (microvolt/meter)	Measurement distance (meters)					
	0.009~0.490	2400/F(KHz)	300					
	0.490~1.705	24000/F(KHz)	30					
	1.705~30	30	30					
	30~88	100	3					
	88~216	150	3					
	216~960	200	3					
	960~1000	500	3					
Test setup:	Below 30MHz							
								
	Above 30MHz							




Test Procedure:	<ol style="list-style-type: none"> Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable. Power on the EUT, the turntable was rotated by 360 degrees to determine the position of the highest radiation. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization. For each suspected emissions, the antenna tower was scan (from 1M to 4M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading. Set the test-receiver system to Peak or CISPR quasi-peak detect function with specified bandwidth under maximum hold mode. When the radiated emissions limits are expressed in terms of the average value of the emissions and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:
■ 9kHz~30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ 30MHz~1GHz

Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV	Limit level dBuV/m	Over limit dB	Remark
45.535	49.85	12.26	0.72	35.96	26.87	40.00	-13.13	QP
107.888	53.06	11.31	1.26	36.79	28.84	43.50	-14.66	QP
112.524	45.01	10.68	1.30	36.82	20.17	43.50	-23.33	QP
198.588	53.10	10.31	1.83	37.32	27.92	43.50	-15.58	QP
239.987	52.76	11.85	2.07	37.37	29.31	46.00	-16.69	QP
286.982	54.01	13.24	2.30	37.41	32.14	46.00	-13.86	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
45.217	58.98	12.26	0.72	35.95	36.01	40.00	-3.99	QP
107.888	63.97	11.31	1.26	36.79	39.75	43.50	-3.75	QP
132.221	59.05	8.01	1.45	36.97	31.54	43.50	-11.96	QP
155.910	56.96	8.05	1.60	37.11	29.50	43.50	-14.00	QP
180.017	55.00	8.90	1.74	37.24	28.40	43.50	-15.10	QP
239.987	52.74	11.85	2.07	37.37	29.29	46.00	-16.71	QP


7.5 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.225 and 15.215
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test Procedure:	<ol style="list-style-type: none"> 1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 <p>The diagram illustrates the test setup for measuring 20dB Emission Bandwidth. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a red cable. The E.U.T is placed on a Non-Conducted Table. The entire setup is positioned above a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test frequency (MHz)	20dB bandwidth (KHz)	Result
13.56	2.837	Pass

Test plot as follows:



7.6 Frequency Stability Measurement

Test Requirement:	FCC Part15 C Section 15.225 (e)
Test Method:	ANSI C63.10: 2013
Receiver setup:	RBW=1KHz, VBW=1KHz, Sweep time=Auto
Limit:	<p>The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency</p> <p>over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage,</p> <p>for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.</p> <p>For battery operated equipment, the equipment tests shall be performed using a new battery.</p>
Test setup:	 <p>The diagram illustrates the test setup. A green 'Spectrum Analyzer' is connected to the 'antenna port' of a yellow 'EUT' (Equipment Under Test) box. The 'EUT' box is situated within a blue 'OVEN' (temperature chamber) to simulate extreme temperatures.</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The transmitter output (antenna port) was connected to the spectrum analyzer. 2. EUT have transmitted absence of modulation signal and fixed channelize 3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth. 4. Set RBW=1KHz, VBW=1KHz with peak detector and maxhold settings. 5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c-f)/f_c \times 10^6$ ppm and the limit is less than ± 100 ppm. 6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value 7. Extreme temperature rule is $-20^\circ\text{C} \sim 50^\circ\text{C}$
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass



Measurement data:

Reference Frequency: 13.56MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit	Result
		Hz	%		
5.0	-20	75	0.00056%	+/- 0.01%	Pass
	-10	87	0.00058%		
	0	73	0.00054%		
	10	82	0.00060%		
	20	89	0.00066%		
	30	81	0.00060%		
	40	75	0.00055%		
	50	87	0.00064%		

Reference Frequency: 13.56MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit	Result
		Hz	ppm		
20	4.25	79	0.00058%	+/- 0.01%	Pass
	5.00	87	0.00064%		
	5.75	81	0.00059%		

8 Test Setup Photo


Radiated Emission



Conducted Emission






9 EUT Constructional Details

















----- End -----