# Test Report of FCC Part 15 C for FCC Certificate On Behalf of

# SHENZHEN BAO'AN RONGYINGDA ELECTRONICS FACTORY

Product description: Remote Wireless Laser Pointer

Model No.: RCL-05

FCC ID: U7Q-RCL-05

Prepared for: SHENZHEN BAO'AN RONGYINGDA ELECTRONICS FACTORY

Fl. 5 East, Baoshu Bld., Baotian Ind. Area, Xixiang, Bao'an,

Shenzhen, Guangdong, China

Prepared by: Bontek Compliance Laboratory Ltd

Rm 802~804, 8/F, Jinmin Bld., Zizhu 6<sup>th</sup> Rd., Zhuzi Lin, Futian,

Shenzhen 518040, P.R. China.

Tel: 86-755-82871080 Fax: 86-755-82871368

Issue Date: April 11, 2007

**Test Date:** April 05~10, 2007

Test by: Reviewed By:

Kendy Wang

Kendy Wang

Tony Wu

## **TABLE OF CONTENTS**

| 1 - GENERAL INFORMATION                                | 3  |
|--|----|
| 1.1 Product Description for Equipment Under Test (EUT) | 3  |
| 1.2 Test Standards                                     | 3  |
| 1.3 Test Summary                                       | 4  |
| 1.4 Test Methodology                                   | 4  |
| 1.5 Test Facility                                      | 4  |
| 1.6 Test Equipment List and Details                    | 5  |
| 2 - SYSTEM TEST CONFIGURATION                          | 6  |
| 2.1 Justification                                      | 6  |
| 2.2 EUT Exercise Software                              | 6  |
| 2.3 Special Accessories                                | 6  |
| 2.4 Equipment Modifications                            | 6  |
| 2.5 Basic Test Setup Block Diagram                     | 6  |
| 3 – DISTURBANCE VOLTAGE AT THE MAINS TERMINALS         | 8  |
| 3.1 Measurement Uncertainty                            | 8  |
| 3.2 Applicable Standard                                | 8  |
| 3.3 Test Description                                   | 8  |
| 4- RADIATED DISTURBANCES                               | 9  |
| 4.1 Measurement Uncertainty                            | 9  |
| 4.2 Limit of Radiated Disturbances                     | 9  |
| 4.3 EUT Setup  | 9  |
| 4.4 Test Receiver Setup                                | 10 |
| 4.5 Test Procedure                                     | 10 |
| 4.6 Corrected Amplitude & Margin Calculation           | 11 |
| 4.7 Radiated Emissions Test Result                     | 11 |
| 5- 20DB BANDWIDTH                                      | 13 |
| 5.1 Measurement Uncertainty                            | 13 |
| 5.2 Limit of 20dB Bandwidth                            | 13 |
| 5.3 EUT Setup  | 13 |
| 5.4 Test Procedure                                     | 13 |
| 5.5 Emissions within Band Edges Test Result            | 14 |
| 6- DUTY CYCLE  | 15 |
| 6.1 Measurement Uncertainty                            | 15 |
| 6.2 EUT Setup  | 15 |
| 6.3 Test Procedure                                     | 15 |
| 6.4 Measurement Result                                 | 15 |

## 1 - GENERAL INFORMATION

# 1.1 Product Description for Equipment Under Test (EUT)

#### **Client Information**

Applicant: SHENZHEN BAO'AN RONGYINGDA ELECTRONICS FACTORY

Address of applicant: Fl. 5 East, Baoshu Bld., Baotian Ind. Area, Xixiang, Bao'an,

Shenzhen, Guangdong, China

Manufacturer: SHENZHEN BAO'AN RONGYINGDA ELECTRONICS FACTORY

Address of manufacturer: Fl. 5 East, Baoshu Bld., Baotian Ind. Area, Xixiang, Bao'an,

Shenzhen, Guangdong, China

## **General Description of E.U.T**

| Items              | Description                                |
|--------------------|--|
| EUT Description:   | Tx of Remote Wireless Laser Pointer        |
| Trade Name:        | N/A  |
| Model No.:         | RCL-05                                     |
| Rated Voltage      | DC 12V for Transmitter                     |
| Frequency range    | 434.01MHz                                  |
| Number of channels | 1  |
| Antenna Type:      | Built-in Antenna                           |
| Channel Separation | None                                       |
| Product Class:     | Low Power Communication Device Transmitter |

<sup>\*</sup> The test data gathered are from the production sample provided by the manufacturer.

#### 1.2 Test Standards

The following Declaration of Conformity report of EUT is prepared in accordance with

FCC Rules and Regulations Part 15 Subpart C Section 15.231

The objective of the manufacturer is to demonstrate compliance with the described above standards.

Report No.: BCT07DR-190E Page 3 of 17

## 1.3 Test Summary

For the EUT described above. The standards used were <u>FCC Part 15 Subpart C Section 15.231</u> for Emissions

Tests Carried Out Under FCC Part 15 Subpart C

| Standard          | Test Items                                 | Status       | Application                  |
|-------------------|--|--------------|------------------------------|
|                   | Disturbance Voltage at The Mains Terminals | х            | N/A, without AC power supply |
| Part 15 Subpart C | Radiation Emission                         | $\checkmark$ |                              |
| Section 15.231    | 20dB Bandwidth                             | $\checkmark$ |                              |
|                   | Duty Cycle                                 |              |                              |

- $\sqrt{\phantom{a}}$  Indicates that the test is applicable
- × Indicates that the test is not applicable

# 1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

The maximum emission levels emanating from the device are compared to the <u>Part 15 Subpart C Section 15.231</u> limits for radiation emissions and the measurement results contained in this test report show that EUT is to be technically compliant with FCC requirements.

All measurement required was performed at laboratory of Shenzhen Huatongwei International Inspection Co., Ltd at Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

## 1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC - Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 662850, November 17, 2003.

Report No.: BCT07DR-190E Page 4 of 17

# 1.6 Test Equipment List and Details

| Equipment                  | Manufacturer    | Model No. | Serial No.   | Last Cal | Calibration<br>Period |
|----------------------------|-----------------|-----------|--------------|----------|-----------------------|
| EMI Test Receiver          | ROHDE & SCHWARZ | ESCS30    | 100038       | 2006/11  | 1 year                |
| EMI Test Receiver          | ROHDE & SCHWARZ | ESPI      | 100106       | 2006/08  | 1 year                |
| Spectrum Analyzer          | Anritsu         | R3263     | 21061558     | 2006/11  | 1 year                |
| Artificial Mains           | ROHDE & SCHWARZ | ESH2-Z5   | 100028       | 2006/11  | 1 year                |
| Pulse Limiter              | ROHDE & SCHWARZ | ESHSZ2    | 100044       | 2006/11  | 1 year                |
| Ultra-Broadband<br>Antenna | ROHDE & SCHWARZ | HL562     | 100015       | 2006/11  | 1 year                |
| LOOP ANTENNA               | ROHDE & SCHWARZ | HFH2-Z2   | 100020       | 2006/11  | 1 year                |
| HORN ANTENNA               | ROHDE & SCHWARZ | HF906     | 100039       | 2006/11  | 1 year                |
| EMI Test Receiver          | ROHDE & SCHWARZ | ESI 26    | 100009       | 2006/11  | 1 year                |
| RF Test Panel              | ROHDE & SCHWARZ | TS / RSP  | 335015/ 0017 | N/A      | N/A                   |
| Turntable                  | ETS             | 2088      | 2149         | N/A      | N/A                   |
| Antenna Mast               | ETS             | 2075      | 2346         | N/A      | N/A                   |

Report No.: BCT07DR-190E Page 5 of 17

## 2 - SYSTEM TEST CONFIGURATION

#### 2.1 Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

#### 2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software offered by manufacture, can let the EUT being normal operation.

## 2.3 Special Accessories

There are no special accessories necessary for compliance of this product supplied by **SHENZHEN BAO'AN RONGYINGDA ELECTRONICS FACTORY** and its respective support equipment manufacturers.

#### 2.4 Equipment Modifications

The EUT tested was not modified by Bontek.

## 2.5 Basic Test Setup Block Diagram




Figure 1: Frequencies measured below 1 GHz configuration

Report No.: BCT07DR-190E Page 6 of 17




Figure 2: Frequencies measured above 1 GHz configuration

Report No.: BCT07DR-190E Page 7 of 17

# 3 – DISTURBANCE VOLTAGE AT THE MAINS TERMINALS

## 3.1 Measurement Uncertainty

All test results complied with Section 15.207 requirements. Measurement Uncertainty is 2.4 dB.

#### 3.2 Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency Range (MHz)   | Limits     | ( dBuV) |
|-------------------------|------------|---------|
| Trequency range (wiriz) | Quasi-Peak | Average |
| 0.150~0.500             | 66~56      | 56∼46   |
| 0.500~5.000             | 56         | 46      |
| 5.000~30.00             | 60         | 50      |

# 3.3 Test Description

The EUT is excused from investigation of Disturbance Voltage at The Mains Terminals, for it is powered by a DC 12V bettary. According to the Section 15.207(d), measurement to demonstrate compliance with the limits of Disturbance Voltage at The Mains Terminals are not required to the devices which only employed bettary power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

Report No.: BCT07DR-190E Page 8 of 17

#### 4- RADIATED DISTURBANCES

#### 4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 4.0$  dB.

#### 4.2 Limit of Radiated Disturbances

According to 15.231(b), the field strength of emissions from Intentional Radiators operated under this section shall not exceed the following:

| Fundamental   | Field Strength of |                     | Field St               | rength of     |
|---------------|-------------------|---------------------|------------------------|---------------|
| Frequency     | Fundamental       |                     | Spu                    | rious         |
| (MHz)         | (dBuV/m)          | (uV/m)              | (dBuV/m)               | (uV/m)        |
| 40.66 - 40.70 | 67.04             | 2,250               | 47.04                  | 225           |
| 70 - 130      | 61.94             | 1,250               | 41.94                  | 125           |
| 130 - 174     | * 61.94 - 71.48   | * 1,250 -3,750      | * 41.94 <b>-</b> 51.48 | * 125 - 375   |
| 174 - 260     | 71.48             | 3,750               | 51.48                  | 375           |
| 260 - 470     | * 71.48 - 81.94   | * 3,750 -<br>12,500 | * 51.48 - 61.94        | * 375 - 1,250 |
| above 470     | 81.94             | 12,500              | 61.94                  | 1,250         |

#### 4.3 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart B limits.

The EUT was placed on the center of the test table. In the frequency range below 1 GHz, Ultra-Broadband Antenna horn-antenna is used. In the frequency range above 1 GHz horn-antenna is used. Test setup refer to **Section 2.5 Basic Test Setup Block Diagram** of this report.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

Report No.: BCT07DR-190E Page 9 of 17

#### 4.4 Test Receiver Setup

According to FCC Part 15 rule, the frequency was investigated from 30 to 5000 MHz. During the radiated emission test, the test receiver was set with the following configurations:

Test Receiver Setting for frequency range below 1000MHz:

Test Receiver Setting for frequency range above 1000MHz:

Detector......Peak
IF Band Width.....1MHz

Antenna Position:

Height......1m to 4m

Polarity......Horizontal and Vertical

#### 4.5 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 4). Power on the EUT and all the supporting units.
- 5). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 6). The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
- 7). For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 8). Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode. Then all data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -10 dB $_{\mu}$ V of specification limits), and are distinguished with a "QP" in the data plots.

Report No.: BCT07DR-190E Page 10 of 17

#### 4.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude Indicated reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Transd.

Transd.= Antenna Factor + Cable Factor - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. -Limit

## 4.7 Radiated Emissions Test Result

| Temperature ( $^{\circ}$ C ) : 22~23   | EUT: Remote Wireless Laser Pointer           |
|--|--|
| Humidity (%RH ): 50~54                 | M/N: RCL-05                                  |
| Barometric Pressure ( mbar ): 950~1000 | Operation Condition: Continuous Transmitting |

Test plots see following pages

Report No.: BCT07DR-190E Page 11 of 17

|  |                       | 434.0  |  | Tx in ope  | eration  |  |  |
|--|-----------------------|--|--|--|--|--|--|
| Maximum<br>Frequency   |                       | Pos  | Emission and                                       |  |  | Limit  | Margin   |
| (MHz)  | Polarity              | m  | Deg°   | Transd   | dBµV/m   | dBµV/m   | dBµV/m   |
| 434.0134   | V                     | 1.21   | 80   | 20.3   | 72.51  | 80.15  | 7.64   |
| 868.0268   | V                     | 1.54   | 256  | 21.5   | 44.05  | 61.94  | 17.89  |
| 1302.0402  | V                     | 1.00   | 2  | 23.4   | 53.77(PK)  | 74.00  | 20.23  |
| 1302.0402  | V                     | 1.00   | 2  | 23.4   | 46.65(AV)  | 54.00  | 7.35   |
| 1736.0536  | V                     | 1.02   | 229  | 23.9   | 45.12(PK)  | 74.00  | 28.88  |
| 1736.0536  | V                     | 1.02   | 229  | 23.9   | 38.00(AV)  | 54.00  | 16.00  |
| 2170.0670  | V                     | 1.00   | 17   | 24.3   | 48.86(PK)  | 74.00  | 25.14  |
| 2170.0670  | V                     | 1.00   | 17   | 24.3   | 41.74(AV)  | 54.00  | 12.26  |
| 2604.0804  | V                     | 1.03   | 4  | 25.1   | 51.40(PK)  | 74.00  | 22.60  |
| 2604.0804  | V                     | 1.03   | 4  | 25.1   | 44.28(AV)  | 54.00  | 9.72   |
| 3038.0938  | V                     | 1.17   | 3  | 25.6   | 47.96(PK)  | 74.00  | 26.04  |
| 3038.0938  | V                     | 1.17   | 3  | 25.6   | 40.84(AV)  | 54.00  | 13.16  |
| 3472.1072  | V                     | 1.00   | 16   | 26.4   | 44.80(PK)  | 74.00  | 29.20  |
| 3472.1072  | V                     | 1.00   | 16   | 26.4   | 37.68(AV)  | 54.00  | 16.32  |
| 4340.1341  | V                     |  |  |  |  |  |  |
| Maximum  |                       |  | Emissio  |  |  | Limit Mar  | Margin   |
| Frequency<br>(MHz)   | Delerity              |  | ition and  |  | dDuV/m   |  |  |
| 434.0134   | Polarity<br>H         | <b>m</b>   | Deg°   | Transd<br>20.4   | <b>dBμV/m</b> 73.34  | <b>dBμV/m</b><br>80.15   | <b>dBμV/m</b><br>6.81  |
| 868.0268   | H                     | 1.21   | 257  |  |  |  |  |
| 000.0200   | 11                    | 1.41   |  |  | 10 15  | 61 07  | 1 21 70  |
| 1302 0402  | н                     |  |  | 21.5   | 40.15  | 61.94  | 21.79  |
| 1302.0402  | Н                     | 2.20   | 304  | 25.2   | 55.27(PK)  | 74.00  | 18.73  |
| 1302.0402  | Н                     | 2.20<br>1.00   | 304<br>304   | 25.2<br>24.9   | 55.27(PK)<br>48.15(AV)   | 74.00<br>54.00   | 18.73<br>5.85  |
| 1302.0402<br>1736.0536   | H                     | 2.20<br>1.00<br>1.00                                 | 304<br>304<br>77                                   | 25.2<br>24.9<br>23.3   | 55.27(PK)<br>48.15(AV)<br>43.63(PK)  | 74.00<br>54.00<br>74.00  | 18.73<br>5.85<br>30.37   |
| 1302.0402<br>1736.0536<br>1736.0536  | H<br>H<br>H           | 2.20<br>1.00<br>1.00<br>1.00                         | 304<br>304<br>77<br>77                             | 25.2<br>24.9<br>23.3<br>23.1                                 | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)   | 74.00<br>54.00<br>74.00<br>54.00                                     | 18.73<br>5.85<br>30.37<br>17.49                                    |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670   | H<br>H<br>H           | 2.20<br>1.00<br>1.00<br>1.00<br>1.10                 | 304<br>304<br>77<br>77<br>345                      | 25.2<br>24.9<br>23.3<br>23.1<br>23.5                         | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)  | 74.00<br>54.00<br>74.00<br>54.00<br>74.00                            | 18.73<br>5.85<br>30.37<br>17.49<br>27.60                           |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670<br>2170.0670  | H<br>H<br>H<br>H      | 2.20<br>1.00<br>1.00<br>1.00<br>1.10<br>1.10         | 304<br>304<br>77<br>77<br>345<br>345               | 25.2<br>24.9<br>23.3<br>23.1<br>23.5<br>23.5                 | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)<br>39.28(AV)                           | 74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00                   | 18.73<br>5.85<br>30.37<br>17.49<br>27.60<br>14.72                  |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670<br>2170.0670<br>2604.0804                           | H<br>H<br>H<br>H      | 2.20<br>1.00<br>1.00<br>1.00<br>1.10<br>1.10         | 304<br>304<br>77<br>77<br>345<br>345<br>304        | 25.2<br>24.9<br>23.3<br>23.1<br>23.5<br>23.5<br>24.1         | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)<br>39.28(AV)<br>55.27(PK)              | 74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00<br>74.00          | 18.73<br>5.85<br>30.37<br>17.49<br>27.60<br>14.72<br>18.73         |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670<br>2170.0670<br>2604.0804<br>2604.0804              | H<br>H<br>H<br>H<br>H | 2.20<br>1.00<br>1.00<br>1.00<br>1.10<br>1.10         | 304<br>304<br>77<br>77<br>345<br>345               | 25.2<br>24.9<br>23.3<br>23.1<br>23.5<br>23.5                 | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)<br>39.28(AV)                           | 74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00                   | 18.73<br>5.85<br>30.37<br>17.49<br>27.60<br>14.72                  |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670<br>2170.0670<br>2604.0804<br>2604.0804<br>3038.0938 | H<br>H<br>H<br>H<br>H | 2.20<br>1.00<br>1.00<br>1.00<br>1.10<br>1.10<br>1.00 | 304<br>304<br>77<br>77<br>345<br>345<br>304<br>304 | 25.2<br>24.9<br>23.3<br>23.1<br>23.5<br>23.5<br>24.1<br>24.0 | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)<br>39.28(AV)<br>55.27(PK)<br>48.15(AV) | 74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00 | 18.73<br>5.85<br>30.37<br>17.49<br>27.60<br>14.72<br>18.73<br>5.85 |
| 1302.0402<br>1736.0536<br>1736.0536<br>2170.0670<br>2170.0670<br>2604.0804<br>2604.0804              | H<br>H<br>H<br>H<br>H | 2.20<br>1.00<br>1.00<br>1.10<br>1.10<br>1.00<br>1.00 | 304<br>304<br>77<br>77<br>345<br>345<br>304<br>304 | 25.2<br>24.9<br>23.3<br>23.1<br>23.5<br>23.5<br>24.1<br>24.0 | 55.27(PK)<br>48.15(AV)<br>43.63(PK)<br>36.51(AV)<br>46.40(PK)<br>39.28(AV)<br>55.27(PK)<br>48.15(AV) | 74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00<br>74.00<br>54.00 | 18.73<br>5.85<br>30.37<br>17.49<br>27.60<br>14.72<br>18.73<br>5.85 |

## Remark:

Report No.: BCT07DR-190E Page 12 of 17

<sup>---</sup> Means that The emission level of the rest measuring harmonic up to 5GHz are so low below applicable limit in operation mode, so the result were not recorded.

#### 5-20dB BANDWIDTH

#### **5.1 Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is <u>+</u>4.0 dB.

#### 5.2 Limit of 20dB Bandwidth

In accordance with Part15.231(c), the fundamental frequency bandwidth was kept within 0.25% of the center frequency for devices operating>70MHz and <900MHz.

| Fundamental Frequency | Limit of 20dB Bandwidth |
|-----------------------|-------------------------|
| (MHz)                 | (kHz)                   |
| 434.0134              | 434013.4x0.0025=1085.03 |

#### 5.3 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2003.

The EUT was placed on the center of the nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

#### **5.4 Test Procedure**

- 1) Turn on the transmitter, and set it to transmit the pulse train continuously.
- Set Test Receiver into spectrum analyzer mode, Tune the spectrum analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth(RBW) to 100kHz and video bandwidth(VBW) to 100kHz, then select Peak function to scan the channel frequency.
- 3) The 20dB bandwidth was measured and recorded.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Report No.: BCT07DR-190E Page 13 of 17

# 5.5 Emissions within Band Edges Test Result

| Temperature ( °C ) : 22~23             | EUT: Remote Wireless Laser Pointer           |
|--|--|
| Humidity (%RH ): 50~54                 | M/N: RCL-05                                  |
| Barometric Pressure ( mbar ): 950~1000 | Operation Condition: Continuous Transmitting |

#### Test plots see following

| Fundamental Frequency<br>(MHz) | 20dB Bandwidth<br>(kHz) | Maximum Limit (kHz) | Pass/Fail |
|--------------------------------|-------------------------|---------------------|-----------|
| 434.0134                       | 61.6                    | 1085.03             | Pass      |



Report No.: BCT07DR-190E Page 14 of 17

# 6- Duty Cycle

## **6.1 Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 4.0$  dB.

# 6.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2003.

The EUT was placed on the center of the nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level.

#### 6.3 Test Procedure

- 1) The EUT was placed on a turntable which is 0.8m above ground plane.
- 2) Set EUT operating in continuous transmitting mode
- 3) Set Test Receiver into spectrum analyzer mode, Tune the spectrum analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth(RBW) to 1000kHz and video bandwidth(VBW) to 1000kHz, Span was set to 0Hz.
- 4) The Duty Cycle was measured and recorded.

#### 6.4 Measurement Result


| Temperature ( °C ) : 22~23             | EUT: Remote Wireless Laser Pointer           |
|--|--|
| Humidity (%RH ): 50~54                 | M/N: RCL-05                                  |
| Barometric Pressure ( mbar ): 950~1000 | Operation Condition: Continuous Transmitting |


Test plots see following pages


Total Pulse Time of Transmitter = 1.4 msecx2 + 0.65msecx11 = 9.95msec


The Duty Cycle= 9.95/25.7= 39%

Report No.: BCT07DR-190E Page 15 of 17









Report No.: BCT07DR-190E Page 17 of 17