

# Heng Sheng Universal Trading Ltd.

# **TEST REPORT**

#### **SCOPE OF WORK**

FCC TESTING-MODEL: 1009537

#### **REPORT NUMBER**

GZHH00326442-001

# **ISSUE DATE**

AUG 21, 2019

#### **PAGES**

24

# **DOCUMENT CONTROL NUMBER**

FCC ID 249\_C © 2017 INTERTEK





# Heng Sheng Universal Trading Ltd.

Application for Certification

FCC ID: U7U1009537

# **Toy RC Speed Bumper Road Rage**

Model: 1009537

2.4GHz Transmitter

Report No.: GZHH00326442-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-18]

Prepared and Checked by:	Approved by:	
Sign on file		
Terry Tang Senior Engineer	Kidd Yang Technical Supervisor	
	Date: Aug 21, 2019	

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Version: 01-November-2017 Page: 1 of 24 FCC ID 249 C



# **MEASUREMENT/TECHNICAL REPORT**

This report concerns (che	eck one:)	Original Grant	X	Class II Ch	nange	
Equipment Type: DXX - F		-				
Deferred grant requested	per 47 CFR (					
		<b>,</b> ,			ate	
Company Name agrees t	o notify the Co	ommission by: _		-1-1-		
of the intended date of ar date.	nouncement	of the product so	that the (	date grant can be	issued	on that
Transition Rules Request	per 15.37?		Yes		No _	X
If no, assumed Part 15, Edition] provision.	Subpart C f	or intentional ra	diator – t	he new 47	CFR [	10-1-18
Report prepared by:						
	101, 201, E Community People's Re	ting Services She Building B, No. GuanHu Subdis Public of China 6-755-8601 6288	308 Wuh strict, Lor	e Avenue, ngHua Distri	Zhangk	

Version: 01-November-2017 Page: 2 of 24 FCC ID 249\_C



# **Table of Contents**

1.0 Summary of Test Result	4
2.0 General Description	5
2.1 Product Description 2.2 Related Submittal(s) Grants 2.3 Test Methodology	5 5
3.0 System Test Configuration	6
3.1 Justification	6 6 6
4.0 Emission Results	7
4.1 Radiated Test Results 4.1.1 Field Strength Calculation 4.1.2 Radiated Emission Configuration Photograph 4.1.3 Radiated Emissions 4.1.4 Transmitter Spurious Emissions	7 8 8 11
5.0 Equipment Photographs	15
6.0 Product Labelling	15
7.0 Technical Specifications	
9.0 Miscellaneous Information	
9.1 Bandedge Plot 9.2 20dB Bandwidth 9.3 Discussion of Pulse Desensitization 9.4 Calculation of Average Factor 9.5 Emissions Test Procedures	18 19 19 22
10 0 Test Fauinment List	24



# 1.0 Summary of Test Result

Applicant: Heng Sheng Universal Trading Ltd.

Applicant Address: Rm 6, 3/F Lladro Centre, 72 Hoi Yuen Road, Kwun Tong

HongKong

Manufacturer: Heng Sheng Universal Trading Ltd.

Manufacturer Address: Rm 6, 3/F Lladro Centre, 72 Hoi Yuen Road, Kwun Tong

HongKong

MODEL: 1009537

FCC ID: U7U1009537

Test Specification	Reference	Results
Transmitter Radiated Emission	15.249 &15.209 &15.205	Pass
Bandedge		
20dB Bandwidth	15.215(c)	Pass

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

Version: 01-November-2017 Page: 4 of 24 FCC ID 249\_C



# 2.0 General Description

# 2.1 Product Description

The equipment under test (EUT) is a Toy RC Speed Bumper Road Rage operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK Antenna Gain: 0dBi

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

# 2.2 Related Submittal(s) Grants

This is an application for certification of controller unit for the Toy RC Speed Bumper Road Rage, and the corresponding car unit which associated with this EUT is subjected to FCC SDOC.

# 2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

# 2.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community GuanHu Subdistrict, LongHua District, Shenzhen, People's Republic of China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).

Version: 01-November-2017 Page: 5 of 24 FCC ID 249\_C



# 3.0 System Test Configuration

#### 3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by DC 3.0V (2 x 1.5V AAA batteries) during the test, only the worst data was reported in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Section 4.

The EUT was operated standalone and placed in the central of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

# 3.2 EUT Exercising Software

There was no special software to exercise the device.

# 3.3 Special Accessories

No special accessories used.

# 3.4 Equipment Modification

Any modifications installed previous to testing by Heng Sheng Universal Trading Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Longhua Branch.

# 3.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

# 3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
N/A	N/A	N/A

Version: 01-November-2017 Page: 6 of 24 FCC ID 249\_C



#### 4.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

#### 4.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

# 4.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where  $FS = Field Strength in dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in  $dB\mu V$ 

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = BA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $RA = 62.0 dB\mu V$ 

AF = 7.4 dB

CF = 1.6 dB

 $AG = 29.0 \, dB$ 

PD = 0 dB

AV = -10 dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \, dB\mu V/m$ 

Level in  $\mu V/m = Common Antilogarithm [(42 dB<math>\mu V/m)/20] = 125.9 \mu V/m$ 

Version: 01-November-2017 Page: 7 of 24 FCC ID 249\_C



4.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

Intertek Report No.: GZHH00326442-001

# 4.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission at 722.615000 MHz

Judgement: Passed by 14.8 dB

#### **TEST PERSONNEL:**

Sign on file

Terry Tang, Senior Engineer
Typed/Printed Name

Jul 12, 2019 Date

Version: 01-November-2017 Page: 8 of 24 FCC ID 249\_C




Applicant: Heng Sheng Universal Trading Ltd.

Date of Test: Jul 12, 2019 Model: 1009537

Worst Case Operating Mode: Transmitting(2417.000MHz)

# ANT Polarity: Horizontal

Level in dBuV/m



Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
40.190000	17.7	1000.0	120.000	Н	13.7	22.3	40.0
55.475000	14.2	1000.0	120.000	Н	9.8	25.8	40.0
682.170000	30.1	1000.0	120.000	Н	23.6	15.9	46.0

#### Remark:

- 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
- 2. QuasiPeak  $(dB\mu V/m) = Corr. (dB/m) + Read Level (dB\mu V)$
- 3. Margin (dB) = Limit Line(dB $\mu$ V/m) Level (dB $\mu$ V/m)




Applicant: Heng Sheng Universal Trading Ltd.

Date of Test: Jul 12, 2019 Model: 1009537

Worst Case Operating Mode: Transmitting(2417.000MHz)

# **ANT Polarity: Vertical**

Level in dBuV/m



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
63.880000	14.2	1000.0	120.000	V	16.1	25.8	40.0
240.220000	19.1	1000.0	120.000	V	15.4	26.9	46.0
722.615000	31.2	1000.0	120.000	V	22.1	14.8	46.0

#### Remark:

- 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
- 2. QuasiPeak ( $dB\mu V/m$ )= Corr. (dB/m)+ Read Level ( $dB\mu V$ )
- 3. Margin (dB) = Limit Line(dB $\mu$ V/m) Level (dB $\mu$ V/m)

Version: 01-November-2017 Page: 10 of 24 FCC ID 249\_C



# 4.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission at 4834.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 4.4 dB

### **TEST PERSONNEL:**

Sign on file

Terry Tang, Senior Engineer
Typed/Printed Name

Jul 12, 2019 Date

Version: 01-November-2017 Page: 11 of 24 FCC ID 249\_C



Applicant: Heng Sheng Universal Trading Ltd.

Date of Test: Jul 12, 2019 Model: 1009537 Worst Case Operating Mode: Transmitting

Table 1

# **Radiated Emissions**

(2417 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2417.000	93.2	36.7	28.1	84.6	114.0	-29.4
Horizontal	4834.000	70.8	36.7	35.5	69.6	74.0	-4.4
Horizontal	7251.000	67.0	36.1	36.5	67.4	74.0	-6.6

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2417.000	93.2	36.7	28.1	23.8	60.8	94.0	-33.2
Horizontal	4834.000	70.8	36.7	35.5	23.8	45.8	54.0	-8.2
Horizontal	7251.000	67.0	36.1	36.5	23.8	43.6	54.0	-10.4

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Version: 01-November-2017 Page: 12 of 24 FCC ID 249\_C



Applicant: Heng Sheng Universal Trading Ltd.

Date of Test: Jul 12, 2019 Model: 1009537 Worst Case Operating Mode: Transmitting

Table 2

# **Radiated Emissions**

(2435 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2435.000	92.5	36.7	28.1	83.9	114.0	-30.1
Horizontal	4870.000	70.4	36.7	35.5	69.2	74.0	-4.8
Horizontal	7305.000	66.9	36.1	36.5	67.3	74.0	-6.7

Polarization	Frequency	Reading	Pre-	Antenna	Average	Net at 3m	Average	Margin
	(MHz)	(dBµV)	Amp	Factor	Factor	(dBµV/m)	Limit	(dB)
			Gain	(dB)	(-dB)		at 3m	
			(dB)				(dBµV/m)	
Horizontal	2435.000	92.5	36.7	28.1	23.8	60.1	94.0	-33.9
Horizontal	4870.000	70.4	36.7	35.5	23.8	45.4	54.0	-8.6
Horizontal	7305.000	66.9	36.1	36.5	23.8	43.5	54.0	-10.5

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Version: 01-November-2017 Page: 13 of 24 FCC ID 249\_C



Applicant: Heng Sheng Universal Trading Ltd.

Date of Test: Jul 12, 2019 Model: 1009537 Worst Case Operating Mode: Transmitting

Table 3

# **Radiated Emissions**

(2452 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2452.000	88.9	36.7	28.1	80.3	114.0	-33.7
Horizontal	4904.000	68.4	36.7	35.5	67.2	74.0	-6.8
Horizontal	7356.000	65.7	36.1	36.5	66.1	74.0	-7.9

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBuV/m)	Margin (dB)
Horizontal	2452.000	88.9	36.7	28.1	23.8	56.5	94.0	-37.5
Horizontal	4904.000	68.4	36.7	35.5	23.8	43.4	54.0	-10.6
Horizontal	7356.000	65.7	36.1	36.5	23.8	42.3	54.0	-11.7

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Version: 01-November-2017 Page: 14 of 24 FCC ID 249\_C



# 5.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

# 6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

# 7.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

# 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Version: 01-November-2017 Page: 15 of 24 FCC ID 249\_C



# 9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, 20dB Bandwidth, the test procedure and calculation of factor such as pulse desensitization.


# 9.1 Bandedge Plot

The test plots are attached as below. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

# **Peak Measurement**

Restricted-band band-edge tests shall be performed as radiated measurements, i.e (Band-edge Plot).

# (i) Lower channel 2417.000 MHz:



	Polarization	Frequency (MHz)	Reading (dBμV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Ī	Horizontal	2400.000	64.0	36.7	28.1	55.4	74.0	-18.6


Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m	Margin (dB)
Horizontal	2400.000	52.6	36.7	28.1	44.0	54.0	-10.0

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBµv/m (Peak Limit) and 54dBµv/m (Average Limit).

Version: 01-November-2017 Page: 16 of 24 FCC ID 249\_C



# (ii) Upper channel 2452.000 MHz:



Polarization	Frequency (MHz)	Reading (dBμV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2483.500	62.5	36.8	29.1	54.8	74.0	-19.2

Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBµV/m	Margin (dB)
Horizontal	2483.500	51.6	36.8	29.1	43.9	54.0	-10.1


The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBμv/m (Peak Limit) and 54dBμv/m (Average Limit).


Version: 01-November-2017 Page: 17 of 24 FCC ID 249\_C



#### 9.2 20dB Bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered. The test plots are reported as below.





Version: 01-November-2017 Page: 18 of 24 FCC ID 249\_C



#### 9.3 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 652.2 $\mu$ s for a digital "1" bit, as shown in the plots of Section 9.4 With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB

# 9.4 Calculation of Average Factor

Averaging factor in  $dB = 20 \log (duty cycle)$ 

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.


The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

The duty cycle is simply the on-time divided by the period:


Therefore, the averaging factor is found by  $20 \log_{10} (0.0649) = -23.8 dB$ 

The test plots are attached as below.

Version: 01-November-2017 Page: 19 of 24 FCC ID 249\_C









#### 9.5 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter up to 1GHz and 1.5 meter above 1GHz in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Section 9.4.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Version: 01-November-2017 Page: 22 of 24 FCC ID 249\_C



# 9.5 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Section 9.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used, RBW 3MHz used for fundamental emission.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

Version: 01-November-2017 Page: 23 of 24 FCC ID 249\_C



# 10.0 <u>Test Equipment List</u>

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	14-Sep-2018	14-Sep-2019
SZ185-01	EMI Receiver	R&S	ESCI	100547	4-Jan-2019	4-Jan-2020
SZ061-09	Horn Antenna	ETS	3115	00092346	16-Oct-2018	16-Oct-2019
SZ061-06	Active Loop Antenna	Electro- Metrics	EM-6876	217	24-May-2019	24-May-2020
SZ061-15	Double- Ridged		3116C-PA	00224718	25-Oct-2018	25-Oct-2019
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	28-May-2019	28-May-2020
SZ181-04	Preamplifie r	Agilent	8449B	3008A024 74	15-Jan-2019	15-Jan-2020
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	15-Dec-2018	15-Dec-2020
SZ062-02	RF Cable	RADIALL	RG 213U		19-Jun-2019	19-Dec-2019
SZ062-05	RF Cable	RADIALL	0.04- 26.5GHz		23-Feb-2019	23-Aug-2019
SZ062-12	RF Cable	RADIALL	0.04- 26.5GHz		23-Feb-2019	23-Aug-2019
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02		28-May-2019	28-May-2020

Version: 01-November-2017 Page: 24 of 24 FCC ID 249\_C