

Valued Quality. Delivered.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**TEST REPORT****Report No.: 14051210HKG-001****Heng Sheng Toys Factory (H.K.) Co., Ltd.**

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: U7UHS-228227)**

**Transmitter****Prepared and Checked by:**  
Tse Ying, Cathy  
Senior Lead Engineer**Approved by:**  
Ng Mei Nar, Chris  
Lead Engineer  
Date: June 11, 2014

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**GENERAL INFORMATION**

|                           |   |
|---------------------------|---|
| Grantee:                  | Heng Sheng Toys Factory (H.K.) Co., Ltd.  |
| Grantee Address:          | Room 6, 3/F., Lladro Centre,<br>72 Hoi Yuen Road, Kwun Tong,<br>Kowloon, Hong Kong. |
| Contact Person:           | Queenie Chan  |
| Tel:                      | (852) 2976 9811   |
| Fax:                      | (852) 2790 3069   |
| e-mail:                   | queenie@hengshengtoys.com   |
| Manufacturer:             | Jinjiang Hengsheng Toys Co. Ltd.  |
| Manufacturer Address:     | Wu Keng Ind. District, Long Hu, Jinjiang, Fujian Province, China.                   |
| Brand Name:               | Heng Sheng  |
| Model:                    | HS2282  |
| Type of EUT:              | Transmitter   |
| Description of EUT:       | All Terrain Cyclone RC  |
| Serial Number:            | N/A   |
| FCC ID:                   | U7UHS-228227  |
| Date of Sample Submitted: | 22 May 2014   |
| Date of Test:             | 22 May 2014 to June 06, 2014  |
| Report No.:               | 14051210HKG-001   |
| Report Date:              | June 11, 2014   |
| Environmental Conditions: | Temperature: +10 to 40°C<br>Humidity: 10 to 90%                                     |

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**SUMMARY OF TEST RESULT**

| TEST SPECIFICATION         | REFERENCE | RESULTS |
|----------------------------|-----------|---------|
| Transmitter Field Strength | 15.227    | Pass    |

The equipment under test is found to be complying with the following standards:  
FCC Part 15, October 1, 2012 Edition

Note:

1. The EUT uses a detachable antenna with unique antenna connector which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**Table of Contents**

|            |  |    |
|------------|--|----|
| <b>1.0</b> | <b><u>General Description</u></b>          | 1  |
| 1.1        | Product Description                        | 1  |
| 1.2        | Related Submittal(s) Grants                | 1  |
| 1.3        | Test Methodology                           | 1  |
| 1.4        | Test Facility                              | 1  |
| <b>2.0</b> | <b><u>System Test Configuration</u></b>    | 2  |
| 2.1        | Justification                              | 2  |
| 2.2        | EUT Exercising Software                    | 2  |
| 2.3        | Special Accessories                        | 2  |
| 2.4        | Measurement Uncertainty                    | 2  |
| 2.5        | Support Equipment List and Description     | 2  |
| <b>3.0</b> | <b><u>Emission Results</u></b>             | 3  |
| 3.1        | Field Strength Calculation                 | 3  |
| 3.2        | Radiated Emission Configuration Photograph | 4  |
| 3.3        | Radiated Emission Data                     | 4  |
| <b>4.0</b> | <b><u>Equipment Photographs</u></b>        | 6  |
| <b>5.0</b> | <b><u>Product Labelling</u></b>            | 6  |
| <b>6.0</b> | <b><u>Technical Specifications</u></b>     | 6  |
| <b>7.0</b> | <b><u>Instruction Manual</u></b>           | 6  |
| <b>8.0</b> | <b><u>Miscellaneous Information</u></b>    | 7  |
| 8.1        | Measured Bandwidth                         | 7  |
| 8.2        | Discussion of Pulse Desensitization        | 8  |
| 8.3        | Calculation of Average Factor              | 8  |
| 8.4        | Emissions Test Procedures                  | 8  |
| <b>9.0</b> | <b><u>Equipment List</u></b>               | 10 |

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**1.0 General Description****1.1 Product Description**

The Equipment Under Test (EUT) is a transmitter of a RC system, which is operating at 27.145MHz as dictated by a crystal. The EUT is powered by 1 x 9V Block size battery. The EUT has a power ON/OFF switch, left control stick and right control stick.

After switching ON the EUT and the corresponding car (ie. Receiver), activating the control stick on the EUT can control the car moving forward, backward, left and right.

Antenna Type: External / Telescope-type antenna (with unique antenna connector)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

**1.2 Related Submittal(s) Grants**

The receiver for this transmitter is exempted from the Part 15 technical rules per 15.101(b).

**1.3 Test Methodology**

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application.

**1.4 Test Facility**

The open area test site used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

**Issuing Laboratory:****Intertek Testing Services Hong Kong Limited**

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



## **2.0 System Test Configuration**

### **2.1 Justification**

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by new 1 x 9V Block size battery.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

### **2.2 EUT Exercising Software**

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

### **2.3 Special Accessories**

There are no special accessories necessary for compliance of this product.

### **2.4 Measurement Uncertainty**

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

**Uncertainty and Compliance** - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

### **2.5 Support Equipment List and Description**

N/A.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

$AV$  = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RR$  =  $RA - AG - AV$  in  $\text{dB}\mu\text{V}$

$LF$  =  $CF + AF$  in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

**Issuing Laboratory:****Intertek Testing Services Hong Kong Limited**

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 54.290 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 5.0 dB

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



Applicant: Heng Sheng Toys Factory (H.K.) Co., Ltd.

Date of Test: June 06, 2014

Model: HS2282

Worst-Case Operating Mode: Transmitting

Table 1

**Radiated Emissions  
Pursuant to FCC Part 15 Section 15.227 Requirement**

| Polari-zation | Frequency (MHz) | Reading (dB $\mu$ V) | Pre-Amp (dB) | Antenna Factor (dB) | Average Factor (dB) | Net at 3m (dB $\mu$ V/m) | Limit at 3m (dB $\mu$ V/m) | Margin (dB) |
|---------------|-----------------|----------------------|--------------|---------------------|---------------------|--------------------------|----------------------------|-------------|
| V             | 27.145          | 60.4                 | 16           | 15.4                | 0.0                 | 59.8                     | 80.0                       | -20.2       |
| V             | 54.290          | 40.0                 | 16           | 11.0                | -                   | 35.0                     | 40.0                       | -5.0        |
| H             | 81.435          | 43.9                 | 16           | 7.0                 | -                   | 34.9                     | 40.0                       | -5.1        |
| H             | 108.580         | 36.5                 | 16           | 14.0                | -                   | 34.5                     | 43.5                       | -9.0        |
| H             | 135.725         | 36.6                 | 16           | 14.0                | -                   | 34.6                     | 43.5                       | -8.9        |
| H             | 162.870         | 34.4                 | 16           | 16.0                | -                   | 34.4                     | 43.5                       | -9.1        |
| H             | 190.015         | 35.0                 | 16           | 16.0                | -                   | 35.0                     | 43.5                       | -8.5        |
| H             | 217.160         | 34.2                 | 16           | 17.0                | -                   | 35.2                     | 46.0                       | -10.8       |
| H             | 244.305         | 31.3                 | 16           | 20.0                | -                   | 35.3                     | 46.0                       | -10.7       |
| H             | 271.450         | 28.5                 | 16           | 22.0                | -                   | 34.5                     | 46.0                       | -11.5       |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Loop antenna is used for the emissions below 30MHz.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**4.0 Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

**5.0 Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

**6.0 Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

**7.0 Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.




## 8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor.

### 8.1 Measured Bandwidth

The plot shows the fundamental emission is confined in the specified band. And it also shows that the emission is at least 34.77 dB below the carrier level at the band edge (26.96 and 27.28 MHz). It meets the requirement of Section 15.227(b).

Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designed (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.



**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



## 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 470 $\mu$ s for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 100kHz, so the pulse desensitivity factor is 0dB.

## 8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

## 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

**Issuing Laboratory:****Intertek Testing Services Hong Kong Limited**

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.



#### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

**Issuing Laboratory:**

Intertek Testing Services Hong Kong Limited

Hong Kong Accreditation Service (HKAS) has accredited this laboratory under the Hong Kong Laboratory Accreditation Scheme (HOKLAS) for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

**9.0 Equipment List****1) Radiated Emissions Test**

| Equipment            | EMI Test Receiver | Log Periodic Antenna | Active Loop H-field (9kHz to 30MHz) |
|----------------------|-------------------|----------------------|-------------------------------------|
| Registration No.     | EW-2666           | EW-0446              | EW-2313                             |
| Manufacturer         | R&S               | EMCO                 | ELECTROMETRI                        |
| Model No.            | ESCI7             | 3146                 | EM-6876                             |
| Calibration Date     | Jun. 20, 2013     | Apr. 30, 2013        | May 06, 2013                        |
| Calibration Due Date | Jun. 20, 2014     | Oct. 30, 2014        | Nov. 06, 2014                       |

| Equipment            | Spectrum Analyzer | Biconical Antenna |
|----------------------|-------------------|-------------------|
| Registration No.     | EW-2188           | EW-2512           |
| Manufacturer         | AGILENTTECH       | EMCO              |
| Model No.            | E4407B            | 3104C             |
| Calibration Date     | Apr. 16, 2014     | Jun. 25, 2013     |
| Calibration Due Date | Apr. 16, 2015     | Dec. 25, 2014     |

**2) Bandedge Measurement**

| Equipment            | Spectrum Analyzer |
|----------------------|-------------------|
| Registration No.     | EW-2249           |
| Manufacturer         | R&S               |
| Model No.            | FSP30             |
| Calibration Date     | Oct. 28, 2013     |
| Calibration Due Date | Oct. 28, 2014     |

**END OF TEST REPORT**