

# TEST REPORT

of

FCC Part 22 Subpart H and Part 24 Subpart E  
FCC ID: U7XM3ORANGE

Equipment Under Test : Industrial PDA phone

Model Name : M3 ORANGE

The addition of model name : CR4100

Serial No. : N/A

Applicant : M3 Mobile

Manufacturer : M3 Mobile

Date of Test(s) : 2010. 08. 25 ~ 2010. 11. 15

Date of Issue : 2010. 11. 15

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date

2010. 11. 15

Grant Lee

Approved By



Date

2010. 11. 15

Feel Jeong

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

# INDEX

	<u>TABLE OF CONTENTS</u>	Page
1. General Information -----	-----	3
2. RF radiated output power & spurious radiated emission -----	-----	7
3. Conducted Output Power -----	-----	13
4. Occupied Bandwidth 99 % -----	-----	15
5. Spurious Emissions At Antenna Terminal-----	-----	21
6. Band Edge -----	-----	25
7. Frequency Stability -----	-----	30

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 1. General information

### 1.1. Testing laboratory

SGS Testing Korea Co., Ltd.

- 705, Dongchun-Dong Sooji-Gu, Yongin-Shi, Kyungki-Do, South Korea.
- Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

Telephone : +82 +31 428 5700

FAX : +82 +31 427 2371

### 1.2. Details of applicant

Applicant : M3 Mobile  
Address : Dongwon-Bldg, 725-30 Yeoksam-Dong, Gangnam-Gu, Seoul, Korea  
Contact Person : Jooheon Kwon  
Phone No. : +82 +2 2022-1328

### 1.3. Description of EUT

<b>Kind of Product</b>	Industrial PDA phone
<b>Modular FCC ID</b>	QIPHC25
<b>Model Name</b>	M3 ORANGE
<b>The addition of model name</b>	CR4100
<b>Serial Number</b>	N/A
<b>Power Supply</b>	DC 3.7 V (Li-Ion Battery)
<b>Rated Power</b>	GSM850 : 33.00 dB m GSM1900 : 30.00 dB m
<b>Frequency Range</b>	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900: 1 850.2 MHz ~ 1 909.8 MHz
<b>Number of Channels</b>	GSM850 : 125 GSM1900 : 300
<b>Class of GPRS</b>	Class 10, Class B

- All models are exactly same for the hardware and software.

#### 1.4. Description of test mode

Band	Frequency (MHz)	Voice GSM	GPRS Data	
			GPRS	GPRS
			1 TX Slot	2 TX Slot
			(dBm)	(dBm)
GSM 850	824.2	<b>32.40</b>	32.30	30.77
	836.6	<b>32.54</b>	32.49	30.89
	848.8	<b>32.51</b>	32.47	30.91
GSM 1900	1850.2	<b>27.69</b>	27.69	25.70
	1880.0	<b>28.85</b>	28.80	26.80
	1909.8	<b>29.61</b>	29.60	27.50

Band	Frequency (MHz)	EDGE Data	
		EDGE	EDGE
		1 TX Slot	2 TX Slot
		(dBm)	(dBm)
EDGE 850	824.2	<b>27.35</b>	27.33
	836.6	<b>27.49</b>	27.46
	848.8	<b>27.51</b>	27.48
EDGE 1900	1850.2	<b>24.30</b>	22.40
	1880.0	<b>26.40</b>	23.30
	1909.8	<b>26.10</b>	24.00

#### GSM (850 / 1900)

We found out the test mode with the highest power level after we analyze all the data rates. So we chose **GSM(850 & 1900) voice** (worst case) as a representative.

## 1.5. Test equipment list

Equipment	Manufacturer	Model	Cal Due.
Signal Generator	Agilent	E4438C	Mar. 31, 2011
Signal Generator	Rohde & Schwarz	SMR40	Jul. 15, 2011
Spectrum Analyzer	Rohde & Schwarz	FSV30	Mar. 31, 2011
Mobile Test Unit	Agilent	E5515C	Mar. 31, 2011
Directional Coupler	Narda	4226-20	Jan. 07, 2011
High Pass Filter	Wainwright	WHK3.0/18G-10SS	Sep. 29, 2011
Band Reject Filter	Wainwright	WRG824/849-814/85 960/10SS	Apr. 01, 2011
DC power Supply	Agilent	U8002A	Jan. 06, 2011
Preamplifier	H.P.	8447F	Jul. 05, 2011
Preamplifier	Empower RF Systems, Inc	2002-BBS2C4AEL	Mar. 31, 2011
Test Receiver	R & S	ESU26	Apr. 08, 2011
Bilog Antenna	SCHWARZBECK MESSELEKTRONIK	VULB9163	Jul. 22, 2011
Horn Antenna	Rohde & Schwarz	HF 906	Oct. 08, 2011
Horn Antenna	SCHWARZBECK	BBH 9120D	Nov. 09, 2011
Dipole Antenna	VHAP/UHAP	975/958	Oct. 10, 2011
Antenna Master	EMCO	1050	N.C.R.
Turn Table	Daeil EMC	DI-1500	N.C.R.
Anechoic Chamber	SY Corporation	L x W x H (9.6 m x 6.4 m x 6.6 m)	Jan. 27, 2011

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1.6. Summary of test results

The EUT has been tested according to the following specifications:

APPLIED STANDARD : FCC Part 22, 24		
Section in FCC part	Test Item	Result
§2.1046 §22.913(a) §24.232(b)	RF Radiated Output Power	Complied
§2.1053 §22.917(e) §24.238(a)	Spurious Radiated Emission	Complied
§2.1046(a)	Conducted Output Power	Complied
§2.1049(h) (i)	Occupied Bandwidth	Complied
§2.1051 §22.917(e) §24.238(a)	Spurious Emission at Antenna Terminal	Complied
§2.1055 §22.355 §24.235	Frequency Stability	Complied
§22.917(e) §24.238(a)	Band Edge	Complied

## 1.7. Test report revision

Revision	Report number	Description
0	F690501/RF-RTL004276	Initial

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)


## 2. RF radiated output power & spurious radiated emission

### 2.1. Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 18 GHz Emissions.




*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

The diagram below shows the test setup for substituted method



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 2.2. Limit

FCC §22.913(a), the ERP of mobile transmitters must not exceed 7 watts. FCC §24.232(b) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

## 2.3. Test procedure : Based on ANSI/TIA 603C: 2004

1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3 m from EUT to correspond to the fundamental frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. During the measurement of the EUT, the resolution bandwidth was to 1 MHz and the average bandwidth was set to 1 MHz.
5. The transmitter shall be switched on, the measuring receiver shall be tuned to the frequency of the transmitter under test.
6. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
7. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
8. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
9. The maximum signal level detected by the measuring receiver shall be noted.
10. The EUT was replaced by half-wave dipole (824 ~ 849 MHz) or horn antenna (1 850 ~ 1 910 MHz) connected to a signal generator.
11. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
12. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
13. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
14. The input level to the substitution antenna shall be recorded as power level in dB m, corrected for any change of input attenuator setting of the measuring receiver.
15. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.

## 2.4. Test result for RF radiated output power

Ambient temperature : (23 ± 2) °C

Relative humidity : 46 % R.H.

### GSM850

Frequency (MHz)	Ant. Pol. (H/V)	S.G level + Amp. (dB m)	Cable loss (dB)	Ant. gain (dB d)	E.R.P.	
					(dB m)	(mW)
824.2	V	40.59	3.42	-11.17	26.00	398.11
824.2	H	41.67	3.42	-11.17	27.08	510.50
836.6	V	38.81	3.38	-11.47	23.97	249.46
836.6	H	40.51	3.38	-11.47	25.67	368.98
848.8	V	37.54	3.33	-11.76	22.44	175.39
848.8	H	40.10	3.33	-11.76	25.00	316.23

### GSM850 (EDGE)

Frequency (MHz)	Ant. Pol. (H/V)	S.G level + Amp. (dB m)	Cable loss (dB)	Ant. gain (dB d)	E.R.P.	
					(dB m)	(mW)
824.2	V	28.96	3.42	-11.17	14.37	27.35
824.2	H	36.60	3.42	-11.17	22.01	158.85

### GSM1900

Frequency (MHz)	Ant. Pol. (H/V)	S.G level + Amp. (dB m)	Cable loss (dB)	Ant. gain (dB i)	E.I.R.P.	
					(dB m)	(mW)
1 850.2	V	21.77	4.87	9.12	26.02	399.94
1 850.2	H	20.65	4.87	9.12	24.90	309.03
1 880.0	V	21.09	4.91	9.20	25.38	345.14
1 880.0	H	19.87	4.91	9.20	24.16	260.62
1 909.8	V	23.65	4.94	9.27	27.98	628.06
1 909.8	H	20.20	4.94	9.27	24.53	283.79

### GSM1900 (EDGE)

Frequency (MHz)	Ant. Pol. (H/V)	S.G level + Amp. (dB m)	Cable loss (dB)	Ant. gain (dB d)	E.I.R.P.	
					(dB m)	(mW)
1 909.8	V	11.04	4.94	9.27	15.37	34.43
1 909.8	H	17.10	4.94	9.27	21.43	139.00

#### Remark:

1. E.R.P. & E.I.R.P = [S.G level + Amp.](dB m) - Cable loss(dB) + Ant. gain (dB d/dB i)

2. The E.I.R.P was measured in three orthogonal EUT position(x-axis, y-axis and z-axis). Worst cases are z-axis.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 2.5. Spurious radiated emission

- Measured output Power : 27.08 dB m = 0.511 W
- Modulation Signal : GSM850
- Distance : 3 meters
- Limit :  $-(43 + 10\log_{10}(W)) = -40.08$  dB c

Frequency (MHz)	Ant. Pol. (H/V)	S.G level (dB m)	Cable loss (dB)	Ant. gain (dB d)	E.R.P (dB m)	dB c	Margin (dB)
Low Channel (824.2 MHz)							
1 648.40	V	-31.86	4.54	6.44	-29.96	-57.04	16.96
1 648.40	H	-37.15	4.54	6.44	-35.25	-62.33	22.25
2 472.62	V	-26.61	5.67	7.97	-24.31	-51.39	11.31
2 472.62	H	-29.09	5.67	7.97	-26.79	-53.87	13.79
Middle Channel (836.6 MHz)							
1 673.20	V	-30.61	4.58	6.51	-28.68	-55.76	15.68
1 673.20	H	-41.46	4.58	6.51	-39.53	-66.61	26.53
2 510.00	V	-21.91	5.72	8.02	-19.61	-46.69	6.61
2 510.00	H	-24.73	5.72	8.02	-22.43	-49.51	9.43
High Channel (848.8 MHz)							
1 697.60	V	-32.79	4.62	6.57	-30.84	-57.92	17.84
1 697.60	H	-43.81	4.62	6.57	-41.86	-68.94	28.86
2 546.59	V	-25.25	5.75	8.07	-22.93	-50.01	9.93
2 546.59	H	-27.60	5.75	8.07	-25.28	-52.36	12.28

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

- Measured output Power : 27.98 dB m = 0.628 W
- Modulation Signal : GSM1900
- Distance : 3 meters
- Limit :  $-(43 + 10\log_{10}(W)) = -40.94$  dB c

Frequency (MHz)	Ant. Pol. (H/V)	S.G level (dB m)	Cable loss (dB)	Ant. gain (dB i)	E.I.R.P (dB m)	dB c	Margin (dB)
Low Channel(1 850.2 MHz)							
3 700.40	V	-39.89	7.13	11.85	-35.17	-63.15	22.17
3 700.40	H	-39.47	7.13	11.85	-34.75	-62.73	21.75
Middle Channel(1 880.0 MHz)							
3 760.00	V	-40.22	7.23	11.85	-35.61	-63.59	22.61
3 760.00	H	-43.64	7.23	11.85	-39.03	-67.01	26.03
High Channel(1 909.8 MHz)							
3 819.60	V	-39.79	7.33	11.84	-35.28	-63.26	22.28
3 819.60	H	-43.67	7.33	11.84	-39.16	-67.14	26.16

**Remark:**

1. E.R.P. & E.I.R.P = S.G level (dB m) - Cable loss (dB) + Ant. gain (dB d/dB i)
2. No more harmonic above 3<sup>rd</sup> harmonic for all channel.


## 3. Conducted Output Power

### 3.1. Limit

Requirements: CFR 47, Section §2.1046

### 3.2. Test Procedure

1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The mobile was set up for the max. output power with pseudo random data modulation.
3. The power was measured with Mobile Communication Test unit.



### 3.3. Test Result

Ambient temperature : (23 ± 2) °C

Relative humidity : 46 % R.H.

Band	Frequency (MHz)	Voice GSM	GPRS Data	
			GPRS	GPRS
			1 TX Slot	2 TX Slot
			(dBm)	(dBm)
GSM 850	824.2	<b>32.40</b>	32.30	30.77
	836.6	<b>32.54</b>	32.49	30.89
	848.8	<b>32.51</b>	32.47	30.91
GSM 1900	1850.2	<b>27.69</b>	27.69	25.70
	1880.0	<b>28.85</b>	28.80	26.80
	1909.8	<b>29.61</b>	29.60	27.50

Band	Frequency (MHz)	EDGE Data	
		EDGE	EDGE
		1 TX Slot	2 TX Slot
		(dBm)	(dBm)
EDGE 850	824.2	<b>27.35</b>	27.33
	836.6	<b>27.49</b>	27.46
	848.8	<b>27.51</b>	27.48
EDGE 1900	1850.2	<b>24.30</b>	22.40
	1880.0	<b>26.40</b>	23.30
	1909.8	<b>26.10</b>	24.00

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 4. Occupied Bandwidth 99 %


### 4.1. Limit

Requirements: CFR 47, Section §2.1049.

### 4.2. Test Procedure

1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The resolution bandwidth of the spectrum analyzer was set.

Occupied Bandwidth 99 % and -26 dB was tested under



### 4.3 Test Results


Ambient temperature : (23 ± 2) °C

Relative humidity : 46 % R.H.


Band	Mode	Frequency (MHz)	Occupied Bandwidth (MHz)
GSM850	Voice	824.2	246.26
		836.6	246.26
		848.8	246.26
	EDGE	848.8	236.27
GSM1900	Voice	1 850.2	242.93
		1 880.0	242.93
		1 909.8	244.59
	EDGE	1 909.8	242.93

Please refer to the following plots.

**GSM850**  
99 %  
Low Channel




Middle Channel



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**High Channel****GSM850 EDGE**

99 %

High Channel



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*



SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**GSM1900**

99 %

Low Channel


**Middle Channel**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.


[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## High Channel

**GSM1900 EDGE**

99 %

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)


## 5. Spurious Emissions at Antenna Terminal

### 5.1. Limit

§ 22.917(e) and §24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency must be attenuated below the transmitting (P) by a factor of at least  $43 + 10\log(P)$  dB.

### 5.2. Test Procedure

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set at 1 MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.
3. Spurious Emission was tested




### 5.3. Test Results


Ambient temperature :  $(23 \pm 2)^\circ\text{C}$

Relative humidity : 46 % R.H.



Please refer to the following plots.

**GSM850**  
Low Channel

## Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


**High Channel****GSM1900  
Low Channel**

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## Middle Channel



## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


## 6. Band Edge

### 6.1. Limit

§ 22.917(e) and §24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency must be attenuated below the transmitting (P) by a factor of at least  $43+10\log(P)$ dB.

### 6.2. Test Procedure


1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The center of the spectrum analyzer was set to block edge frequency.




### 6.3. Test Results

Ambient temperature : ( 23  $\pm$  2 ) °C  
Relative humidity : 46 % R.H.

Please refer to the following plots.

**GSM850**  
Low Channel



## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.


[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**GSM850 EDGE**  
Low Channel**High Channel**


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**GSM1900**  
Low Channel


## High Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**GSM1900 EDGE**  
Low Channel

## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 7. Frequency Stability

### 7.1. Limit

Requirements: FCC § 2.1055 (a), § 2.1055 (d) & following:


According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table of this section.

For Mobile devices operating in the 824 to 849 MHz band at a power level less than or equal to 3 Watts, the limit specified in Table C-1 is +/- 2.5 ppm.

§24.235 The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 7.2. Test Procedure

1. Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators.
2. The EUT was placed inside the temperature chamber.
3. After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.



### 7.3. Test Results

Ambient temperature : ( 23 ± 2) °C

Relative humidity : 46 % R.H.

#### GSM850 mode at middle channel

Reference Frequency: 836.6 MHz, Limit: 2.5 ppm			
Frequency Stability versus Temperature			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
50	3.7	-88	-0.105
40		-64	-0.076
30		-75	-0.090
23		-83	-0.099
10		-68	-0.082
0		-79	-0.094
-10		-70	-0.083
-20		-63	-0.076
-30		-77	-0.092
Frequency Stability versus power Supply			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
23	4.155	-72	-0.086
	DC 3.25 (batt. End point)	-68	-0.081

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

**GSM1900 mode at middle channel**

<b>Reference Frequency: 1 880.0 MHz, Limit: 2.5 ppm</b>			
<b>Frequency Stability versus Temperature</b>			
<b>Environment Temperature (°C)</b>	<b>Power Supplied (Vdc)</b>	<b>Frequency Measure with Time Elapse</b>	
		<b>Frequency Error (Hz)</b>	<b>ppm</b>
50	3.7	-83	-0.044
40		-76	-0.040
30		-89	-0.048
23		-71	-0.038
10		-83	-0.044
0		-71	-0.038
-10		-62	-0.033
-20		-81	-0.043
-30		-64	-0.034
<b>Frequency Stability versus power Supply</b>			
<b>Environment Temperature (°C)</b>	<b>Power Supplied (Vdc)</b>	<b>Frequency Measure with Time Elapse</b>	
		<b>Frequency Error (Hz)</b>	<b>Ppm</b>
23	4.155	-69	-0.037
	3.25 (batt. End point)	-83	-0.044

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)