




1.) Label drawings:

1	<p>Model: AP One Rugged with M12 Connector</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p> <p>M?</p>   <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	peplink
2	<p>Model: AP One Rugged Extreme</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p> <p>M?</p>   <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	peplink
3	<p>Model: AP One Rugged EX</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p> <p>M?</p>   <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	peplink

4	<p>Model: AP One Rugged M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>peplink   CE FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	peplink
Default Access	Username: admin http://192.168.50.1 Password: admin			
5	<p>Model: PismoAC6M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>peplink   CE FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	peplink
Default Access	Username: admin http://192.168.50.1 Password: admin			
6	<p>Model: PismoAC6 M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>peplink   CE FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	peplink
Default Access	Username: admin http://192.168.50.1 Password: admin			

1	<p>Model: AP One Rugged with M12 Connector</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	  <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	PEPWAVE
2	<p>Model: AP One Rugged Extreme</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	  <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	PEPWAVE
3	<p>Model: AP One Rugged EX</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	  <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	PEPWAVE

4	<p>Model: AP One Rugged M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>PEPWAVE  CE</p> <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	PEPWAVE
Default Access	Username: admin http://192.168.50.1 Password: admin			
5	<p>Model: PismoAC6M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>PEPWAVE  CE</p> <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	PEPWAVE
Default Access	Username: admin http://192.168.50.1 Password: admin			
6	<p>Model: PismoAC6 M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>PEPWAVE  CE</p> <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	PEPWAVE
Default Access	Username: admin http://192.168.50.1 Password: admin			

1	<p>Model: AP One Rugged with M12 Connector</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Pismo
Default Access	Username: admin http://192.168.50.1 Password: admin				
2	<p>Model: AP One Rugged Extreme</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Pismo
Default Access	Username: admin http://192.168.50.1 Password: admin				
3	<p>Model: AP One Rugged EX</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <table border="1"> <tr> <td>Default Access</td><td>Username: admin http://192.168.50.1 Password: admin</td></tr> </table> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Default Access	Username: admin http://192.168.50.1 Password: admin	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p>	Pismo
Default Access	Username: admin http://192.168.50.1 Password: admin				

4	<p>Model: AP One Rugged M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Pismo
5	<p>Model: PismoAC6M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Pismo
6	<p>Model: PismoAC6 M12</p> <p>Product Code: APO-RUG-N Serial No.: 2935-31BD-6E24 LAN MAC: 00-1A-DD-4E-FB-A0 AP Password: DD4EFBA0</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Default Access Username: admin http://192.168.50.1 Password: admin</p> </div> <p>Input: 12-36V DC</p> <p>Made in Taiwan</p>  <p>M?</p>	    <p>FCC ID: U8G-P1AC6M12 IC: 20682-P1AC6M12 CAN ICES-3(A)/NMB-3(A)</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>	Pismo

FCC ID : [U8G-P1AC6M12](#)

2.) FCC / IC Label Location:

