

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart B, Class A

ANSI C63.4–2014

ANSI C63.4a–2017

Report No.: FDBCIC-WTW-P24100659 R2

FCC ID: U8G-P1MT01

Product: Peplink Pepwave Wireless Product

Brand:  **PEP WAVE**

Model No.: MAX BR1 Mini

Series Model: MAX-BR1-MINI-LTE-US-T-PRM, MAX-BR1-MINI-LTEA-US-T-PRM,
MAX-BR1-MINI-LTE-US-DC-T-PRM, MAX-BR1-MINI-LTEA-US-DC-T-PRM, AP One
Rugged, APO-AC-RUG
(refer to item 3.1 for more details)

Received Date: 2024/10/29

Test Date: 2024/11/7 ~ 2024/11/9

Issued Date: 2024/12/24

Applicant: PISMO LABS TECHNOLOGY LIMITED

Address: A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle
Peak Road, Cheung Sha Wan, Hong Kong

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 328930 / TW1050

Designation Number:

Approved by: _____

Leo Hsu

Leo Hsu / Project Engineer

Date: _____

2024/12/24

This test report consists of 26 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Lena Wang / Specialist



Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 Description of EUT	6
3.2 Primary Clock Frequencies of Internal Source	6
3.3 Features of EUT	6
3.4 Operating Modes of EUT and Determination of Worst Case Operating Mode	7
3.5 Test Program Used and Operation Descriptions	8
3.6 Connection Diagram of EUT and Peripheral Devices	9
3.7 Configuration of Peripheral Devices and Cable Connections	9
4 Test Instruments	10
4.1 Conducted Emissions from Power Ports	10
4.2 Radiated Emissions up to 1 GHz	11
4.3 Radiated Emissions above 1 GHz.....	12
5 Limits of Test Items.....	13
5.1 Conducted Emissions from Power Ports	13
5.2 Radiated Emissions up to 1 GHz	13
5.3 Radiated Emissions above 1 GHz.....	13
6 Test Arrangements	14
6.1 Conducted Emissions from Power Ports	14
6.2 Radiated Emissions up to 1 GHz	15
6.3 Radiated Emissions above 1 GHz.....	16
7 Test Results of Test Item	17
7.1 Conducted Emissions from Power Ports	17
7.2 Radiated Emissions up to 1 GHz	19
7.3 Radiated Emissions above 1 GHz.....	21
8 Pictures of Test Arrangements	25
9 Information of the Testing Laboratories	26

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Release Control Record

Issue No.	Description	Date Issued
FDBCIC-WTW-P24100659	Original release.	2024/11/26
FDBCIC-WTW-P24100659 R1	1. Revise section 3.7 ID A's Model No. 2. Add series models 3. Revise section 3.1 note 1	2024/12/12
FDBCIC-WTW-P24100659 R2	Add FCC ID	2024/12/24

1 Certificate

Product: Peplink Pepwave Wireless Product

Brand: 

Test Model: MAX BR1 Mini

Series Model: MAX-BR1-MINI-LTE-US-T-PRM, MAX-BR1-MINI-LTEA-US-T-PRM,
MAX-BR1-MINI-LTE-US-DC-T-PRM, MAX-BR1-MINI-LTEA-US-DC-T-PRM, AP One Rugged,
APO-AC-RUG
(refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: PISMO LABS TECHNOLOGY LIMITED

Test Date: 2024/11/7 ~ 2024/11/9

Standard: 47 CFR FCC Part 15, Subpart B, Class A
ANSI C63.4–2014
ANSI C63.4a–2017

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

2 Summary of Test Results

The test items that the EUT need to perform in accordance with its interfaces, evaluated functions, are as follows:

Standard / Clause	Test Item	Result	Remark
FCC Part 15.107	Conducted Emissions from Power Ports	Pass	Minimum passing Class A margin is -20.78 dB at 0.33800 MHz
FCC Part 15.109	Radiated Emissions up to 1 GHz	Pass	Minimum passing Class A margin is -7.74 dB at 40.54 MHz
FCC Part 15.109	Radiated Emissions above 1 GHz	Pass	Minimum passing Class A margin is -13.73 dB at 10947.27 MHz

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)	Maximum allowable uncertainty (±)
Conducted Emissions from Power Ports	9 kHz ~ 30 MHz	2.90 dB	3.4 dB (U_{cispr})
Radiated Emissions up to 1 GHz	30 MHz ~ 1 GHz	4.63 dB	6.3 dB (U_{cispr})
Radiated Emissions above 1 GHz	1 GHz ~ 6 GHz	4.91 dB	5.2 dB (U_{cispr})
	6 GHz ~ 18 GHz	4.42 dB	5.5 dB (U_{cispr})
	18 GHz ~ 40 GHz	4.52 dB	-

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 Description of EUT

Product	Peplink Pepwave Wireless Product
Brand	
Test Model	MAX BR1 Mini
Series Model	MAX-BR1-MINI-LTE-US-T-PRM, MAX-BR1-MINI-LTEA-US-T-PRM, MAX-BR1-MINI-LTE-US-DC-T-PRM, MAX-BR1-MINI-LTEA-US-DC-T-PRM, AP One Rugged, APO-AC-RUG
Model Difference	Refer to Note as below
Sample Status	Engineering sample
Power Supply Rating	Refer to Note as below

Note:

1. All models are listed as below.

Brand	Model	Difference
	MAX BR1 Mini	The differences are only the model and market segmentation. (with Cellular & GPS feature)
	MAX-BR1-MINI-LTE-US-T-PRM	
	MAX-BR1-MINI-LTEA-US-T-PRM	
	MAX-BR1-MINI-LTE-US-DC-T-PRM	
	MAX-BR1-MINI-LTEA-US-DC-T-PRM	For marketing purpose (without Cellular & GPS feature)
	AP One Rugged	
	APO-AC-RUG	

2. The EUT uses following accessories.

Item	Brand	Model	AC Input	DC Output	DC Output Cable
Adapter	LEI	MU24D1120200-A1	100-240Vac 50/60Hz 0.7A	12Vdc 2.0A	Non-Shielded, 1.5m

3.2 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 5.85 GHz, provided by PISMO LABS TECHNOLOGY LIMITED, for detailed internal source, please refer to the manufacturer's specifications.

3.3 Features of EUT

The tests reported herein were performed according to the method specified by PISMO LABS TECHNOLOGY LIMITED, for detailed feature description, please refer to the manufacturer's specifications or user's manual.
Please refer to appendix of the report if the applicant has provided additional descriptions of the EUT.

3.4 Operating Modes of EUT and Determination of Worst Case Operating Mode

The EUT has been pre-tested under following test modes.

Test Condition	
Mode	Conducted Emissions from Power Ports
1	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
2	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(240 Vac, 60 Hz)
3	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(10 Vdc from Molex Power Port by Power Supply) + Input Power(120 Vac, 60 Hz)
4	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(30 Vdc from Molex Power Port by Power Supply) + Input Power(120 Vac, 60 Hz)
5	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(from 802.3at PoE input by LAN 1) + PoE injector + Input Power(120 Vac, 60 Hz)

Note: The worst case is that mode 1 is shown in bold.

Mode	Radiated Emissions up to 1 GHz
1	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
2	EUT(Stand-up) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
3	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(WP68-M002C-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
4	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot B(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
5	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EC25-AFXD) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
6	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(WCDMA Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
7	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 41) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
8	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(Molex Power Port by Power Supply) + Input Power(10 Vdc)
9	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(Molex Power Port by Power Supply) + Input Power(30 Vdc)
10	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(from 802.3at PoE input by LAN 1)

Notes:

1. Refer to Certified cellular module report worst band to test.
2. The worst SIM card slot is: Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)
3. The WWAN pretest worst band is LTE Band 5
4. The Molex Power Port worst rating is 10 Vdc
5. There are both standby mode and normal mode to be pre-tested then normal mode has the highest emission value.
6. The worst case is that mode 1 is shown in bold.


Test modes are presented in the report as below.

Test Condition	
Mode	Conducted Emissions from Power Ports
A	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
Mode	Radiated Emissions up to 1 GHz
A	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)
Mode	Radiated Emissions above 1 GHz
A	EUT(Laying-flat) + LAN 1-2(1Gbps) + WAN(1Gbps) + SIM(Slot A(EM7411) + e-sim(MFXS-M006b-MFOCMW)) + WWAN(LTE Band 5) + GPS(Rx) + WiFi(2.4G + 5G) + EUT power(12 Vdc from Adapter) + Adapter(MU24D1120200-A1) + Input Power(120 Vac, 60 Hz)

3.5 Test Program Used and Operation Descriptions

- The EUT powered by Adapter.
- The EUT linked with Laptop / PC, which acted as a communication partners via LAN cable and WLAN.
- The communication partners sent data to the EUT via LAN and WLAN and transmission.
- The EUT communicated data with the Radio Communication Analyzer / GPS simulator which acted as a communication partner.

3.6 Connection Diagram of EUT and Peripheral Devices



3.7 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Antenna*2	peplink PEPWAVE	04-410188-00	N/A	N/A	Supplied by applicant
B	SIM Card	R&S	CMW-Z05	N/A	N/A	Provided by Lab
C	GPS Antenna	YUAN CHEN TECH CO., LTD	A400-00001-01	N/A	N/A	Supplied by applicant
D	Laptop*2	DELL	Latitude E5420	C6F33F3	N/A	Provided by Lab
		DELL	Latitude E5420	6RS33F3	N/A	Provided by Lab
E	Radio Communication Analyzer	Anritsu	MT8820C	6201010284	N/A	Provided by Lab
F	Laptop*2	DELL	Latitude 5501	F42VP13	N/A	Provided by Lab
		DELL	Latitude 5501	942VP13	N/A	Provided by Lab
G	PC	DELL	D14M	4287266606	N/A	Provided by Lab
H	GPS simulator	T&E	GSG-64	201902	N/A	Provided by Lab
I	Antenna*2	WIESON	ARY121-1976-001-00	N/A	N/A	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	Antenna	1	5	Yes	0	Supplied by applicant
2	Cat.5e	2	10	No	0	Provided by Lab
3	Cat.5e	1	10	No	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Conducted Emissions from Power Ports

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance HUBER+SUHNER	E1-011315	13	2023/11/22	2024/11/21
50 ohm terminal resistance	E1-011279	04	2023/11/22	2024/11/21
	E1-011280	05	2023/11/22	2024/11/21
EMI Test Receiver R&S	ESCI	100613	2023/12/4	2024/12/3
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2024/1/6	2025/1/5
LISN R&S	ENV216	101826	2024/3/25	2025/3/24
	ESH3-Z5	100311	2024/9/5	2025/9/4
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2024/1/6	2025/1/5
Software BVADT	BVADT_Conc_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2024/8/28	2025/8/27

Notes:

1. The test was performed in HY - Conduction 1.
2. The VCCI Site Registration No. is C-12040.
3. Tested Date: 2024/11/7

4.2 Radiated Emissions up to 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower (H)	MFA-440	970705	N/A	N/A
Antenna Tower (V)	MFA-440	9707	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-148	2023/12/14	2024/12/13
		9168-156	2023/12/14	2024/12/13
Controller (H)	MF7802	08093	N/A	N/A
Controller (V)	MF7802	074	N/A	N/A
EMI Test Receiver R&S	ESR3	102783	2023/12/13	2024/12/12
	ESR7	101264	2024/4/16	2025/4/15
Fixed Attenuator Mini-Circuits	UNAT-5+	PAD-CH(H)-01	2024/8/25	2025/8/24
		PAD-CH(V)-01	2024/8/25	2025/8/24
Preamplifier Sonoma	310N	352923	2024/5/1	2025/4/30
		352924	2024/5/1	2025/4/30
RF Coaxial Cable TIMES	LMR-600(11.8M)+LMR-400 (7M)	CABLE-CH1(HOR)-01	2024/8/25	2025/8/24
	LMR-600(18M)+LMR-400 (7M)	CABLE-CH1(VER)-01	2024/8/25	2025/8/24
Software	ADT_Radiated_V8.8.09	N/A	N/A	N/A
Turn Table	DS430	50303	N/A	N/A

Notes:

1. The test was performed in HY - 10M Chamber. The test site validated date: 2024/7/27 (NSA)
2. The VCCI Site Registration No. is R-11893.
3. Tested Date: 2024/11/9

4.3 Radiated Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower BVADT	AT100	AT93021702	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	3	N/A	N/A
Controller BVADT	SC100	SC93021702	N/A	N/A
Fixed Attenuator Mini-Circuits	BW-K3-2W44+	PAD-CH3-04	2024/7/6	2025/7/5
	BW-N4W5+	PAD-CH3-03	2024/7/6	2025/7/5
Horn Antenna ETS-Lindgren	3117	00034126	2024/10/18	2025/10/17
Horn Antenna Schwarzbeck	BBHA 9120D	209	2023/11/12	2024/11/11
	BBHA 9170	148	2023/11/12	2024/11/11
		BBHA9170241	2024/10/18	2025/10/17
Notch Filter Micro-Tronics	BRM17690-01	002	2024/8/25	2025/8/24
	BRM50716-01	G010	2024/8/25	2025/8/24
Preamplifier Agilent	8449B	3008A02465	2024/1/6	2025/1/5
Preamplifier EMCI	EMC012645SE	980338	2024/5/1	2025/4/30
	EMC184045SE	980610	2024/5/1	2025/4/30
PXA Signal Analyzer Keysight	N9030B	MY60070562	2024/2/27	2025/2/26
RF Coaxial Cable EMCI	EM102-KMKM-1M	#01	2024/8/25	2025/8/24
	EM102-KMKM-3M	#01	2024/8/25	2025/8/24
	EMC102-KM-KM-1000	200311	2024/7/6	2025/7/5
	EMC102-KM-KM-3000	200313	2024/7/6	2025/7/5
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104&EMC104-SM-SM- 8000	Cable-CH3- 03(309224+170907)	2024/7/6	2025/7/5
Software BVADT	ADT_Radiated_V8.8.09	N/A	N/A	N/A
Turn Table BVADT	TT100	TT93021702	N/A	N/A

Notes:

1. The test was performed in HY - 966 Chamber 2. The test site validated date: 2024/4/27 (VSWR)
2. The VCCI Site Registration No. is G-20126.
3. Tested Date: 2024/11/8

5 Limits of Test Items

5.1 Conducted Emissions from Power Ports

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Notes: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Radiated Emissions up to 1 GHz

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBµV/m)				
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39.1	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960				
960-1000	49.5	43.5	47	37

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40.0	50.5	40.5
88-216	54.0	43.5		
216-230	56.9	46.0		
230-960				
960-1000	60.0	54.0	57.5	47.5

Notes: 1. The lower limit shall apply at the transition frequencies.

5.3 Radiated Emissions above 1 GHz

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40GHz, whichever is lower

Radiated Emissions Limits at 3 meters (dBuV/m)		
Frequency range	Class A	Class B
Above 1GHz	Avg: 60 Peak: 80	Avg: 54 Peak: 74


Notes: 1. These limit levels apply for a measurement distance of 3 m. If using a different measurement distance, the measured levels shall be extrapolated to the 3 m limit distance using a factor of 20 dB per decade of distance. The measurement distance shall place the measurement antenna in the far field of the ITE or digital apparatus under test.

6 Test Arrangements

6.1 Conducted Emissions from Power Ports

- For the table-top EUT is placed on a 0.8 meter insulation table; for the floor standing EUT shall be insulated (by insulation of 12 mm) from the horizontal reference ground plane. The EUT is placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units are connected to the power mains through another LISN. They provide coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.




For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

6.2 Radiated Emissions up to 1 GHz

- For the table-top EUT is placed on a 0.8 meter to the top of rotating table; for the floor standing EUT shall be insulated (by insulation of 12 mm) from the horizontal reference ground plane. The rotating table is rotated 360 degrees to determine the position of the highest radiation. If the equipment requires a dedicated ground connection, this shall be provided and bonded to the RGP.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is up to 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency up to 1GHz.




For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

6.3 Radiated Emissions above 1 GHz

- For the table-top EUT is placed on a 0.8 meter to the top of rotating table; for the floor standing EUT shall be insulated (by insulation of 12 mm) from the horizontal reference ground plane. The rotating table is rotated 360 degrees to determine the position of the highest radiation. If the equipment requires a dedicated ground connection, this shall be provided and bonded to the RGP.
- The EUT was set $d = 3$ meters for 1 GHz to 18 GHz and $d = 1.5$ meters for 18 GHz to 40 GHz away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

Note: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7 Test Results of Test Item

7.1 Conducted Emissions from Power Ports


Mode A

Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 70 % RH, 989.6 mbar
Tested by	Rene Chen		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.72	40.52	25.70	50.24	35.42	79.00	66.00	-28.76	-30.58
2	0.16535	9.72	40.96	29.32	50.68	39.04	79.00	66.00	-28.32	-26.96
3	0.19000	9.72	37.45	25.89	47.17	35.61	79.00	66.00	-31.83	-30.39
4	0.32600	9.79	35.02	30.26	44.81	40.05	79.00	66.00	-34.19	-25.95
5	0.36130	9.81	34.98	32.51	44.79	42.32	79.00	66.00	-34.21	-23.68
6	1.90600	9.95	24.49	17.27	34.44	27.22	73.00	60.00	-38.56	-32.78

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 70 % RH, 989.6 mbar
Tested by	Rene Chen		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17000	9.70	41.39	30.35	51.09	40.05	79.00	66.00	-27.91	-25.95
2	0.19400	9.71	37.74	27.77	47.45	37.48	79.00	66.00	-31.55	-28.52
3	0.21800	9.72	35.00	26.89	44.72	36.61	79.00	66.00	-34.28	-29.39
4	0.27000	9.77	26.58	18.40	36.35	28.17	79.00	66.00	-42.65	-37.83
5	0.33800	9.82	36.83	35.40	46.65	45.22	79.00	66.00	-32.35	-20.78
6	0.35800	9.84	35.45	32.46	45.29	42.30	79.00	66.00	-33.71	-23.70

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.2 Radiated Emissions up to 1 GHz


Mode A

Frequency Range	30 MHz ~ 1 GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 72 % RH, 987.1 mbar
Tested By	Fox Chang		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	51.57	17.10 QP	39.00	-21.90	4.00 H	92	29.81	-12.71
2	77.79	20.55 QP	39.00	-18.45	4.00 H	310	37.07	-16.52
3	91.37	19.19 QP	43.50	-24.31	3.50 H	144	37.81	-18.62
4	147.95	18.77 QP	43.50	-24.73	3.50 H	103	31.86	-13.09
5	162.50	21.16 QP	43.50	-22.34	3.50 H	333	34.05	-12.89
6	471.41	25.13 QP	46.40	-21.27	1.50 H	239	32.69	-7.56

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.




Frequency Range	30 MHz ~ 1 GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 72 % RH, 987.1 mbar
Tested By	Fox Chang		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.54	31.26 QP	39.00	-7.74	3.50 V	270	44.73	-13.47
2	77.53	27.74 QP	39.00	-11.26	4.00 V	350	44.48	-16.74
3	125.00	26.08 QP	43.50	-17.42	2.00 V	22	41.22	-15.14
4	162.50	29.88 QP	43.50	-13.62	1.00 V	146	43.05	-13.17
5	249.96	20.67 QP	46.40	-25.73	1.00 V	199	34.95	-14.28
6	479.98	23.89 QP	46.40	-22.51	1.50 V	34	31.49	-7.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.



7.3 Radiated Emissions above 1 GHz


Mode A

Frequency Range	1 GHz ~ 18 GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1 MHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 72 % RH, 987 mbar
Tested By	Bryant Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3216.23	49.68 PK	80.00	-30.32	2.00 H	280	44.11	5.57
2	3216.23	44.03 AV	60.00	-15.97	2.00 H	280	38.46	5.57
3	7262.80	53.56 PK	80.00	-26.44	1.25 H	88	39.10	14.46
4	7262.80	41.42 AV	60.00	-18.58	1.25 H	88	26.96	14.46
5	10947.27	59.15 PK	80.00	-20.85	1.25 H	121	39.95	19.20
6	10947.27	46.27 AV	60.00	-13.73	1.25 H	121	27.07	19.20

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.




Frequency Range	1 GHz ~ 18 GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1 MHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 72 % RH, 986.8 mbar
Tested By	Bryant Hsu		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3215.98	53.14 PK	80.00	-26.86	1.00 V	266	47.57	5.57
2	3215.98	43.44 AV	60.00	-16.56	1.00 V	266	37.87	5.57
3	7152.87	53.95 PK	80.00	-26.05	1.99 V	277	39.61	14.34
4	7152.87	41.29 AV	60.00	-18.71	1.99 V	277	26.95	14.34
5	12522.60	58.56 PK	80.00	-21.44	1.25 V	289	40.38	18.18
6	12522.60	45.35 AV	60.00	-14.65	1.25 V	289	27.17	18.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.




Frequency Range	18 GHz ~ 40 GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1 MHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 72 % RH, 986.9 mbar
Tested By	Bryant Hsu		

Antenna Polarity & Test Distance : Horizontal at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	27937.40	51.45 PK	86.00	-34.55	1.00 H	178	52.29	-0.84
2	27937.40	39.30 AV	66.00	-26.70	1.00 H	178	40.14	-0.84
3	34492.67	54.41 PK	86.00	-31.59	1.24 H	319	50.46	3.95
4	34492.67	41.92 AV	66.00	-24.08	1.24 H	319	37.97	3.95
5	38850.87	57.23 PK	86.00	-28.77	2.00 H	20	50.70	6.53
6	38850.87	44.97 AV	66.00	-21.03	2.00 H	20	38.44	6.53

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.




Frequency Range	18 GHz ~ 40 GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1 MHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 72 % RH, 986.9 mbar
Tested By	Bryant Hsu		

Antenna Polarity & Test Distance : Vertical at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	27353.67	51.78 PK	86.00	-34.22	1.25 V	284	52.31	-0.53
2	27353.67	38.96 AV	66.00	-27.04	1.25 V	284	39.49	-0.53
3	34494.87	53.16 PK	86.00	-32.84	1.25 V	344	49.19	3.97
4	34494.87	41.85 AV	66.00	-24.15	1.25 V	344	37.88	3.97
5	38852.33	55.24 PK	86.00	-30.76	1.25 V	205	48.70	6.54
6	38852.33	44.84 AV	66.00	-21.16	1.25 V	205	38.30	6.54

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---