



Registration No. DAT-P-207/05

FCC ID: U9A277IWLAN-V200

EMI -- TEST REPORT

- FCC Part 15.249 -

| | | |
|--------------------------|-----------------------|---------------|
| Test Report No. : | T33234-03-00AA | 22. June 2009 |
| | | Date of issue |

Type / Model Name : SIMATIC Mobile Panel 277F WLAN / 277 WLAN

Product Description : Mobile Human Machine Interface

Applicant : Siemens AG, Industry Sector, IIA AS RD ST TT

Address : Werner-von-Siemens-Str. 50
92224 Amberg, Germany

Manufacturer : Siemens AG, Industry Sector, IIA AS FA HMI

Address : Gleiwitzer Str. 555
90475 Nürnberg, Germany

Licence holder : Siemens AG, Industry Sector, IIA AS RD ST TT

Address : Werner-von-Siemens-Str. 50
92224 Amberg, Germany

| |
|--|
| Test Result according to the standards listed in clause 1 test standards: |
|--|

POSITIVE



DAT-P-207/05-00

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: U9A277IWLAN-V200

Contents

| | |
|--|-----------|
| 1 TEST STANDARDS | 3 |
| 2 SUMMARY | 4 |
| 3 EQUIPMENT UNDER TEST | 5 |
| 3.1 Photo documentation of the EUT – Please see attachment A | 5 |
| 3.2 Power supply system utilised | 5 |
| 3.3 Test setup | 5 |
| 3.4 Short description of the equipment under test (EUT) | 6 |
| 4 TEST ENVIRONMENT | 7 |
| 4.1 Address of the test laboratory | 7 |
| 4.2 Environmental conditions | 7 |
| 4.3 Statement of the measurement uncertainty | 7 |
| 4.4 Measurement protocol for FCC, VCCI and AUSTEL | 8 |
| 5 TEST CONDITIONS AND RESULTS | 9 |
| 5.1 Conducted emissions | 9 |
| 5.2 Radiated emission of the fundamental frequency | 13 |
| 5.3 Radiated emissions outside specified frequency bands | 16 |
| 5.4 20 dB Bandwidth | 25 |
| 5.5 Maximum Permissible Exposure (MPE) | 28 |
| 5.6 Antenna application | 30 |
| 6 USED TEST EQUIPMENT AND ACCESSORIES | 31 |

FCC ID: U9A277IWLAN-V200

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 15 Subpart A - General (October, 2008)

| | |
|-----------------------------------|---|
| Part 15, Subpart A, Section 15.31 | Measurement standards |
| Part 15, Subpart A, Section 15.33 | Frequency range of radiated measurements |
| Part 15, Subpart A, Section 15.35 | Measurement detector functions and bandwidths |
| Part 15, Subpart A, Section 15.38 | Incorporation by reference |

FCC Rules and Regulations Part 15 Subpart C - Intentional Radiators (October, 2008)

| | |
|------------------------------------|--|
| Part 15, Subpart C, Section 15.203 | Antenna requirement |
| Part 15, Subpart C, Section 15.204 | External radio frequency power amplifiers and antenna modifications |
| Part 15, Subpart C, Section 15.207 | AC Line conducted emissions |
| Part 15, Subpart C, Section 15.209 | Radiated emissions, general requirements |
| Part 15, Subpart C, Section 15.249 | Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz |

FCC Rules and Regulations Part 15 Subpart B - Unintentional Radiators (October, 2008)

| | |
|---------------------------------------|--|
| Part 15, Subpart B, Section 15.107(a) | AC Line conducted emissions |
| Part 15, Subpart B, Section 15.109(a) | Radiated emissions, general requirements |

FCC Rules and Regulations Part 1 Subpart I - Procedures Implementing the National Environmental Policy Act of 1969

| | |
|-----------------------------------|---|
| Part 1, Subpart I, Section 1.1310 | Radiofrequency radiation exposure limits. |
|-----------------------------------|---|

OET Bulletin 65, 65A, 65B, 65C Edition 97-01, August 1997 – Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.

| | |
|----------------------------------|---|
| ANSI C63.4: 2003 | Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz. |
| ANSI C95.1:1992 | IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz |
| CISPR 16-4-2: 2003 | Uncertainty in EMC measurement |
| CISPR 22: 2005 EN 55022: 2006 | Information technology equipment |

FCC ID: U9A277IWLAN-V200

2 SUMMARY

GENERAL REMARKS:

The EuT consists of 1 WLAN miniPCI module and 1 Effective Range Module (Chirp 2.45 GHz) which measure the distance between Mobile Panel and accompanying Transponder.

The Effective Range Module is connected to an internal dual port patch antenna (gain=2.6 / 2.7 dBic).

The frequency range was scanned from 9 kHz to 25000 MHz. All emissions not reported in this test report are more than 20 dB below the specified limit.

The Mobile Panel 277F IWLAN offers the possibility of having the mobile safety functions of emergency stop and enable available at any point of a machine or plant. The 277 IWLAN doesn't have the safety function. Both are electronically identical however the 277 IWLAN is not equipped with the relevant parts necessary for the safety function.

All tests have been carried out with the full equipped 277F IWLAN Mobile Panel.

This test report describes only the assessment of the Effective Range Module in the 2.4 GHz frequency band. The EuT has been measured in active transmitting mode. All measurements have been carried out radiated.

The receive mode is too short to be measured.

FINAL ASSESSMENT:

The equipment under test **fulfills** the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 19. March 2009

Testing concluded on : 29. April 2009

Checked by:

Tested by:

Klaus Gegenfurtner
Dipl.-Ing.(FH)
Manager: Radio Group

Anton Altmann
Dipl.-Ing.(FH)

FCC ID: U9A277IWLAN-V200

3 EQUIPMENT UNDER TEST


3.1 Photo documentation of the EUT – Please see attachment A

3.2 Power supply system utilised

Power supply voltage : 7.2 V DC Battery

Power supply voltage (alternative) : Input: 110-240 V / 47-63 Hz / 1φ Power supply
Output: +12 V DC

3.3 Test setup



FCC ID: U9A277IWLAN-V200

3.4 Short description of the equipment under test (EUT)

The SIMATIC Mobile Panel 277 IWLAN / 277F IWLAN permits mobile operation at any point in the system. The HMI device communicates with the PLC via WLAN. The HMI device is equipped with a zone recognition function. The simple battery-powered operation and ergonomic design of the HMI device permit safe working with the Mobile Panel 277 IWLAN over extended periods. The operator can operate the system wireless at almost any location on the machine or system.

Number of tested samples: 1
Serial number: Prototype

EuT operation mode:

The equipment under test was operated during the measurement under the following conditions:

- Continuous transmitting mode

EuT configuration:

(The CDF filled by the applicant can be viewed at the test laboratory.)

The following peripheral devices and interface cables were connected during the measurements:

- AC/DC power supply Model : FAIRWAY Model: VE50-1200
- Power supply 12 V Model : 6000A
- _____ Model : _____

FCC ID: U9A277IWLAN-V200

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

mikes-testingpartners gmbh
Ohmstrasse 2-4
94342 STRASSKIRCHEN
GERMANY

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader may notice that tolerances within the calibration of the equipment and facilities may cause additional uncertainty. The measurement uncertainty is calculated for all measurements listed in this test report acc. to CISPR 16-4-2 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurement“ and documented in the mikes-testingpartners gmbh quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, mikes-testingpartners gmbh, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component diversity and modifications in production processes may result in additional deviation. If necessary, refer to the test lab for the actual measurement uncertainty for specific tests. The manufacturer has the sole responsibility of continued compliance of the EUT.

FCC ID: U9A277IWLAN-V200

4.4 Measurement protocol for FCC, VCCI and AUSTEL

4.4.1 GENERAL INFORMATION

4.4.1.1 Test methodology

Conducted and radiated disturbance testing is performed according to the procedures set out by the International Special Committee on Radio Interference (CISPR) Publication 22, European Standard EN 55022 as shown under section 1 of this report.

The test methods used comply with CISPR Publication 22, EN 55022 - "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement" and with ANSI C63.4 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

In compliance with 47 CFR Part 15 Subpart A, Section 15.38 testing for FCC compliance may be achieved by following the procedures set out in ANSI C63.4 and applying the CISPR 22 limits.

4.4.1.2 Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral using the appropriate impedance characteristic or left unterminated. Where appropriate, cables are manually manipulated with respect to each other thus obtaining maximum disturbances from the unit.

4.4.2 DETAILS OF TEST PROCEDURES

4.4.2.1 General Standard Information

The test methods used comply with CISPR Publication 22, EN 55022 - "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement" and with ANSI C63.4 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

FCC ID: U9A277IWLAN-V200

5 TEST CONDITIONS AND RESULTS

5.1 Conducted emissions

For test instruments and accessories used see section 6 Part **A 4**.

5.1.1 Description of the test location

Test location: Shielded Room S2

5.1.2 Photo documentation of the test set-up



FCC ID: U9A277IWLAN-V200

5.1.3 Applicable standard

According to FCC Part 15, Section 15.207(a):

Except as shown in paragraphs (b) and (c) of this Section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of Emission (MHz) | Conducted limit (dB μ V) | |
|--------------------------------|------------------------------|------------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56 * | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency

5.1.4 Description of Measurement

The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection and a line impedance stabilization network (LISN) with $50\Omega/50\mu H$ (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 cm above the floor and is positioned 40 cm from the vertical ground plane (wall) of the screen room. The correction factors for cable loss are stored in the memory of the EMI receiver therefore the final level (dB μ V) appears directly in the reading of the EMI receiver. If the minimum limit margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasi-peak and average detection and recorded. The measurement is performed attending the US AC mains 120V/60 Hz.

To convert between dB μ V and μ V, the following conversions apply:

$$\begin{aligned} \text{dB}\mu\text{V} &= 20(\log \mu\text{V}) \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

5.1.5 Test result

Frequency range: 0.15 MHz - 30 MHz

Min. limit margin -5.6 dB at 26 MHz

The requirements are **FULFILLED**.

Remarks: The EuT keeps the requirements of EN 55022 class B.


FCC ID: U9A277IWLAN-V200

5.1.6 Test protocol

Test point: L1
 Operation mode: Continuous transmitting mode
 Remarks: Effective range module and WLAN 5 GHz aktiv
 Date: 19.03.2009
 Tested by: Anton Altmann

Result: passed

| Frequency MHz | QP Level dB(µV) | QP Margin dB | QP Limit dB | AV Level dB(µV) | AV Margin dB | AV Limit dB |
|------------------|--------------------|-----------------|----------------|--------------------|-----------------|----------------|
| 0.19 | 49.0 | -15.0 | 64.0 | 38.9 | -15.2 | 54.0 |
| 0.255 | 43.2 | -18.4 | 61.6 | 31.4 | -20.2 | 51.6 |
| 0.51 | 33.5 | -22.5 | 56.0 | 26.6 | -19.4 | 46.0 |
| 0.895 | 30.0 | -26.0 | 56.0 | 25.7 | -20.3 | 46.0 |
| 0.96 | 29.7 | -26.3 | 56.0 | 25.8 | -20.2 | 46.0 |
| 1.855 | 30.7 | -25.3 | 56.0 | 27.6 | -18.4 | 46.0 |
| 2.495 | 31.8 | -24.2 | 56.0 | 28.0 | -18.0 | 46.0 |
| 3.325 | 32.6 | -23.4 | 56.0 | 28.7 | -17.3 | 46.0 |
| 4.03 | 30.9 | -25.1 | 56.0 | 26.4 | -19.6 | 46.0 |
| 26 | 44.6 | -15.4 | 60.0 | 44.4 | -5.6 | 50.0 |




FCC ID: U9A277IWLAN-V200

Test point: N
 Operation mode: Continuous transmitting mode
 Remarks: Effective range module and WLAN 5 GHz aktiv
 Date: 19.03.2009
 Tested by: Anton Altmann

Result: passed

| Frequency MHz | QP Level dB(µV) | QP Margin dB | QP Limit dB | AV Level dB(µV) | AV Margin dB | AV Limit dB |
|------------------|--------------------|-----------------|----------------|--------------------|-----------------|----------------|
| 0.19 | 47.8 | -16.2 | 64.0 | 38.4 | -15.6 | 54.0 |
| 0.255 | 42.2 | -19.4 | 61.6 | 32.5 | -19.1 | 51.6 |
| 0.32 | 37.2 | -22.6 | 59.7 | 28.9 | -20.8 | 49.7 |
| 0.51 | 31.0 | -25.0 | 56.0 | 25.7 | -20.3 | 46.0 |
| 1.725 | 28.9 | -27.1 | 56.0 | 24.9 | -21.1 | 46.0 |
| 2.685 | 31.2 | -24.8 | 56.0 | 27.8 | -18.2 | 46.0 |
| 3.325 | 31.4 | -24.6 | 56.0 | 27.6 | -18.4 | 46.0 |
| 4.22 | 29.5 | -26.5 | 56.0 | 25.3 | -20.7 | 46.0 |
| 18.415 | 32.2 | -27.8 | 60.0 | 20.2 | -29.8 | 50.0 |
| 26 | 42.5 | -17.5 | 60.0 | 42.2 | -7.8 | 50.0 |



FCC ID: U9A277IWLAN-V200

5.2 Radiated emission of the fundamental frequency


For test instruments and accessories used see section 6 Part **CPR 3**.

5.2.1 Description of the test location

Test location: Anechoic Chamber A2

Test distance: 3 metres

5.2.2 Photo documentation of the test set-up



FCC ID: U9A277IWLAN-V200

5.2.1 Applicable standard

According to FCC Part 15C, Section 15.249(a):

The fieldstrength of emissions from intentional radiators within these frequency bands shall comply with the following table:

| Fundamental Frequency (MHz) | Fieldstrength of Fundamental | |
|--------------------------------|------------------------------|----------------|
| | (mV/m) | (dB μ V/m) |
| 902 - 928 | 50 | 94 |
| 2400 - 2483.5 | 50 | 94 |
| 5725 - 5875 | 50 | 94 |
| 24.0 - 24.25 GHz | 250 | 108 |

5.2.2 Description of Measurement

As shown in Section 15.35(b) the emissions above 1000 MHz are based on average limits. However the peak fieldstrength shall not exceed the maximum permitted average limit by more than 20 dB. The set up of the EUT shall be in accordance with ANSI C63.4. The fundamental frequency has been measured radiated using a spectrum analyzer at a distance of 3 m with the following settings:

Peak measurements: RBW=1 MHz, VBW=1 MHz, Peak detector

Average measurements: RBW=1MHz, VBW=10 Hz, Peak detector

5.2.3 Test result

| Frequency (MHz) | Reading Level Pk (dB μ V) | Reading Level AV (dB μ V) | Bandwidth (kHz) | Correction Factor (dB/m) | Corrected Level Pk (dB μ V/m) | Corrected Level AV (dB μ V/m) | Average Limit (dB μ V/m) | Delta (dB) |
|--------------------|-------------------------------------|-------------------------------------|--------------------|--------------------------------|---|---|------------------------------------|---------------|
| 2449 | 99.7 | --- | 1000 | -9.4 | 90.3 | --- | 94 | -3.7 |

Note: Where correction factor means cable loss, amplifier gain and antenna factor.

The value at 2449 MHz is the highest emission in the frequency band from 2400 to 2483.5 MHz.


The requirements are **FULFILLED**.

Remarks:

- Because the peak value is below the average limit, no AV-measurement has been performed.
- The EuT is transmitting only in the designed band and not in any restricted bands.
- For detailed test result refer to following plot.

FCC ID: U9A277IWLAN-V200

R
S



Date: 27.APR.2009 10:28:12

FCC ID: U9A277IWLAN-V200

5.3 Radiated emissions outside specified frequency bands

For test instruments and accessories used see section 6 Part **SER 1, SER 2, SER 3**.


5.3.1 Description of the test location

Test location: OATS1
Test distance: 3 metres

Test location: Anechoic Chamber A2
Test distance: 3 metres

5.3.2 Photo documentation of the test set-up

Anechoic chamber



FCC ID: U9A277IWLAN-V200

OATS1 (30-1000 MHz)



OATS1 (9 kHz-30 MHz)



FCC ID: U9A277IWLAN-V200

5.3.3 Applicable standard

According to FCC Part 15C, Section 15.249 (d):

Emission radiated outside of the specified frequency bands, except harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated limit in FCC Part 15C, Section 15.209, whichever is the lesser attenuation.

5.3.4 Description of Measurement

The radiated spurious emissions of the EUT are measured in the frequency range from 9 kHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. Measurements between 9 kHz and 1000 MHz are based employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. The set up of the EUT shall be in accordance with ANSI C63.4.

The emissions above 1000 MHz have been measured using a peak detector and RBW=VBW=1 MHz. The peak field strength must comply with the limits specified in Section 15.35 (b). Then the VBW have been set to 10 Hz, while maintaining all of the other instrument settings. The peak level now must comply with the limit specified in Section 15.209. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit.

5.3.5 Test result f < 1 GHz

| Frequency (MHz) | Reading Level QP (dB μ V) | Reading Level AV (dB μ V) | Bandwidth (kHz) | Correction Factor (dB/m) | Corrected Level QP (dB μ V/m) | Corrected Level AV (dB μ V/m) | Limit (dB μ V/m) | Delta (dB) |
|-----------------|-------------------------------|-------------------------------|-----------------|--------------------------|-----------------------------------|-----------------------------------|----------------------|------------|
| 0.009-0.150 | --- | --- | 0.200 | --- | --- | --- | --- | --- |
| 26 | 23.0 | --- | 9 | 20.0 | 43.0 | --- | 69.5 | -26.5 |
| 52 | 9.8 | --- | 120 | 15.2 | 25.0 | --- | 40.0 | -15.0 |
| 78 | 23.1 | --- | 120 | 12.0 | 35.1 | --- | 40.0 | -4.9 |
| 104 | 17.6 | --- | 120 | 11.6 | 29.2 | --- | 43.5 | -14.3 |
| 130 | 20.9 | --- | 120 | 14.0 | 34.9 | --- | 43.5 | -8.6 |
| 208 | 16.2 | --- | 120 | 14.2 | 30.4 | --- | 43.5 | -13.1 |
| 260 | 11.4 | --- | 120 | 15.7 | 27.1 | --- | 46.0 | -18.9 |
| 286 | 28.6 | --- | 120 | 16.6 | 45.2 | --- | 46.0 | -0.8 |
| 312 | 15.2 | --- | 120 | 17.3 | 32.5 | --- | 46.0 | -13.5 |
| 338 | 25.6 | --- | 120 | 17.8 | 43.4 | --- | 46.0 | -2.6 |
| 364 | 11.9 | --- | 120 | 18.4 | 30.3 | --- | 46.0 | -15.7 |
| 390 | 16.3 | --- | 120 | 18.9 | 35.2 | --- | 46.0 | -10.8 |
| 416 | 12.3 | --- | 120 | 19.5 | 31.8 | --- | 46.0 | -14.2 |
| 442 | 7.2 | --- | 120 | 20.1 | 27.3 | --- | 46.0 | -18.7 |
| 494 | 18.7 | --- | 120 | 21.4 | 40.1 | --- | 46.0 | -5.9 |
| 546 | 18.5 | --- | 120 | 22.6 | 41.1 | --- | 46.0 | -4.9 |
| 598 | 13.3 | --- | 120 | 23.9 | 37.2 | --- | 46.0 | -8.8 |
| 650 | 8.8 | --- | 120 | 24.7 | 33.5 | --- | 46.0 | -12.5 |
| 702 | 6.2 | --- | 120 | 25.6 | 31.8 | --- | 46.0 | -14.2 |
| 858 | 4.3 | --- | 120 | 28.1 | 32.4 | --- | 46.0 | -13.6 |

Remark: According to Section 15.31 (f) (2): The measurement below 30 MHz has been performed at a distance of 3 m. The results have been extrapolated to the specified distance by using the square of an inverse linear distance extrapolation factor of 40 dB/decade.

FCC ID: U9A277IWLAN-V200

5.3.6 Test result $f > 1$ GHz

| Frequency (MHz) | Level PK (dB μ V) | Duty Cycle Correction (dB) | Level AV (dB μ V) | Correction Factor (dB) | Corrected Level PK (dB μ V/m) | Corrected Level AV (dB μ V/m) | Limit PK (dB μ V/m) | Limit AV (dB μ V/m) | Delta (dB) |
|--------------------|--------------------------|----------------------------------|--------------------------|------------------------------|---|---|----------------------------|----------------------------|---------------|
| 2399.5 | 61.2 | --- | --- | -9.6 | 51.6 | --- | 74 | --- | -22.4 |
| 2483.5 | 68.7 | --- | 46.9 | -9.4 | 59.3 | 37.5 | 74 | 54 | -16.5 |
| 4928 | 56.4 | --- | --- | 1.8 | 58.2 | --- | 74 | --- | -15.8 |
| 7408 | 47.6 | --- | --- | 5.8 | 53.4 | --- | 74 | --- | -20.6 |
| 9648 | 44.3 | --- | --- | 7.6 | 51.9 | --- | 74 | --- | -22.1 |
| 18-25 GHz | --- | --- | --- | --- | --- | --- | --- | --- | --- |

Note: Where correction factor means cable loss, amplifier gain and antenna factor.

Remark: The limits according to Section 15.209 apply as appropriate limits because they are the lesser attenuation.

Limits according to FCC Part 15C, Section 15.209:

| Frequency (MHz) | Field strength (dB μ V/m) | Measurement distance (m) |
|--------------------|----------------------------------|-----------------------------|
| 0.009 - 0.490 | 2400/f(kHz) | 300 |
| 0.490 - 1.705 | 24000/f(kHz) | 30 |
| 1.705 - 30.0 | 30 | 30 |
| 30 - 88 | 40 | 3 |
| 88 - 216 | 43,5 | 3 |
| 216 - 960 | 46 | 3 |
| Above 960 | 54 | 3 |


The requirements are **FULFILLED**.

Remarks: The measurement was performed up to the 10th harmonic (25000 MHz).

For detailed test result please refer to following plots.


FCC ID: U9A277IWLAN-V200

Spurious emissions from 30 to 300 MHz



Date: 29.APR.2009 08:58:40


Spurious emissions from 300 to 1000 MHz



Date: 29.APR.2009 09:19:03


FCC ID: U9A277IWLAN-V200

Spurious emissions from 1 to 4 GHz
(incl. Fundamental carrier)



Date: 27.APR.2009 10:38:51


Spurious emissions from 4 to 12 GHz



Date: 27.APR.2009 10:45:58


FCC ID: U9A277IWLAN-V200

Spurious emissions from 12 to 18 GHz




Date: 27.APR.2009 10:52:38

Spurious emissions from 18 to 25 GHz




FCC ID: U9A277IWLAN-V200

AV and Pk plot at the upper-out of band




Date: 27.APR.2009 10:33:46




FCC ID: U9A277IWLAN-V200

Fundamental reference plot



Date: 27.APR.2009 10:28:12
Marker-Delta Plot at lower out-of band



Date: 27.APR.2009 10:21:49

Calculation of Pk-Value according to the Marker-Delta Method:

1. Pk value of fundamental field strength as reference: 90.3 dBµV/m
2. Amplitude delta between the fundamental and spurious emission: 38.7 dB
3. Calculated attenuation of spurious emission: $90.3 - 38.7 = 51.6$ dBµV/m
4. No need of AV measurement because the Pk value is below the AV limit.

Remark: The Marker-Delta Method is described in Public Notice DA 00-705 (Released March 30, 2000).

FCC ID: U9A277IWLAN-V200

5.4 20 dB Bandwidth

For test instruments and accessories used see section 6 Part **MB**.

5.4.1 Description of the test location

Test location: AREA4 (Climatic chamber)

5.4.2 Photo documentation of the test set-up



FCC ID: U9A277IWLAN-V200

5.4.3 Applicable standard

According to FCC Part 15, Section 15.215(c):

Intentional radiators operating under the provisions to the general emission limits, as contained in Section 15.217 through Section 15.257, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from the frequency stability of the transmitter over expected variation in temperature and supply voltage.

5.4.4 Description of Measurement

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio of -20 dB. The reference level is the level of the highest signal amplitude observed from the transmitter at the fundamental frequency. The measurement has been carried out with normal modulation at normal and extreme test conditions.

Spectrum analyser settings:

RBW = VBW: 100 kHz

Detector: AV

Trace mode: Max hold

Sweep time: 60 s

5.4.5 Test result

Manufacturer declared permitted frequency band:

Lowest frequency: 2400.0 MHz

Highest frequency: 2483.5 MHz

| Test conditions | | Test result | |
|--------------------------|--------------------------|-----------------|----------|
| | | Frequency (MHz) | |
| T_{nom} (20 °C) | V_{nom} (7.2 V) | f_L | 2400.250 |
| | | f_H | 2481.424 |
| T_{max} (0 °C) | V_{min} (5.8 V) | f_L | 2400.350 |
| | | f_H | 2481.280 |
| | V_{max} (8.6 V) | f_L | 2400.355 |
| | | f_H | 2481.280 |
| T_{min} (45 °C) | V_{min} (5.8 V) | f_L | 2400.360 |
| | | f_H | 2481.275 |
| | V_{max} (8.6 V) | f_L | 2400.355 |
| | | f_H | 2481.280 |
| Measurement uncertainty | | +/- 500 kHz | |

Where f_L Lowest frequency at the appropriate side band level

f_H Highest frequency at the appropriate side band level

Band edge limits: f_{Lm} = Lowest f_L (measured) 2400.250 MHz

and


f_{Hm} = Highest f_H (measured) 2481.424 MHz

The requirements are **FULFILLED**.


Remarks: For detailed results please refer to following plots.

FCC ID: U9A277IWLAN-V200

Bandwidth Plots



Date: 29.APR.2009 10:04:11



Date: 29.APR.2009 10:10:08

FCC ID: U9A277IWLAN-V200

5.5 Maximum Permissible Exposure (MPE)

For test instruments and accessories used see section 6 Part **CPC 3**.

5.5.1 Description of the test location

Test location: Anechoic Chamber A2

5.5.2 Applicable standard

According to FCC Part 15 Subpart 15.247 (i): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

The test methods used comply with ANSI/IEEE C95.1-1992, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz".

This test report shows the compliance with the limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and the criteria to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in FCC 1.1307(b).

5.5.3 Description of Measurement

The maximum total power radiated by the antenna has been calculated using the following far field calculation formula:

$$E = \frac{\sqrt{30 * P_{out} * G}}{R}$$

where

E = E-field strength [V/m]

P_{out} = output power to antenna [W]

G = gain of antenna (linear scale)

R = distance between antenna and observation point [m]

The electrical field strength have been measured radiated as described in clause 5.2 of this document. Through the Friis transmission formula, which is a far field assumption, the maximum MPE at a defined distance away from the product, can be calculated.

$$\text{Friis transmission formula: } P_d = \frac{P_{out} * G}{4 * \pi * r^2}$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna (linear scale)

r = distance between antenna and observation point [cm]

FCC ID: U9A277IWLAN-V200

5.5.4 Test result

| Frequency (MHz) | Max Power Output to Antenna (dBm) | Antenna gain (dBi) | Power Density (mW/cm ²) | Limit of Power Density (mW/cm ²) |
|-----------------|-----------------------------------|--------------------|-------------------------------------|--|
| 2449 | -4.9 | 0.324 | 0.00006 | 1.0 |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational / Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | 100 | 6 |
| 3.0 – 30 | 1842/f | 4.89/f | 900/f ² | 6 |
| 30 - 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | --- | --- | f/300 | 6 |
| 1500-100000 | --- | --- | 5.0 | 6 |
| (B) Limits for General Population / Uncontrolled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | 100 | 30 |
| 3.0 – 30 | 824/f | 2.19/f | 180/f ² | 30 |
| 30 - 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | --- | --- | f/1500 | 30 |
| 1500-100000 | --- | --- | 1.0 | 30 |

f = Frequency in MHz

5.5.5 Compliance regarding Co-location and Co-transmission

Applicable standard: ANSI/IEEE C95.1-1999, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", Clause 4.1.1. e):

For mixed or broadband fields at a number of frequencies for which there are different values of the MPE, the fraction of the MPE (in terms of E, H, or power density (S)) occurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity (1.0, or 100 % in terms of percentage).

1. MPE of Effective Range Module: $P_d = 0.00006 \text{ mW/cm}^2$
Limit: 1 mW/cm²
Fraction of MPE: 0.6 %
2. MPE of WLAN-Module (5 GHz): $P_d = \text{mW/cm}^2$
Limit: 1 mW/cm²
Fraction of MPE: %

The requirements are **FULFILLED**.

Remarks: For the test result of WLAN-Module please refer to Test report T33234-03-02AA
(mikes-testingpartners gmbh)

FCC ID: U9A277IWLAN-V200

5.6 Antenna application

5.6.1 Applicable standard

According to FCC Part 15C, Section 15.203(a):

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The EUT's antenna meets the requirement of FCC Part 15C, Section 15.203 and 15.204

5.6.2 Result

The requirements are **FULFILLED**.

Remarks: The EuT is equipped with an internal dual port patch antenna (gain=2.6 / 2.7 dBic).
The EuT don't have any external antenna connectors.

FCC ID: U9A277IWLAN-V200

6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

| Test ID | Model / Type | Kind of Equipment | Manufacturer | Equipment No. |
|---------|---|---|---|--|
| A 4 | ESHS 30 FSP 30 ESH 2 - Z 5 N-4000-BNC N-1500-N ESH 3 - Z 2 PE1540 | EMI Test Receiver Spectrum Analyzer LISN RF Cable RF Cable Pulse Limiter Power Supply | Rohde & Schwarz München Rohde & Schwarz München Rohde & Schwarz München mikes-testingpartners gmbh mikes-testingpartners gmbh Rohde & Schwarz München Phillips Fluke GmbH | 02-02/03-05-002 02-02/11-05-001 02-02/20-05-004 02-02/50-05-138 02-02/50-05-140 02-02/50-05-155 02-02/50-07-031 |
| CPR 3 | FSP 30 AFS4-01000400-10-10P-4 BBHA 9120 E 251 Sucoflex N-2000-SMA PE1540 Multiflex 141-SMA-N-1500 | Spectrum Analyzer RF Amplifier 1-4 GHz Broadband Horn Antenn RF Cable Power Supply Coaxicable | Rohde & Schwarz München PARZICH GMBH Schwarzbeck Mess-Elektron novotronik Signalverarbeit Phillips Fluke GmbH novotronik Signalverarbeit | 02-02/11-05-001 02-02/17-05-003 02-02/24-05-006 02-02/50-05-075 02-02/50-07-031 02-02/50-09-016 |
| MB | FSP 30 WK-340/40 PE1540 | Spectrum Analyzer Climatic Chamber Power Supply | Rohde & Schwarz München Weiss Umwelttechnik GmbH Phillips Fluke GmbH | 02-02/11-05-001 02-02/45-05-001 02-02/50-07-031 |
| SER 1 | FMZB 1516 ESCS 30 PE1540 | Magnetic Field Antenna EMI Test Receiver Power Supply | Schwarzbeck Mess-Elektron Rohde & Schwarz München Phillips Fluke GmbH | 01-02/24-01-018 02-02/03-05-001 02-02/50-07-031 |
| SER 2 | ESVS 30 VULB 9168 S10162-B KK-EF393-21N-16 NW-2000-NB PE1540 | EMI Test Receiver Trilog Broad Band Anten RF Cable 33 m RF Cable 20 m RF Cable Power Supply | Rohde & Schwarz München Schwarzbeck Mess-Elektron Huber + Suhner Huber + Suhner Huber + Suhner Phillips Fluke GmbH | 02-02/03-05-006 02-02/24-05-005 02-02/50-05-031 02-02/50-05-033 02-02/50-05-113 02-02/50-07-031 |
| SER 3 | FSP 30 AFS4-01000400-10-10P-4 AMF-4F-04001200-15-10P AFS5-12001800-18-10P-6 3117 BBHA 9170, Amplifier, Mixe BBHA 9170, Amplifier Sucoflex N-1600-SMA | Spectrum Analyzer RF Amplifier 1-4 GHz RF Amplifier 4-12 GHz RF Amplifier 12-18 GHz Horn Antenna 1-18 GHz Reception System 30-40 Reception System 20-30 RF Cable | Rohde & Schwarz München PARZICH GMBH PARZICH GMBH PARZICH GMBH EMCO Elektronik GmbH mikes-testingpartners gmbh mikes-testingpartners gmbh novotronik Signalverarbeit | 02-02/11-05-001 02-02/17-05-003 02-02/17-05-004 02-02/17-06-002 02-02/24-05-009 02-02/30-09-001 02-02/30-09-002 02-02/50-05-073 |

FCC ID: U9A277IWLAN-V200

| Equipment No. | Next Calibration | Last Calibration | Next Verification | Last Verification |
|-----------------|------------------|------------------|-------------------|-------------------|
| 02-02/03-05-002 | 05/06/2010 | 05/06/2009 | | |
| 02-02/11-05-001 | 04/20/2010 | 04/20/2009 | | |
| 02-02/20-05-004 | 03/13/2011 | 03/13/2008 | 10/29/2009 | 04/29/2009 |
| 02-02/50-05-138 | | | | |
| 02-02/50-05-140 | | | | |
| 02-02/50-05-155 | 10/03/2009 | 04/03/2009 | | |
| 02-02/50-07-031 | | | | |
| 02-02/11-05-001 | 04/20/2010 | 04/20/2009 | | |
| 02-02/17-05-003 | | | | |
| 02-02/24-05-006 | 11/08/2009 | 05/08/2009 | | |
| 02-02/50-05-075 | | | | |
| 02-02/50-07-031 | | | | |
| 02-02/50-09-016 | | | | |
| 02-02/11-05-001 | 04/20/2010 | 04/20/2009 | | |
| 02-02/45-05-001 | 9/01/2010 | 09/01/2005 | 07/12/2009 | 01/12/2009 |
| 02-02/50-07-031 | | | | |
| 01-02/24-01-018 | 02/23/2010 | 02/23/2009 | | |
| 02-02/03-05-001 | 12/10/2009 | 12/10/2008 | | |
| 02-02/50-07-031 | | | | |
| 02-02/03-05-006 | 07/30/2009 | 07/30/2008 | | |
| 02-02/24-05-005 | 05/06/2011 | 05/06/2008 | 09/02/2009 | 03/02/2009 |
| 02-02/50-05-031 | | | | |
| 02-02/50-05-033 | | | | |
| 02-02/50-05-113 | | | | |
| 02-02/50-07-031 | | | | |
| 02-02/11-05-001 | 04/20/2010 | 04/20/2009 | | |
| 02-02/17-05-003 | | | | |
| 02-02/17-05-004 | | | | |
| 02-02/17-06-002 | | | | |
| 02-02/24-05-009 | 02/04/2010 | 02/04/2009 | | |
| 02-02/30-09-001 | 01/26/2010 | 01/26/2009 | | |
| 02-02/30-09-002 | 01/26/2010 | 01/26/2009 | | |
| 02-02/50-05-073 | | | | |