

**TEST REPORT****Report Number: HK12100111-1**

Application  
for  
Original Grant of 47 CFR Part 15 Certification

433MHz Transmitter (Smoke Detector)

**FCC ID: U9K-SD1000**

Prepared and Checked by:

---

Koo Wai Ip  
Senior Lead Engineer

Approved by:

---

Nip Ming Fung, Melvin  
Assistant Manager  
November 28, 2012

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

# INTERTEK TESTING SERVICES

---

---

## GENERAL INFORMATION

<b>Applicant Name:</b>	SimpliSafe, Inc.
<b>Applicant Address:</b>	1035 Cambridge Street, Suite 18A, Cambridge, Massachusetts 02141, U.S.A.
<b>FCC Specification Standard:</b>	FCC Part 15, October 1, 2010 Edition
<b>FCC ID:</b>	U9K-SD1000
<b>FCC Model(s):</b>	SSSD1
<b>Type of EUT:</b>	Security/Remote Control Transmitter
<b>Description of EUT:</b>	433MHz Transmitter (Smoke Detector)
<b>Serial Number:</b>	N/A
<b>Sample Receipt Date:</b>	October 08, 2012
<b>Date of Test:</b>	October 29 - November 15, 2012
<b>Report Date:</b>	November 28, 2012
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Humidity: 10 to 90%

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0 Test Results Summary &amp; Statement of Compliance</b> .....	4
1.1 Summary of Test Results .....	4
1.2 Statement of Compliance .....	4
<b>2.0 General Description</b> .....	6
2.1 Product Description .....	6
2.2 Test Methodology .....	6
2.3 Test Facility .....	6
<b>3.0 System Test Configuration</b> .....	8
3.1 Justification .....	8
3.2 EUT Exercising Software .....	9
3.3 Details of EUT and Description of Accessories .....	10
3.4 Measurement Uncertainty .....	10
<b>4.0 Test Results</b> .....	12
4.1 Field Strength Calculation .....	12
4.2 Radiated Emissions .....	13
4.2.1 Radiated Emission Configuration Photograph .....	13
4.2.2 Radiated Emission Data .....	13
4.2.3 Transmitter Duty Cycle Calculation .....	16
4.3 Transmitter Bandwidth and 5-Second Transmission .....	19
4.3.1 Measured Bandwidth .....	19
4.3.2 5-Second Transmission Requirement .....	20
4.4 AC Power Line Conducted Emission .....	21
<b>5.0 Equipment List</b> .....	23

---

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 1**  
**TEST RESULTS SUMMARY & STATEMENT OF COMPLIANCE**

# INTERTEK TESTING SERVICES

---

## 1.0 Test Results Summary & Statement of Compliance

### 1.1 Summary of Test Results

Test Items	FCC Part 15 Section	Results	Details see section
Antenna Requirement	15.203	Pass	2.1
Radiated Emission	15.231(b)	Pass	4.2
5-Second Transmission Requirement	15.231(a2)	Pass	4.3.2
Bandwidth	15.231(c)	Pass	4.3.1
Radiated Emission in Restricted Bands	15.205	Pass	4.2
AC Power Line Conducted Emission	15.207	N/A	N/A

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

### 1.2 Statement of Compliance

The equipment under test is found to be complying with the following standard:

FCC Part 15, October 1, 2010 Edition

---

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 2**  
**GENERAL DESCRIPTION**

# INTERTEK TESTING SERVICES

---

## 2.0 General Description

### 2.1 Product Description

The SSSD1 is a 433MHz Transmitter (Smoke Detector). It operates at 433.92MHz. The Smoke Detector is powered by a 3VDC CR123A Lithium Battery.

The antenna used in Smoke Sensor is integral, and the test sample is a prototype.

The circuit description is saved with filename: descri.pdf.

### 2.2 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Preliminary radiated scans and all radiated measurements were performed in Open Area Test Sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 2.3 Test Facility

The open area test site facility used to collect the radiated data is at Roof Top of Intertek Testing Services Hong Kong Ltd., which is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**INTERTEK TESTING SERVICES**

---

---

**EXHIBIT 3**  
**SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 3.0 System Test Configuration

#### 3.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The EUT was powered by a new lithium battery.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the EUT attached to peripherals, they were connected and operational to simulate typical use.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For transmitter radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz. The resolution bandwidth was 1 MHz for frequencies above 1000 MHz.

Radiated emission measurement for transmitter was performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

## INTERTEK TESTING SERVICES

---

### 3.1 Justification - Cont'd

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 4.2.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period (Teff) was referred to Exhibit 4.2.3. With the resolution bandwidth 100kHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

All relevant operation modes have been tested, and the worst case data was included in this report.

### 3.2 EUT Exercising Software

There was no special software to exercise the device. Once the button was depressed, the unit transmitted the typical signal. For simplicity of testing, the unit was wired to transmit continuously.

## INTERTEK TESTING SERVICES

---

### 3.3 Details of EUT and Description of Accessories

#### Details of EUT:

A battery (provided with the unit) was used to power the device. Its description is listed below.

- (1) Operated Battery: A 3VDC CR123A Lithium Battery (Supplied by Intertek)

#### Description of Peripherals:

There are no special accessories necessary for compliance of this product.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

---

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 4**  
**TEST RESULTS**

# INTERTEK TESTING SERVICES

---

## 4.0 Test Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

### 4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where       $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

$PD$  = Pulse Desensitization in dB

$AV$  = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflects the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

#### Example

Assume a receiver reading of 62.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

## INTERTEK TESTING SERVICES

---

---

### 4.2 Radiated Emissions

#### 4.2.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
at

433.920 MHz

The worst case radiated emission configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

#### 4.2.2 Radiated Emission Data

The data in tables 1-2 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Passed by 0.2 dB margin compare with average limit

## INTERTEK TESTING SERVICES

---

Mode: TX

Table 1

### Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp (dB)	Antenna factor (dB)	Average Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	433.920	77.4	16	25.0	5.8	80.6	80.8	-0.2
H	867.840	29.5	16	31.0	5.8	38.7	60.8	-22.1
<b>H</b>	<b>1301.760</b>	<b>49.3</b>	<b>33</b>	<b>26.1</b>	<b>5.8</b>	<b>36.6</b>	<b>54.0</b>	<b>-17.4</b>
H	1735.680	47.9	33	27.2	5.8	36.3	60.8	-24.5
H	2169.600	44.4	33	29.4	5.8	35.0	60.8	-25.8
H	2603.520	43.2	33	30.4	5.8	34.8	60.8	-26.0
H	3037.440	41.5	33	31.9	5.8	34.6	60.8	-26.2
H	3471.360	41.3	33	31.9	5.8	34.4	60.8	-26.4

NOTES: 1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

# INTERTEK TESTING SERVICES

---

Mode: TX

Table 2

## Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp (dB)	Antenna factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	433.920	77.4	16	25.0	86.4	100.8	-14.4
H	867.840	29.5	16	31.0	44.5	80.8	-36.3
<b>H</b>	<b>1301.760</b>	<b>49.3</b>	<b>33</b>	<b>26.1</b>	<b>42.4</b>	<b>74.0</b>	<b>-31.6</b>
H	1735.680	47.9	33	27.2	42.1	80.8	-38.7
H	2169.600	44.4	33	29.4	40.8	80.8	-40.0
H	2603.520	43.2	33	30.4	40.6	80.8	-40.2
H	3037.440	41.5	33	31.9	40.4	80.8	-40.4
H	3471.360	41.3	33	31.9	40.2	80.8	-40.6

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

## INTERTEK TESTING SERVICES

---

---

### 4.2.3 Transmitter Duty Cycle Calculation

Duty Cycle (DC)

= Maximum On time in 100ms [Last 100ms of Data Packet] / 100ms

= 51ms / 100ms


$$\begin{aligned}\text{Average Factor (AF)} &= 20 \log(\text{DC}) \\ &= 20 * \log (0.51) \\ &= -5.8 \text{dB}\end{aligned}$$

The plots of the timing are saved as below.


# INTERTEK TESTING SERVICES

## Plots of the timing

### SYNC




### Preamble




## INTERTEK TESTING SERVICES

## Plots of the timing

## Data “1”



## Data “0”



# INTERTEK TESTING SERVICES


## 4.3 Transmitter Bandwidth and 5-Second Transmission

### 4.3.1 Measured Bandwidth

The plot shows the fundamental emission when modulated is saved as below. From the plot, the bandwidth is observed to be 154kHz, at 20dBc where the bandwidth limit is 1084kHz.

Therefore, the EUT meets the requirement of FCC Part 15 Section 15.231(c).

### Plot of bandwidth




## INTERTEK TESTING SERVICES

---

### 4.3.2 5-Second Transmission Requirement

- [ ] Pursuant to FCC Part 15 Section 15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released. The EUT meets the requirement. The plot of the 5-second transmission requirement is saved as below.
- [x] Pursuant to FCC Part 15 Section 15.231(a)(2), a transmitter activated automatically shall cease transmitter within 5 seconds after activation. The EUT meets the requirement. The plot of the 5-second transmission requirement is saved as below.

### Plot of 5-second



## INTERTEK TESTING SERVICES

---

---

### 4.4 AC Power Line Conducted Emission

- Not applicable – EUT is only powered by battery for operation.
- EUT connects to AC power line. Emission Data is listed in following pages.
- Base Unit connects to AC power line and has transmission. Handset connects to AC power line but has no transmission. Emission Data of Base Unit is listed in following pages.

---

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 5**  
**EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

---

### 5.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Log Periodic Antenna	Double Ridged Guide Antenna
Registration No.	EW-2500	EW-0446	EW-1015
Manufacturer	ROHDE SCHWARZ	EMCO	EMCO
Model No.	ESCI	3146	3115
Calibration Date	Feb. 24, 2012	Oct. 31, 2011	Aug. 24, 2011
Calibration Due Date	Feb. 24, 2013	Apr. 30, 2013	Feb. 24, 2013

Equipment	Biconical Antenna 20MHz to 200MHz	Spectrum Analyzer	Spectrum Analyzer
Registration No.	EW-2512	EW-2253	EW-2466
Manufacturer	EMCO	R&S	ROHDE SCHWARZ
Model No.	3104C	FSP40	FSP30
Calibration Date	Nov. 15, 2011	Jan. 12, 2012	Jul. 06, 2012
Calibration Due Date	May. 15, 2013	Jan. 12, 2013	Jul. 06, 2013

**END OF TEST REPORT**