

Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 1 of 39

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 22 SUBPART H and PART 24 SUBPART E REQUIREMENT

OF

Product Name: Notebook

Brand Name: CLEVO

Model Name: M72R

FCC ID: **U9M-M72R**

GSM Module ID: N7NMC8775

Report No.: ER/2007/50022

Issue Date: Jun. 20, 2007

FCC Rule Part: 2 & 24E& 22H

Prepared for CLEVO CO.

No. 129, Hsing-Te Road, Sun Chung City 241,

Taipei Hsien, Taiwan, R.O.C.

Prepared by SGS Taiwan Ltd.

No. 134, Wu Kung Rd., Wuku Industrial Zone,

Taipei County, Taiwan.

Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、偽造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 2

VERIFICATION OF COMPLIANCE

CLEVO CO. **Applicant:**

No. 129, Hsing-Te Road, Sun Chung City 241, Taipei Hsien, Taiwan,

R.O.C.

Product Name: Notebook

FCC ID Number: U9M-M72R

Brand Name: CLEVO

Model No.: M72R

Model Difference: N/A

File Number: ER/2007/50022

Date of test: May 16, 2007 ~ Jun. 20, 2007

May 16, 2007 **Date of EUT Received:**

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in TIA/EIA-603-1-1998 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rule FCC PART 22 subpart H and FCC PART 24 subpart E.

The test results of this report relate only to the tested sample identified in this report.

Test By:	Sky Wang	Date	Jun. 20, 2007	
	Sky Wang / Sr. Engineer			
Prepared By:	Ena Row	Date	Jun. 20, 2007	
	Eva Kao / Sr. Engineer			
Approved By	Timent du	Date	Jun. 20, 2007	
_	Vincent Su / Manager			

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告 未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 3

Version

Version No.	Date
00	May 24, 2007
01	Jun. 20, 2007



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 4

Table of Contents

1.	GEN	ERAL INFORMATION	6
	1.1	Product Description	<i>6</i>
	1.2	Related Submittal(s) / Grant (s)	<i>6</i>
	1.3	Test Methodology	<i>6</i>
	1.4	Test Facility	7
	1.5	Special Accessories	7
	1.6	Equipment Modifications	7
2.	SYS	TEM TEST CONFIGURATION	8
	2.1	EUT Configuration	8
	2.2	EUT Exercise	8
	2.3	Test Procedure	8
	2.4	Configuration of Tested System	9
3.	SUM	IMARY OF TEST RESULTS	10
4.	DES	CRIPTION OF TEST MODES	10
5.	RF P	POWER OUTPUT MEASUREMENT	11
	5.1	Standard Applicable	11
	5.2	Test Set-up:	11
	5.3	Measurement Procedure	11
	5.4	Measurement Equipment Used:	12
	5.5	Measurement Result	12
6.	ERP	, EIRP MEASUREMENT	13
	6.1	Standard Applicable	13
	6.2	Test SET-UP (Block Diagram of Configuration)	13
	6.3	Measurement Procedure	15
	6.4	Measurement Equipment Used:	16
	6.5	Measurement Result	17
7.	FIEI	LD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	18
	7.1	Standard Applicable	18
	7.2	EUT Setup (Block Diagram of Configuration)	18
	7.3	Measurement Procedure	20
	7.4	Measurement Equipment Used:	21
	7.5	Measurement Result	21

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 5

8.	AC F	POWER LINE CONDUCTED EMISSION TEST	34
		Standard Applicable	
		EUT Setup	
	8.3	Measurement Procedure	34
	8.4	Measurement Equipment Used:	35
		Measurement Result	



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 6

GENERAL INFORMATION

1 1 Product Description

1.1 Product Descri	711011			
Product Name	Notebook			
Model Name	M72R			
Model Difference	N/A			
Trade Name	CLEVO			
	14.8 Vdc re-charge	eable battery or 19Vdc by AC/DC power adapter		
Power Supply	Battery Model:	M720SBAT-4, Supplier: LI SHIN		
	Adapter Model:	0335A1965, Supplier: LI SHIN		

GSM:

Frequency Range and	GSM 850: 824 MHz – 849 MHz	33 dBm	
Power	GSM 1900: 1850 MHz –1910 MHz	30 dBm	
Type of Emission	Emission 300KGXW		
Software Version	Rev 1.0		
Hardware Version	H1_0_0_1		

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: U9M-M72R filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4 (2003) and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057.



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 7

Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 and CISPR 22/EN 55022 requirements. Site No. 1(3 &10 meters) Registration Number: 94644, Both OATS and Anechoic chamber (3 meters) was accredited by TAF (0513). Canada Registration Number: 4620A-1

1.5 **Special Accessories**

Not available for this EUT intended for grant.

1.6 Equipment Modifications

Not available for this EUT intended for grant.

f (886-2) 2298-2698

www.sgs.com.tw



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 8

SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 **EUT Exercise**

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency which was for the purpose of the measurements.

2.3 **Test Procedure**

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7&13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 1.0 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8&13 of ANSI C63.4-2003.




Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 9

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Remote Side

CMU200

Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1.	Universal Radio Communication Tester	R&S	CMU200	102189	shielded	Un-shielded

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告 未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 10

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§2.1046(a)		
§22.913(a)	RF Power Output	Compliant
§24.232(a)		
§2.1046(a)		
§22.913(a)	ERP/ EIRP measurement	Compliant
§24.232(a)		
§2.1049(h)	99% Occupied Bandwidth	N/A
§2.1051	Out of Band Emissions at Antenna	
§22.917(a)	Terminals and	N/A
§24.238(a)	Band Edge	
§2.1053		
§22.917(a)	Field Strength of Spurious Radiation	Compliant
§24.238(a)		
§2.1055(a)(1)(b)	Frequency Stability vs. Temperature	N/A
§2.1055(d)(1)(2)	Frequency Stability vs. Voltage	N/A
§15.107;§15.207	AC Power Line Conducted Emission	Compliant

4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

EUT staying in continuous transmitting mode. Channel low, Mid and High for each type and band with rated data rate are chosen for testing.

The GSM module was approved and the FCC ID number is N7NMC8775. Thus, the output power, ERP/EIRP, Field Strength of Spurious Radiation and AC Power Line Conducted Emission were tested.



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 11

RF POWER OUTPUT MEASUREMENT


5.1 Standard Applicable

According to FCC §2.1046.

FCC 22.913(a) Mobile station are limited to 7W.

FCC 24.232(b) Mobile station are limited to 2W.

5.2 Test Set-up:



Note: Measurement setup for testing on Antenna connector

Measurement Procedure

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a power meter. Transmitter output was read off the power meter in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to the power meter reading.



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 12

5.4 Measurement Equipment Used:

Conducted Emission Test Site								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
TYPE		NUMBER	NUMBER	CAL.				
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2007	03/28/2008			
Spectrum Analyzer	Agilent	E7405A	US41160416	06/28/2006	06/29/2007			
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2006	11/10/2007			
Communication Test	R&S	SMU200	N/A	N/A	N/A			
Power Sensor	Anritsu	MA2490A	31431	06/28/2006	06/29/2007			
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2006	06/29/2007			
Temperature Chamber	TERCHY	MHG-120LF	911009	10/14/2006	10/13/2007			
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	N/A	N/A			
Attenuator	Mini-Circult	BW-S10W5	N/A	09/23/2006	09/22/2007			
Attenuator	Mini-Circult	BW-S6W5	N/A	09/23/2006	09/22/2007			
Splitter	Agilent	11636B	51728	09/23/2006	09/22/2007			
DC Power Supply	TOPWARD	3303A	N/A	N/A	N/A			

5.5 Measurement Result

EUT Mode	Frequency (MHz)	СН	Power meter Reading (dBm)	Path Loss (dB)	Peak Power (dBm)
	824.20	128	13.62	17.80	31.42
GSM 850	836.60	190	13.97	17.80	31.77
	848.80	251	14.10	17.80	31.90

EUT Mode	Frequency (MHz)	СН	Power Meter Reading (dBm)	Path Loss (dB)	Peak Power (dBm)
PCS 1900	1850.20	512	11.02	17.80	28.82
	1880.00	661	11.13	17.80	28.93
	1909.80	810	11.21	17.80	29.01

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 破放、請注意此條款列印於背面,亦可在<u>www.sgs.com</u>中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。

SGS Taiwan Ltd.
台灣檢驗科技股份有限公司

t (886-2) 2299-3939

f (886-2) 2298-2698

www.sgs.com.tw



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 13

ERP, EIRP MEASUREMENT

Standard Applicable


According to FCC §2.1046

FCC 22.913(a) Mobile station are limited to 7W ERP.

FCC 24.232(b) Mobile station are limited to 2W EIRP.

6.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



f (886-2) 2298-2698

www.sgs.com.tw


t (886-2) 2299-3939




Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 14

(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



(C) Substituted Method Test Set-UP





Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 15

6.3 Measurement Procedure

The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows:

EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows:

ERP = S.G. output (dBm) + Antenna Gain (dBd) - Cable Loss (dB)

EIRP = S.G. output (dBm) + Antenna Gain (dBi) – Cable Loss (dB)

f (886-2) 2298-2698

www.sgs.com.tw



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 16

6.4 Measurement Equipment Used:

EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.
TYPE		NUMBER	NUMBER	CAL.	
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2007	03/28/2008
Spectrum Analyzer	Agilent	7405A	US41160416	06/28/2006	06/29/2007
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2006	11/10/2007
Communication Test	R&S	SMU200	N/A	N/A	N/A
Bilog Antenna	SCHWAZBECK	VULB9163	152	06/03/2006	06/02/2007
Horn antenna	Schwarzbeck	BBHA 9120D	309/320	08/16/2006	08/15/2007
Pre-Amplifier	HP	8447D	2944A09469	07/19/2006	07/18/2007
Pre-Amplifier	HP	8494B	3008A00578	02/26/2007	02/25/2008
Signal Generator	R&S	SMR40	100210	02/09/2007	02/10/2008
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	10/09/2006	10/08/2007
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	10/09/2006	10/08/2007
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-0.5M	0.5m	10/09/2006	10/08/2007
Site NSA	SGS	966 chamber	N/A	11/17/2006	11/16/2007
Attenuator	Mini-Circult	BW-S10W5	N/A	09/23/2006	09/22/2007
Dipole Antenna	Schwarzbeck	VHAP	908/909	06/10/2006	06/11/2007
Dipole Antenna	Schwarzbeck	UHAP	891/892	06/10/2006	06/11/2007
Horn antenna	Schwarzbeck	BBHA 9120D	N/A	08/16/2006	08/15/2007



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 17

6.5 Measurement Result

EUT Mode	Frequency (MHz)	СН	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)		
	824.20	128	V	114.60	28.21	-7.87	3.62	16.71	38.45		
	624.20	120	126	120	Н	126.49	40.22	-7.87	3.62	28.72	38.45
GSM 850	836.60	190	V	114.63	28.38	-7.88	3.65	16.85	38.45		
USM 650	050.00	630.00	190	190	Н	126.64	40.41	-7.88	3.65	28.88	38.45
	848.80	848.80 251	V	114.88	28.76	-7.88	3.68	17.20	38.45		
	040.00	231	Н	124.42	38.23	-7.88	3.68	26.67	38.45		

EUT Mode	Frequency (MHz)	СН	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)						
	1850.20	512	V	123.65	19.26	9.90	5.56	23.60	33.00						
	1030.20	312	312	312	Н	126.41	22.23	9.90	5.56	26.57	33.00				
PCS 1900	1880.00	661	V	124.77	20.41	9.99	5.61	24.79	33.00						
FCS 1900	1000.00		001	001	001	001	001	001	001	Н	126.48	22.34	9.99	5.61	26.71
	1000.90	9.80 810	1909.80 810	V	125.08	20.75	10.08	5.66	25.17	33.00					
	1909.00			Н	125.65	21.54	10.08	5.66	25.96	33.00					

Remark:	
(1)	The RBW,VBW of SPA for frequency
	Below 1GHz was RBW=100 KHz, VBW=300KHz,
	Above 1GHz was RBW= 1MHz , VBW= 3MHz



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 18

FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT


7.1 Standard Applicable

According to FCC §2.1053,

FCC §22.917(a),§24.238(a), the magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specified in the instruction manual and/ or alignment procedure, shall not be less than 43 + 10 log (mean output power in watts) dBc below the mean power output outside a license's frequency block (-13dBm)

7.2 EUT Setup (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz







Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 19

(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



(C) Substituted Method Test Set-UP





Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 20

Measurement Procedure 7.3

The EUT was placed on a non-conductive, The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

ERP = S.G. output (dBm) + Antenna Gain(dBd) - Cable Loss (dB)

EIRP = S.G. output (dBm) + Antenna Gain(dBi) - Cable Loss <math>(dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 21

7.4 Measurement Equipment Used:

EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.
TYPE		NUMBER	NUMBER	CAL.	
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2007	03/28/2008
Spectrum Analyzer	Agilent	7405A	US41160416	06/28/2006	06/29/2007
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2006	11/10/2007
Communication Test	R&S	SMU200	N/A	N/A	N/A
Bilog Antenna	SCHWAZBECK	VULB9163	152	06/03/2006	06/02/2007
Horn antenna	Schwarzbeck	BBHA 9120D	309/320	08/16/2006	08/15/2007
Pre-Amplifier	HP	8447D	2944A09469	07/19/2006	07/18/2007
Pre-Amplifier	HP	8494B	3008A00578	02/26/2007	02/25/2008
Signal Generator	R&S	SMR40	100210	02/09/2007	02/10/2008
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	10/09/2006	10/08/2007
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	10/09/2006	10/08/2007
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-0.5M	0.5m	10/09/2006	10/08/2007
Site NSA	SGS	966 chamber	N/A	11/17/2006	11/16/2007
Attenuator	Mini-Circult	BW-S10W5	N/A	09/23/2006	09/22/2007
Dipole Antenna	Schwarzbeck	VHAP	908/909	06/10/2006	06/11/2007
Dipole Antenna	Schwarzbeck	UHAP	891/892	06/10/2006	06/11/2007
Horn antenna	Schwarzbeck	BBHA 9120D	N/A	08/16/2006	08/15/2007

7.5 **Measurement Result**

Refer to attach tabular data sheets.



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 22

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Operation Mode : TX CH Low Test Date: Jun. 20, 2007

Fundamental Frequency : 824.20 MHz Test By: Sky Temperature Pol: Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
823.98	80.40	V	-5.99	-7.87	3.62	-17.49	-13.00	-4.49
1648.40	43.60	V	-60.98	9.29	5.23	-56.92	-13.00	-43.92
2472.60	54.80	V	-46.21	10.08	6.53	-42.66	-13.00	-29.66
3296.80		V		12.17	7.71		-13.00	
4121.00	47.60	V	-48.52	12.61	8.86	-44.77	-13.00	-31.77
4945.20		V		12.65	9.74		-13.00	
5769.40		V		13.55	10.54		-13.00	
6593.60		V		12.05	11.30		-13.00	
7417.80		V		11.49	12.10		-13.00	
8242.00		V		11.48	12.71		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 23

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Operation Mode : TX CH Low Test Date: Jun. 20, 2007

Fundamental Frequency : 824.20 MHz Test By: Sky

Temperature Pol: Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
824.00	75.70	Н	-10.57	-7.87	3.62	-22.07	-13.00	-9.07
1648.40	52.40	Н	-52.00	9.29	5.23	-47.94	-13.00	-34.94
2472.60	58.40	Н	-42.51	10.08	6.53	-38.96	-13.00	-25.96
3296.80		Н		12.17	7.71		-13.00	
4121.00	43.70	Н	-52.55	12.61	8.86	-48.80	-13.00	-35.80
4945.20		Н		12.65	9.74		-13.00	
5769.40		Н		13.55	10.54		-13.00	
6593.60		Н		12.05	11.30		-13.00	
7417.80		Н		11.49	12.10		-13.00	
8242.00		Н		11.48	12.71		-13.00	

_	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 24

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Jun. 20, 2007 Operation Mode : TX CH Mid Test Date:

Fundamental Frequency: 836.60 MHz Test By: Sky Temperature Pol: Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1673.20	43.70	V	-60.86	9.36	5.27	-56.76	-13.00	-43.76
2509.80	63.50	V	-37.28	10.09	6.58	-33.78	-13.00	-20.78
3346.40	49.20	V	-49.66	12.28	7.79	-45.18	-13.00	-32.18
4183.00		V		12.62	8.93		-13.00	
5019.60		V		12.67	9.81		-13.00	
5856.20		V		13.68	10.62		-13.00	
6692.80		V		11.95	11.39		-13.00	
7529.40		V		11.45	12.20		-13.00	
8366.00		V		11.59	12.81		-13.00	

_	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- $4 \text{ ERP/EIRP } (dBm) = SG \text{ Setting}(dBm) + Antenna Gain } (dB/dBi) Cable loss } (dB)$



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 25

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Jun. 20, 2007 Operation Mode : TX CH Mid Test Date:

Fundamental Frequency: 836.60 MHz Test By: Sky

Temperature Pol: Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1673.20	47.20	Н	-57.18	9.36	5.27	-53.08	-13.00	-40.08
2509.80	58.50	Н	-42.20	10.09	6.58	-38.70	-13.00	-25.70
3346.40		Н		12.28	7.79		-13.00	
4183.00		Н		12.62	8.93		-13.00	
5019.60		Н		12.67	9.81		-13.00	
5856.20		Н		13.68	10.62		-13.00	
6692.80		Н		11.95	11.39		-13.00	
7529.40		Н		11.45	12.20		-13.00	
8366.00		Н		11.59	12.81		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 26

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Operation Mode Jun. 20, 2007 : TX CH High Test Date:

Fundamental Frequency: 848.80 MHz Test By: Sky Temperature Pol: Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
849.02	83.10	V	-3.02	-7.88	3.68	-14.58	-13.00	-1.58
1697.60	48.40	V	-56.14	9.44	5.31	-52.01	-13.00	-39.01
2546.40	67.90	V	-32.74	10.20	6.63	-29.18	-13.00	-16.18
3395.20		V		12.38	7.87		-13.00	
4244.00	45.20	V	-50.46	12.63	9.00	-46.83	-13.00	-33.83
5092.80		V		12.74	9.88		-13.00	
5941.60		V		13.81	10.70		-13.00	
6790.40		V		11.86	11.48		-13.00	
7639.20		V		11.40	12.27		-13.00	
8488.00		V		11.70	12.91		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 27

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Operation Mode Jun. 20, 2007 : TX CH High Test Date:

Fundamental Frequency: 848.80 MHz Test By: Sky

Temperature Pol: Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
849.02	77.20	Н	-8.99	-7.88	3.68	-20.55	-13.00	-7.55
1697.60	43.60	Н	-60.75	9.44	5.31	-56.62	-13.00	-43.62
2546.40	63.10	Н	-37.50	10.20	6.63	-33.94	-13.00	-20.94
3395.20		Н		12.38	7.87		-13.00	
4244.00		Н		12.63	9.00		-13.00	
5092.80		Н		12.74	9.88		-13.00	
5941.60		Н		13.81	10.70		-13.00	
6790.40		Н		11.86	11.48		-13.00	
7639.20		Н		11.40	12.27		-13.00	
8488.00		Н		11.70	12.91		-13.00	

	30MHz - 80MHz: 5.04dB				
Measurement uncertainty	80MHz -1000MHz: 3.76dB				
	1GHz - 13GHz: 4.45dB				

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 28

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

Operation Mode : TX CH Low **Test Date** Jun. 20, 2007

Fundamental Frequency: 1850.20MHz Test By: Sky Temperature Pol: Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1850.00	76.80	V	-27.59	9.90	5.56	-23.25	-13.00	-10.25
3700.40	55.70	V	-42.23	12.61	8.31	-37.93	-13.00	-24.93
5550.60	46.90	V	-43.94	13.23	10.33	-41.04	-13.00	-28.04
7400.80		V		11.50	12.08		-13.00	
9251.00		V		11.92	13.50		-13.00	
11101.20		V		11.66	15.11		-13.00	
12951.40		V		13.63	16.60		-13.00	
14801.60		V		12.76	17.95		-13.00	
16651.80		V		15.92	19.14		-13.00	
18502.00		V		18.75	10.40		-13.00	

	30MHz - 80MHz: 5.04dB				
Measurement uncertainty	80MHz -1000MHz: 3.76dB				
	1GHz - 13GHz: 4.45dB				

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 29

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

Operation Mode : TX CH Low **Test Date** Jun. 20, 2007

Fundamental Frequency: 1850.20MHz Test By: Sky

Temperature Pol: Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1850.00	81.30	Н	-22.88	9.90	5.56	-18.54	-13.00	-5.54
3700.40	46.80	Н	-51.24	12.61	8.31	-46.94	-13.00	-33.94
5550.60	46.20	Н	-44.85	13.23	10.33	-41.95	-13.00	-28.95
7400.80		Н		11.50	12.08		-13.00	
9251.00		Н		11.92	13.50		-13.00	
11101.20		Н		11.66	15.11		-13.00	
12951.40		Н		13.63	16.60		-13.00	
14801.60		Н		12.76	17.95		-13.00	
16651.80		Н		15.92	19.14		-13.00	
18502.00		Н		18.75	10.40		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 30

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

: TX CH Mid Test Date Jun. 20, 2007 Operation Mode

Fundamental Frequency: 1880MHz Test By Sky Temperature Pol Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
3760.00	56.70	V	-40.96	12.60	8.39	-36.74	-13.00	-23.74
5640.00	46.20	V	-44.38	13.36	10.41	-41.43	-13.00	-28.43
7520.00		V		11.45	12.19		-13.00	
9400.00		V		11.93	13.61		-13.00	
11280.00		V		11.92	15.27		-13.00	
13160.00		V		13.33	16.71		-13.00	
15040.00		V		13.76	18.15		-13.00	
16920.00		V		15.27	19.32		-13.00	
18800.00		V		18.68	16.58		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

Remark:

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)

f (886-2) 2298-2698

www.sgs.com.tw



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 31

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

Operation Mode : TX CH Mid Test Date Jun. 20, 2007

Fundamental Frequency: 1880MHz Sky Test By

Temperature Pol Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
3760.00	53.10	Н	-44.67	12.60	8.39	-40.46	-13.00	-27.46
5640.00	44.30	Н	-46.45	13.36	10.41	-43.50	-13.00	-30.50
7520.00		Н		11.45	12.19		-13.00	
9400.00		Н		11.93	13.61		-13.00	
11280.00		Н		11.92	15.27		-13.00	
13160.00		Н		13.33	16.71		-13.00	
15040.00		Н		13.76	18.15		-13.00	
16920.00		Н		15.27	19.32		-13.00	
18800.00		Н		18.68	16.58		-13.00	

	30MHz - 80MHz: 5.04dB			
Measurement uncertainty	80MHz -1000MHz: 3.76dB			
	1GHz - 13GHz: 4.45dB			

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 32

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

Operation Mode : TX CH High Test Date Jun. 20, 2007

Fundamental Frequency: 1909.8 MHz Test By Sky Temperature Pol Vertical : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1910.00	77.30	V	-27.03	10.08	5.66	-22.61	-13.00	-9.61
3981.60	50.10	V	-46.56	12.60	8.69	-42.66	-13.00	-29.66
5972.40		V		13.86	10.73		-13.00	
7963.20		V		11.27	12.49		-13.00	
9954.00		V		12.08	14.24		-13.00	
11944.80		V		13.08	15.87		-13.00	
13935.60		V		11.82	17.21		-13.00	
15926.40		V		17.08	18.70		-13.00	
17917.20		V		9.63	19.97		-13.00	
19908.00		V		18.88	21.24		-13.00	-

_	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 33

Radiated Spurious Emission Measurement Result: PCS 1900 Mode

Operation Mode : TX CH High Test Date Jun. 20, 2007

Fundamental Frequency: 1909.8 MHz Test By Sky

Temperature Pol Horizontal : 25°C

Humidity : 65%

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
1910.00	81.20	Н	-22.91	10.08	5.66	-18.49	-13.00	-5.49
3981.60		Н		12.60	8.69		-13.00	
5972.40		Н		13.86	10.73		-13.00	
7963.20		Н		11.27	12.49		-13.00	
9954.00		Н		12.08	14.24		-13.00	
11944.80		Н		13.08	15.87		-13.00	
13935.60		Н		11.82	17.21		-13.00	
15926.40		Н		17.08	18.70		-13.00	
17917.20		Н		9.63	19.97		-13.00	
17188.20		Н		14.47	19.52		-13.00	

	30MHz - 80MHz: 5.04dB
Measurement uncertainty	80MHz -1000MHz: 3.76dB
	1GHz - 13GHz: 4.45dB

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 ERP/EIRP (dBm) = SG Setting(dBm) + Antenna Gain (dB/dBi) Cable loss (dB)



Report No.: ER/2007/50022 **Issue Date: Jun. 20, 2007**

Page: 34

AC POWER LINE CONDUCTED EMISSION TEST

8.1 Standard Applicable

According to §15.207. The emission value for frequency within 150KHz to 30MHz shall not exceed criteria of below chart.

Frequency range		mits (uV)
MHz	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note

8.2 EUT Setup

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2001.
- 2. The EUT was plug-in DC power adaptort and was placed on the center of the back edge on the test table. The peripherals like earphone was placed on the side of the EUT. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
- 3. The Power adaptor was connected with 110Vac/60Hz power source.

8.3 **Measurement Procedure**

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

^{1.} The lower limit shall apply at the transition frequencies

^{2.} The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Page: 35

8.4 Measurement Equipment Used:

	Conducted Emission Test Site											
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.							
ТҮРЕ		NUMBER	NUMBER	CAL.								
EMC Analyzer	HP	8594EM	3624A00203	09/02/2006	09/03/2007							
EMI Test Receiver	R&S	ESCS30	828985/004	06/09/2006	06/10/2007							
Transient Limiter	HP	11947A	3107A02062	09/02/2006	09/03/2007							
LISN	Rolf-Heine	NNB-2/16Z	99012	12/31/2006	12/30/2007							
LISN	Rolf-Heine	NNB-2/16Z	99013	12/24/2006	12/23/2007							
Coaxial Cables	N/A	No. 3, 4	N/A	12/24/2006	12/23/2007							

8.5 Measurement Result

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Temperature:

Air Pressure:


hpa

Humidity:

Page: 36

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	GSM 850 LINK		Test Date:	Apr. 24, 2007	
Temperature:	25 ℃	Humidity:	65 %	Test By:	Sky



Power:

Distance:

AC 120V/60Hz

Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP)

EUT: NOTEBOOK

M/N: M72S

Note: GSM 850 LINK

No.	Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over			
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1	*	0.1540	47.59	0.46	48.05	65.78	-17.73	QP		
2		0.1750	45.16	0.48	45.64	64.72	-19.08	QP		
3		0.2050	44.73	0.52	45.25	63.41	-18.16	QP		
4		0.2700	39.17	0.56	39.73	61.12	-21.39	QP		
5		0.3400	38.07	0.59	38.66	59.20	-20.54	QP		
6		3.7400	36.60	0.96	37.56	56.00	-18.44	QP		

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告 未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007


Temperature:

Air Pressure:

62.%

Humidity:

Page: 37



Phase:

Power:

Distance:

Ν

AC 120V/60Hz

Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP)

EUT: NOTEBOOK

M/N: M72S

Note: GSM 850 LINK

No.	Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over			
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1		0.1550	48.00	0.46	48.46	65.73	-17.27	QP		
2	×	0.2050	45.62	0.52	46.14	63.41	-17.27	QP		
3		0.3400	38.62	0.59	39.21	59.20	-19.99	QP		
4		0.4800	36.52	0.65	37.17	56.34	-19.17	QP		
5		0.6200	37.30	0.69	37.99	56.00	-18.01	QP		
6		3.7400	34.74	0.96	35.70	56.00	-20.30	QP		



Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Humidity:


Air Pressure:

62 %

Page: 38

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	GSM 1900 LINK		Test Date:	Apr. 24, 2007	
Temperature:	25 ℃	Humidity:	65 %	Test By:	Sky



Power:

Distance:

AC 120V/80Hz

Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP)

EUT: NOTEBOOK

M/N: M72S

Note: GSM 1900 LINK

No. Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over			
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1	0.1516	46.67	0.45	47.12	65.91	-18.79	QP		
2 *	0.2050	45.19	0.52	45.71	63.41	-17.70	QP		
3	0.2750	38.75	0.56	39.31	60.97	-21.66	QP		
4	0.3400	38.48	0.59	39.07	59.20	-20.13	QP		
5	0.4100	38.13	0.62	38.75	57.65	-18.90	QP		
6	3.9000	36.32	0.97	37.29	56.00	-18.71	QP		

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作 發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告 未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴




Report No.: ER/2007/50022 Issue Date: Jun. 20, 2007

Humidity:

Air Pressure:

62.%

Page: 39



Power:

Distance:

AC 120V/60Hz

Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP)

EUT: NOTEBOOK

M/N: M72S

Note: GSM 1900 LINK

No. Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over			
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1 *	0.1516	48.81	0.45	49.26	65.91	-16.65	QP		
2	0.2050	45.40	0.52	45.92	63.41	-17.49	QP		
3	0.2750	39.02	0.56	39.58	60.97	-21.39	QP		
4	0.4100	39.09	0.62	39.71	57.65	-17.94	QP		
5	0.4800	35.85	0.65	36.50	56.34	-19.84	QP		
6	3.9000	35.79	0.97	36.76	56.00	-19.24	QP		