# Summit Semiconductor LLC

## Summit FS848 Master Module (Wheeler)

Report No. FOCU0081.2

Report Prepared By



www.nwemc.com 1-888-EMI-CERT

© 2010 Northwest EMC, Inc



22975 NW Evergreen Parkway Suite 400 Hillsboro, Oregon 97124

#### **Certificate of Test**

Last Date of Test: July 27, 2010 Summit Semiconductor LLC

Model: Summit FS848 Master Module (Wheeler)

Emissions					
Test Description	Specification	Test Method	Pass/Fail		
Maximum Permissible Exposure	FCC 2.1091:2010	OET Bulletin 65, Supplement C Ed 01-01	Pass		

Modifications made to the product
See the Modifications section of this report

#### **Test Facility**

The measurement facility used to collect the data is located at:

Northwest EMC, Inc. 22975 NW Evergreen Parkway, Suite 400 Hillsboro, OR 97124

Phone: (503) 844-4066 Fax: 844-3826

This site has been fully described in a report filed with and accepted by the FCC (Federal Communications Commission) and Industry Canada (Site filing #2834D-1).

Approved By:

Dean Ghizzone, President

RAJVK

NVLAP Lab Code: 200630-0

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America.

Product compliance is the responsibility of the client, therefore the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. This Report may only be duplicated in its entirety. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test.

#### **Revision History**

Revision 05/05/03

Revision Description		Date	Page Number
00	None		



## Accreditations and Authorizations

#### **FCC**

Accredited by NVLAP for performance of FCC radio, digital, and ISM device testing. Our Open Area Test Sites, certification chambers, and conducted measurement facilities have been fully described in reports filed with the FCC and accepted by the FCC in letters maintained in our files. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by the FCC as a Telecommunications Certification Body (TCB). This allows Northwest EMC to certify transmitters to FCC specifications in accordance with 47 CFR 2.960 and 2.962.



#### **NVLAP**

Northwest EMC, Inc. is accredited under the United States Department of Commerce, National Institute of Standards and Technology, and National Voluntary Laboratory Accreditation Program for satisfactory compliance with the requirements of ISO/IEC 17025 for Testing Laboratories. The NVLAP accreditation encompasses Electromagnetic Compatibility Testing in accordance with the European Union EMC Directive 2004/108/EC, and ANSI C63.4. Additionally, Northwest EMC is accredited by NVLAP to perform radio testing in accordance with the European Union R&TTE Directive 1999/5/EEC, the requirements of FCC, and the RSS radio standards for Industry Canada.



NVLAP LAB CODE 200629-0 NVLAP LAB CODE 200630-0 NVLAP LAB CODE 200676-0 NVLAP LAB CODE 200761-0 NVLAP LAB CODE 200881-0

#### **Industry Canada**

Accredited by NVLAP for performance of Industry Canada RSS and ICES testing. Our Open Area Test Sites and certification chambers comply with RSS-Gen, Issue 2 and have been filed with Industry Canada and accepted. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by NIST and recognized by Industry Canada as a Certification Body (CB) per the APEC Mutual Recognition Arrangement (MRA). This allows Northwest EMC to certify transmitters to Industry Canada technical requirements. (Site Filing Numbers - Hillsboro: 2834D-1, 2834D-2, Sultan: 2834C-1, Irvine: 2834B-1, 2834B-2, Brooklyn Park: 2834E-1)



#### CAB

Designated by NIST and validated by the European Commission as a Conformity Assessment Body (CAB) to conduct tests and approve products to the EMC directive and transmitters to the R&TTE directive, as described in the U.S. - EU Mutual Recognition Agreement.



#### **NEMKO**

Assessed and accredited by NEMKO (Norwegian testing and certification body) for European emissions and immunity testing. As a result of NEMKO's laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification (Authorization No. ELA 119).





## Accreditations and Authorizations

#### Australia/New Zealand

The National Association of Testing Authorities (NATA), Australia has been appointed by the ACA as an accreditation body to accredit test laboratories and competent bodies for EMC standards. Accredited test reports or assessments by competent bodies must carry the NATA logo. Test reports made by an overseas laboratory that has been accredited for the relevant standards by an overseas accreditation body that has a Mutual Recognition Agreement (MRA) with NATA are also accepted as technical grounds for product conformity. The report should be endorsed with the respective logo of the accreditation body (NVLAP).



#### **VCCI**

Accepted as an Associate Member to the VCCI, Acceptance No. 564. Conducted and radiated measurement facilities have been registered in accordance with Regulations for Voluntary Control Measures, Article 8. (Registration Numbers. - Hillsboro: C-1071, R-1025, G-84, C-2687, T-1658, and R-2318, Irvine: R-1943, G-85, C-2766, and T-1659, Sultan: R-871, G-83, C-1784, and T-1511, Brooklyn Park: R-3125, G-86, G-141, C-3464, and T-1634).



#### **BSMI**

Northwest EMC has been designated by NIST and validated by C-Taipei (BSMI) as a CAB to conduct tests as described in the APEC Mutual Recognition Agreement (US0017). License No.SL2-IN-E-1017.



#### **GOST**

Northwest EMC, Inc. has been assessed and accredited by the Russian Certification bodies Certinform VNIINMASH, CERTINFO, SAMTES, and Federal CHEC, to perform EMC and Hygienic testing for Information Technology Products. As a result of their laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification



#### **KCC**

Northwest EMC, Inc is a CAB designated by MRA partners and recognized by Korea. (Assigned Lab Numbers: Hillsboro: US0017, Irvine: US0158, Sultan: US0157)



#### **VIETNAM**

Vietnam MIC has approved Northwest EMC as an accredited test lab. Per Decision No. 194/QD-QLCL (dated December 15, 2009), Northwest EMC test reports can be used for Vietnam approval submissions.



#### SCOPE

For details on the Scopes of our Accreditations, please visit: http://www.nwemc.com/accreditations/



#### **Northwest EMC Locations**






Oregon Labs EV01-EV12 22975 NW Evergreen Pkwy Suite 400 Hillsboro, OR 97124 (503) 844-4066 California Labs OC01-OC13 41 Tesla Irvine, CA 92618 (949) 861-8918 Minnesota Labs MN01-MN08 9349 W Broadway Ave. Brooklyn Park, MN 55445 (763) 425-2281 Washington Labs SU01-SU07 14128 339<sup>th</sup> Ave. SE Sultan, WA 98294 (360) 793-8675

New York Labs WA01-WA04 4939 Jordan Rd. Elbridge, NY 13060 (315) 685-0796







Rev 11/17/06

#### Party Requesting the Test

Company Name:	Summit Semiconductor LLC
Address:	22867 NW Bennett St. Suite 200
City, State, Zip:	Hillsboro, OR 97124
Test Requested By:	Alex Macdonald
Model:	Summit FS848 Master Module (Wheeler)
Receipt Date of Samples:	July 27, 2010
Equipment Design Stage:	Pre-production
Equipment Condition:	No Damage

#### Information Provided by the Party Requesting the Test

Functional Description of the EUT (Equipment Under Test):	
UNII Radio Module	

Testing Objective:
To demonstrate compliance with FCC requirements for RF exposure for 2.1091 mobile devices.

#### **Maximum Permissible Exposure (MPE)**

#### OVERVIEW

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons. ANSI C95.1-1992 specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits. If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance. If the use of warning labels on a transmitter is not effective or desirable, the alternative of performing SAR evaluation with the device at its closest range to persons under normal operating conditions may be used. The field strength and power density limits adopted by the FCC are based on whole-body averaged exposure and the assumption of RF field levels relate most accurately to estimating whole-body averaged SAR. This means some local values of exposures exceeding the stated field strength and power density limits may not necessarily imply non-compliance if the spatial average of spatially averaged RF fields over the exposed portions of a person's body does not exceed the limits.

#### **COMPLIANCE WITH 47 CFR 15.247(i)**

"Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter."

The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The highest gain antenna has a gain of 2.2 dBi. The maximum peak conducted output power is 33.1 mW. The maximum peak radiated power is 55.0 mW (EIRP). Per 47 CFR 1.1310, the EUT meets the General Population / Uncontrolled exposure limits listed in Table 1.

#### **COMPLIANCE WITH 47 CFR 15.407(f)**

"U-NII devices are subject to the radio frequency radiation exposure requirements specified in §1.1307(b), §2.1091 and §2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request."

The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The highest gain antenna has a gain of 2.2 dBi. The maximum peak conducted output power is 45.7 mW. The maximum peak radiated power is 75.9 mW (EIRP). Per 47 CFR 1.1310, the EUT meets the General Population / Uncontrolled exposure limits listed in Table 1. The fundamental emissions and unwanted emissions meet all applicable FCC requirements for RF exposure.

#### COMPLIANCE WITH FCC KDB 447498 D01 Mobile Portable RF Exposure V04

The EUT radio is a stand-alone mobile transmitter used greater than 20 cm from all other simultaneous transmitting antennas.

"KDB 447498 D01 Mobile Portable RF Exposure v04" provides the procedures, requirements, and authorization policies for mobile and portable devices. Item #7 best fits the exposure condition described in this report. Since this mobile device is categorically excluded from routine evaluation; per footnote 1 of KDB 447498, simple calculations may be used to estimate the power density to demonstrate compliance with 47 CFR 1.1310 requirements. The attached estimate shows MPE limits are met at a 20 cm boundary.

#### **FCC LIMITS FOR MPE**

Limits for General Population /Uncontrolled Expsoure: 47 CFR 1.1310

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	(V/m)	(A/m)	(mW/cm <sup>2</sup> )	(minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30
1500 - 100000			1	30

f = frequency in MHz

#### METHOD OF EVALUATION

The exposure level at a 20 cm distance from the EUT's transmitting antenna is calculated using the general equation:

$$S = \frac{P * G}{4 * \pi * R^2}$$

Where: S = power density (mW/cm2)

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

P\*G = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is summarized in the following table:

<sup>\* =</sup> Plane-wave equivalent power density

NORTHWEST	Maritiment British	attala Essa	(MDE)		XMit 2008.12.29
EMC	Maximum Permis	sible Exp	osure (MPE)		
EUT:	Summit FS848 Master Module (Wheeler)			Work Order: FOCU0081	•
Serial Number:	A146			Date: 07/27/10	
Customer:	Summit Semiconductor LLC			Temperature: 23	
Attendees:				Humidity: 45%	
Project:	None			Barometric Pres.: 30.16 in	
Evaluated by:	Greg Kiemel	Power:	120V, 60 Hz	Job Site: EV06	
SPECIFICATIONS			Method		
FCC 2.1091:2010			OET Bulletin 65, Suppleme	nt C Ed 01-01	
COMMENTS					
None					
DEVIATIONS FROM	TEST STANDARD				
No Deviations					
	Equal (	UV. 0			
	A DE	JU.K.P			
	Signature	5			

Radio	Antenna Type	Antenna Manufacture r	Antenna Part No.	Transmit Frequency (MHz)	Max Peak Conducted Output Power (mW)	Antenna Gain (dBi)	Minimum Antenna Cable Loss (dB)	Power Density @ 20 cm (mW/cm²)	General Population Exposure Limit from 1.1310 (mW/cm²)
LINII	1/4 wave	Aeon	C6276-510001A	5700	45.7	2.2	0	0.015	1
UNII	dipole	Technology	C6276-510001A	5825	33.1	2.2	0	0.011	1