SUMMIT SEMICONDUCTOR LLC

22867 NW Bennett Street, Suite 200 Hillsboro, OR 97124 USA Phone: 503 615-7700 • Fax: 503 615-4232 http://www.summitsemi.com

15 July 2010

Federal Communications Commission Authorization and Evaluation Branch 7435 Oakland Mills Road Columbia, MD 21046

Subject: Request for unlicensed Limited Modular Transmitter Approval.

Dear Application Examiner:

Summit Semiconductor LLC hereby requests FCC Equipment Authorization and Evaluation branch to approve Summit Semiconductor LLC Model 444-2203, digital wireless audio master device, FCC ID-UA9100, limited modular approval for a 21 channel DFS enabled transmitter. This letter addresses the information required by points one through eight of 47 CFR 15.212.

- "The modular transmitter must have its own RF shielding." The transmitter radio section of the module is enclosed within a RF shield. The RF shield is solder mounted to exposed grounding of the circuit board. The point of contact between the shield and the board has multiple ground contacts. The internal photos exhibit has pictures of the wireless master device with and without the shield. The shield suppresses spurious radiations as per FCC requirements.
- 2. "The modular transmitter must have buffered modulation/data inputs." The 444-2203 has buffered data inputs that pass through an embedded processor. RF modulation controls are generated on board. Firmware will also not allow the end user to access RF modulation / data rate control settings of the RF circuitry. No change in input data or control signal can affect the RF data rate or type. This method insures compliance with Part 15 requirements under conditions of excessive data rates or over modulation.
- 3. "The modular transmitter must have its own power supply regulation." The 444-2203 digital wireless master device receives power from an external +3.3 VDC and external +5.0 VDC supply on the customer's host controller board. The +3.3 VDC supply sources some circuitry directly and is also regulated to +1.5 and +2.8 VDC as well. The +5.0 VDC supply sources circuitry directly. In order to comply with the requirement that all voltages be regulated, we have included an over voltage detection circuit which ceases RF transmission when the input voltages exceed their +10% threshold, either independently or together.
- 4. "The modular transmitter antenna must comply with the antenna and transmission system requirements of section 15.203, and 15.204(c)." The modular device complies with all FCC antenna requirements. The 444-2203 digital wireless master device offers a UFL style RF connector interface. This requires either a permanently attached antenna, or will be offered with a UFL to RP-SMA cable that is a non-standard attachment method. Both methods meet FCC requirements. A list of usable antennas is provided in the antenna report included with the certification submission.
- 5. "The modular transmitter must be tested in a stand-alone configuration." As described in the technical report exhibit and the test set up photos of the test report included in the filing for FCC equipment authorization, the 444-2203 digital wireless master device module was tested as a stand alone device. The device is designed with an industry standard 40 pin multi pin flex cable and was tested in typical configuration which is greater than 10 cm in length from the host device.
- 6. "The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying the FCC identification number." A FCC ID and model number is labeled on every modular device. FCC ID label and location exhibit has a photograph which shows the exact location of the label. Since the FCC ID number will not be visible when the module is installed inside the host audio source, another label with the same FCC ID will be applied to the exterior of the host/master enclosure.

SUMMIT SEMICONDUCTOR LLC

22867 NW Bennett Street, Suite 200 Hillsboro, OR 97124 USA Phone: 503 615-7700 • Fax: 503 615-4232

http://www.summitsemi.com

- 7. "The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements." The EUT complies with all specific rules such as modulation scheme, modulation type, bandwidth, antenna requirements, power supply regulation, and suppression of spurious emissions and so on. A detailed user manual is provided with every EUT which instructs the user to maintain compliance as per the requirements of the Commission. The manual also cautions the user not to make any changes or modifications not approved by the party responsible for compliance. Please see the operating description exhibit for further details to understand how the EUT complies with specific rules and operating requirements as per FCC.
- 8. "The modular transmitter must comply with any applicable RF exposure requirements in its final configuration." The EUT is compliant with all applicable RF exposure requirements and EUT is operated in a manner that ensures the public is not exposed to radio frequency in excess of Federal Communication Commission's guidelines. Please see the RF exposure exhibit.

Best Regards

James Svoboda Engineering Manager