Awarepoint Corporation 8899 University Center Lane Suite 330 San Diego, CA 92122 Phone: (858) 535-8100 Fax: (858) 535-1808 www.awarepoint.com



6/07/06 TÜV America, Inc. TCB 10040 Mesa Rim Road San Diego, CA 92121

Re: SAR Calculation for Awarepoint model T1

Applicant: AwarePoint Corporation

The following is the SAR calculation for the Awarepoint model T1 using the system's maximum RF emission. The calculation is based on FCC47CFR Part 2 and OET 65.

Per OET 65:

Maximum Permissible Exposure is Freq. (in MHz)/1500 = MPE mW/cm² 2400 MHz/1500 = 1.6 mW/ cm²

0dBm Transmitter Power (Max) 3dBi Antenna Gain (Max) 0dBm + 0dBi = +3dBm EIRP +3dBm EIRP = 2mW EIRP 1.6 mW/cm² = 2 mW/(4* π *r²) r = $\sqrt{(2mW/(4*\pi*1.6 \text{ mW/cm}^2))}$ r = 0.315 cm or 3.15 mm

Since the distance from the surface of the T1 enclosure to the antenna is greater than 3.15mm, it is impossible to violate the SAR limit.

Sincerely,

Derek Smith

Director of Technology Tel: (858) 535-8100 Fax: (858) 535-1808