

SAR TEST REPORT

No. 2007SAR00003

for

Paragon Wireless Inc.

GSM/WiFi Dual-Mode Phone

hipi 2300

With

Hardware Version: MB03318T000

Software Version:

P1_WINMOBILE_PARAGON_A_3_00_00_SHIP_Build_W

Issued Date: 2007-03-16



No. DAT-P-114/01-01

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry




No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel: +86(0)10-62303288-2105, Fax: +86(0)10-62304793 Email: welcome@emcite.com. www.emcite.com

TABLE OF CONTENT

| | |
|--|------------|
| 1 TEST LABORATORY | 4 |
| 1.1 TESTING LOCATION | 4 |
| 1.2 TESTING ENVIRONMENT | 4 |
| 1.3 PROJECT DATA | 4 |
| 2 CLIENT INFORMATION | 4 |
| 2.1 APPLICANT INFORMATION | 4 |
| 2.2 MANUFACTURER INFORMATION | 4 |
| 3 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 5 |
| 3.1 ABOUT EUT | 5 |
| 3.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 5 |
| 3.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST | 5 |
| 4 OPERATIONAL CONDITIONS DURING TEST | 6 |
| 4.1 SCHEMATIC TEST CONFIGURATION | 6 |
| 4.2 SAR MEASUREMENT SET-UP | 6 |
| 4.3 DASY4 E-FIELD PROBE SYSTEM | 7 |
| 4.4 E-FIELD PROBE CALIBRATION | 8 |
| 4.5 OTHER TEST EQUIPMENT | 9 |
| 4.6 EQUIVALENT TISSUES | 9 |
| 4.7 SYSTEM SPECIFICATIONS | 10 |
| 5 CHARACTERISTICS OF THE TEST | 11 |
| 5.1 APPLICABLE LIMIT REGULATIONS | 11 |
| 5.2 APPLICABLE MEASUREMENT STANDARDS | 11 |
| 6 CONDUCTED OUTPUT POWER MEASUREMENT | 11 |
| 6.1 SUMMARY | 11 |
| 6.2 CONDUCTED POWER | 12 |
| 7 TEST RESULTS | 13 |
| 7.1 DIELECTRIC PERFORMANCE | 13 |
| 7.2 SYSTEM VALIDATION | 13 |
| 7.3 SUMMARY OF MEASUREMENT RESULTS | 14 |
| 7.4 CONCLUSION | 17 |
| 8 MEASUREMENT UNCERTAINTY | 18 |
| 9 MAIN TEST INSTRUMENTS | 19 |
| ANNEX A: MEASUREMENT PROCESS | 20 |
| ANNEX B TEST LAYOUT | 21 |
| ANNEX C: GRAPH RESULTS | 26 |
| ANNEX D: SYSTEM VALIDATION RESULTS | 134 |
| ANNEX E: PROBE CALIBRATION CERTIFICATE | 137 |

SAR TEST REPORT

| | | | | | |
|--------------------------|--|---|--|--|--|
| Test report No. | 2007SAR00003 | Date of report | March 16 th , 2007 | | |
| Test laboratory | TMC Beijing, Telecommunication Metrology Center of MIIT | Client | Paragon Wireless Inc. | | |
| Test device | Product name: GSM/WiFi Dual-Mode Phone Model type: hipi 2300 Series number: 004401091504056 GPRS Class: 10 | | | | |
| Test reference documents | <p>EN 50360-2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>EN 50361-2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.</p> <p>IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.</p> <p>OET Bulletin 65 (Edition 97-01) and Supplement C (Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.</p> <p>IEC 62209-1: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1:Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)</p> <p>IEC 62209-2 (Draft): Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the Specific Absorption Rate (SAR)in the head and body for 30MHz to 6GHz Handheld and Body-Mounted Devices used in close proximity to the Body</p> | | | | |
| Test conclusion | <p>Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.</p> <p>General Judgment: Pass</p> | | | | |
| Signature |  Lu Bingsong Deputy Director of the laboratory (Approved for this report) |  Qi Dianyuan SAR Project Leader (Reviewed for this report) |  Sun Qian SAR Test Engineer (Prepared for this report) | | |

1 Test Laboratory

1.1 Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII
Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China
Postal Code: 100083
Telephone: 00861062303288
Fax: 00861062304793

1.2 Testing Environment

Temperature: Min. = 15 °C, Max. = 30 °C
Relative humidity: Min. = 30%, Max. = 70%
Ground system resistance: < 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.
Reflection of surrounding objects is minimized and in compliance with requirement of standards.

1.3 Project Data

Project Leader: Qi Dianyuan
Test Engineer: Sun Qian
Testing Start Date: Feb 05, 2007
Testing End Date: Feb 07, 2007

2 Client Information

2.1 Applicant Information

Company Name: Paragon Wireless Inc.
Address /Post: A-1801, E-wing Center, No.113 Zhichun Road, Haidian District, Beijing 100086, P.R.China
City: Beijing
Postal Code: 100086
Country: P.R.China
Telephone: 010-62616660-270
Fax: 010-62616669

2.2 Manufacturer Information

Company Name: Paragon Wireless Inc.
Address /Post: A-1801, E-wing Center, No.113 Zhichun Road, Haidian District, Beijing 100086, P.R.China
City: Beijing
Postal Code: 100086
Country: P.R.China
Telephone: 010-62616660-270
Fax: 010-62616669

3 Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1 About EUT

Description: GSM/WiFi Dual-Mode Phone
Model: hipi 2300
Frequency Band: 850MHz/1900MHz/WLAN



Picture 1: Constituents of the sample

3.2 Internal Identification of EUT used during the test

| EUT ID* | SN or IMEI | HW Version | SW Version |
|---------|-----------------|-------------|---|
| EUT1 | 004401091504056 | MB03318T000 | P1_WINMOBILE_PARAGON_A_3_00_00_SHIP_Build_W |

*EUT ID: is used to identify the test sample in the lab internally.

3.3 Internal Identification of AE used during the test

| AE ID* | Description | Model | SN | Manufacturer |
|--------|----------------|-----------|----------------|-----------------------------------|
| AE1 | Travel Adapter | TA-12E | 609-6205001816 | SHENZHENTENWEI ELECTRONICSCO.,LTD |
| AE2 | Battery | UF553450Z | BYD0605002935 | Huizhou Desay Battery Co.Ltd |

*AE ID: is used to identify the test sample in the lab internally.

4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration


During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 128, 190 and 251 respectively in the case of GSM 850 MHz, or to 512, 661 and 810 respectively in the case of 1900 MHz. The EUT is commanded to operate at maximum transmitting power. A communication link is set up with the test mode software for Wifi mode test. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 1, 6 and 11 respectively in the case of 2450 MHz. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 30 dB.

4.2 SAR Measurement Set-up

These measurements were performed with the automated near-field scanning system DASY4 Professional from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m), which positions the probes with a positional repeatability of better than $\pm 0.02\text{mm}$. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit.

A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4 Professional, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.



Picture 2: SAR Lab Test Measurement Set-up


The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

4.3 Dasy4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ET3DV6 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$.


ET3DV6 Probe Specification

| | |
|--------------|--|
| Construction | Symmetrical design with triangular core Built-in optical fiber for surface detection System(ET3DV6 only) |
| Calibration | In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at frequencies of 450MHz, 900MHz and 1.8GHz (accuracy $\pm 8\%$) Calibration for other liquids and frequencies upon request |
| Frequency | 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz) |



Picture 3: ET3DV6 E-field Probe

| | |
|-------------------|---|
| Directivity | ±0.2 dB in brain tissue (rotation around probe axis) ±0.4 dB in brain tissue (rotation normal probe axis) |
| Dynamic Range | 5u W/g to > 100mW/g; Linearity: ±0.2dB |
| Surface Detection | ±0.2 mm repeatability in air and clear liquids over diffuse reflecting surface(ET3DV6 only) |
| Dimensions | Overall length: 330mm Tip length: 16mm Body diameter: 12mm Tip diameter: 6.8mm Distance from probe tip to dipole centers: 2.7mm |
| Application | General dosimetry up to 3GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms |



Picture 4: ET3DV6 E-field

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than ± 10%. The spherical isotropy was evaluated and found to be better than ± 0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),
 C = Heat capacity of tissue (brain or muscle),
 ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,
 ρ = Tissue density (kg/m^3).

Note: Please check Annex E to see the Probe Certificate.



Picture 5: Device Holder

4.5 Other Test Equipment

4.5.1 Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

4.5.2 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness 2±0.1 mm

Filling Volume Approx. 20 liters

Dimensions 810 x 1000 x 500 mm (H x L x W)

Available Special



4.6 Equivalent Tissues

Picture 6: Generic Twin Phantom

The liquid used for the frequency range of 800-2000

MHz consisted of water, sugar, salt and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table 4 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528.

Table 1. Composition of the Head Tissue Equivalent Matter

| MIXTURE % | FREQUENCY 850MHz |
|------------------------------------|-------------------------|
| Water | 41.45 |
| Sugar | 56.0 |
| Salt | 1.45 |
| Preventol | 0.1 |
| Cellulose | 1.0 |
| Dielectric Parameters Target Value | f=850MHz ε=41.5 σ=0.90 |
| MIXTURE % | FREQUENCY 1900MHz |
| Water | 55.242 |
| Glycol monobutyl | 44.452 |
| Salt | 0.306 |
| Dielectric Parameters Target Value | f=1900MHz ε=40.0 σ=1.40 |

| MIXTURE % | FREQUENCY 2450MHz | | |
|------------------------------------|--------------------|-----------------|---------------|
| Water | 71.88 | | |
| Glycol monobutyl | 27.96 | | |
| Salt | 0.16 | | |
| Dielectric Parameters Target Value | $f=2450\text{MHz}$ | $\epsilon=39.2$ | $\sigma=1.80$ |

Table 2. Composition of the Body Tissue Equivalent Matter

| MIXTURE % | FREQUENCY 850MHz | | |
|------------------------------------|--------------------|-----------------|---------------|
| Water | 52.5 | | |
| Sugar | 45.0 | | |
| Salt | 1.4 | | |
| Preventol | 0.1 | | |
| Cellulose | 1.0 | | |
| Dielectric Parameters Target Value | $f=850\text{MHz}$ | $\epsilon=55.2$ | $\sigma=0.97$ |
| MIXTURE % | FREQUENCY 1900MHz | | |
| Water | 69.91 | | |
| Glycol monobutyl | 29.96 | | |
| Salt | 0.13 | | |
| Dielectric Parameters Target Value | $f=1900\text{MHz}$ | $\epsilon=53.3$ | $\sigma=1.52$ |
| MIXTURE % | FREQUENCY 2450MHz | | |
| Water | 68.64 | | |
| Glycol monobutyl | 31.36 | | |
| Salt | 0.00 | | |
| Dielectric Parameters Target Value | $f=2450\text{MHz}$ | $\epsilon=53.6$ | $\sigma=1.81$ |

4.7 System Specifications

4.7.1 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX90L

Repeatability: ± 0.02 mm

No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium III

Clock Speed: 800 MHz

Operating System: Windows 2000

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic

Software: DASY4 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

EN 50360–2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

It specifies the maximum exposure limit of **2.0 W/kg** as averaged over any 10 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

EN 50361–2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

OET Bulletin 65 (Edition 97-01) and Supplement C (Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

IEC 62209-1-2005: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)

IEC 62209-2 (Draft): Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the Specific Absorption Rate (SAR) in the head and body for 30MHz to 6GHz Handheld and Body-Mounted Devices used in close proximity to the Body

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

6 CONDUCTED OUTPUT POWER MEASUREMENT

6.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure the maximum power transmission and proper

modulation. This result contains conducted output power and ERP for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

6.2 Conducted Power

6.2.1 Measurement Methods

The EUT was set up for the maximum output power. The channel power was measured with Agilent Spectrum Analyzer E4440A.

6.2.2 Measurement result

The conducted power measurement results for 850MHz and 1900MHz is as Table 3 listed.

Table 3: Conducted Power Measurement Results

| 850MHZ | | Conducted Power | | |
|-----------------------|--|----------------------------|---------------------------|----------------------------|
| | | Channel 251 (848.8MHz) | Channel 190 (836.6MHz) | Channel 128 (824.2MHz) |
| Before SAR Test (dBm) | | 32.86 | 32.95 | 32.92 |
| After SAR Test (dBm) | | 32.91 | 32.97 | 32.95 |
| 1900MHZ | | Conducted Power | | |
| | | Channel 810 (1909.8MHz) | Channel 661 (1880MHz) | Channel 512 (1850.2MHz) |
| Before SAR Test (dBm) | | 28.21 | 29.19 | 29.26 |
| After SAR Test (dBm) | | 28.56 | 29.09 | 29.35 |

The conducted Transmitter peak power for WiFi mode is listed as following :

T nom = 25 °C T min = -10 °C T max = 55 °C

V nom = 3.9 V V min = 3.7V V max = 4.2 V

| Mode | Test Condition | Transmitter peak power (dBm) | | |
|---------|----------------|------------------------------|------------------------|-------------------------|
| | | Channel 1 (2412MHz) | Channel 6 (2437MHz) | Channel 11 (2462MHz) |
| 802.11b | Tnom | Vnom | 14.22 | 14.20 |
| | | Vmax | 15.18 | 14.61 |
| | | Vmin | 14.71 | 14.69 |
| | Tmin | Vnom | 15.45 | 15.12 |
| | Tmax | Vnom | 13.95 | 14.22 |
| 802.11g | Tnom | Vnom | 15.89 | 14.62 |
| | | Vmax | 16.50 | 14.76 |
| | | Vmin | 16.36 | 15.20 |
| | Tmin | Vnom | 16.82 | 15.45 |
| | Tmax | Vnom | 14.73 | 14.76 |

6.2.3 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 7 to Table 12 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

7 TEST RESULTS

7.1 Dielectric Performance

Table 4: Dielectric Performance of Head Tissue Simulating Liquid

| | | | |
|---|------------------|---|---|
| Measurement is made at temperature 23.3 °C and relative humidity 49%. Liquid temperature during the test: 22.5°C | | | |
| / | Frequency | Permittivity ϵ | Conductivity σ (S/m) |
| Target value | 850 MHz | 41.5 | 0.90 |
| | 1900 MHz | 40.0 | 1.40 |
| | 2450 MHz | 39.2 | 1.80 |
| Measurement value (Average of 10 tests) | 850 MHz | 41.7 | 0.88 |
| | 1900 MHz | 39.2 | 1.45 |
| | 2450 MHz | 38.9 | 1.83 |

Table 5: Dielectric Performance of Body Tissue Simulating Liquid

| | | | |
|---|------------------|---|---|
| Measurement is made at temperature 23.3 °C and relative humidity 49%. Liquid temperature during the test: 22.5°C | | | |
| / | Frequency | Permittivity ϵ | Conductivity σ (S/m) |
| Target value | 850 MHz | 55.2 | 0.97 |
| | 1900 MHz | 53.3 | 1.52 |
| | 2450MHz | 53.6 | 1.81 |
| Measurement value (Average of 10 tests) | 850 MHz | 53.4 | 1.00 |
| | 1900 MHz | 51.5 | 1.57 |
| | 2450MHz | 51.2 | 1.89 |

7.2 System Validation

Table 6: System Validation

| | | | |
|--|------------------|---|---|
| Measurement is made at temperature 23.3 °C, relative humidity 49%, input power 250 mW. Liquid temperature during the test: 22.3°C | | | |
| Liquid parameters | Frequency | Permittivity ϵ | Conductivity σ (S/m) |
| Liquid parameters | 835 MHz | 41.7 | 0.88 |
| | 1900 MHz | 39.2 | 1.45 |
| | 2450 MHz | 38.9 | 1.83 |
| Verification results | Frequency | Target value (W/kg) | |
| | | 10 g Average | 1 g Average |
| | 835 MHz | 1.55 | 2.375 |
| | 1900 MHz | 5.125 | 9.925 |
| | 2450 MHz | 6.0 | 13.1 |
| | | Measurement value (W/kg) | |
| | | 10 g Average | 1 g Average |
| | | 1.62 | 2.48 |
| | | 5.27 | 9.91 |
| | | 6.08 | 13.21 |

Note: Target Values used are one fourth of those in IEEE Std 1528-2003 (feeding power is normalized to 1 Watt), i.e. 250 mW is used as feeding power to the validation dipole (SPEAG using).

7.3 Summary of Measurement Results

Table 7: SAR Values (850MHz-Head)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|--|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Left hand, Touch cheek, Top frequency(See Fig.1) | 0.119 | 0.179 | -0.200 |
| Left hand, Touch cheek, Mid frequency(See Fig.3) | 0.139 | 0.210 | -0.034 |
| Left hand, Touch cheek, Bottom frequency(See Fig.5) | 0.131 | 0.196 | 0.009 |
| Left hand, Tilt 15 Degree, Top frequency(See Fig.7) | 0.067 | 0.100 | 0.069 |
| Left hand, Tilt 15 Degree, Mid frequency(See Fig.9) | 0.089 | 0.131 | -0.040 |
| Left hand, Tilt 15 Degree, Bottom frequency(See Fig.11) | 0.092 | 0.136 | -0.068 |
| Right hand, Touch cheek, Top frequency(See Fig.13) | 0.126 | 0.189 | 0.035 |
| Right hand, Touch cheek, Mid frequency(See Fig.15) | 0.150 | 0.226 | 0.200 |
| Right hand, Touch cheek, Bottom frequency(See Fig.17) | 0.149 | 0.223 | -0.154 |
| Right hand, Tilt 15 Degree, Top frequency(See Fig.19) | 0.070 | 0.108 | 0.062 |
| Right hand, Tilt 15 Degree, Mid frequency(See Fig.21) | 0.096 | 0.146 | 0.017 |
| Right hand, Tilt 15 Degree, Bottom frequency(See Fig.23) | 0.103 | 0.158 | -0.076 |

Table 8: SAR Values (850MHz-GPRS)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|---|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Body, Towards Ground, Top frequency(See Fig.25) | 0.161 | 0.234 | -0.089 |
| Body, Towards Ground, Mid frequency(See Fig.27) | 0.253 | 0.358 | -0.167 |
| Body, Towards Ground, Bottom frequency(See Fig.29) | 0.244 | 0.346 | -0.107 |
| Body, Towards Phantom, Top frequency(See Fig.31) | 0.062 | 0.088 | -0.027 |
| Body, Towards Phantom, Mid frequency(See Fig.33) | 0.076 | 0.108 | -0.200 |
| Body, Towards Phantom, Bottom frequency(See Fig.35) | 0.089 | 0.124 | 0.100 |

Table 9: SAR Values (1900MHz-Head)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|--|----------------------------------|----------------|-------------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g | 1 g | |
| Left hand, Touch cheek, Top frequency(See Fig.37) | 0.279 | 0.471 | 0.011 |
| Left hand, Touch cheek, Mid frequency(See Fig.39) | 0.311 | 0.521 | 0.027 |
| Left hand, Touch cheek, Bottom frequency(See Fig.41) | 0.359 | 0.601 | 0.010 |
| Left hand, Tilt 15 Degree, Top frequency(See Fig.43) | 0.256 | 0.457 | -0.097 |
| Left hand, Tilt 15 Degree, Mid frequency(See Fig.45) | 0.294 | 0.523 | -0.008 |
| Left hand, Tilt 15 Degree, Bottom frequency(See Fig.47) | 0.324 | 0.571 | -0.013 |
| Right hand, Touch cheek, Top frequency(See Fig.49) | 0.295 | 0.536 | 0.078 |
| Right hand, Touch cheek, Mid frequency(See Fig.51) | 0.325 | 0.585 | -0.014 |
| Right hand, Touch cheek, Bottom frequency(See Fig.53) | 0.386 | 0.695 | 0.029 |
| Right hand, Tilt 15 Degree, Top frequency(See Fig.55) | 0.275 | 0.509 | -0.045 |
| Right hand, Tilt 15 Degree, Mid frequency(See Fig.57) | 0.301 | 0.556 | 0.088 |
| Right hand, Tilt 15 Degree, Bottom frequency(See Fig.59) | 0.359 | 0.657 | -0.048 |

Table 10: SAR Values (1900MHz-GPRS)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|---|----------------------------------|----------------|-------------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g | 1 g | |
| Body, Towards Ground, Top frequency(See Fig.61) | 0.335 | 0.572 | -0.046 |
| Body, Towards Ground, Mid frequency(See Fig.63) | 0.424 | 0.719 | -0.069 |
| Body, Towards Ground, Bottom frequency(See Fig.65) | 0.509 | 0.866 | 0.016 |
| Body, Towards Phantom, Top frequency(See Fig.67) | 0.140 | 0.229 | -0.200 |
| Body, Towards Phantom, Mid frequency(See Fig.69) | 0.170 | 0.279 | -0.005 |
| Body, Towards Phantom, Bottom frequency(See Fig.71) | 0.191 | 0.312 | -0.112 |

Table 11: SAR Values (WLAN, Mode 802.11b-Head)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|--|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Left hand, Touch cheek, Top frequency(See Fig.73) | 0.00601 | 0.034 | 0.189 |
| Left hand, Touch cheek, Mid frequency(See Fig.74) | 0.00136 | 0.00912 | 0.195 |
| Left hand, Touch cheek, Bottom frequency(See Fig.75) | 0.028 | 0.122 | 0.176 |
| Left hand, Tilt 15 Degree, Top frequency(See Fig.76) | 0.000371 | 0.00187 | -0.109 |
| Left hand, Tilt 15 Degree, Mid frequency(See Fig.77) | 0.032 | 0.076 | -0.192 |
| Left hand, Tilt 15 Degree, Bottom frequency(See Fig.78) | 0.029 | 0.067 | 0.183 |
| Right hand, Touch cheek, Top frequency(See Fig.79) | 0.00695 | 0.029 | 0.200 |
| Right hand, Touch cheek, Mid frequency(See Fig.80) | 0.00212 | 0.010 | -0.195 |
| Right hand, Touch cheek, Bottom frequency(See Fig.81) | 0.00402 | 0.020 | -0.191 |
| Right hand, Tilt 15 Degree, Top frequency(See Fig.82) | 0.016 | 0.042 | 0.159 |
| Right hand, Tilt 15 Degree, Mid frequency(See Fig.83) | 0.00308 | 0.012 | 0.148 |
| Right hand, Tilt 15 Degree, Bottom frequency(See Fig.84) | 0.00128 | 0.00539 | 0.200 |

Table 12: SAR Values (WLAN, Mode 802.11g-Head)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|--|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Left hand, Touch cheek, Top frequency(See Fig.85) | 0.019 | 0.060 | -0.182 |
| Left hand, Touch cheek, Mid frequency(See Fig.86) | 0.061 | 0.172 | 0.177 |
| Left hand, Touch cheek, Bottom frequency(See Fig.87) | 0.033 | 0.081 | 0.145 |
| Left hand, Tilt 15 Degree, Top frequency(See Fig.88) | 0.013 | 0.069 | -0.091 |
| Left hand, Tilt 15 Degree, Mid frequency(See Fig.89) | 0.024 | 0.131 | 0.200 |
| Left hand, Tilt 15 Degree, Bottom frequency(See Fig.90) | 0.023 | 0.073 | -0.180 |
| Right hand, Touch cheek, Top frequency(See Fig.91) | 0.015 | 0.034 | -0.154 |
| Right hand, Touch cheek, Mid frequency(See Fig.92) | 0.00618 | 0.020 | 0.108 |
| Right hand, Touch cheek, Bottom frequency(See Fig.93) | 0.00125 | 0.00587 | 0.193 |
| Right hand, Tilt 15 Degree, Top frequency(See Fig.94) | 0.032 | 0.147 | -0.097 |
| Right hand, Tilt 15 Degree, Mid frequency(See Fig.95) | 0.000375 | 0.00159 | 0.146 |
| Right hand, Tilt 15 Degree, Bottom frequency(See Fig.96) | 0.00111 | 0.00414 | -0.127 |

Table 13: SAR Values (WLAN, Mode 802.11b-Body)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|---|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | Power Drift (dB) |
| | 10 g Average | 1 g Average | |
| Body Towards Ground, Top frequency(See Fig.97) | 0.000225 | 0.00121 | -0.200 |
| Body Towards Ground, Mid frequency(See Fig.98) | 0.00972 | 0.037 | -0.192 |
| Body Towards Ground, Bottom frequency(See Fig.99) | 9.2e-005 | 0.000584 | 0.197 |
| Body Towards Phantom, Top frequency(See Fig.100) | 0.000208 | 0.00167 | 0.187 |
| Body Towards Phantom, Mid frequency(See Fig.101) | 0.000167 | 0.00103 | -0.170 |
| Body Towards Phantom, Bottom frequency(See Fig.102) | 0.00163 | 0.00947 | -0.200 |

Table 14: SAR Values (WLAN, Mode 802.11g-Body)

| Limit of SAR (W/kg) | 10 g | 1 g | Power Drift (dB) |
|---|---------------------------|-------------|------------------|
| | Average | Average | |
| Test Case | Measurement Result (W/kg) | | Power Drift (dB) |
| | 10 g Average | 1 g Average | |
| Body Towards Ground, Top frequency(See Fig.103) | 0.00305 | 0.00945 | -0.157 |
| Body Towards Ground, Mid frequency(See Fig.104) | 0.000437 | 0.00233 | 0.200 |
| Body Towards Ground, Bottom frequency(See Fig.105) | 0.000911 | 0.00357 | 0.188 |
| Body Towards Phantom, Top frequency(See Fig.106) | 0.000727 | 0.00333 | -0.154 |
| Body Towards Phantom, Mid frequency(See Fig.107) | 0.000112 | 0.000553 | 0.176 |
| Body Towards Phantom, Bottom frequency(See Fig.108) | 0.000348 | 0.00183 | -0.192 |

7.4 Conclusion

Localized Specific Absorption Rate (SAR) of this fixed terminal station has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

8 Measurement Uncertainty

| SN | a | Type | c | d | e = f(d,k) | f | h = c x f / e | k |
|----|---|------|--------------------|------------------|---------------|-----------------|----------------------------|----------|
| | Uncertainty Component | | Tol. (\pm %) | Prob. . Dist. | Div. | c_i (1 g) | 1 g u_i (\pm %) | v_i |
| 1 | System repetivity | A | 0.5 | N | 1 | 1 | 0.5 | 9 |
| | Measurement System | | | | | | | |
| 2 | Probe Calibration | B | 5 | N | 2 | 1 | 2.5 | ∞ |
| 3 | Axial Isotropy | B | 4.7 | R | $\sqrt{3}$ | $(1-c_p)^{1/2}$ | 4.3 | ∞ |
| 4 | Hemispherical Isotropy | B | 9.4 | R | $\sqrt{3}$ | $\sqrt{c_p}$ | | ∞ |
| 5 | Boundary Effect | B | 0.4 | R | $\sqrt{3}$ | 1 | 0.23 | ∞ |
| 6 | Linearity | B | 4.7 | R | $\sqrt{3}$ | 1 | 2.7 | ∞ |
| 7 | System Detection Limits | B | 1.0 | R | $\sqrt{3}$ | 1 | 0.6 | ∞ |
| 8 | Readout Electronics | B | 1.0 | N | 1 | 1 | 1.0 | ∞ |
| 9 | RF Ambient Conditions | B | 3.0 | R | $\sqrt{3}$ | 1 | 1.73 | ∞ |
| 10 | Probe Positioner Mechanical Tolerance | B | 0.4 | R | $\sqrt{3}$ | 1 | 0.2 | ∞ |
| 11 | Probe Positioning with respect to Phantom Shell | B | 2.9 | R | $\sqrt{3}$ | 1 | 1.7 | ∞ |
| 12 | Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation | B | 3.9 | R | $\sqrt{3}$ | 1 | 2.3 | ∞ |
| | Test sample Related | | | | | | | |
| 13 | Test Sample Positioning | A | 4.9 | N | 1 | 1 | 4.9 | N-1 |
| 14 | Device Holder Uncertainty | A | 6.1 | N | 1 | 1 | 6.1 | N-1 |
| 15 | Output Power Variation - SAR drift measurement | B | 5.0 | R | $\sqrt{3}$ | 1 | 2.9 | ∞ |
| | Phantom and Tissue Parameters | | | | | | | |
| 16 | Phantom Uncertainty (shape and thickness tolerances) | B | 1.0 | R | $\sqrt{3}$ | 1 | 0.6 | ∞ |
| 17 | Liquid Conductivity - deviation from target values | B | 5.0 | R | $\sqrt{3}$ | 0.64 | 1.7 | ∞ |
| 18 | Liquid Conductivity - measurement uncertainty | B | 5.0 | N | 1 | 0.64 | 1.7 | M |
| 19 | Liquid Permittivity - deviation from target values | B | 5.0 | R | $\sqrt{3}$ | 0.6 | 1.7 | ∞ |
| 20 | Liquid Permittivity - measurement uncertainty | B | 5.0 | N | 1 | 0.6 | 1.7 | M |
| | Combined Standard Uncertainty | | | RSS | | | 11.25 | |
| | Expanded Uncertainty (95% CONFIDENCE INTERVAL) | | | K=2 | | | 22.5 | |

9 MAIN TEST INSTRUMENTS

Table 15: List of Main Instruments

| No. | Name | Type | Serial Number | Calibration Date | Valid Period |
|-----|------------------|--------------|---------------|--------------------------|--------------|
| 01 | Network analyzer | HP 8753E | US38433212 | August 30,2006 | One year |
| 02 | Power meter | NRVD | 101253 | June 20, 2006 | One year |
| 03 | Power sensor | NRV-Z5 | 100333 | | |
| 04 | Power sensor | NRV-Z6 | 100011 | September 2, 2006 | One year |
| 05 | Signal Generator | E4433B | US37230472 | September 4, 2006 | One Year |
| 06 | Amplifier | VTL5400 | 0505 | No Calibration Requested | |
| 07 | BTS | CMU 200 | 105948 | August 15, 2006 | One year |
| 08 | E-field Probe | SPEAG ET3DV6 | 1736 | December 1, 2006 | One year |
| 09 | DAE | SPEAG DAE3 | 536 | July 11, 2006 | One year |

END OF REPORT BODY

ANNEX A: MEASUREMENT PROCESS

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the reference point was measured and was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of the phantom was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the flat phantom and the horizontal grid spacing was 10 mm x 10 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.


Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7 x 7 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x ~ y and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.

c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation is repeated.




Picture A: SAR Measurement Points in Area Scan

ANNEX B TEST LAYOUT



Picture B1: Specific Absorption Rate Test Layout



Picture B2: Liquid depth in the Flat Phantom (850 MHz)



Picture B3 Liquid depth in the Flat Phantom (1900MHz)




Picture B4 Liquid depth in the Flat Phantom (2450MHz)



Picture B5: Left Hand Touch Cheek Position




Picture B6: Left Hand Tilt 15° Position




Picture B7: Right Hand Touch Cheek Position



Picture B8: Right Hand Tilt 15° Position



Picture B9: Body-worn Position (toward ground, the distance from handset to the bottom of the Phantom is 1.5cm)



Picture B10: Body-worn Position (toward phantom, the distance from handset to the bottom of the Phantom is 1.5cm)