FCC

TESTREPORT

ISSUED BY Shenzhen BALUN Technology Co., Ltd.




FOR

CS108 Sled Handheld for RFID/2D Barcode

ISSUED TO Convergence Systems Ltd.

11/F., Tower 1, Tern Centre, 237 Queen's Road, Central, Hong Kong.



Tested by: Zong Liyou (Engineer) Approved by: Wei Yanguan Report No.: BL-SZ1730414-701

EUT Name: CS108 Sled Handheld for RFID/2D

Barcode

Model Name: CS108-2

Brand Name: CSL

> FCC ID: UB4CS108C1GEN2

Test Standard: FCC 47 CFR Part 2.1093

ANSI C95.1: 1999, IEEE 1528: 2013

Maximum SAR: Hand-held (10 g): 0.707 W/kg

Test Conclusion: Pass

> Test Date: Jun. 01, 2017

Date of Issue: Jun. 12, 2017

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055 TEL: +86-755-66850100, FAX: +86-755-61824271

Email: info@baluntek.com www.baluntek.com



Revision History

VersionIssue DateRevisions ContentRev. 01Jun. 12, 2017Initial Issue

TABLE OF CONTENTS

1 GE	ENERAL INFORMATION	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
1.3	Test Environment Condition	4
1.4	Announce	4
2 PR	RODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Ancillary Equipment	5
2.6	Technical Information	6
3 SU	JMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	7
3.3	Test Result Summary	9
3.4	Test Uncertainty	10
4 SA	AR MEASUREMENT SYSTEM	12
4.1	Definition of Specific Absorption Rate (SAR)	12
4.2	SATIMO SAR System	12
5 SY	STEM VERIFICATION	21
5.1	Antenna Port Test Requirement	21
5.2	Purpose of System Check	21
5.3	System Check Setup	21
6 EU	JT TEST POSITION CONFIGURATUONS	22
6.1	Head Exposure Conditions	22



	6.2	Body-worn Position Conditions	23
	6.3	Hotspot Mode Exposure Position Conditions	24
7	SAR M	EASUREMENT PROCEDURES	25
	7.1	SAR Measurement Process Diagram	25
	7.2	SAR Scan General Requirements	26
	7.3	SAR Measurement Procedure	27
	7.4	Area & Zoom Scan Procedures	27
8	CONDU	JCTED RF OUPUT POWER	28
	8.1	RFID	28
	8.2	Bluetooth	28
	8.3	Rated RF Power Output	28
9	EUT A	NTENNA LOCATION SKETCH	29
	9.1	SAR Test Exclusion Consider Table	30
1	0 TEST F	RESULTS	31
	10.1	RFID (Handheld SAR)	31
1	1 SAR M	easurement Variability	32
1:	2 SIMUL	TANEOUS TRANSMISSION	33
	12.1	Simultaneous Transmission Mode Consider	33
	12.2	Estimated SAR Calculation	34
	12.3	Sum SAR of Simultaneous Transmission	35
1	3 TEST E	EQUIPMENTS LIST	36
A	NNEX A	SIMULATING LIQUID VERIFICATION RESULT	37
A	NNEX B	SYSTEM CHECK RESULT	38
A	NNEX C	TEST DATA	41
A	NNEX D	EUT EXTERNAL PHOTOS	42
A	NNEX E	SAR TEST SETUP PHOTOS	42
Α	NNFX F	CALIBRATION REPORT	42



1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Addross	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.		
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China		
The laboratory has been listed by Industry Canada electromagnetic emission measurements. The recognition test site are 11524A-1. The laboratory has been listed by US Federal Commission to perform electromagnetic emission measurements are cognition numbers of test site are 832625. The laboratory is a testing organization accredited by Cl Accreditation Service for Conformity Assessment (CNAS)			
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055		

1.3 Test Environment Condition

Ambient Temperature	20 to 23°C
Ambient Relative Humidity	35 to 48%
Ambient Pressure	100 to 102KPa

1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Convergence Systems Ltd.
Address	11/F., Tower 1, Tern Centre, 237 Queen's Road, Central, Hong Kong.

2.2 Manufacturer Information

Manufacturer	Convergence Systems Ltd.	
Address	11/F., Tower 1, Tern Centre, 237 Queen's Road, Central, Hong Kong.	

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	CS108 Sled Handheld for RFID/2D Barcode
Model Name Under Test	CS108-2
Series Model Name	N/A
Description of Model	N/A
Name Differentiation	N/A
Hardware Version	v1.0
Software Version	v1.0
Dimensions (Approx.)	161mm x 90mm x 161mm
Weight (Approx.)	600g
Network and Wireless connectivity	Bluetooth, RFID

2.5 Ancillary Equipment

	Battery	
	Brand Name	EEMB
	Model No.	LP605590
Ancillary Equipment 1	Serial No.	N/A
	Capacitance	3400 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	USB Cable	
Ancillary Equipment 2	Length(Approx.)	85 cm



2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	RFID, Bluetooth		
Frequency Range	RFID	902.75 MHz ~ 927.25 MHz	
Frequency Kange	Bluetooth	2400 MHz ~ 2483.5	5 MHz
Antonna Typo	RFID: Plastic Loaded Patch Antenna		
Antenna Type	Bluetooth: Ceramic Chip Antenna		
DTM	Not Support		
Hotspot Function	Not Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Туре		
Product	□ Production ur	nit	☐ Identical prototype



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title	
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules	
•		and Regulations	
2	ANSI/IEEE Std.	IEEE Standard for Safety Levels with Respect to Human Exposure	
	C95.1-1999	to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz	
	IEEE Std. 1528- 2013	Recommended Practice for Determining the Peak Spatial-Average	
3		Specific Absorption Rate (SAR) in the Human Head from Wireless	
		Communications Devices: Measurement Techniques	
4	FCC KDB 447498	Mobile and Portable Device RF Exposure Procedures and	
4	D01 v06	Equipment Authorization Policies	
_	FCC KDB 865664	SAR Measurement 100 MHz to 6 GHz	
5	D01 v01r04		
	FCC KDB 865664	RF Exposure Reporting	
6	D02 v01r02		
7	FCC KDB 648474	CAR Evaluation Considerations for Wireless Handacts	
/	D04 v01r03	SAR Evaluation Considerations for Wireless Handsets	

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, Handheld SAR limit is 4.0 W/kg as averaged over any 10 gram of tissue.

Table of Exposure Limits:

	SAR Value (W/Kg)				
Body Position	General Population/	Occupational/			
	Uncontrolled Exposure	Controlled Exposure			
Whole-Body SAR	0.08	0.4			
(averaged over the entire body)	0.08	0.4			
Partial-Body SAR	1.60	8.0			
(averaged over any 1 gram of tissue)	1.00	8.0			
SAR for hands, wrists, feet and					
ankles	4.0	20.0			
(averaged over any 10 grams of tissue)					



NOTE:

General Population/Uncontrolled: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.



3.3 Test Result Summary

3.3.1 Highest SAR (10 g Value)

Band	Maximum Scaled SAR 10g (W/kg) Handheld	Maximum Report SAR 10g (W/kg) Handheld	Limit (W/kg)
RFID	0.707	0.707	4.0
Verdict		Pass	

3.3.2 Highest Simultaneous SAR

Position	Simultaneous Configuration	Simultaneous SAR (W/kg)	Limit (W/kg)	Verdict
Handheld	RFID + Bluetooth	0.715	4.0	Pass



3.4 Test Uncertainty

3.4.1 Measurement uncertainly evaluation for SAR test

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528 This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

offiliderice level using a coverage factor of k=2.	Tol	Prob.	·	Ci	Ci	1g Ui	10g Ui	
Uncertainty Component	(+- %)	Dist.	Div.	(1g)	(10g)	(+-%)	(+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	0.7	0.7	1.41	1.41	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0.7	0.7	2.38	2.38	~
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	~
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	~
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algoritms for	0.0	1	$\sqrt{3}$	4	4	4.00	4.00	
Max. SAR Evaluation	2.3	R	√3	1	1	1.33	1.33	∞
Test Sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	N-1
Device Holder Uncertainty	1.0	N	1	1	1	1.00	1.00	N-1
Output power Variation - SAR drift measurement	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Liquid conductivity (deviation from target values)	2.5	N	$\sqrt{3}$	0.64	0.43	0.92	0.62	∞
Liquid conductivity - measurement uncertainty	5.0	N	1	0.64	0.43	3.20	2.15	M
Liquid permittivity (deviation from target values)	2.5	N	$\sqrt{3}$	0.60	0.49	0.87	0.71	∞
Liquid permittivity - measurement uncertainty	5.0	N	1	0.60	0.49	3.00	2.45	M
Combined Standard Uncertainty		RSS				10.14	9.67	
Expanded Uncertainty (95% Confidence interval)		k				20.29	19.35	



3.4.2 Measurement uncertainly evaluation for system check

This measurement uncertainty budget is suggested by IEEE 1528. The break down of the individual uncertainties is as follows:

das ioliows.	Tol	Prob.		Ci	Ci	1g Ui	10g Ui	
Uncertainty Component		Dist.	Div.	(1g)	(10g)	(+-%)	(+-%)	Vi
Measurement System	•			•				
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	0.7	0.7	1.41	1.41	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0.7	0.7	2.38	2.38	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Probe Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance		R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell		R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algoritms for	2.3	R	$\sqrt{3}$	1	1	1.33	1 22	∞
Max. SAR Evaluation	2.3	K	ν3	'	1	1.33	1.33	
Dipole								
Deviation of experimental dipole	5.5	R	$\sqrt{3}$	1	1	3.20	3.20	∞
Dipole axis to liquid distance	2.0	R	1	1	1	1.20	1.20	∞
Power drift	4.7	R	$\sqrt{3}$	1	1	2.70	2.70	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Liquid conductivity (deviation from target values)	2.5	N	$\sqrt{3}$	0.64	0.43	0.92	0.62	∞
Liquid conductivity - measurement uncertainty	5.0	N	1	0.64	0.43	3.20	2.15	M
Liquid permittivity (deviation from target values)	2.5	N	$\sqrt{3}$	0.60	0.49	0.87	0.71	∞
Liquid permittivity - measurement uncertainty	5.0	N	1	0.60	0.49	3.00	2.45	M
Combined Standard Uncertainty		RSS				10.22	9.75	
Expanded Uncertainty		k				20.44	19.50	
(95% Confidence interval)								



4 SAR MEASUREMENT SYSTEM

4.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational / controlled exposure limits are higher than the limits for general population /uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

 $\boldsymbol{\rho}$ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 SATIMO SAR System

4.2.1 SATIMO SAR System Diagram






These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 850 mm), which positions the probes with a positional repeatability of better than \pm 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit.

The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in SAR standard with accuracy of better than ±10%. The spherical isotropy was evaluated with the procedure described in SAR standard and found to be better than ±0.25 dB. The phantom used was the SAM Phantom as described in FCC supplement C, IEEE P1528.

4.2.2 Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- · High precision (repeatability ±0.035 mm)
- · High reliability (industrial design)
- · Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

4.2.3 E-Field Probe

For the measurements the Specific Dosimetric E-Field Probe SN 34/15 EPGO 265 with following specifications is used

-- Dynamic range: 0.01-100 W/kg

- Tip Diameter: 2.5 mm

Lower detection limit: 7 mW/kg (repeatability better than +/- 1mm)
Probe linearity: +/- 0.07 dB




- Calibration range: 450 MHz to 5800 MHz for head & body simulating liquid. Angle between probe axis (evaluation axis) and surface normal line: less than 30°



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC62209-1/2 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\sigma} \cos^2\left(\pi \frac{y}{a}\right) c^{(2\pi/\sigma)}$$

Where:

Pfw = Forward Power Pbw = Backward Power

a and b = Waveguide Dimensions

ı = Skin Depth

Keithley configuration

Rate = Medium; Filter = ON; RDGS=10; FILTER TYPE = MOVING AVERAGE; RANGE AUTO After each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.



The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are: CF(N)=SAR(N)/VIin(N) (N=1,2,3)

The linearised output voltage Vlin(N) is obtained from the displayed output voltage V(N) using $Vlin(N)=V(N)^*(1+V(N)/DCP(N))$ (N=1,2,3)

Where the DCP is the diode compression point in mV.



4.2.4 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


Photo of Phantom SN 30/13 SAM103

Photo of Phantom SN 30/13 SAM104



Serial Number	Positionner Material	Permittivity	Loss Tangent
SN 30/13 SAM103	Gelcoat with fiberglass	3.4	0.02
SN 30/13 SAM104	Gelcoat with fiberglass	3.4	0.02





Serial Number		Left Head	Right Head			Flat Part		
	2	2.00	2	2.03	1	2.09		
	3	2.02	3	2.05	2	2.10		
	4	2.04	4	2.04	3	2.09		
CN 20/42 CAM402	5	2.04	5	2.07	4	2.11		
SN 30/13 SAM103	6	2.02	6	2.07	5	2.11		
	7	2.01	7	2.09	6	2.09		
	8	2.04	8	2.10	7	2.11		
	9	2.02	9	2.09	-	-		
	2	2.05	2	2.06	1	2.03		
	3	2.08	3	2.03	2	2.03		
	4	2.05	4	2.03	3	2.01		
CN 20/42 CAM404	5	2.06	5	2.02	4	2.03		
SN 30/13 SAM104	6	2.08	6	2.02	5	2.03		
	7	2.06	7	2.04	6	2.00		
	8	2.07	8	2.04	7	1.98		
	9	2.07	9	2.05	-	-		



4.2.5 Device Holder

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of \pm 0.5 mm would produce a SAR uncertainty of \pm 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.




Serial Number	Holder Material	Permittivity	Loss Tangent
SN 25/13 MSH87	Deirin	3.7	0.005
SN 25/13 MSH88	Deirin	3.7	0.005

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	σ (S/m)	3
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Fraguesov/MLI=\	Water	H	lexyl Carbito	ol	Triton X-100		Conductivity	Permittivity
Frequency(MHz)	(%)		(%)		(%	6)	σ (S/m)	3
5200	62.52		17.24		17.24		4.66	36.0
5800	62.52		17.24		17.24		5.27	35.3
		Body (Fro	m instrun	nent man	ufacturer)			
Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	σ (S/m)	ε
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5





Frequency(MHz)	Water	DGBE	Salt	Conductivity	Permittivity
Frequency(IVII 12)	vvalei	(%)	(%)	σ (S/m)	ε
5200	78.60	21.40	/	5.54	47.86
5800	78.50	21.40	0.1	6.0	48.20



5 SYSTEM VERIFICATION

5.1 Antenna Port Test Requirement


The SATIMO SAR system is equipped with one or more system validation kits. These units together with the predefined measurement procedures within the SATIMO software enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

5.2 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.3 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:





6 EUT TEST POSITION CONFIGURATUONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

6.1.1 Define two imaginary lines on the handset

- (a) The vertical center line passes through two points on the front side of the handset the midpoint of the width w t of the handset at the level of the acoustic output, and the midpoint of the width w b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



6.1.2 Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.





6.1.3 Tilted Position

- (a) To position the device in the "cheek" position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.



6.2 Body-worn Position Conditions


Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worstcase exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by




users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance <= 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions


For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





7 SAR MEASUREMENT PROCEDURES

7.1 SAR Measurement Process Diagram





7.2 SAR Scan General Requirements

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz	
Maximum distance from	closest meas	surement point	5±1 mm	½·δ·ln(2)±0.5 mm	
(geometric center of prob	e sensors) t	o phantom surface	3±1 IIIII	72°0°111(2)±0.5 111111	
Maximum probe angle from	om probe axi	s to phantom surface	30°±1°	20°±1°	
normal at the measurement	ent location		30 ±1	20 ±1	
			≤ 2 GHz: ≤ 15 mm	3–4 GHz: ≤ 12 mm	
			2 – 3 GHz: ≤ 12 mm	4 – 6 GHz: ≤ 10 mm	
			When the x or y dimension of t	he test device, in the	
Maximum area scan spat	ial resolution	n: ∆x Area , ∆y Area	measurement plane orientation	n, is smaller than the above,	
			the measurement resolution m	ust be ≤ the corresponding x	
			or y dimension of the test device	ce with at least one	
			measurement point on the test device.		
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm	3–4 GHz: ≤ 5 mm*	
waximum zoom scan spa	atiai resolutio	п: Δх 200m , Δу 200m	2 –3 GHz: ≤ 5 mm*	4 – 6 GHz: ≤ 4 mm*	
			≤ 5 mm	3–4 GHz: ≤ 4 mm	
	unifor	m grid: Δz Zoom (n)		4–5 GHz: ≤ 3 mm	
				5–6 GHz: ≤ 2 mm	
Maximum zoom scan		∆ z Zoom (1):		3–4 GHz: ≤ 3 mm	
spatial resolution,		between 1st two	≤ 4 mm	4–5 GHz: ≤ 2.5 mm	
normal to phantom	graded	points closest to	2411111	5–6 GHz: ≤ 2 mm	
surface	graded	phantom surface		5–0 GHZ. ≤ 2 IIIIII	
	gna	∆ z Zoom (n>1):	≤ 1.5·Δz 2	Zoom (n-1)	
		between subsequent			
		points			
Minimum zoom				3–4 GHz: ≥ 28 mm	
scan volume		x, y, z	≥30 mm	4–5 GHz: ≥ 25 mm	
Scari volume				5–6 GHz: ≥ 22 mm	

Note:

- 1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
- 2. *When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is \leq 1.4 W/kg, \leq 8 mm, \leq 7 mm and \leq 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



7.3 SAR Measurement Procedure

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



8 CONDUCTED RF OUPUT POWER

8.1 RFID

Mode	Channal	Freq.	Peak Power
Mode	Channel	(MHz)	(dBm)
RFID	1	902.75	26.39
	26	915.25	26.28
	50	927.25	25.88

8.2 Bluetooth

Mode	BLE			
Channel	0	19	39	
Frequency (MHz)	2402	2440	2480	
Peak Power (dBm)	-0.31	-1.21	-3.84	


8.3 Rated RF Power Output

Mode	Range(dBm)
RFID	25.75-26.50

Band	Mode	Range(dBm)
Bluetooth	BLE	(-3.95)-(-0.20)



9 EUT ANTENNA LOCATION SKETCH





9.1 SAR Test Exclusion Consider Table

According with FCC KDB 447498 D01, Appendix A, <SAR Test Exclusion Thresholds for 100 MHz − 6 GHz and ≤ 50 mm> Table, this Device SAR test configurations consider as following :

		May Boy	Max. Peak Power		Test Position Configurations						
Band	Mode	IVIAX. Ped	ak Powei	Hand-held	Hand-held	Hand-held	Hand-held	Hand-held	Hand-held		
		dBm	mW	Front	Back	Left	Right	Тор	Bottom		
RFID	Distan	ce to User		8 mm	25 mm	11 mm	11 mm	68 mm	21 mm		
Krib	RFID	26.50	446.68	Yes	No	Yes	Yes	Yes	Yes		
Bluetooth	Distan	ce to User		94 mm	63 mm	63mm	120 mm	21 mm	98 mm		
Didelootii	Bluetooth BLE	-0.20	0.95	No	No	No	No	No	No		

Note:

- 1. Maximum power is the source-based time-average power and represents the maximum RF output power among production units.
- 2. Per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- 3. Per KDB 447498 D01, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
- 4. Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- a. f(GHz) is the RF channel transmit frequency in GHz
- b. Power and distance are rounded to the nearest mW and mm before calculation
- c. The result is rounded to one decimal place for comparison
- d. For < 50 mm distance, we just calculate mW of the exclusion threshold value (3.0) to do compare.

This formula is [3.0] / [$\sqrt{f(GHz)}$] ·[(min. test separation distance, mm)] = exclusion threshold of mW.

- 5. Per KDB 447498 D01, at 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a. [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b. [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz



10 TEST RESULTS

10.1 RFID (Extremity SAR)

Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (%)	10 g Meas. SAR (W/Kg)	Meas. Power (dBm)	Max. tune-up Power(dBm)	Scaling Factor	10 g Scaled SAR (W/Kg)	Meas. No.
Handheld	Handheld										
	Front Side	0	1	902.75	-3.41	0.668	26.39	26.50	1.03	0.685	/
	Left Edge	0	1	902.75	-3.12	0.218	26.39	26.50	1.03	0.224	/
RFID	Right Edge	0	1	902.75	-3.08	0.180	26.39	26.50	1.03	0.185	/
	Top Edge	0	1	902.75	-2.84	0.048	26.39	26.50	1.03	0.049	/
	Bottom Edge	0	1	902.75	0.72	0.689	26.39	26.50	1.03	0.707	1#
Note 1: F	Refer to ANNE	C for th	e detaile	d test dat	a for each	n test con	figuration.				



11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

- 1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
- 2. When the highest measured SAR is >= 0.80 W/kg, repeat that measurement once.
- 3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20, or when the original or repeated measurement is >= 1.45 W/kg, perform a second repeated measurement.
- 4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20, and the original, first or second repeated measurement is >= 1.5 W/kg, perform a third repeated measurement.

The following procedures are applied to determine if repeated measurement are required. The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor 5 for occupational exposure to the corresponding SAR thresholds.

The highest measured SAR is 0.707 W/kg less than 4.0 W/kg, so repeated measurement is not required



12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 10g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR for hands, wrists, feet and ankles limit (SAR 10g 4.0 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 10g is greater than the SAR for hands, wrists, feet and ankles limit (SAR 10g 4.0 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Consider

NO	Mada	+ Bluetooth
NO.	Mode	Body
1	RFID	+Bluetooth



12.2Estimated SAR Calculation

According to KDB 447498 D01 when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of <= 1 W/kg to determine simultaneous transmission SAR test exclusion.

Estimated SAR =
$$\frac{Max.Tune\ Up\ Power(mw)}{Min\ Test\ Separation\ Dis\ tan\ ce} * \frac{\sqrt{f_{GHz}}}{x}$$
 (where $_x$ = 18.75 for 10-g SAR)

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 1 W/kg is used for SAR-10g.

Band	Mode	Position	Antenna To user (mm)	SAR Testing	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Frequency (GHz)	Calculation Distance/Gap (mm)	Estimated SAR (W/kg)
		Front side	10	NO	-0.20	0.95	2.402	10	0.008
Bluetooth	GFSK	Right Edge	10	NO	-0.20	0.95	2.402	10	0.008
Didelootii	GFSK	Bottom Edge	10	NO	-0.20	0.95	2.402	10	0.008
		Top Edge	10	NO	-0.20	0.95	2.402	10	0.008



12.3Sum SAR of Simultaneous Transmission

12.3.1 Sum Handheld SAR of Simultaneous Transmission

Simultaneous Mode	Mode	Max. 10g SAR (W/kg)	10g Sum SAR (W/kg)	SPLSR (Yes/No)	
RFID + Bluetooth	RFID	0.707	0.715	No	
KEID + Bluetootti	Bluetooth	0.008	0.715	No	



13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
900 MHz Dipole	SATIMO	SID 900	S/N 25/13 DIP 0G900-247	2015/03/16	2018/03/15
E-Field Probe	MVG	SSE2	S/N 34/15 EPGO 265	2016/09/15	2017/09/14
Antenna	SATIMO	ANTA3	SN 17/13 ZNTA45	N/A	N/A
Phantom1	SATIMO	SAM	SN 30/13 SAM103	N/A	N/A
Phantom2	SATIMO	SAM	SN 30/13 SAM104	N/A	N/A
Dielectric Probe Kit	SATIMO	SCLMP	SN 25/13 OCPG56	2016/07/13	2017/07/12
MultiMeter	Kaithlay	MultiMeter	4024022	2016/07/13	2017/07/12
Multiweter	Keithley	2000	4024022	2010/07/13	2017/07/12
Signal Generator	R&S	SMF100A	1167.0000k02/104260	2016/07/13	2017/07/12
Power Meter	Agilent	E4419B	GB40201833	2016/07/13	2017/07/12
Power Sensor	Agilent	E9300A	MY41498012	2016/07/13	2017/07/12
Power Sensor	Agilent	E9300A	MY41499891	2016/07/13	2017/07/12
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Network Analyzer	R&S	ZVL-6	101380	2016/07/13	2017/07/12
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: Per KDB 865664 Dipole SAR Validation Verification, BALUN LAB has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss in within 20% of calibrated measurement.



ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (℃)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ε)	Target Conductivity (σ) (S/m)	Target Permittivity (ε)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2017.06.01	Body	900	21.2	1.06	56.49	1.05	55.00	0.95	2.71

Note: The tolerance limit of Conductivity and Permittivity is± 5%.



ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10% (for 10 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)	Targeted SAR(W/kg)	Tolerance (%)
2017.06.01	Body	900	100	0.747	7.47	7.25	2.72	6.99	7.34
Note: The tol	Note: The tolerance limit of System validation ±10%.								



System Performance Check Data(900 MHz Body)

Type: Phone measurement (Complete) E-Field Probe: SN 34/15 SSE2 EPGO265 Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2017.06.01

Measurement duration: 13 minutes 38 seconds

Experimental conditions.


Phantom File	surf_sam_plan.txt
Phantom	Validation plane
Band	900MHz
Signal	CW
Frequency (MHz)	900.000000
Relative permittivity (real part)	56.490438
Conductivity (S/m)	1.063187
Power drift (%)	0.280000
Ambient Temperature:	22.3°C
Liquid Temperature:	21.2°C
ConvF:	1.92
Crest factor:	1:1






Maximum location: X=1.00, Y=-1.00 SAR Peak: 1.67 W/kg

SAR 10 g (W/Kg)	0.747369
SAR 1g (W/Kg)	1.170173







ANNEX C TEST DATA

MEAS. 1 Body Plane with Bottom Side 0mm on Channel 1 in RFID mode

Test Date: 1/6/2017

Measurement duration: 11 minutes 8 seconds

Signal: RFID, f=902.75 MHz, Duty Cycle: 1:1.0 **Liquid Parameters:** Permittivity: 56.17; Conductivity: 1.06 S/m


Test condition: Ambient Temperature: 22.3°C, Liquid Temperature: 21.2°C

Probe:SN 34/15 SSE2 EPGO265, ConvF: 1.92Area Scan:sam_direct_droit2_surf10mm.txt, h= 5.00 mmZoom Scan:5x5x7,dx=8mm, dy=8mm, dz=5mm,Complete


Maximum location: X=-10.000000, Y=-12.000000

SAR 10g (W/Kg): 0.688579 SAR 1g (W/Kg): 1.183767 Power drift (%): 0.72

3D screen shot



Z Axis Scan





ANNEX D EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1730414-AW.pdf".

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document "BL-SZ1730414-AS.pdf".

ANNEX F CALIBRATION REPORT

Please refer the document "CALIBRATION REPORT.pdf".

--END OF REPORT--