

849 NW State Road 45 Newberry, FL 32669 USA Phone: 888.472.2424 or

352.472.5500

Fax: 352.472.2030

Email: <u>info@timcoengr.com</u>
Website: <u>www.timcoengr.com</u>

FCC PART 97 AMATEUR RADIO TEST REPORT

| Applicant | TOKYO HY-POWER LABS, INC. | | |
|----------------------------|---------------------------|--|--|
| Address | 1-1 HATANAKA 3 CHOME, | | |
| | NIIZA SAITAMA | | |
| | 352-0012 JAPAN | | |
| FCC ID | UB9HL-15Kfx | | |
| Model Number | HL-1.5Kfx | | |
| Product Description | LINEAR AMP | | |
| Date Sample Received | 5/2/2006 | | |
| Date Tested | 6/5/2006 | | |
| Tested By | RICHARD BLOCK | | |
| Approved By | FRANK DENUZZO | | |
| Report Number | 895UT6 TestReport | | |
| Total Pages | 25 | | |
| Test Results | | | |

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.





TABLE OF CONTENT

| STATEMENT OF COMPLIANCE | 3 |
|--|----|
| GENERAL INFORMATION | 4 |
| EMC EQUIPMENT LIST | 6 |
| TEST PROCEDURES | 7 |
| RF POWER OUTPUT | 8 |
| SPURIOUS EMISSIONS - INTER MODULATION DISTORTION | 10 |
| FIELD STRENGTH OF SPURIOUS EMISSIONS | 17 |
| AC CONDUCTED POWER | 21 |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





STATEMENT OF COMPLIANCE

This equipment has been tested in accordance with the standards identified in the referenced test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report and demonstrate that the equipment complies with the appropriate standards. No modifications were made to the equipment during testing in order to demonstrate compliance with these standards.

I attest that the necessary measurements were made by me or under my supervision, at TIMCO ENGINEERING, INC. located at 849 N.W. State Road 45, Newberry, Florida 32669 USA.

Authorized by: Frank DeNuzzo

Frenh Delluggo

Signature:

Function: Engineer

Date: June 15, 2006

Tested by: Richard Block

Signature: on file

Date: June 15, 2006

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





GENERAL INFORMATION

DUT Specification

| The test results relate only to the items tested. | | | |
|---|--|--|--|
| DUT Description | LINEAR AMPLIFIER | | |
| FCC ID | UB9HL-15KFX | | |
| Model Number | HL-1.5Kfx | | |
| Serial Number | N/A | | |
| Operating Frequency | 1.8-21 MHz (as sold), 1.8-30MHz and 50-54MHz | | |
| | (Amateur Service only) | | |
| No. of Channels | Single | | |
| Type of Emission | N/A | | |
| Modulation | | | |
| DUT Power Source | ☑ 240 VAC/50– 60Hz; 120 VAC/50-60Hz | | |
| | ☐ DC Power | | |
| | ☐ Battery Operated Exclusively | | |
| Test Item | ☐ Prototype | | |
| | □ Pre-Production | | |
| | ☐ Production | | |
| Type of Equipment | ⊠ Fixed | | |
| | ☐ Mobile | | |
| | ☐ Portable | | |
| Antenna | N/A | | |
| Antenna Connector | PL 259 | | |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX



Test Facility: The test sites used by Timco Engineering Inc. for radiated and conducted emission data are located at 849 NW State Road 45 Newberry, FL 32669 USA.

Test Condition: The DUT was tested in the laboratory in an environment with normal temperature and humidity. The temperature was 26°C with a relative humidity of 50%.

Modification to the DUT: No modification was made to the DUT during testing.

Test Exercise (e.g software description, test signal, etc.): The DUT was placed in continuous transmit mode of operation.

Applicable Standards: TIA 603 & ANSI C63.4 – 2003

FCC CFR 47 Part 97 FCC CRF 47 Part 15

Other information:

The amplifier is capable of operation in the amateur radio bands below 30 MHz and additionally in the 6 meter amateur band (50-54 MHz). The amplifier is NOT capable of operation on any frequency or frequencies between 24 MHz and 35 MHz as marketed. Instructions for modification to operate in the 12 meter, 10 meter, and 6 meter bands are available only to licensed amateur radio operators upon request from the manufacturer. The amplifier is shipped with 24.5 MHz, 28 MHz, and 50 MHz bands disabled and inoperative.

- 1. The amplifier is incapable of amplification above 54 MHz.
- 2. The amplifier requires 80 Watts of drive to obtain full output power. Reduction in RF input power reduces the output power as shown on Page 8.
- 3. The conducted spurious emissions tables are shown on Pages 17 through 20. The amplifier was modified per manufacturer's instructions to verify spurious RF radiation in the 24 MHz, 28 MHz, and 50 MHz amateur bands. This information is shown separately on Page 20.
- 4. The gain of the amplifier is under 15 dB on all bands and under all conditions.
- 5. The amplifier in the off or standby state does not amplify and merely passes through the exciter energy to the antenna port. The spurious emissions of the transceiver were unaffected.

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





EMC EQUIPMENT LIST

| Device | Manufacturer Model Serial | | Serial Number | Cal/Char Date | Due Date |
|--|-----------------------------------|------------------|--------------------------|------------------|----------|
| Analyzer Tan Tower Spectrum Analyzer | HP | 8566B Opt 462 | 3138A07786 3144A20661 | CAL 12/7/05 | 12/7/07 |
| Analyzer Tan Tower RF Preselector | НР | 85685A | 3221A01400 | CAL 12/7/05 | 12/7/07 |
| Analyzer Tan Tower Quasi-Peak Adapter | НР | 85650A | 3303A01690 | CAL 12/8/05 | 12/8/07 |
| Analyzer Tan Tower Preamplifier | HP | 8449B-H02 | 3008A00372 | CAL 12/8/05 | 12/8/07 |
| Antenna: Biconnical | Electro- Metrics | BIA-25 | 1171 | CAL 4/29/05 | 4/29/07 |
| Antenna: Log-Periodic | Electro- Metrics | LPA-25 | 1122 | CAL 8/26/04 | 8/26/06 |
| Antenna: Double- Ridged Horn | Electro- Metrics | RGA-180 | 2319 | CAL 12/29/04 | 12/29/06 |
| LISN | Electro- Metrics | ANS-25/2 | 2604 | CAL 8/27/04 | 8/27/06 |
| Termaline Wattmeter | Bird Electronic Corporation | 611 | 16405 | CAL 7/16/04 | 7/16/06 |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





TEST PROCEDURES:

Radiation Interference: The test procedure used was TIA 603 using a HEWLETT PACKARD spectrum analyzer with a pre-selector. In the frequency range 10 kHz to 30 MHz the RBW was 10 kHz and from 30-1000 MHz the RBW of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz.

Formula Of Conversion Factors: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) Meter Reading + ACF + CL = FS

33 20 dBuV + 10.36 dB/m + 0.4 dB = 30.76 dBuV/m @ 3m

TIA 603 Measurement Procedures: The DUT was placed on a non-conducting table 80 cm above the ground plane with the DUT located in the center of the table. With the antenna vertical a preliminary scan was done at 1 meters distance, the DUT was moved to a 3.0-meter distance and the antenna height varied and also placed in a horizontal position. The frequency was scanned from 9.0 kHz to 1.0 GHz. When an emission was found, the table was rotated to produce the maximum signal strength.

Part 97.313

Power Output Power shall not exceed 1.5 PEP Watts into a 50 ohm resistive load. There are no user power controls.

Part 2.1033(c)(8)

DC Voltages and Current into Final Amplifier:

INPUT POWER - (60Volts)(50Amps) = 3000 Watts

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






RF POWER OUTPUT

Rule Parts No.: Part 2.1046(a), Part 97.313

Requirements: 97.313

Test Procedure: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector with a nominal input voltage of 240 AC Volts. The transmitter was properly adjusted and the maximum RF output power was measured at 900 Watts.

Test Setup:



Test Data:

Output Power: With disabling jumper (as sold) (Input/Output: Not to exceed 15 dB Gain)

| Freq (MHz) | Power in (W) | Power out (W) |
|------------|--------------|---------------|
| 1.900 | 80 | 850 |
| 3.750 | 80 | 850 |
| 7.150 | 80 | 900 |
| 10.125 | 80 | 800 |
| 14.150 | 80 | 900 |
| 18.110 | 80 | 900 |
| 21.200 | 80 | 900 |

(Input/Output= 0 dB gain)

| 11 | out, output of | 1D Sail) |
|--------|----------------|----------|
| 24.890 | >=60 | 40 |
| 28.000 | >=60 | 40 |
| 29.700 | >=60 | 40 |
| 52.000 | >=60 | 40 |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






RF POWER OUTPUT (with modification)

Rule Parts No.: Part 2.1046(a), Part 97.313

Requirements: 97.313

Test Procedure: The amplifier was modified per manufacturer's instruction to include the 24, 28, and 50 MHz amateur radio bands and tested. RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector with a nominal input voltage of 240 AC Volts. The transmitter was properly adjusted and the maximum RF output power was measured at 900 Watts.

Test Setup:



Test Data:

Output Power: (Modified for Amateur Service only)

| Freq (MHz) | Power in (W) | Power out (W) |
|------------|--------------|---------------|
| 1.900 | 80 | 850 |
| 3.750 | 80 | 850 |
| 7.150 | 80 | 900 |
| 10.125 | 80 | 800 |
| 14.150 | 80 | 900 |
| 18.110 | 80 | 900 |
| 21.200 | 80 | 900 |

| 24.890 | 80 | 800 |
|--------|----|-----|
| 28.000 | 80 | 850 |
| 29.700 | 80 | 800 |
| 52.000 | 80 | 550 |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





SPURIOUS EMISSIONS - INTER MODULATION DISTORTION

Rule Parts No.: Part 2.1053

Requirements:

Method of Measurement: Exciter operating in SSB (A3E, J3E) mode with two equaltone audio applied to the microphone input. Amplifier under test driven to 900 W PEP output at the center of the band with typically 80 W input power.

Test Data: Please see the following plots

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





2006/03/10

HL-1.5KFX S/N 0520003


INTER MODULATION DISTORTION

Vertical resolution: 10dB/div. Horizontal resolution: 1.5 k Hz/div.

Input signal: Two equal RF signals, separated by 1.5 k Hz.


 $1.82 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) 900W PEP

Input Signals



 $1.9 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) 900W PEP

Input Signals



APPLICANT: TOKYO HY-POWER LABS, INC.


FCC ID: UB9HL-15KFX






3.55MHz (- 750Hz / +750Hz) 900W PEP

Input Signals




 $3.8 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) 900W PEP

Input Signals



 $7.05 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) 900W PEP

Input Signals




FCC ID: UB9HL-15KFX






10.1MHz (- 750Hz / +750Hz) 800W PEP

Input Signals




 $14.3 \mathrm{MHz}$ (- $750 \mathrm{Hz} \, / \, + 750 \mathrm{Hz})$ 900W PEP

Input Signals



 $18.1 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) 900W PEP


Input Signals



FCC ID: UB9HL-15KFX








FCC ID: UB9HL-15KFX






 $28.5 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) $800 \mathrm{W}$ PEP

Input Signals




 $29.5 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) $800 \mathrm{W}$ PEP

Input Signals



 $50.5\mathrm{MHz}$ (- $750\mathrm{Hz}\,/\,+750\mathrm{Hz})$ $500\mathrm{W}$ PEP

Input Signals




FCC ID: UB9HL-15KFX










 $53.9 \mathrm{MHz}$ (- $750 \mathrm{Hz} \, / \, + 750 \mathrm{Hz})$ $500 \mathrm{W} \, \mathrm{PEP}$

 $52.0 \mathrm{MHz}$ (- $750 \mathrm{Hz}$ / + $750 \mathrm{Hz}$) $500 \mathrm{W}$ PEP

Input Signals



APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





STRENGTH OF SPURIOUS EMISSIONS

Rule Parts No.: Part 2.1053 & Part 97.307 (d) (e)


Requirements: The FCC Limits for spurious emissions of a transmitting operating

on a frequency below 30 MHz must be at least 43dB below the mean power. For the transmitter frequency operating at 50 MHz, the RF spurious emissions must be at least 60 dB below the mean power

of the fundamental.

Method Of Measurements:

Test Setup:



Test Data:

(As Sold)

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 1.9 | 1.90 | 59.15 | 0 | N/A |
| 1.9 | 3.80 | -21.58 | 80.73 | PASS |
| 1.9 | 5.70 | -3.06 | 62.21 | PASS |
| 1.9 | 7.60 | -26.00 | 85.15 | PASS |
| 1.9 | 9.50 | -26.00 | 85.15 | PASS |
| 1.9 | 11.40 | -26.00 | 85.15 | PASS |
| 1.9 | 13.30 | -24.38 | 83.53 | PASS |
| 1.9 | 15.20 | -26.00 | 85.15 | PASS |
| 1.9 | 17.10 | -26.00 | 85.15 | PASS |
| 1.9 | 19.00 | -26.00 | 85.15 | PASS |

Note: -26.0 dBm is noise floor

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX





| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 3.75 | 3.75 | 59.93 | 0 | N/A |
| 3.75 | 7.50 | -17.65 | 77.58 | PASS |
| 3.75 | 11.25 | -12.46 | 72.39 | PASS |
| 3.75 | 15.00 | -26.00 | 85.93 | PASS |
| 3.75 | 18.75 | -18.80 | 78.73 | PASS |
| 3.75 | 22.50 | -26.00 | 85.93 | PASS |
| 3.75 | 26.25 | -16.39 | 76.32 | PASS |
| 3.75 | 30.00 | -26.00 | 85.93 | PASS |
| 3.75 | 33.75 | -15.15 | 75.08 | PASS |
| 3.75 | 37.50 | -26.00 | 85.93 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 7.15 | 7.15 | 59.52 | 0 | N/A |
| 7.15 | 14.30 | -7.64 | 67.16 | PASS |
| 7.15 | 21.45 | -14.59 | 74.11 | PASS |
| 7.15 | 28.60 | -26.00 | 85.52 | PASS |
| 7.15 | 35.75 | -19.47 | 78.99 | PASS |
| 7.15 | 42.90 | -26.00 | 85.52 | PASS |
| 7.15 | 50.05 | -26.00 | 85.52 | PASS |
| 7.15 | 57.20 | -26.00 | 85.52 | PASS |
| 7.15 | 64.35 | -17.89 | 77.41 | PASS |
| 7.15 | 71.50 | -26.00 | 85.52 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 10.125 | 10.125 | 59.14 | 0 | N/A |
| 10.125 | 20.250 | -2.54 | 61.68 | PASS |
| 10.125 | 30.375 | 6.15 | 52.99 | PASS |
| 10.125 | 40.500 | -26.00 | 85.14 | PASS |
| 10.125 | 50.625 | -18.22 | 77.36 | PASS |
| 10.125 | 60.750 | -26.00 | 85.14 | PASS |
| 10.125 | 70.875 | -21.67 | 80.81 | PASS |
| 10.125 | 81.000 | -26.00 | 85.14 | PASS |
| 10.125 | 91.125 | -26.00 | 85.14 | PASS |
| 10.125 | 101.250 | -26.00 | 85.14 | PASS |

FCC ID: UB9HL-15KFX





| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 14.15 | 14.150 | 59.55 | 0 | N/A |
| 14.15 | 28.300 | -0.58 | 60.13 | PASS |
| 14.15 | 42.450 | 6.11 | 53.44 | PASS |
| 14.15 | 56.600 | -26.00 | 85.55 | PASS |
| 14.15 | 70.750 | -17.98 | 77.53 | PASS |
| 14.15 | 84.900 | -26.00 | 85.55 | PASS |
| 14.15 | 99.050 | -26.00 | 85.55 | PASS |
| 14.15 | 113.200 | -26.00 | 85.55 | PASS |
| 14.15 | 127.350 | -26.00 | 85.55 | PASS |
| 14.15 | 141.500 | -26.00 | 85.55 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 18.11 | 18.110 | 59.51 | 0 | N/A |
| 18.11 | 36.220 | -2.24 | 61.75 | PASS |
| 18.11 | 54.330 | 2.98 | 56.53 | PASS |
| 18.11 | 72.440 | -26.00 | 85.51 | PASS |
| 18.11 | 90.550 | -26.00 | 85.51 | PASS |
| 18.11 | 108.660 | -26.00 | 85.51 | PASS |
| 18.11 | 126.770 | -26.00 | 85.51 | PASS |
| 18.11 | 144.880 | -26.00 | 85.51 | PASS |
| 18.11 | 162.990 | -26.00 | 85.51 | PASS |
| 18.11 | 181.100 | -26.00 | 85.51 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 21.2 | 21.200 | 59.51 | 0 | N/A |
| 21.2 | 42.400 | -2.24 | 61.75 | PASS |
| 21.2 | 63.600 | 2.98 | 56.53 | PASS |
| 21.2 | 84.800 | -26.00 | 85.51 | PASS |
| 21.2 | 106.000 | -26.00 | 85.51 | PASS |
| 21.2 | 127.200 | -26.00 | 85.51 | PASS |
| 21.2 | 148.400 | -26.00 | 85.51 | PASS |
| 21.2 | 169.600 | -26.00 | 85.51 | PASS |
| 21.2 | 190.800 | -26.00 | 85.51 | PASS |
| 21.2 | 212.000 | -26.00 | 85.51 | PASS |

FCC ID: UB9HL-15KFX





Modified per manufacturer's instructions: For Amateur Service Only

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 24.9 | 24.900 | 59.00 | 0 | N/A |
| 24.9 | 49.800 | -1.00 | 60.00 | PASS |
| 24.9 | 74.700 | 7.50 | 51.50 | PASS |
| 24.9 | 99.600 | -26.00 | 85.00 | PASS |
| 24.9 | 124.500 | -26.00 | 85.00 | PASS |
| 24.9 | 149.400 | -26.00 | 85.00 | PASS |
| 24.9 | 174.300 | -26.00 | 85.00 | PASS |
| 24.9 | 199.200 | -26.00 | 85.00 | PASS |
| 24.9 | 224.100 | -26.00 | 85.00 | PASS |
| 24.9 | 249.00 | -26.00 | 85.00 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 43 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 28.0 | 28.000 | 59.00 | 0 | N/A |
| 28.0 | 56.000 | -2.75 | 61.75 | PASS |
| 28.0 | 84.000 | -11.00 | 70.0 | PASS |
| 28.0 | 112.000 | -26.00 | 85.00 | PASS |
| 28.0 | 140.000 | -26.00 | 85.00 | PASS |
| 28.0 | 168.000 | -26.00 | 85.00 | PASS |
| 28.0 | 196.000 | -26.00 | 85.00 | PASS |
| 28.0 | 224.000 | -26.00 | 85.00 | PASS |
| 28.0 | 252.000 | -26.00 | 85.00 | PASS |
| 28.0 | 280.000 | -26.00 | 85.00 | PASS |

| TF (MHz) | EF (MHz) | M reading (dBm) | dB below carrier | 60 dB Below Fundamental |
|-------------|-------------|--------------------|---------------------|----------------------------|
| 52.0 | 52.000 | 57.40 | 0 | N/A |
| 52.0 | 104.00 | -10.04 | 67.44 | PASS |
| 52.0 | 156.00 | -26.00 | 83.40 | PASS |
| 52.0 | 208.00 | -26.00 | 83.40 | PASS |
| 52.0 | 260.00 | -26.00 | 83.40 | PASS |
| 52.0 | 312.00 | -26.00 | 83.40 | PASS |
| 52.0 | 364.00 | -26.00 | 83.40 | PASS |
| 52.0 | 416.00 | -26.00 | 83.40 | PASS |
| 52.0 | 468.00 | -26.00 | 83.40 | PASS |
| 52.0 | 520.00 | -26.00 | 83.40 | PASS |

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX REPORT: V:\T\THP\895UT6\895UT6 TestReport.doc





POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: Part 15.207

Requirements:

| Frequency (MHz) | Quasi Peak Limits (dBuV) | Average Limits (dBuV) |
|--------------------|-----------------------------|-----------------------|
| 0.15 - 0.5 | 66 – 56 | 56 – 46 |
| 0.5 – 5.0 | 56 | 46 |
| 5.0 – 30 | 60 | 50 |

Test Procedure: ANSI Standard C63.4-2003. The spectrum was scanned from 0.15

to 30 MHz.

Test Data: The attached graphs represent the emissions read for power line

conducted for this device. Both lines were observed.

APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






POWERLINE CONDUCTED PLOT – LINE 1 – 115V

NOTES:

POWER LINE CONDUCTED -- LINE 1 TOKYO HY-POWER LABS, INC. FCC ID: XXX HL-1.5Kfx

FCC 15.107 Mask Class B



APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






POWERLINE CONDUCTED PLOT - LINE 2 - 115V

NOTES:

POWER LINE CONDUCTED -- LINE 2 TOKYO HY-POWER LABS, INC. FCC ID: XXX HL-1.5Kfx

FCC 15.107 Mask Class B



APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






POWERLINE CONDUCTED PLOT - LINE 1 - 230V

NOTES:

POWER LINE CONDUCTED -- LINE 1 TOKYO HY-POWER LABS, INC. FCC ID: XXX HL-1.5Kfx

FCC 15.107 Mask Class B



APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX






POWERLINE CONDUCTED PLOT - LINE 2 - 230V

NOTES:

POWER LINE CONDUCTED -- LINE 2 TOKYO HY-POWER LABS, INC. FCC ID: XXX HL-1.5Kfx

FCC 15.107 Mask Class B



APPLICANT: TOKYO HY-POWER LABS, INC.

FCC ID: UB9HL-15KFX