

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART B &C REQUIREMENT**

OF

Digital Wireless Conference System

MODEL No.: EW023C, EW023D, EW023M

Trademark: 

FCC ID: UBTEW023

REPORT NO: E0807682F

ISSUE DATE: October 22, 2008

Prepared for
**Ningbo Soundking Group Co., Ltd.
818#, Chengxin Road, Yinzhou Investment Industry P,
Ningbo City, Zhejiang Province, P.R.China.**

Prepared by
DONGGUAN EMTEK CO., LTD

**No.281,Guantai Road,Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

VERIFICATION OF COMPLIANCE

Applicant:	Ningbo Soundking Group Co., Ltd. 818#, Chengxin Road, Yinzhou Investment Industry P, Ningbo City, Zhejiang Province, P.R.China.
Product Description:	Digital Wireless Conference System
Trademark:	
Model Number:	EW023C, EW023D, EW023M (Note: The samples are the same, except the appearance is different; we prepare EW023C for EMC test. The three models are based on the same FCC ID No.UBTEW023.)
File Number:	E0807682F
Date of Test:	October 15, 2008 to October 20, 2008

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.249.

The test results of this report relate only to the tested sample identified in this report.

Approved By


David Lee

David Lee / Q.A. Manager
DONGGUAN EMTEK CO., LTD.

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	5
1.3 TEST METHODOLOGY	5
1.4 SPECIAL ACCESSORIES.....	5
1.5 EQUIPMENT MODIFICATIONS	5
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE.....	7
2.3 TEST PROCEDURE.....	7
2.4 LIMITATION	7
2.5 CONFIGURATION OF TESTED SYSTEM.....	9
3. SUMMARY OF TEST RESULTS	10
4. DESCRIPTION OF TEST MODES.....	10
5. CONDUCTED EMISSIONS TEST (NOT APPLY IN THE REPORT)	11
5.1 MEASUREMENT PROCEDURE:.....	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	11
5.3 MEASUREMENT EQUIPMENT USED:	11
5.4 MEASUREMENT RESULT:.....	11
5.5 CONDUCTED MEASUREMENT PHOTOS:.....	11
6. RADIATED EMISSION TEST	12
6.1 MEASUREMENT PROCEDURE.....	12
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	13
6.3 MEASUREMENT EQUIPMENT USED:	14
6.4 OUT OF BAND RADIATED MEASUREMENT RESULT	14
6.5 RADIATED MEASUREMENT PHOTOS:	18
7. OCCUPIED BANDWIDTH.....	19
7.1 MEASUREMENT PROCEDURE	19
7.2 TEST SET-UP(BLOCK DIAGRAM OF CONFIGURATION).....	19
7.3 MEASUREMENT EQUIPMENT USED:	19
7.4 MEASUREMENT RESULTS:	19
8. BAND EDGE TEST	22
8.1 MEASUREMENT PROCEDURE	22
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	22
8.3 MEASUREMENT RESULTS:	22
9. ANTENNA APPLICATION.....	23

9.1 ANTENNA REQUIREMENT.....	23
9.2 ANTENNA CONSTRUCTION AND DIRECTIONAL GAIN.....	23

1.1 Product Description

The Ningbo Soundking Group Co., Ltd.. Model: EW023C (referred to as the EUT in this report) The EUT is an short range, lower power, Digital Wireless Conference System designed as an " Input Device". It is designed by way of utilizing the GFSK modulation achieves the system operating.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: Group A : 2.402, 2.410, 2.419, 2.431, 2.439GHz
Group B : 2.402, 2.452, 2.460, 2.473, 2.481GHz
- B). Modulation: GFSK
- C). Number of Channel: 10
- D). Antenna Designation: internal
- E). Power Supply: DC 3.3V

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: UBTEW023 filing to comply with Section 15.249 of the FCC Part 15, Subpart B and Subpart C Rules, The composite system (receiver) is compliance with Subpart B is authorized under a VoC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description
EMC Lab. : Accredited by CNAS, 2007.07.27
The certificate is valid until 2012.07.26
The Laboratory has been assessed and proved to be in compliance
with CNAS/CL01:2005
The Certificate Registration Number is L3150

Accredited by TUV Rheinland Shenzhen, 2008.5
The certificate is valid until 2009.12
The Laboratory has been assessed according to the requirements
ISO/IEC 17025:1999

Accredited by FCC, January 03, 2006
The Certificate Registration Number is 247565.

Accredited by Industry Canada, August 30, 2005
The Certificate Registration Number is 46405-4480

Name of Firm : DONGGUAN EMTEK CO., LTD
Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

1. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions (Not apply in the report)

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the **frequency range between 0.15 MHz and 30MHz** using **CISPR Quasi-Peak and average detector mode**.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

2.4 Limitation

(1) Conducted Emission (Not apply in the report)

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Radiated Emissions FCC Rule: 15.249(a)

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency(MHz)	Filed Strength of Fundamental(at 3m)		Filed Strength of Harmonics(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88.0	68.0

Radiated Emissions

FCC Rule: 15.249(d)(e)

FCC Part 15, Subpart C Section 15.209 limit of radiated emission for frequency below 1000GHz. The emissions from an intentional radiator shall not exceed the field strength level specified in the following table:

Frequency (MHz)	Field strength μ V/m	Distance(m)	Field strength at 3m $\text{dB}\mu\text{V/m}$
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

Remark: 1. Emission level in $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

FCC Part 15, Section 15.35(b) limit of radiated emission for frequency above 1000MHz

Frequency(MHz)	Class A($\text{dB}\mu\text{V/m}$)(at 3m)		Class B($\text{dB}\mu\text{V/m}$)(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

2.5 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Digital Wireless Conference System	Soundking	EW023C	UBTEW023	N/A	EUT

Note:

(1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

2. Summary Of Test Results

FCC Rules	Description Of Test	Result
§ 15.207	Conducted Emission	N/A
§ 15.249 (a),(b),(d) (e) § 15.209	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant

3. Description of test modes

The EUT (Digital Wireless Conference System) has been tested under normal operating condition. Three channels of EUT (the lowest channel, the middle channel and the highest channel) have been chosen for testing under Normal Operating condition. In this report, all the measured datum of the three channels have been reported. No software used to control the EUT for staying in continuous transmitting mode for testing.

Channel	Frequency(MHz)
Group A 1	2402MHz
Group A 5	2439MHz
Group B 5	2481MHz

4. Conducted Emissions Test (Not apply in the report)

5.1 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the three highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)

5.3 Measurement Equipment Used:

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2008	05/29/2009
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2008	05/29/2009
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2008	05/29/2009
50ΩCoaxial Switch	Anritsu	MP59B	M20531	05/29/2008	05/29/2009

5.4 Measurement Result:

N/A

5.5 Conducted Measurement Photos:

N/A


5. Radiated Emission Test

6.1 Measurement Procedure


- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSP7	839511/010	05/29/2008	05/29/2009
Spectrum Analyzer	HP	E4407B	839840481	05/29/2008	05/29/2009
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2008	05/29/2009
Pre-Amplifier	HP	8447D	2944A07999	05/29/2008	05/29/2009
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2008	05/29/2009
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2008	05/29/2009
Horn Antenna	Electro-Metrics	EM-6961	103314	05/29/2008	05/29/2009
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2008	05/29/2009

6.4 Out of Band Radiated Measurement Result

Operation Mode: On Test Date : October 18, 2008
 Frequency Range: 30~1000MHz Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
36.81	V	28.63	40.00	-11.37	Peak
75.96	V	31.54	43.50	-11.96	Peak
158.61	V	29.61	43.50	-13.89	Peak
314.81	V	32.42	46.00	-13.58	Peak
538.98	V	35.90	46.00	-10.10	Peak
638.55	V	34.83	46.00	-11.17	Peak
39.58	H	31.82	40.00	-8.18	Peak
155.97	H	29.84	43.50	-13.66	Peak
381.51	H	32.67	46.00	-13.33	Peak
529.91	H	34.81	46.00	-11.19	Peak
539.17	H	32.65	46.00	-13.35	Peak
651.55	H	35.68	46.00	-10.32	Peak

Note: (1) All Readings are Peak Value.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.209.

Operation Mode: TX (Group A1 2402MHz) Test Date : October 18, 2008
Frequency Range: 1-25GHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (GHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
2.402(F)	V	110.23	90.26	114	94	-3.77	-3.74
4.804	V	69.25	50.32	74	54	-4.75	-3.68
7.206	V	50.68	37.40	74	54	-23.32	-16.60
9.608	V	53.26	34.42	74	54	-20.74	-19.58
12.010	V	52.21	32.64	74	54	-21.79	-21.36
14.412	V	65.72	49.26	74	54	-8.28	-4.74
16.814	V	52.42	40.26	74	54	-21.58	-13.74
19.216	V	50.24	41.74	74	54	-23.76	-12.26
21.618	V	51.38	42.20	74	54	-22.62	-11.80
24.020	V	55.26	41.78	74	54	-18.74	-12.22
2.402(F)	H	110.36	90.35	114	94	-3.64	-3.65
4.804	H	68.24	50.12	74	54	-5.76	-3.88
7.206	H	48.25	38.50	74	54	-25.75	-15.50
9.608	H	40.63	36.42	74	54	-33.37	-17.58
12.010	H	44.58	35.51	74	54	-29.42	-18.49
14.412	H	62.35	48.21	74	54	-11.65	-5.79
16.814	H	54.24	42.39	74	54	-19.76	-11.61
19.216	H	56.85	43.76	74	54	-17.15	-10.24
21.618	H	52.20	41.03	74	54	-21.80	-12.97
24.020	H	54.68	43.46	74	54	-19.32	-10.54

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.249.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: TX(Group A5 2439MHz) Test Date : October 18, 2008
 Frequency Range: 1-25GHz Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: Andy

Freq. (GHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
2.439(F)	V	109.35	89.52	114	94	-4.65	-4.48
4.878	V	69.35	49.21	74	54	-4.65	-4.79
7.317	V	68.52	45.25	74	54	-5.48	-8.75
9.756	V	52.23	40.78	74	54	-21.77	-13.22
12.195	V	44.24	32.55	74	54	-29.76	-21.45
14.634	V	60.41	47.24	74	54	-13.59	-6.76
17.073	V	62.48	45.25	74	54	-11.52	-8.75
19.512	V	55.24	42.13	74	54	-18.76	-11.87
21.951	V	56.87	43.25	74	54	-17.13	-10.75
24.390	V	63.65	50.26	74	54	-10.35	-3.74
2.439(F)	H	109.46	90.11	114	94	-4.54	-3.89
4.878	H	68.52	48.35	74	54	-5.48	-5.65
7.317	H	68.46	48.58	74	54	-5.54	-5.42
9.756	H	50.34	39.35	74	54	-23.66	-14.65
12.195	H	43.34	33.69	74	54	-30.66	-20.31
14.634	H	52.13	40.20	74	54	-21.87	-13.80
17.073	H	45.69	33.68	74	54	-28.31	-20.32
19.512	H	53.67	41.14	74	54	-20.33	-13.86
21.951	H	55.75	40.28	74	54	-18.25	-13.72
24.390	H	50.33	37.26	74	54	-23.67	-16.74

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.249.

Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: TX (Group B5 2481MHz) Test Date : October 18, 2008
Frequency Range: 1-25GHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (GHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
2.481(F)	V	109.65	90.23	114	94	-4.35	-3.77
4.962	V	68.52	48.69	74	54	-5.48	-5.31
7.443	V	65.25	45.68	74	54	-8.75	-8.32
9.924	V	50.34	32.65	74	54	-23.66	-21.35
12.405	V	43.65	34.26	74	54	-30.35	-19.74
14.886	V	65.46	50.10	74	54	-8.54	-3.90
17.367	V	62.15	47.28	74	54	-11.85	-6.72
19.848	V	53.45	42.15	74	54	-20.55	-11.85
22.329	V	45.72	34.26	74	54	-28.28	-19.74
24.810	V	53.44	46.20	74	54	-20.56	-7.80
2.481(F)	H	110.32	89.45	114	94	-3.68	-4.55
4.962	H	68.34	48.67	74	54	-5.66	-5.33
7.443	H	65.36	46.31	74	54	-8.64	-7.69
9.924	H	50.36	40.21	74	54	-23.64	-13.79
12.405	H	44.35	34.62	74	54	-29.65	-19.38
14.886	H	62.20	49.26	74	54	-11.80	-4.74
17.367	H	56.57	42.36	74	54	-17.43	-11.64
19.848	H	53.42	40.10	74	54	-20.58	-13.90
22.329	H	55.48	42.28	74	54	-18.52	-11.72
24.810	H	58.75	46.76	74	54	-15.25	-7.24

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.249.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

6.5 Radiated Measurement Photos:



6. Occupied Bandwidth

7.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Set SPA Center Frequency = fundamental frequency, RBW=100KHz,VBW=300KHz.
4. Set SPA Max hold. Mark peak.

7.2 Test SET-UP(Block Diagram of Configuration)

Same as 6.2 Radiated Emission Measurement.

7.3 Measurement Equipment Used:

Same as 6.3 Radiated Emission Measurement.


7.4 Measurement Results:

The field strength of any emission which appear outside of this band shall not exceed the general radiated emission limits in section 15.209.


Refer to attached data chart.

Band Width Test Data:

Low frequency



Middle frequency




DONGGUAN EMTEK CO., LTD.
REPORT NO:E0807682F

FCC ID:UBTEW023

DATE: 10/22/2008

High frequency




8. Band EDGE test

8.1 Measurement Procedure

1. The EUT was Operating in could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	October 22, 2008
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
<2400	-15.22	-69.98	54.76	>20dBc
>2483.5	-18.12	-70.97	52.85	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		QP	AV	QP	AV
<2400	V	48.92	31.51	74.00	54.00
>2483.5	V	50.56	33.24	74.00	54.00

9. Antenna Application

9.1 Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible part shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Antenna construction and directional gain

The EUT's antenna used a chip antenna and integrated on PCB .