

TEST REPORT

FCC ID:UCC-C22221000

Product: C2s Dual-band 2x2 802.11ac WiFi AP/Bridge

Model No.: C2-2221-000

Additional Model No.: N/A

Trade Mark: Altai

Report No.: TCT160413E007

Issued Date: Jul. 12, 2016

Issued for:

Altai Technologies Limited

Unit 209, 2/F, Lakeside 2, 10 Science Park West Avenue, HK Science Park,
Shatin, Hong Kong

Issued By:

Shenzhen Tongce Testing Lab.

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification.....	3
2. Test Result Summary	4
3. EUT Description	5
4. Genera Information.....	7
4.1. Test environment and mode.....	7
4.2. Description of Support Units.....	8
5. Facilities and Accreditations	9
5.1. Facilities	9
5.2. Location	9
5.3. Measurement Uncertainty.....	9
6. Test Results and Measurement Data	10
6.1. Antenna requirement	10
6.2. Conducted Emission.....	11
6.3. Maximum Conducted (Average) Output Power	15
6.4. Emission Bandwidth	17
6.5. Power Spectral Density.....	28
6.6. Conducted Band Edge and Spurious Emission Measurement	38
6.7. Radiated Spurious Emission Measurement.....	80

Appendix A: Photographs of Test Setup

Appendix B: Photographs of EUT

1. Test Certification

Product:	C2s Dual-band 2x2 802.11ac WiFi AP/Bridge
Model No.:	C2-2221-000
Additional Model No.:	N/A
Applicant:	Altai Technologies Limited
Address:	Unit 209, 2/F, Lakeside 2, 10 Science Park West Avenue, HK Science Park, Shatin, Hong Kong
Manufacturer:	Altai Technologies Limited
Address:	Unit 209, 2/F, Lakeside 2, 10 Science Park West Avenue, HK Science Park, Shatin, Hong Kong
Date of Test:	Apr. 13 –Jul. 12, 2016
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v03r05 KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

SKY Luo

SKY Luo

Date:

Jul. 12, 2016

Reviewed By:

Joe Zhou

Joe Zhou

Date:

Jul. 12, 2016

Approved By:

Tomsin

Tomsin

Date:

Jul. 12, 2016

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§5.247(d) §2.1051 §2.1053	PASS
Conducted Spurious Emission	§15.205/§15.209 §2.1051 §2.1053	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product Name:	C2s Dual-band 2x2 802.11ac WiFi AP/Bridge
Model :	C2-2221-000
Additional Model:	N/A
Trade Mark:	Altai
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel Separation:	5MHz
Number of Channel:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Modulation Technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation Technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal antenna
Antenna Gain:	6dBi
Power Supply:	DC 24V from adapter Adapter information: Model:SEW2401000P Input:100~240V, 1A Output:24V,1000mA

Operation Frequency each of channel For 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel For 802.11n (HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (HT20)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

Antenna and Band width

Antenna	One antenna with Two (TX) output port	
Band width mode	20MHz	40MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

Remark: "V" means support, "X" means not support

IEEE 802.11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate/MCS
802.11n(HT20)	2	MCS0-23
802.11n(HT40)	2	MCS0-23

TX output power setting

Mode	Power setting (dBm)
802.11b for Lowest channel setting	25
802.11b for Middle channel setting	27
802.11b for Highest channel setting	24
802.11g for Lowest channel setting	25
802.11g for Middle channel setting	27
802.11g for Highest channel setting	24
802.11n(HT20) for Lowest channel setting	23
802.11n(HT20) for Middle channel setting	27
802.11n(HT20) for Highest channel setting	22
802.11n(HT40) for Lowest channel setting	23
802.11n(HT40) for Middle channel setting	27
802.11n(HT40) for Highest channel setting	23

4. Genera Information

4.1. Test environment and mode

Operating Environment:

Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar

Test Mode:

Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations (The value of duty cycle is 98.46%)
-------------------	---

The sample was placed (0.8m/1.5m for below/above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps

Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 802.11n(H40) Duty cycle setting during the transmission is 98.46% with maximum power setting for all modulations.

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Notebook	G485	LB00402300	N/A	LENOVO

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331
Shenzhen Tongce Testing Lab
The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing
- CNAS - Registration No.: CNAS L6165
Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

Tel: 86-755-36638142


5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^{\circ}\text{C}$
7	Humidity	$\pm 1.0\%$


6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The EUT has two Internal antennas which permanently attached, and the best case gain of the antennas are 6dBi for 2.4G, 9dBi for 5G.	
	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	TX Mode														
Test Procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														
Remark	The worst mode 11b middle channel reported only.														

6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	100139	Sep. 11, 2016
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 16, 2016
Coax cable	TCT	CE-05	N/A	Sep. 11, 2016
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site Chamber #2

Phase: L1

Temperature: 23 (C)

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measurement dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1734	20.59	11.48	32.07	64.79	-32.72	QP	
2		0.1734	12.18	11.48	23.66	54.79	-31.13	AVG	
3		0.3492	21.14	11.39	32.53	58.98	-26.45	QP	
4		0.3492	12.69	11.39	24.08	48.98	-24.90	AVG	
5		0.5484	32.69	11.29	43.98	56.00	-12.02	QP	
6	*	0.5484	28.93	11.29	40.22	46.00	-5.78	AVG	
7		0.9469	21.97	11.18	33.15	56.00	-22.85	QP	
8		0.9469	13.57	11.18	24.75	46.00	-21.25	AVG	
9		1.4937	20.54	11.42	31.96	56.00	-24.04	QP	
10		1.4937	9.41	11.42	20.83	46.00	-25.17	AVG	
11		21.1719	23.03	10.58	33.61	60.00	-26.39	QP	
12		21.1719	17.42	10.58	28.00	50.00	-22.00	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site Chamber #2

Phase: N

Temperature: 23 (C)

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1891	15.48	11.49	26.97	64.07	-37.10	QP	
2		0.1891	4.53	11.49	16.02	54.07	-38.05	AVG	
3		0.3727	18.30	11.37	29.67	58.44	-28.77	QP	
4		0.3727	9.10	11.37	20.47	48.44	-27.97	AVG	
5		0.5406	28.33	11.29	39.62	56.00	-16.38	QP	
6	*	0.5406	21.51	11.29	32.80	46.00	-13.20	AVG	
7		0.9703	20.28	11.18	31.46	56.00	-24.54	QP	
8		0.9703	12.82	11.18	24.00	46.00	-22.00	AVG	
9		2.0875	21.53	11.66	33.19	56.00	-22.81	QP	
10		2.0875	14.38	11.66	26.04	46.00	-19.96	AVG	
11		21.6641	25.43	10.63	36.06	60.00	-23.94	QP	
12		21.6641	20.86	10.63	31.49	50.00	-18.51	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)


Q.P. =Quasi-Peak

AVG =average

is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.3. Maximum Conducted (Average) Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3) & Part 2 J Section 2.1046
Test Method:	KDB558074 and KDB662911
Limit:	30dBm
Test Setup:	 The diagram illustrates the test setup. On the left is a green box labeled 'Power meter'. A line connects it to a small white box labeled 'ATT' (attenuator). Another line connects the 'ATT' box to a yellow box labeled 'EUT' (Equipment Under Test).
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the result in the test report.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Attenuation	MCL	VAT-10W2 +	1135	N/A
Power Meter	Agilent	N1911A	MY45101557	Sep. 12, 2016
Power Sensor	Agilent	N1922A	MY44124432	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data

Configuration IEEE 802.11b/ Output 0+ Output 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	23.35	23.92	26.65	27.00	PASS
Middle	23.28	24.35	26.86	27.00	PASS
Highest	23.45	23.69	26.58	27.00	PASS

Configuration IEEE 802.11g/ Output 0+ Output 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	23.16	23.25	26.22	27.00	PASS
Middle	23.62	23.57	26.61	27.00	PASS
Highest	23.83	23.97	26.91	27.00	PASS

Configuration IEEE 802.11n(HT20)/ Output 0+ Output 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	23.22	24.55	26.95	27.00	PASS
Middle	23.52	23.28	26.41	27.00	PASS
Highest	23.65	23.54	26.61	27.00	PASS

Configuration IEEE 802.11n(HT40)/ Output 0+ Output 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	23.35	23.56	26.47	27.00	PASS
Middle	23.51	23.57	26.55	27.00	PASS
Highest	23.54	23.45	26.51	27.00	PASS

Directional gain = $GANT + 10 \log(NANT)$ dBi = $6 + 10 \log(2) = 9$ dBi
So limit = $30 - (9 - 6) = 27$ dBm

6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2) & Part 2 J Section 2.1049
Test Method:	KDB558074
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r05. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Set the spectrum to test 99%OBW. 5. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.4.3. Test data

Output 0:

Test channel	6dB Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	7.06	15.11	15.11	32.52
Middle	6.56	14.40	14.95	35.00
Highest	6.56	13.18	15.47	26.27
Limit:	>500k			
Test Result:	PASS			

Output 1:

Test channel	6dB Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	6.09	12.63	15.13	33.81
Middle	6.56	14.11	15.95	28.85
Highest	6.55	15.66	15.29	27.60
Limit:	>500k			
Test Result:	PASS			

Output 0:

Test channel	99% Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	11.31	16.26	17.34	35.66
Middle	11.68	16.34	17.48	35.87
Highest	12.15	16.58	17.44	35.46
Limit:	>500k			
Test Result:	PASS			


Output 1:

Test channel	99% Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	10.99	16.26	17.39	35.71
Middle	11.68	16.31	17.46	35.77
Highest	11.97	16.43	17.48	35.40
Limit:	>500k			
Test Result:	PASS			


Test plots as follows:

Output 0:
802.11b Modulation


Lowest channel



Middle channel




Highest channel




802.11g Modulation

Lowest channel



Middle channel




Highest channel




802.11n (HT20) Modulation


Lowest channel



Middle channel



Highest channel




802.11n (HT40) Modulation


Lowest channel



Middle channel




Highest channel




Output 1: 802.11b Modulation


Lowest channel



Middle channel




Highest channel




802.11g Modulation

Lowest channel



Middle channel




Highest channel




802.11n (HT20) Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT40) Modulation


Lowest channel



Middle channel



Highest channel



6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074, KDB662911
Limit:	The Average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows Measurement Procedure 10.3 Method AVGPDS of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v03r05 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 5. Detector = RMS, Sweep time = auto couple. 6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to

international system unit (SI).

6.5.3. Test data

Configuration IEEE 802.11b/ Output 0+ Output 1

Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	1.18	-1.60	3.02	5dBm/3kHz	PASS
Middle	1.25	1.31	4.29	5dBm/3kHz	PASS
Highest	-1.85	-1.48	1.35	5dBm/3kHz	PASS

Configuration IEEE 802.11g/ Output 0+ Output 1

Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	-3.85	-3.95	-0.89	5dBm/3kHz	PASS
Middle	-2.27	-3.34	0.24	5dBm/3kHz	PASS
Highest	-4.97	-5.48	-2.21	5dBm/3kHz	PASS

Configuration IEEE 802.11n (HT20)/ Output 0+ Output 1

Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	-5.54	-5.29	-2.40	5dBm/3kHz	PASS
Middle	-2.92	-3.75	-0.30	5dBm/3kHz	PASS
Highest	-6.25	-6.23	-3.23	5dBm/3kHz	PASS

Configuration IEEE 802.11n (HT40)/ Output 0+ Output 1

Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Output 0	Output 1	Total		
Lowest	-11.67	-8.07	-6.50	5dBm/3kHz	PASS
Middle	-7.68	-7.69	-4.67	5dBm/3kHz	PASS
Highest	-8.96	-10.53	-6.66	5dBm/3kHz	PASS

Directional gain = $GANT + 10 \log(NANT) \text{ dBi} = 6 + 10 \log(2) = 9 \text{ dBi}$
 So limit = $8 - (9 - 6) = 5 \text{ dBm/MHz}$

Test plots as follows:

Output 0:
802.11b Modulation

Lowest channel



Middle channel




Highest channel




802.11g Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT20) Modulation


Lowest channel



Middle channel




Highest channel



802.11n (HT40) Modulation


Lowest channel



Middle channel



Highest channel



Output 1:
802.11b Modulation

Lowest channel



Middle channel




Highest channel




802.11g Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT20) Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT40) Modulation

Lowest channel



Middle channel



Highest channel



6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 5. Measure and record the results in the test report. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


6.6.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RF-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.3. Test Data

Output 0: 802.11b Modulation









Lowest Channel

100kHz PSD reference Level




Spurious emission





Middle Channel






Highest Channel

802.11g Modulation




100kHz PSD reference Level



Band Edge



Spurious emission









Lowest Channel

100kHz PSD reference Level




Spurious emission





Middle Channel





100kHz PSD reference Level



Band Edge



Spurious emission






Highest Channel

802.11n (HT20) Modulation




100kHz PSD reference Level



Band Edge




Spurious emission









Lowest Channel

100kHz PSD reference Level



Spurious emission









100kHz PSD reference Level



Band Edge



Spurious emission





Highest Channel

802.11n (HT40) Modulation




100kHz PSD reference Level



Band Edge



Spurious emission





Lowest Channel

100kHz PSD reference Level



Spurious emission

