

# TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: NTT-DoCoMo P-03D

FCC ID: UCE111045A

To: FCC Part 15.225: 2011 Subpart C

**Test Report Serial No:**  
RFI-RPT-RP83567JD01B

This Test Report Is Issued Under The Authority  
Of Chris Guy, Head of Global Approvals:



Checked By:	Ian Watch
Signature:	
Date of Issue:	12 October 2011

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

This page has been left intentionally blank.

**Table of Contents**

<b>1. Customer Information .....</b>	<b>4</b>
<b>2. Summary of Testing .....</b>	<b>5</b>
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
<b>3. Equipment Under Test (EUT) .....</b>	<b>6</b>
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	8
<b>4. Operation and Monitoring of the EUT during Testing .....</b>	<b>9</b>
4.1. Operating Modes	9
4.2. Configuration and Peripherals	9
<b>5. Measurements, Examinations and Derived Results .....</b>	<b>10</b>
5.1. General Comments	10
5.2. Test Results	11
5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions	11
5.2.2. Receiver/Idle Mode Radiated Spurious Emissions	14
5.2.3. Transmitter Fundamental Field Strength	16
5.2.4. Transmitter Radiated Spurious Emissions	17
5.2.5. Transmitter Band Edge Radiated Emissions	19
5.2.6. Transmitter 20 dB Bandwidth	20
5.2.7. Transmitter Frequency Stability (Temperature & Voltage Variation)	21
<b>6. Measurement Uncertainty .....</b>	<b>22</b>
<b>Appendix 1. Test Equipment Used.....</b>	<b>23</b>

## **1. Customer Information**

<b>Company Name:</b>	Panasonic Mobile Communications Development of Europe Ltd.
<b>Address:</b>	Panasonic House Willoughby Road Bracknell Berkshire RG12 8FP United Kingdom

## 2. Summary of Testing

### 2.1. General Information

<b>Specification Reference:</b>	47CFR15.225
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2011: Part 15 Subpart C (Radio Frequency Devices) - Section 15.225
<b>Specification Reference:</b>	47CFR15.107 and 47CFR15.109
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2011: Part 15 Subpart B (Radio Frequency Devices) - Sections 15.107 and 15.109
<b>Specification Reference:</b>	47CFR15.209
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2011: Part 15 Subpart C (Intentional Radiators) - Section 15.209
<b>Site Registration:</b>	209735
<b>Location of Testing:</b>	RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH.
<b>Test Dates:</b>	06 September 2011 to 05 October 2011

### 2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 15.107(a)	Receiver/Idle Mode AC Conducted Spurious Emissions	✓
Part 15.109	Receiver/Idle Mode Radiated Spurious Emissions	✓
Part 15.225(a)(b)(c)(d)	Transmitter Fundamental Field Strength	✓
Part 15.209(a), 15.225(d)	Transmitter Radiated Spurious Emissions	✓
Part 15.209(a), 15.225(c)(d)	Transmitter Band Edge Radiated Emissions	✓
Part 2.1049	Transmitter 20 dB Bandwidth	✓
Part 15.225(e)	Transmitter Frequency Stability (Temperature & Voltage Variation)	✓

**Key to Results**

✓ = Complied    ✘ = Did not comply

### 2.3. Methods and Procedures

<b>Reference:</b>	ANSI C63.4 (2009)
<b>Title:</b>	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>Reference:</b>	ANSI C63.10 (2009)
<b>Title:</b>	American National Standard for Testing Unlicensed Wireless Devices

### 2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

### **3. Equipment Under Test (EUT)**

#### **3.1. Identification of Equipment Under Test (EUT)**

<b>Brand Name:</b>	NTT DoCoMo
<b>Model Name or Number:</b>	P-03D
<b>IMEI:</b>	357979040014460
<b>Hardware Version Number:</b>	Revision C
<b>Software Version Number:</b>	ACPU: 01.05.001 CCPU: 18.10.18.02
<b>FCC ID:</b>	UCE111045A

<b>Brand Name:</b>	NTT DoCoMo
<b>Description:</b>	Battery
<b>Model Name or Number:</b>	P23

<b>Brand Name:</b>	NTT DoCoMo
<b>Description:</b>	AC Charger
<b>Model Name or Number:</b>	FOMA AC Adapter 01

<b>Brand Name:</b>	NTT DoCoMo
<b>Description:</b>	DC Charger
<b>Model Name or Number:</b>	FOMA DC Adapter 01

<b>Brand Name:</b>	NTT DoCoMo
<b>Description:</b>	Data cable
<b>Model Name or Number:</b>	FOMA USB Cable with Charge Function

<b>Brand Name:</b>	NTT DoCoMo
<b>Description:</b>	Personal Hands Free Headset
<b>Model Name or Number:</b>	Earphone set 01 (stereo) EB-M70090

### **3.2. Description of EUT**

The equipment under test was a single mode UMTS cellular handset with RFID.

### **3.3. Modifications Incorporated in the EUT**

No modifications were applied to the EUT during testing.

### **3.4. Additional Information Related to Testing**

<b>Tested Technology:</b>	RFID	
<b>Category of Equipment:</b>	Transceiver	
<b>Channel Spacing:</b>	Single channel device	
<b>Transmit Frequency Range:</b>	13.56 MHz	
<b>Receive Frequency Range:</b>	13.56 MHz	
<b>Power Supply Requirement:</b>	Nominal	3.7 V
	Minimum	3.4 V
	Maximum	4.2 V
<b>Tested Temperature Range:</b>	Minimum	-20°C
	Maximum	50°C

### **3.5. Support Equipment**

The following support equipment was used to exercise the EUT during testing:

<b>Brand Name:</b>	Not Stated
<b>Description:</b>	Micro SD Memory Card
<b>Model Name or Number:</b>	Not Stated

<b>Brand Name:</b>	Not Stated
<b>Description:</b>	Dummy Battery
<b>Model Name or Number:</b>	Not Stated

<b>Brand Name:</b>	Buffalo
<b>Description:</b>	USB Hub
<b>Model Name or Number:</b>	BSH3U01

## **4. Operation and Monitoring of the EUT during Testing**

### **4.1. Operating Modes**

The EUT was tested in the following operating mode(s):

- Receiver/Idle mode.
- Constantly transmitting at full power with a modulated carrier in RFID test mode.

### **4.2. Configuration and Peripherals**

The EUT was tested in the following configuration(s):

- The RFID transmitter test mode was enabled using a USIM supplied by the customer.
- Receiver Idle/standby mode radiated spurious emission tests were performed with the AC Charger connected to the EUT as this was found to be the worst case during pre-scans. All accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- Transmitter radiated spurious emission tests were performed with the USB cable with charge function connected to the EUT as this was found to be the worst case during pre-scans. All appropriate accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- As the EUT is not capable of transmitting while charging, no AC Mains conducted emissions tests were performed in transmit mode.

## **5. Measurements, Examinations and Derived Results**

### **5.1. General Comments**

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6: Measurement Uncertainties* for details.

## **5.2. Test Results**

### **5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions**

#### **Test Summary:**

<b>Test Engineer:</b>	Sarah Williams	<b>Test Date:</b>	27 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.107(a)
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Section 6.2 referencing ANSI C63.4

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	28
<b>Relative Humidity (%):</b>	36

#### **Results: Live / Quasi Peak**

Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.150000	Live	41.6	66.0	24.4	Complied
0.159000	Live	42.9	65.5	22.6	Complied
0.208500	Live	35.5	63.3	27.8	Complied
1.621500	Live	36.0	56.0	20.0	Complied
3.727500	Live	29.2	56.0	26.8	Complied
16.129500	Live	11.3	60.0	48.7	Complied

#### **Results: Live / Average**


Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.159000	Live	30.9	55.5	24.6	Complied
0.163500	Live	29.2	55.3	26.1	Complied
0.213000	Live	24.3	53.1	28.8	Complied
1.617000	Live	22.7	46.0	23.3	Complied
3.772500	Live	21.9	46.0	24.1	Complied
16.134000	Live	6.8	50.0	43.2	Complied

**Idle Mode AC Conducted Spurious Emissions (continued)****Results: Neutral / Quasi Peak**


Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.154500	Neutral	42.5	65.8	23.3	Complied
0.204000	Neutral	36.1	63.4	27.3	Complied
1.248000	Neutral	35.2	56.0	20.8	Complied
1.725000	Neutral	37.6	56.0	18.4	Complied
3.853500	Neutral	32.9	56.0	23.1	Complied
16.260000	Neutral	11.3	60.0	48.7	Complied

**Results: Neutral / Average**

Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.159000	Neutral	31.5	55.5	24.0	Complied
0.208500	Neutral	27.8	53.3	25.5	Complied
1.234500	Neutral	24.1	46.0	21.9	Complied
1.716000	Neutral	27.3	46.0	18.7	Complied
3.844500	Neutral	21.3	46.0	24.7	Complied
16.228500	Neutral	20.8	50.0	29.2	Complied

**Idle Mode AC Conducted Spurious Emissions (continued)**

Live



Neutral

*Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.*

### **5.2.2. Receiver/Idle Mode Radiated Spurious Emissions**

#### **Test Summary:**

<b>Test Engineer:</b>	Andrew Edwards	<b>Test Date:</b>	06 September 2011 & 08 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.109
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Sections 6.3, 6.4 and 6.5 referencing ANSI C63.4
<b>Frequency Range:</b>	9 kHz to 1000 MHz

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	26
<b>Relative Humidity (%):</b>	35



#### **Results: Quasi Peak**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
41.408	Vertical	17.0	40.0	23.000	Complied
51.388	Vertical	18.2	40.0	21.800	Complied
317.259	Vertical	10.1	46.0	35.900	Complied
869.292	Horizontal	22.0	46.0	24.000	Complied

#### **Note(s):**

1. Limits below 30 MHz are specified at a test distance of 30 metres, whilst below 0.49 MHz they are specified at a test distance of 300 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.
3. Final measurement values include corrections for antenna factor and cable losses.
4. All emissions on the 9 kHz to 150 kHz plot were investigated and found to be radiating from the test site turntable.
5. All other emissions shown on the pre-scan plots were investigated and found to be >20 dB below the applicable limit or below the measurement system noise floor.
6. Measurements in the range 30 MHz to 1 GHz were performed in a semi-anechoic chamber (RFI Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres

## Receiver/Idle Mode Radiated Spurious Emissions (continued)



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying table.

### **5.2.3. Transmitter Fundamental Field Strength**

#### **Test Summary:**

<b>Test Engineer:</b>	Andrew Edwards	<b>Test Date:</b>	06 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.225(a)(b)(c)(d)
<b>Test Method Used:</b>	ANSI C63.10 Section 6.4

#### **Environmental Conditions:**


<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	39

#### **Results: Quasi Peak**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit at 30 m (dB $\mu$ V/m)	Margin (dB)	Result
13.56	90° to EUT	-8.4	84.0	92.4	Complied

#### **Note(s):**

1. The limit is specified at a test distance of 30 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres. A distance extrapolation factor of 40 dB was used.



### **5.2.4. Transmitter Radiated Spurious Emissions**

#### **Test Summary:**

<b>Test Engineer:</b>	Andrew Edwards	<b>Test Date:</b>	06 September 2011 & 07 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.225(d) & 15.209(a)
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Sections 6.3, 6.4 and 6.5 referencing ANSI C63.4
<b>Frequency Range:</b>	9 kHz to 1000 MHz

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	26
<b>Relative Humidity (%):</b>	35




#### **Results: Quasi Peak**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
40.677	Vertical	27.2	40.0	12.8	Complied
149.169	Horizontal	23.2	43.5	20.3	Complied
162.718	Horizontal	28.2	43.5	15.3	Complied
370.493	Vertical	33.3	46.0	12.7	Complied
894.948	Horizontal	32.5	46.0	13.5	Complied
976.332	Horizontal	33.9	54.0	20.1	Complied

#### **Note(s):**

1. Limits below 30 MHz are specified at a test distance of 30 metres, whilst below 0.49 MHz they are specified at a test distance of 300 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.
3. Final measurement values include corrections for antenna factor and cable losses.
4. The emission shown at approximately 13.56 MHz is the fundamental.
5. All emissions on the 9 kHz to 150 kHz plot were investigated and found to be radiating from the test site turntable.
6. All other emissions shown on the pre-scan plots were investigated and found to be >20 dB below the applicable limit or below the measurement system noise floor.
7. Measurements in the range 30 MHz to 1 GHz were performed in a semi-anechoic chamber (RFI Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

## Transmitter Radiated Spurious Emissions (continued)



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying table.

### **5.2.5. Transmitter Band Edge Radiated Emissions**

#### **Test Summary:**

<b>Test Engineer:</b>	Andrew Edwards	<b>Test Date:</b>	06 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.225(c)(d) & 15.209(a)
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Section 6.9.2

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	39

#### **Results: Quasi Peak Lower Band Edge**


Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
13.11	-31.9	29.5	61.4	Complied

#### **Results: Quasi Peak Upper Band Edge**

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
14.01	-32.5	29.5	62.0	Complied

#### **Note(s):**

1. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required.
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.



### 5.2.6. Transmitter 20 dB Bandwidth

## **Test Summary:**



<b>Test Engineer:</b>	Sarah Williams	<b>Test Date:</b>	09 September 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	2.1049
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Section 6.9.1

## **Environmental Conditions:**

<b>Temperature (°C):</b>	28
<b>Relative Humidity (%):</b>	37

## Results:



### **5.2.7. Transmitter Frequency Stability (Temperature & Voltage Variation)**

#### **Test Summary:**

<b>Test Engineer:</b>	Sarah Williams	<b>Test Date:</b>	09 September 2011 & 05 October 2011
<b>Test Sample IMEI:</b>	357979040014460		

<b>FCC Part:</b>	15.225(e)
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Section 6.8.1 and 6.8.2

#### **Environmental Conditions:**

<b>Ambient Temperature (°C):</b>	30
<b>Ambient Relative Humidity (%):</b>	34

#### **Results: Maximum frequency error of the EUT with variations in ambient temperature**

Temperature (°C)	Time after Start-up			
	0 minutes	2 minutes	5 minutes	10 minutes
-20	13.559953 MHz	13.559950 MHz	13.559950 MHz	13.559946 MHz
20	13.559988 MHz	13.559988 MHz	13.559986 MHz	13.559986 MHz
50	13.559932 MHz	13.559932 MHz	13.559934 MHz	13.559936 MHz

Frequency with Worst Case Deviation (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
13.559932	68	0.000501	0.01	0.009499	Complied

#### **Results: Maximum frequency error of the EUT with variations in nominal operating voltage at an ambient temperature of 20°C**

Supply Voltage (V)	Nominal Frequency (MHz)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
3.4	13.56	13.559986	14	0.000103	0.01	0.009897	Complied
3.7	13.56	13.559991	9	0.000066	0.01	0.009934	Complied
4.2	13.56	13.559987	13	0.000096	0.01	0.009904	Complied

## **6. Measurement Uncertainty**

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±3.25 dB
20 dB Bandwidth	13 MHz to 14 MHz	95%	±0.92 ppm
Frequency Stability	13 MHz to 14 MHz	95%	±0.92 ppm
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	±3.53 dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	±2.94 dB
Transmitter Fundamental Field Strength	13 MHz to 14 MHz	95%	±3.53 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

## Appendix 1. Test Equipment Used

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	05 Mar 2012	12
A1834	Attenuator	Hewlett Packard	8491B	10444	26 Jul 2012	12
A553	Antenna	Chase	CBL6111A	1593	26 Mar 2012	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	05 Apr 2012	12
E013	Environmental Chamber	Sanyo	ATMOS	None	Calibrated Before Use	-
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	29 May 2012	12
M1068	Thermometer	Iso-Tech	RS55	93102884	10 Nov 2011	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	13 Jul 2012	12
M1269	Multimeter	Fluke	179	90250210	20 Jul 2012	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	04 Feb 2012	12
M1568	Magnetic Loop	Rohde & Schwarz	HFH2-Z2	879284/2	27 Jan 2012	12
S011	DC Power Supply Unit	INSTEK	PR-3010H	9401270	Calibration not required	-

**NB** In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.