

TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: Panasonic Mobile Comms Dev of Europe Ltd VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Test Report Serial No: RFI/SARE1/RP72912JD01A

| This Test Report Is Issued Under The Authority Of Steve Flooks, Service Leader RPG: | | |
|---|------------------------------|--|
| pp | | |
| Checked By: Joe Lomako | Report Copy No: PDF01 | |
| The | | |
| Issue Date: 17 December 2007 | Test Dates: 10 December 2007 | |

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may be copied in full. The results in this report apply only to the sample(s) tested.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 2 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

This page has been left intentionally blank.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 3 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Table of Contents

| 1. Customer Information | 4 |
|--|----|
| 2. Equipment Under Test (EUT) | 5 |
| 3. Test Specification, Methods and Procedures | 9 |
| 4. Deviations from the Test Specification | 10 |
| 5. Operation and Configuration of the EUT during Testing | 11 |
| 6. Summary of Test Results | 13 |
| 7. Measurements, Examinations and Derived Results | 14 |
| Appendix 1. Test Equipment Used | 23 |
| Test Equipment Used (Continued) | 24 |
| Appendix 2. Measurement Methods | 26 |
| Appendix 3. SAR Distribution Scans | 28 |
| Appendix 4. Photographs | 39 |
| Appendix 5. Validation of System | 56 |
| Appendix 6. Simulated Tissues | |
| Appendix 7. DASY4 System Details | 58 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 4 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

1. Customer Information

| Company Name: | Panasonic Mobile Comms Dev of Europe Ltd | |
|---------------|---|--|
| Address: | 2 Gables Way Colthrop Thatcham Berkshire RG19 4ZB | |
| Contact Name: | Mr. M Hargreaves | |

Serial No: RFI/SARE1/RP72912JD01A

Page: 5 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

2. Equipment Under Test (EUT)

The following information (with the exception of the date of receipt) has been supplied by the customer:

2.1. Description of EUT

The equipment under test is a Tri-Band Dual Mode (W-CDMA/GSM) mobile telephone handset.

2.2. Identification of Equipment Under Test (EUT)

| Description: | Mobile Handset |
|----------------------------------|--------------------|
| Brand Name: | Panasonic |
| Model Name or Number: | VS7x |
| Serial Number: | Sample C8 |
| IMEI Number: | 00 4401220367144 |
| Hardware Version Number: | Rev A |
| Software Version Number: | 822PVA07 |
| Hardware Revision of GSM Module: | Not Applicable |
| Software Revision of GSM Module: | Not Applicable |
| FCC ID Number: | UCE207005A |
| Country of Manufacture: | Japan |
| Date of Receipt: | 10th December 2007 |

2.3. Modifications Incorporated in the EUT

During the course of testing the EUT was not modified.

Serial No: RFI/SARE1/RP72912JD01A

Page: 6 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

2.4. Accessories

The following accessories were supplied with the EUT during testing:

| Description: | Battery |
|-------------------------|--------------------|
| Brand Name: | SANYO |
| Model Name or Number: | VS7a |
| Serial Number: | None Stated |
| Cable Length and Type: | Not Applicable |
| Country of Manufacture: | Japan |
| Connected to Port | 10th December 2007 |

| Description: | Battery |
|-------------------------|--------------------|
| Brand Name: | SANYO |
| Model Name or Number: | VS7a |
| Serial Number: | None Stated |
| Cable Length and Type: | Not Applicable |
| Country of Manufacture: | Japan |
| Connected to Port | 10th December 2007 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 7 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

2.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

| Description: | Universal Radio Communication Test Set |
|------------------------|--|
| Brand Name: | Rohde & Schwarz |
| Model Name or Number: | CMU200 |
| Serial Number: | 1100.0008.02 |
| Cable Length and Type: | 1.5 Utiflex |
| Connected to Port: | RF (Input/Output) Air Link |

| Description: | Radio Communication Analyser |
|------------------------|------------------------------|
| Brand Name: | Anritsu |
| Model Name or Number: | MT8820A |
| Serial Number: | 6K00000647 |
| Cable Length and Type: | 1.5m Utiflex |
| Connected to Port: | RF (Input/Output) Air Link |

| Description: | Radio Communication Analyser |
|------------------------|------------------------------|
| Brand Name: | Anritsu |
| Model Name or Number: | MT8820A |
| Serial Number: | 6K00000647 |
| Cable Length and Type: | 1.5m Utiflex |
| Connected to Port: | RF (Input/Output) Air Link |

Serial No: RFI/SARE1/RP72912JD01A

Page: 8 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

2.6. Additional Information Related to Testing

| Equipment Category | PCS1900 / GPRS1900 / Bluetooth | | |
|--|---|------------------------|--------------------|
| Type of Unit | Portable Transceiver | | |
| Intended Operating Environment: | Within GSM and Bluetooth Coverage | | |
| Transmitter Maximum Output Power Characteristics: | PCS1900 | 30 dBm | |
| Transmitter Frequency Range: | PCS1900 | (1850 to 1910) MHz | |
| Transmitter Frequency Allocation of EUT When Under Test: | Channel Number | Channel Description | Frequency (MHz) |
| | 512 | Low | 1850.2 |
| | 660 | Middle | 1879.8 |
| | 810 | High | 1909.8 |
| Modulation(s): | GMSK 217Hz | | |
| Modulation Scheme (Crest Factor): | GSM 8.3; GPRS 4 | | |
| Antenna Type: | Internal | | |
| Antenna Length: | Unknown | | |
| Number of Antenna Positions: | 1 Fixed | | |
| Power Supply Requirement: | Internal Battery Supply 3.7 V (Nominal) | | |
| Battery Type(s): | Lithium-ion | | |

Serial No: RFI/SARE1/RP72912JD01A

Page: 9 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

3. Test Specification, Methods and Procedures

3.1. Test Specification

| Reference: | OET Bulletin 65 Supplement C: (2001-01) |
|------------------|--|
| Title: | Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields. |
| Purpose of Test: | To determine whether the equipment met the basic restrictions as defined in OET Bulletin 65 Supplement C: (2001-01) using the SAR averaging method as described in the test specification above. |

3.2. Methods and Procedures Reference Documentation

The methods and procedures used were as detailed in:

Federal Communications Commission, "Evaluating compliance with FCC Guidelines for human exposure to radio frequency electromagnetic fields", OET Bulletin 65 Supplement C, FCC, Washington, D.C, 20554, 2001.

Thomas Schmid, Oliver Egger and Neils Kuster, "Automated E-field scanning system for dosimetric assessments", IEEE Transaction on microwave theory and techniques, Vol. 44, pp. 105-113, January 1996.

Neils Kuster, Ralph Kastle and Thomas Schmid, "Dosimetric evaluation of mobile communications equipment with know precision", IEICE Transactions of communications, Vol. E80-B, No.5, pp. 645-652, May 1997.

3.3. Definition of Measurement Equipment

The measurement equipment used complied with the requirements of the standards referenced in the methods & procedures section above. Appendix 1 contains a list of the test equipment used.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 10 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

4. Deviations from the Test Specification

There were no deviations from the test specification.

Serial No: RFI/SARE1/RP72912JD01A

Page: 11 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

5. Operation and Configuration of the EUT during Testing

5.1. Operating Modes

The EUT was tested in the following operating mode(s) unless otherwise stated:

- GPRS1900 data allocated with Bluetooth enabled
- PCS1900 call allocated with Bluetooth enabled

The reason for choosing this configuration was that it has been defined by the customer as being typical of normal use and likely to be worst case.

Serial No: RFI/SARE1/RP72912JD01A

Page: 12 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

5.2. Configuration and Peripherals

The EUT was tested in the following configuration(s) unless otherwise stated:

Standalone mobile station with the head and body-worn configurations against the 'SAM' phantom.

Head Configuration

- a) The handset was placed in a normal operating position with the centre of the ear-piece aligned with the ear canal on the phantom.
- b) With the ear-piece touching the phantom the centre line of the handset was aligned with an imaginary plane (X and Y axis) consisting of three lines connecting both ears and the mouth.
- c) For the cheek position the handset was gradually moved towards the cheek until any point of the mouth-piece or keypad touched the cheek.
- d) For the tilted position the EUT was positioned as for the cheek position, and then the horizontal angle was increased by fifteen degrees (the phone keypad was moved away from the cheek by fifteen degrees).
- e) SAR measurements were evaluated at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimise the drift.
- f) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- g) The location of the maximum spatial SAR distribution (hot spot) was determined relative to the handset and its antenna.
- h) The EUT was transmitting at full power throughout the duration of the test powered by a fully charged battery.

Body Configuration

- a) The EUT was placed in a normal operating position where the centre of EUT was aligned with the centre reference point on the flat section of the 'SAM' phantom.
- b) With the EUT touching the phantom at an imaginary centre line. The EUT was aligned with a marked plane (X and Y axis) consisting of two lines.
- c) For the touch-safe position the handset was gradually moved towards the flat section of the 'SAM' phantom until any point of the EUT touched the phantom.
- d) For position(s) greater then 0mm separation the EUT was positioned as per the touch-safe position, and then the vertical height was decreased/adjusted as required.
- e) SAR measurements were evaluated at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimise the drift.
- f) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- g) The location of the maximum spatial SAR distribution (hot spot) was determined relative to the handset and its antenna.
- h) The EUT was transmitting at full power throughout the duration of the test powered by a fully charged battery.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 13 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

6. Summary of Test Results

| Test Name | Specification Reference | Compliancy Status |
|---|---|-------------------|
| Specific Absorption Rate- GPRS1900 Body Configuration 1g | OET Bulletin 65 Supplement C: (2001-01) | Complied |
| Specific Absorption Rate-PCS1900 Body Configuration 1g | OET Bulletin 65 Supplement C: (2001-01) | Complied |
| Specific Absorption Rate-PCS1900 Head Configuration 1g | OET Bulletin 65 Supplement C: (2001-01) | Complied |

6.1. Location of Tests

All the measurements described in this report were performed at the premises of RFI Global Services Ltd, Ewhurst Park, Ramsdell, Basingstoke, Hampshire, RG26 5RQ.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 14 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7. Measurements, Examinations and Derived Results

7.1. General Comments

This section contains test results only.

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to section 8 for details of measurement uncertainties.

Serial No: RFI/SARE1/RP72912JD01A

Page: 15 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7.2. Test Results

7.2.1.Specific Absorption Rate - PCS1900 Head Configuration 1g

Test Summary:

| Tissue Volume: | 1g |
|-----------------------|-------|
| Maximum Level (W/kg): | 0.643 |

Environmental Conditions:

| Temperature Variation in Lab (°C): | 24.0 to 23.0 |
|---------------------------------------|--------------|
| Temperature Variation in Liquid (°C): | 24.0 to 23.0 |

Results:

| EUT Position | Phantom Configuration | Channel Number | Level (W/kg) | Limit (W/kg) | Margin (W/kg) | Note(s) | Result |
|--------------|--------------------------|-------------------|-----------------|-----------------|------------------|---------|----------|
| Touch | Left | 660 | 0.412 | 1.600 | 1.188 | - | Complied |
| Tilt | Left | 660 | 0.553 | 1.600 | 1.047 | - | Complied |
| Touch | Right | 660 | 0.412 | 1.600 | 1.188 | - | Complied |
| Tilt | Right | 660 | 0.643 | 1.600 | 0.957 | - | Complied |

Serial No: RFI/SARE1/RP72912JD01A

Page: 16 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7.2.2. Specific Absorption Rate - PCS1900 Body Configuration 1g

Test Summary:

| Tissue Volume: | 1g |
|-----------------------|-------|
| Maximum Level (W/kg): | 0.133 |

Environmental Conditions:

| Temperature Variation in Lab (°C): | 23.0 to 23.0 |
|---------------------------------------|--------------|
| Temperature Variation in Liquid (°C): | 23.0 to 23.0 |

Results:

| EUT Position | Phantom Configuration | Channel Number | Level (W/kg) | Limit (W/kg) | Margin (W/kg) | Note(s) | Result |
|-----------------------------------|--------------------------|-------------------|-----------------|-----------------|------------------|---------|----------|
| Front of EUT Facing Phantom | Flat (SAM) | 660 | 0.133 | 1.600 | 1.467 | 1 | Complied |

Note(s):

1. SAR measurements were performed with the EUT at a separation distance of 15mm from the 'SAM' phantom flat section.

Serial No: RFI/SARE1/RP72912JD01A

Page: 17 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7.2.3.Specific Absorption Rate - GPRS1900 Body Configuration 1g

Test Summary:

| Tissue Volume: | 1g |
|-----------------------|-------|
| Maximum Level (W/kg): | 0.334 |

Environmental Conditions:

| Temperature Variation in Lab (°C): | 23.0 to 23.0 |
|---------------------------------------|--------------|
| Temperature Variation in Liquid (°C): | 23.0 to 23.0 |

Results:

| EUT Position | EUT Position Phantom Channel Level (W/kg) | | Limit Margin (W/kg) | | Note(s) | Result | |
|--|---|-----|---------------------|-------|---------|--------|----------|
| Front of EUT Facing Flat (SAM) Phantom | | 660 | 0.170 | 1.600 | 1.430 | 1 | Complied |
| Rear of EUT Facing Phantom | Flat (SAM) | 660 | 0.334 | 1.600 | 1.266 | 1 | Complied |
| Rear of EUT Facing Phantom With PHF | Flat (SAM) | 660 | 0.253 | 1.600 | 1.347 | 1 | Complied |

Note(s):

2. SAR measurements were performed with the EUT at a separation distance of 15mm from the 'SAM' phantom flat section.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 18 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7.2.4. EIRP/ERP Measurement

| Channel Number Frequency (MHZ) | | TX Power before Test (dBm) | Note |
|--------------------------------|--------|----------------------------|------|
| 512 | 1850.2 | 22.0 | EIRP |
| 660 | 1879.8 | 24.1 | EIRP |
| 810 | 1909.8 | 24.5 | EIRP |

Serial No: RFI/SARE1/RP72912JD01A

Page: 19 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

7.2.5. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently, the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor, such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

| Test Name | Confidence Level | Calculated Uncertainty |
|---|---------------------|---------------------------|
| Specific Absorption Rate - PCS1900 Head Configuration 1g | 95% | ±18.44 |
| Specific Absorption Rate - PCS1900 Body Configuration 1g | 95% | ±18.30 |
| Specific Absorption Rate - GPRS1900 Body Configuration 1g | 95% | ±18.30 |

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty, the published guidance of the appropriate accreditation body is followed.

Serial No: RFI/SARE1/RP72912JD01A

Page: 20 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Measurement Uncertainty (Continued)

7.3. Specific Absorption Rate Uncertainty at PCS1900 Head 1g, EGSM Modulation Scheme calculated in accordance with IEC 62209-1 & IEEE 1528

| Type | Source of uncertainty | + | - Value | Probability | Divisor | C _{i (10g)} | | dard rtainty | υ _i or |
|------|---|--------|---------|----------------|---------|----------------------|------------|-----------------|-------------------|
| Туре | Source of uncertainty | Value | - value | Distribution | DIVISOR | | + u (%) | - u (%) | v _{eff} |
| В | Probe calibration | 11.000 | 11.000 | normal (k=2) | 2.0000 | 1.0000 | 5.500 | 5.500 | ∞ |
| В | Axial Isotropy | 0.500 | 0.500 | normal (k=2) | 2.0000 | 1.0000 | 0.250 | 0.250 | ∞ |
| В | Hemispherical Isotropy | 2.600 | 2.600 | normal (k=2) | 2.0000 | 1.0000 | 1.300 | 1.300 | ∞ |
| В | Spatial Resolution | 0.500 | 0.500 | Rectangular | 1.7321 | 1.0000 | 0.289 | 0.289 | ∞ |
| В | Boundary Effect | 0.769 | 0.769 | Rectangular | 1.7321 | 1.0000 | 0.444 | 0.444 | ∞ |
| В | Linearity | 0.600 | 0.600 | Rectangular | 1.7321 | 1.0000 | 0.346 | 0.346 | ∞ |
| В | Detection Limits | 0.200 | 0.200 | Rectangular | 1.7321 | 1.0000 | 0.115 | 0.115 | ∞ |
| В | Readout Electronics | 0.560 | 0.560 | normal (k=2) | 2.0000 | 1.0000 | 0.280 | 0.280 | × × |
| В | Response Time | 0.000 | 0.000 | Rectangular | 1.7321 | 1.0000 | 0.000 | 0.000 | 8 |
| В | Integration Time | 1.730 | 1.730 | Rectangular | 1.7321 | 1.0000 | 0.999 | 0.999 | × × |
| В | RF Ambient conditions | 3.000 | 3.000 | Rectangular | 1.7321 | 1.0000 | 1.732 | 1.732 | × × |
| В | Probe Positioner Mechanical Restrictions | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | ∞ |
| В | Probe Positioning with regard to Phantom Shell | 2.850 | 2.850 | Rectangular | 1.7321 | 1.0000 | 1.645 | 1.645 | ∞ |
| В | Extrapolation and integration/ Maximum SAR evaluation | 5.080 | 5.080 | Rectangular | 1.7321 | 1.0000 | 2.933 | 2.933 | × × |
| Α | Test Sample Positioning | 0.584 | 0.584 | normal (k=1) | 1.0000 | 1.0000 | 0.584 | 0.584 | 10 |
| Α | Device Holder uncertainty | 0.154 | 0.154 | normal (k=1) | 1.0000 | 1.0000 | 0.154 | 0.154 | 10 |
| В | Phantom Uncertainty | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | 8 |
| В | Drift of output power | 5.000 | 5.000 | Rectangular | 1.7321 | 1.0000 | 2.887 | 2.887 | × × |
| В | Liquid Conductivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6400 | 1.848 | 1.848 | × |
| Α | Liquid Conductivity (measured value) | 4.370 | 4.370 | normal (k=1) | 1.0000 | 0.6400 | 2.797 | 2.797 | 5 |
| В | Liquid Permittivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6000 | 1.732 | 1.732 | × × |
| Α | Liquid Permittivity (measured value) | 4.450 | 4.450 | normal (k=1) | 1.0000 | 0.6000 | 2.670 | 2.670 | 5 |
| | Combined standard uncertainty | | | t-distribution | | | 9.41 | 9.41 | >300 |
| | Expanded uncertainty | | | k = 1.96 | | | 18.44 | 18.44 | >300 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 21 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Measurement Uncertainty (Continued)

7.4. Specific Absorption Rate Uncertainty at PCS1900 Body 1g, EGSM Modulation Scheme calculated in accordance with IEC 62209-1 & IEEE 1528

| | Source of uncertainty | + | - Value | Probability | | | Standard Uncertainty | | ບ _i or |
|------|---|--------|---------|----------------|---------|----------------------|-------------------------|------------|-------------------|
| Туре | | Value | | Distribution | Divisor | C _{i (10g)} | + u (%) | - u (%) | Veff |
| В | Probe calibration | 11.000 | 11.000 | normal (k=2) | 2.0000 | 1.0000 | 5.500 | 5.500 | ∞ |
| В | Axial Isotropy | 0.500 | 0.500 | normal (k=2) | 2.0000 | 1.0000 | 0.250 | 0.250 | ∞ |
| В | Hemispherical Isotropy | 2.600 | 2.600 | normal (k=2) | 2.0000 | 1.0000 | 1.300 | 1.300 | ∞ |
| В | Spatial Resolution | 0.500 | 0.500 | Rectangular | 1.7321 | 1.0000 | 0.289 | 0.289 | ∞ |
| В | Boundary Effect | 0.769 | 0.769 | Rectangular | 1.7321 | 1.0000 | 0.444 | 0.444 | ∞ |
| В | Linearity | 0.600 | 0.600 | Rectangular | 1.7321 | 1.0000 | 0.346 | 0.346 | ∞ |
| В | Detection Limits | 0.200 | 0.200 | Rectangular | 1.7321 | 1.0000 | 0.115 | 0.115 | ∞ |
| В | Readout Electronics | 0.560 | 0.560 | normal (k=2) | 2.0000 | 1.0000 | 0.280 | 0.280 | ∞ |
| В | Response Time | 0.000 | 0.000 | Rectangular | 1.7321 | 1.0000 | 0.000 | 0.000 | ∞ |
| В | Integration Time | 1.730 | 1.730 | Rectangular | 1.7321 | 1.0000 | 0.999 | 0.999 | ∞ |
| В | RF Ambient conditions | 3.000 | 3.000 | Rectangular | 1.7321 | 1.0000 | 1.732 | 1.732 | ∞ |
| В | Probe Positioner Mechanical Restrictions | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | ∞ |
| В | Probe Positioning with regard to Phantom Shell | 2.850 | 2.850 | Rectangular | 1.7321 | 1.0000 | 1.645 | 1.645 | 8 |
| В | Extrapolation and integration/ Maximum SAR evaluation | 5.080 | 5.080 | Rectangular | 1.7321 | 1.0000 | 2.933 | 2.933 | ∞ |
| Α | Test Sample Positioning | 0.584 | 0.584 | normal (k=1) | 1.0000 | 1.0000 | 0.584 | 0.584 | 10 |
| Α | Device Holder uncertainty | 0.154 | 0.154 | normal (k=1) | 1.0000 | 1.0000 | 0.154 | 0.154 | 10 |
| В | Phantom Uncertainty | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | ∞ |
| В | Drift of output power | 5.000 | 5.000 | Rectangular | 1.7321 | 1.0000 | 2.887 | 2.887 | 8 |
| В | Liquid Conductivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6400 | 1.848 | 1.848 | 8 |
| Α | Liquid Conductivity (measured value) | 4.170 | 4.170 | normal (k=1) | 1.0000 | 0.6400 | 2.669 | 2.669 | 5 |
| В | Liquid Permittivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6000 | 1.732 | 1.732 | ∞ |
| Α | Liquid Permittivity (measured value) | 4.230 | 4.230 | normal (k=1) | 1.0000 | 0.6000 | 2.538 | 2.538 | 5 |
| | Combined standard uncertainty | | | t-distribution | | | 9.34 | 9.34 | >400 |
| | Expanded uncertainty | | | k = 1.96 | | | 18.30 | 18.30 | >400 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 22 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Measurement Uncertainty (Continued)

7.5. Specific Absorption Rate Uncertainty at GPRS1900 Body 1g, EGSM Modulation Scheme calculated in accordance with IEC 62209-1 & IEEE 1528

| Туре | Source of uncertainty | + | - Value | Probability | Divisor | | Standard Uncertainty | | υ _i or |
|------|---|--------|---------|----------------|---------|----------------------|-------------------------|------------|-------------------|
| туре | | Value | - value | Distribution | DIVISOR | C _{i (10g)} | + u (%) | - u (%) | υ _{eff} |
| В | Probe calibration | 11.000 | 11.000 | normal (k=2) | 2.0000 | 1.0000 | 5.500 | 5.500 | ~ |
| В | Axial Isotropy | 0.500 | 0.500 | normal (k=2) | 2.0000 | 1.0000 | 0.250 | 0.250 | ∞ |
| В | Hemispherical Isotropy | 2.600 | 2.600 | normal (k=2) | 2.0000 | 1.0000 | 1.300 | 1.300 | 8 |
| В | Spatial Resolution | 0.500 | 0.500 | Rectangular | 1.7321 | 1.0000 | 0.289 | 0.289 | ∞ |
| В | Boundary Effect | 0.769 | 0.769 | Rectangular | 1.7321 | 1.0000 | 0.444 | 0.444 | ∞ |
| В | Linearity | 0.600 | 0.600 | Rectangular | 1.7321 | 1.0000 | 0.346 | 0.346 | ∞ |
| В | Detection Limits | 0.200 | 0.200 | Rectangular | 1.7321 | 1.0000 | 0.115 | 0.115 | ~ |
| В | Readout Electronics | 0.560 | 0.560 | normal (k=2) | 2.0000 | 1.0000 | 0.280 | 0.280 | ~ |
| В | Response Time | 0.000 | 0.000 | Rectangular | 1.7321 | 1.0000 | 0.000 | 0.000 | 8 |
| В | Integration Time | 1.730 | 1.730 | Rectangular | 1.7321 | 1.0000 | 0.999 | 0.999 | 8 |
| В | RF Ambient conditions | 3.000 | 3.000 | Rectangular | 1.7321 | 1.0000 | 1.732 | 1.732 | 8 |
| В | Probe Positioner Mechanical Restrictions | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | ∞ |
| В | Probe Positioning with regard to Phantom Shell | 2.850 | 2.850 | Rectangular | 1.7321 | 1.0000 | 1.645 | 1.645 | 8 |
| В | Extrapolation and integration/ Maximum SAR evaluation | 5.080 | 5.080 | Rectangular | 1.7321 | 1.0000 | 2.933 | 2.933 | 8 |
| Α | Test Sample Positioning | 0.584 | 0.584 | normal (k=1) | 1.0000 | 1.0000 | 0.584 | 0.584 | 10 |
| Α | Device Holder uncertainty | 0.154 | 0.154 | normal (k=1) | 1.0000 | 1.0000 | 0.154 | 0.154 | 10 |
| В | Phantom Uncertainty | 4.000 | 4.000 | Rectangular | 1.7321 | 1.0000 | 2.309 | 2.309 | 8 |
| В | Drift of output power | 5.000 | 5.000 | Rectangular | 1.7321 | 1.0000 | 2.887 | 2.887 | × × |
| В | Liquid Conductivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6400 | 1.848 | 1.848 | ∞ |
| Α | Liquid Conductivity (measured value) | 4.170 | 4.170 | normal (k=1) | 1.0000 | 0.6400 | 2.669 | 2.669 | 5 |
| В | Liquid Permittivity (target value) | 5.000 | 5.000 | Rectangular | 1.7321 | 0.6000 | 1.732 | 1.732 | oc |
| Α | Liquid Permittivity (measured value) | 4.230 | 4.230 | normal (k=1) | 1.0000 | 0.6000 | 2.538 | 2.538 | 5 |
| | Combined standard uncertainty | | | t-distribution | | | 9.34 | 9.34 | >400 |
| | Expanded uncertainty | | | k = 1.96 | | | 18.30 | 18.30 | >400 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 23 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Appendix 1. Test Equipment Used

| RFI No. | Instrument | Manufacturer | Type No. | Serial No. | Date Last Calibrated | Cal. Interval (Months) |
|---------|---------------------------------|---------------------------------------|----------------------|------------------|--|------------------------------|
| A034 | Narda 20W Termination | Narda | 374BNM | 8706 | Calibrated as part of system | - |
| A1094 | Digital Camera | Sony | MVC - FD81 | 125805 | - | - |
| A1097 | SMA Directional Coupler | MiDISCO | MDC6223- 30 | None | Calibrated as part of system | - |
| A1137 | 3dB Attenuator | Narda | 779 | 04690 | Calibrated as part of system | - |
| A1174 | Dielectric Probe Kit | Agilent Technologies | 85070C | Us99360072 | Calibrated before use | - |
| A1328 | Handset Positioner | Schmid & Partners | Modification | SD 000 H01 DA | - | - |
| A1184 | Data Acquisition Electronics | Schmid & Partner | DAE3 | 394 | 24 May 2007 | 12 months |
| A1185 | Probe | Schmid & Partner | ET3 DV6 | 1528 | 06 July 2007 | 12 months |
| A1238 | SAM Phantom | Schmid & Partners | SAM b | 001 | Calibrated before use | - |
| A1566 | SAM Phantom | Schmid & Partners | SAM a | 002 | Calibrated before use | - |
| A1237 | 1900 MHz Dipole Kit | Schmid & Partner Engineering AG | D1900V2 | 540 | 11 June 2007 | 24 months |
| A1497 | Amplifier | Mini-Circuits | zhl-42w (sma) | e020105 | Calibrated as part of system | - |
| A215 | 20 dB Attenuator | Narda | 766-20 | 9402 | Calibrated as part of system | - |
| A512 | Double ridged Horn | EMCO | 3115 | 3993 | 17 Sept 2004 (Monitoring use only) | - |
| C1144 | Cable | Rosenberger MICRO-COAX | FA147AF00 1503030 | 41842-1 | Calibrated as part of system | - |

Serial No: RFI/SARE1/RP72912JD01A

Page: 24 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Test Equipment Used (Continued)

| RFI No. | Instrument | Manufacturer | Type No. | Serial No. | Date Last Calibrated | Cal. Interval (Months) |
|---------|---|---------------------------|----------------------|---------------------|--|------------------------------|
| C1145 | Cable | Rosenberger MICRO-COAX | FA147AF00 3003030 | 41843-1 | Calibrated as part of system | - |
| C1146 | Cable | Rosenberger MICRO-COAX | FA147AF03 0003030 | 41752-1 | Calibrated as part of system | - |
| C1092 | Cable | RS Components | 293-334 | 1087200-3 3402 | Internal Calibration | - |
| G051 | Signal Generator | Gigatronics | 7100/.01-20 | 749472 | Calibrated before use | - |
| G0528 | Robot Power Supply | Schmid & Partner | DASY | None | Calibrated before use | - |
| G087 | PSU | Thurlby Thandar | CPX200 | 100701 | Calibrated before use | - |
| M010 | NRV Power Meter | Rohde & Schwarz | NRV | 882 317/065 | 06 July 2007 | 12 months |
| M1015 | Network Analyser | Agilent Technologies | 8753ES | US39172406 | 24 September 2007 | 12 months |
| M1047 | Robot Arm | Staubli | RX908 L | F00/SD89A1/ A/01 | Calibrated before use | - |
| M1069 | Diode Power Sensor | Rohde & Schwarz | NRV-Z2 | 838824/010 | 19 April 2007 | 12 months |
| M1129 | Power Sensor | Rohde & Schwarz | URY-Z2 | 890242/16 | 12 June 2007 | 12 |
| M136 | Temperature/Humidity /Pressure Meter | RS Components | None | None | Internal Calibration | - |
| M509 | Thermometer | Testo | 110 | 40378800433 | 20 April 2007 | 12 months |
| M1140 | Radio Communication Analyser | Anritsu | MT8820A | 6K0000047 | 16 March 2006 (Calibration Not Required) | - |
| M1270 | Temperature/Humidity /Pressure Meter | RS Components | None | None | Internal Calibration | - |
| M1093 | Communications Test Set | Will tek | 4202S | 0513018 | - | - |
| S256 | SAR Lab | RFI | Site 56 | N/A | Calibrated before use | - |

NB In accordance with UKAS requirements, all the measurement equipment is on a calibration schedule.

RFI GLOBAL SERVICES LTD

Test Report

Serial No: RFI/SARE1/RP72912JD01A

Page: 25 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

A.1.1. Calibration Certificates

This section contains the calibration certificates and data for the Probe(s) and Dipole(s) used, which are not included in the total number of pages for this report.

A1185 12/07/07 NM

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client

RF

Certificate No: ET3-1528 Juli07

| | 2011 | | |
|---------------------------------------|--|--|--|
| CANEL TANGON | GERTHE CAT | | |
| Object | ET3DV6 - SN:1 | 528 | |
| | | | in the state of th |
| Calibration procedure(s) | QA CAL-01.v6 | | |
| į | Calibration proc | edure for desimetric E-field probes | |
| | Paragraph Company | | |
| | | | |
| Calibration date: | July 6, 2007 | | |
| Condition of the calibrated item | In Tolerance | | |
| | | | |
| | | tional standards, which realize the physical units of | |
| The measurements and the unce | rtainties with confidence | probability are given on the following pages and are | e part of the certificate. |
| All calibrations have been conduc | cted in the closed laborate | ory facility: environment temperature (22 ± 3)°C and | d humidity < 70%. |
| Calibration Equipment used (M& | ΓE critical for calibration) | | |
| Primary Standards | ID# | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
| Power meter E4419B | GB41293874 | 29-Mar-07 (METAS, No. 217-00670) | Mar-08 |
| Power sensor E4412A | MY41495277 | 29-Mar-07 (METAS, No. 217-00670) | Mar-08 |
| Power sensor E4412A | MY41498087 | 29-Mar-07 (METAS, No. 217-00670) | Mar-08 |
| Reference 3 dB Attenuator | SN: S5054 (3c) | 10-Aug-06 (METAS, No. 217-00592) | Aug-07 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 29-Mar-07 (METAS, No. 217-00671) | Mar-08 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 10-Aug-06 (METAS, No. 217-00593) | Aug-07 |
| Reference Probe ES3DV2 | SN: 3013 | 4-Jan-07 (SPEAG, No. ES3-3013_Jan07) | Jan-08 |
| DAE4 | SN: 654 | 20-Apr-07 (SPEAG, No. DAE4-654_Apr07) | Apr-08 |
| Secondary Standards | ID# | Check Date (in house) | Scheduled Check |
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (SPEAG, in house check Nov-05) | In house check: Nov-07 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (SPEAG, in house check Oct-06) | In house check: Oct-07 |
| | Name | Function | Signature |
| Calibrated by: | Katja Pokovic | Technical Manager | 10 VL |
| | | and the second s | |
| Approved by: | 2.57 | _ | |
| Approved by: | Niefs Kuster | Qualify Manager | |
| | William Control of the Control of th | | |
| This colibration continues of all and | Ab | 5 11 11 11 11 11 11 11 11 11 11 11 11 11 | Issued: July 6, 2007 |
| This calibration certificate shall no | it be reproduced except in | n full without written approval of the laboratory. | |

Certificate No: ET3-1528_Jul07

Page 1 of 9

Calibration Laboratory of

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura

Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL

tissue simulating liquid

NORMx,y,z

sensitivity in free space

ConF

sensitivity in TSL / NORMx,y,z

DCP Polarization φ

diode compression point

D i : "

 ϕ rotation around probe axis

Polarization 9

 ϑ rotation around an axis that is in the plane normal to probe axis (at

measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORMx,y,z: Assessed for E-field polarization θ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not effect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)x,y,z = NORMx,y,z * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ET3DV6

SN:1528

Manufactured:

March 21, 2000

Last calibrated:

July 12, 2006

Recalibrated:

July 6, 2007

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: ET3DV6 SN:1528

Diode Compression^B

July 6, 2007

| NormX | 1.52 ± 10.1% | μ V/(V/m) ² | DCP X | 96 mV |
|-------|---------------------|----------------------------|-------|--------------|
| NormY | 1.83 ± 10.1% | μ V/(V/m) ² | DCP Y | 94 mV |
| NormZ | 1.57 ± 10.1% | μ V/(V/m) ² | DCP Z | 96 mV |

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL

900 MHz

Typical SAR gradient: 5 % per mm

| Sensor Center to | 3.7 mm | 4.7 mm | |
|-----------------------|------------------------------|--------|-----|
| SAR _{be} [%] | Without Correction Algorithm | 8.9 | 4.7 |
| SAR _{be} [%] | With Correction Algorithm | 0.1 | 0.2 |

TSL

1750 MHz

Typical SAR gradient: 10 % per mm

| Sensor Center t | 3.7 mm | 4.7 mm | |
|-----------------------|------------------------------|--------|-----|
| SAR _{be} [%] | Without Correction Algorithm | 10.1 | 5.9 |
| SAR _{be} [%] | With Correction Algorithm | 0.3 | 0.6 |

Sensor Offset

Probe Tip to Sensor Center

2.7 mm


The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.


Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field: \pm 6.3% (k=2)

Receiving Pattern (ϕ), ϑ = 0°









Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Dynamic Range f(SAR_{head})

(Waveguide R22, f = 1800 MHz)







Uncertainty of Linearity Assessment: ± 0.6% (k=2)

ET3DV6 SN:1528 July 6, 2007

Conversion Factor Assessment






| f [MHz] | Validity [MHz] ^C | TSL | Permittivity | Conductivity | Alpha | Depth | ConvF Uncertainty |
|---------|-----------------------------|------|--------------|--------------|-------|-------|--------------------|
| 835 | ± 50 / ± 99 | Head | 41.5 ± 5% | 0.90 ± 5% | 0.32 | 2.62 | 6.39 ± 11.0% (k=2) |
| 900 | ± 50 / ± 100 | Head | 41.5 ± 5% | 0.97 ± 5% | 0.37 | 2.41 | 6.30 ± 11.0% (k=2) |
| 1750 | ± 50 / ± 100 | Head | 40.1 ± 5% | 1.37 ± 5% | 0.51 | 2.72 | 5.12 ± 11.0% (k=2) |
| 1900 | ± 50 / ± 100 | Head | 40.0 ± 5% | 1.40 ± 5% | 0.58 | 2.53 | 4.98 ± 11.0% (k=2) |
| | | | | | | | |
| | | | | | | | |
| 835 | ± 50 / ± 100 | Body | 55.2 ± 5% | 0.97 ± 5% | 0.31 | 2.80 | 6.19 ± 11.0% (k=2) |
| 900 | ± 50 / ± 100 | Body | 55.0 ± 5% | 1.05 ± 5% | 0.32 | 2.89 | 5.90 ± 11.0% (k=2) |
| 1750 | ± 50 / ± 100 | Body | 53.4 ± 5% | 1.49 ± 5% | 0.67 | 2.32 | 4.78 ± 11.0% (k=2) |
| 1900 | ± 50 / ± 100 | Body | 53.3 ± 5% | 1.52 ± 5% | 0.75 | 2.22 | 4.57 ± 11.0% (k=2) |

 $^{^{\}rm C}$ The validity of \pm 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ , ϑ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

A1237

20/06/07

NM

Calibration Laboratory of

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client

RF

Certificate No: D1900V2-540 Jun07

Accreditation No.: SCS 108

CALIBRATION CERTIFICATE

Object

D1900V2 - SN: 540

Calibration procedure(s)

QA CAL-05.v7

Calibration procedure for dipole validation kits

Calibration date:

June 11, 2007

Condition of the calibrated item

In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID# | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|-----------------------------|------------------|---|------------------------|
| Power meter EPM-442A | GB37480704 | 03-Oct-06 (METAS, No. 217-00608) | Oct-07 |
| Power sensor HP 8481A | US37292783 | 03-Oct-06 (METAS, No. 217-00608) | Oct-07 |
| Reference 20 dB Attenuator | SN: 5086 (20g) | 10-Aug-06 (METAS, No 217-00591) | Aug-07 |
| Reference 10 dB Attenuator | SN: 5047.2 (10r) | 10-Aug-06 (METAS, No 217-00591) | Aug-07 |
| Reference Probe ET3DV6 | SN: 1507 | 19-Oct-06 (SPEAG, No. ET3-1507_Oct06) | Oct-07 |
| Reference Probe ES3DV3 | SN: 3025 | 19-Oct-06 (SPEAG, No. ES3-3025_Oct06) | Oct-07 |
| DAE4 | SN 601 | 30-Jan-07 (SPEAG, No. DAE4-601_Jan07) | Jan-08 |
| | | - | |
| Secondary Standards | ID# | Check Date (in house) | Scheduled Check |
| Power sensor HP 8481A | MY41092317 | 18-Oct-02 (SPEAG, in house check Oct-05) | In house check: Oct-07 |
| RF generator Agilent E4421B | MY41000675 | 11-May-05 (SPEAG, in house check Nov-05) | In house check: Nov-07 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (SPEAG, in house check Oct-06) | In house check: Oct-07 |
| | | | |
| | Name | Function | Signature |
| Calibrated by: | Claudio Leubler | Laboratory Technician | |

Katja Pokovic

Technical Manager

Issued: June 14, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D1900V2-540_Jun07

Approved by:

Calibration Laboratory of

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst

C Service suisse d'étalonnage Servizio svizzero di taratura

Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation

The Swiss Accreditation Service is one of the signatories to the EA

Accreditation No.: SCS 108

Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL tissue simulating liquid

ConvF sensitivity in TSL / NORM x,y,z

N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

d) DASY4 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| DASY Version | DASY4 | V4.7 |
|------------------------------|---------------------------|-------------|
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom V5.0 | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 1900 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|----------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 40.0 | 1.40 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 39.7 ± 6 % | 1.46 mho/m ± 6 % |
| Head TSL temperature during test | (21.5 ± 0.2) °C | | |

SAR result with Head TSL

| SAR averaged over 1 cm ³ (1 g) of Head TSL | condition | |
|---|--------------------|----------------------------|
| SAR measured | 250 mW input power | 9.25 mW / g |
| SAR normalized | normalized to 1W | 37.0 mW / g |
| SAR for nominal Head TSL parameters ¹ | normalized to 1W | 36.1 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
|---|--------------------|----------------------------|
| SAR measured | 250 mW input power | 4.89 mW / g |
| SAR normalized | normalized to 1W | 19.6 mW / g |
| SAR for nominal Head TSL parameters ¹ | normalized to 1W | 19.3 mW / g ± 16.5 % (k=2) |

Certificate No: D1900V2-540_Jun07

¹ Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|----------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 53.3 | 1.52 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 51.8 ± 6 % | 1.58 mho/m ± 6 % |
| Body TSL temperature during test | (21.2 ± 0.2) °C | | |

SAR result with Body TSL

| SAR averaged over 1 cm³ (1 g) of Body TSL | Condition | |
|--|--------------------|----------------------------|
| SAR measured | 250 mW input power | 9.52 mW / g |
| SAR normalized | normalized to 1W | 38.1 mW / g |
| SAR for nominal Body TSL parameters ² | normalized to 1W | 38.0 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | - |
|---|--------------------|----------------------------|
| SAR measured | 250 mW input power | 5.14 mW / g |
| SAR normalized | normalized to 1W | 20.6 mW / g |
| SAR for nominal Body TSL parameters ² | normalized to 1W | 20.7 mW / g ± 16.5 % (k=2) |

Certificate No: D1900V2-540_Jun07

² Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Appendix

Antenna Parameters with Head TSL

| Impedance, transformed to feed point | 51.9 Ω + 5.1 jΩ |
|--------------------------------------|-----------------|
| Return Loss | - 25.4 dB |

Antenna Parameters with Body TSL

| Impedance, transformed to feed point | 47.7 Ω + 4.8 jΩ |
|--------------------------------------|-----------------|
| Return Loss | - 25.3 dB |

General Antenna Parameters and Design

| Electrical Delay (one direction) | 1.197 ns |
|----------------------------------|----------|
| | |

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| Manufactured by | SPEAG |
|-----------------|---------------|
| Manufactured on | July 26, 2001 |

Certificate No: D1900V2-540_Jun07

DASY4 Validation Report for Head TSL

Date/Time: 11.06.2007 10:40:22

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:540

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL U10 BB;

Medium parameters used: f = 1900 MHz; $\sigma = 1.46$ mho/m; $\varepsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

Probe: ET3DV6 - SN1507 (HF); ConvF(4.97, 4.97, 4.97); Calibrated: 19.10.2006

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 30.01.2007

Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA;;

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.9 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 15.7 W/kg


SAR(1 g) = 9.25 mW/g; SAR(10 g) = 4.89 mW/g

Maximum value of SAR (measured) = 10.2 mW/g



0 dB = 10.2 mW/g

Impedance Measurement Plot for Head TSL



DASY4 Validation Report for Body TSL

Date/Time: 11.06.2007 11:24:00

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:540

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL U10 BB;

Medium parameters used: f = 1900 MHz; $\sigma = 1.59$ mho/m; $\varepsilon_r = 55.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

Probe: ET3DV6 - SN1507 (HF); ConvF(4.43, 4.43, 4.43); Calibrated: 19.10.2006

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 30.01.2007

Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA;;

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.9 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 15.8 W/kg


SAR(1 g) = 9.52 mW/g; SAR(10 g) = 5.14 mW/g

Maximum value of SAR (measured) = 10.6 mW/g



0 dB = 10.6 mW/g

Impedance Measurement Plot for Body TSL



Serial No: RFI/SARE1/RP72912JD01A

Page: 26 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Appendix 2. Measurement Methods

A.2.1. Evaluation Procedure

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a) (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices worn about the ear during normal operation, both the left and right ear positions were evaluated at the centre frequency of the band at maximum power. The side, which produced the greatest SAR, determined which side of the phantom would be used for the entire evaluation. The positioning of the head worn device relative to the phantom was dictated by the test specification identified in section 3.1 of this report.
 - (ii) For body worn devices or devices which can be operated within 20 cm of the body, the flat section of the SAM phantom was used were the size of the device(s) is normal. for bigger devices and base station the 2mm Oval phantom is used for evaluation. The type of device being evaluated dictated the distance of the EUT to the outer surface of the phantom flat section.
- b) The SAR was determined by a pre-defined procedure within the DASY4 software. The exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm or appropriate resolution.
- c) A 5x5x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d) If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

Serial No: RFI/SARE1/RP72912JD01A

Page: 27 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

A.2.2. Specific Absorption Rate (SAR) Measurements to OET Bulletin 65 Supplement C: (2001-01)

Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields

SAR measurements were performed in accordance with Appendix D of the standard FCC OET Bulletin 65 Supplement C: 2001, against appropriate limits for each measurement position in accordance with the standard.

The test was performed in a shielded enclosure with the temperature controlled to remain between +18.0°C and +25.0°C. The tissue equivalent material fluid temperature was controlled to give a maximum variation of ± 2.0°C

Prior to any SAR measurements on the EUT, system validation and material dielectric property measurements were conducted. In the absence of a detailed procedure within the specification, system validation and material dielectric property measurements were performed in accordance with Appendix C and Appendix D of FCC OET Bulletin 65 Supplement C: 2001.

Following the successful system validation and material dielectric property measurements, a SAR versus time sweep shall be performed within 10 mm of the phantom inner surface. If the EUT power output is stable after three minutes then the measurement probe will perform a coarse surface level scan at each test position in order to ascertain the location of the maximum local SAR level. Once this area had been established, a 5x5x7 cube of 343 points (5 mm spacing in each axis $\approx 27g$) will be centred at the area of concern. Extrapolation and interpolation will then be carried out on the 27g of tissue and the highest averaged SAR over a 10g cube determined.

Once the maximum interpolated SAR measurement is complete; the coarse scan is visually assessed to check for secondary peaks within 50% of the maximum SAR level. If there are any further SAR measurements required, extra 5x5x7 cubes shall be centred on each of these extra local SAR maxima.

At the end of each position test case a second time sweep shall be performed to check whether the EUT has remained stable throughout the test.

Serial No: RFI/SARE1/RP72912JD01A

Page: 28 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd

VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

Appendix 3. SAR Distribution Scans

This appendix contains SAR distribution scans which are not included in the total number of pages for this report.

| Scan Reference Number | Title |
|--------------------------|--|
| SCN/72912JD01/001 | Front Of EUT Facing Phantom PCS CH660 |
| SCN/72912JD01/002 | Front Of EUT Facing Phantom GPRS CH660 |
| SCN/72912JD01/003 | Rear Of EUT Facing Phantom GPRS CH660 |
| SCN/72912JD01/004 | Rear Of EUT Facing Phantom With PHF GPRS CH660 |
| SCN/72912JD01/005 | Touch Left PCS CH660 |
| SCN/72912JD01/006 | Tilt Left PCS CH660 |
| SCN/72912JD01/007 | Touch Right PCS CH660 |
| SCN/72912JD01/008 | Tilt Right PCS CH660 |
| SCN/72912JD01/009 | System Performance Check 1900MHz Head 10 12 07 |
| SCN/72912JD01/010 | System Performance Check 1900MHz Body 10 12 07 |

Serial No: RFI/SARE1/RP72912JD01A

Page: 29 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd


VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

SCN/72912JD01/001: Front Of EUT Facing Phantom PCS CH660

Date: 10/12/2007

DUT: Panasonic VS7x; Type: VS7x (Sample C8); Serial: 004401220367144



0 dB = 0.143 mW/g

Communication System: PCS 1900; Frequency: 1879.8 MHz; Duty Cycle: 1:8.3

Medium: 1900 MHz MSL Medium parameters used (interpolated): f = 1879.8 MHz; $\sigma = 1.48$ mho/m; $\varepsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section DASY4 Configuration:

- Probe: ET3DV6 - SN1528; ConvF(4.57, 4.57, 4.57); Calibrated: 06/07/2007

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn394; Calibrated: 24/05/2007
- Phantom: SAM 12a; Type: SAM 4.0; Serial: TP:1193
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Front Of EUT Facing Phantom - Middle/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.144 mW/g

Front Of EUT Facing Phantom - Middle/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.18 V/m; Power Drift = 0.056 dB, Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.082 mW/g

Maximum value of SAR (measured) = 0.143 mW/g

Serial No: RFI/SARE1/RP72912JD01A

Page: 30 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd


VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

SCN/72912JD01/002: Front Of EUT Facing Phantom GPRS CH660

Date: 10/12/2007

DUT: Panasonic VS7x; Type: VS7x (Sample C8); Serial: 004401220367144



0 dB = 0.183 mW/g

Communication System: GPRS 1900; Frequency: 1879.8 MHz;Duty Cycle: 1:4

Medium: 1900 MHz MSL Medium parameters used (interpolated): f = 1879.8 MHz; $\sigma = 1.48$ mho/m; $\varepsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section DASY4 Configuration:

- Probe: ET3DV6 - SN1528; ConvF(4.57, 4.57, 4.57); Calibrated: 06/07/2007

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn394; Calibrated: 24/05/2007
- Phantom: SAM 12a; Type: SAM 4.0; Serial: TP:1193
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Front Of EUT Facing Phantom - Middle/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.186 mW/g

Front Of EUT Facing Phantom - Middle/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.33 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.264 W/kg

SAR(1 g) = 0.170 mW/g; SAR(10 g) = 0.107 mW/g

Maximum value of SAR (measured) = 0.183 mW/g

Serial No: RFI/SARE1/RP72912JD01A

Page: 31 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd


VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

SCN/72912JD01/003: Rear Of EUT Facing Phantom GPRS CH660

Date: 10/12/2007

DUT: Panasonic VS7x; Type: VS7x (Sample C8); Serial: 004401220367144



0 dB = 0.360 mW/g

Communication System: GPRS 1900; Frequency: 1879.8 MHz; Duty Cycle: 1:4

Medium: 1900 MHz MSL Medium parameters used (interpolated): f = 1879.8 MHz; $\sigma = 1.48$ mho/m; $\varepsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1528; ConvF(4.57, 4.57, 4.57); Calibrated: 06/07/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn394; Calibrated: 24/05/2007
- Phantom: SAM 12a; Type: SAM 4.0; Serial: TP:1193
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Rear Of EUT Facing Phantom - Middle/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.369 mW/g

Rear Of EUT Facing Phantom - Middle/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 8.00 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.534 W/kg

SAR(1 g) = 0.334 mW/g; SAR(10 g) = 0.206 mW/gMaximum value of SAR (measured) = 0.360 mW/g

Serial No: RFI/SARE1/RP72912JD01A

Page: 32 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd


VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

SCN/72912JD01/004: Rear Of EUT Facing Phantom With PHF GPRS CH660

Date: 10/12/2007

DUT: Panasonic VS7x; Type: VS7x (Sample C8); Serial: 004401220367144



0 dB = 0.270 mW/g

Communication System: GPRS 1900; Frequency: 1879.8 MHz; Duty Cycle: 1:4

Medium: 1900 MHz MSL Medium parameters used (interpolated): f = 1879.8 MHz; $\sigma = 1.48$ mho/m; $\varepsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section DASY4 Configuration:

- Probe: ET3DV6 - SN1528; ConvF(4.57, 4.57, 4.57); Calibrated: 06/07/2007

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn394; Calibrated: 24/05/2007
- Phantom: SAM 12a; Type: SAM 4.0; Serial: TP:1193
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Rear Of EUT Facing Phantom With PHF - Middle/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.282 mW/g

Rear Of EUT Facing Phantom With PHF - Middle/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 7.59 V/m; Power Drift = -0.068 dB

Peak SAR (extrapolated) = 0.410 W/kg

SAR(1 g) = 0.253 mW/g; SAR(10 g) = 0.156 mW/gMaximum value of SAR (measured) = 0.270 mW/g

Serial No: RFI/SARE1/RP72912JD01A

Page: 33 of 60

Issue Date: 17 December 2007

Test of: Panasonic Mobile Comms Dev of Europe Ltd


VS7x

To: OET Bulletin 65 Supplement C: (2001-01)

SCN/72912JD01/005: Touch Left PCS CH660

Date: 10/12/2007

DUT: Panasonic VS7x; Type: VS7x (Sample C8); Serial: 004401220367144



0 dB = 0.452 mW/g

Communication System: PCS 1900; Frequency: 1879.8 MHz; Duty Cycle: 1:8.3

Medium: 1900 MHz HSL Medium parameters used (interpolated): f = 1879.8 MHz; $\sigma = 1.46$ mho/m; $\varepsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section DASY4 Configuration:

- Probe: ET3DV6 - SN1528; ConvF(4.98, 4.98, 4.98); Calibrated: 06/07/2007

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn394; Calibrated: 24/05/2007
- Phantom: SAM 12b; Type: SAM 4.0; Serial: TP:1197
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Touch Left - Middle/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.446 mW/g

Touch Left - Middle/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.0 V/m; Power Drift = 0.128 dB

Peak SAR (extrapolated) = 0.825 W/kg

SAR(1 g) = 0.412 mW/g; SAR(10 g) = 0.215 mW/gMaximum value of SAR (measured) = 0.452 mW/g