



# TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: SoftBank 001P

FCC ID: UCE210035A

To: FCC Part 15.225: 2010 Subpart C

**Test Report Serial No:**  
RFI-RPT-RP79566JD05A V3.0

**Version 3.0 supersedes all previous versions**

**This Test Report Is Issued Under The Authority  
Of Chris Guy, Head of Global Approvals:**

A handwritten signature in black ink.

<b>Checked By:</b>	A. Henriques
<b>Signature:</b>	A handwritten signature in black ink.
<b>Date of Issue:</b>	14 December 2010

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

This page has been left intentionally blank.

**Table of Contents**

<b>1. Customer Information .....</b>	<b>4</b>
<b>2. Summary of Testing .....</b>	<b>5</b>
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
<b>3. Equipment Under Test (EUT) .....</b>	<b>6</b>
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	8
<b>4. Operation and Monitoring of the EUT during Testing .....</b>	<b>9</b>
4.1. Operating Modes	9
4.2. Configuration and Peripherals	9
<b>5. Measurements, Examinations and Derived Results .....</b>	<b>10</b>
5.1. General Comments	10
5.2. Test Results	11
5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions	11
5.2.2. Receiver/Idle Mode Radiated Spurious Emissions	12
5.2.3. Transmitter Fundamental Field Strength	14
5.2.4. Transmitter Radiated Spurious Emissions	15
5.2.5. Transmitter Band Edge Radiated Emissions	17
5.2.6. Transmitter 20 dB Bandwidth	18
5.2.7. Transmitter Frequency Stability (Temperature & Voltage Variation)	19
<b>6. Measurement Uncertainty .....</b>	<b>20</b>
<b>Appendix 1. Test Equipment Used .....</b>	<b>21</b>

## **1. Customer Information**

<b>Company Name:</b>	Panasonic Mobile Communications Development of Europe Ltd.
<b>Address:</b>	Panasonic House Willoughby Road Bracknell Berkshire RG12 8FP United Kingdom

## 2. Summary of Testing

### 2.1. General Information

<b>Specification Reference:</b>	47CFR15.225
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart C (Radio Frequency Devices) - Section 15.225
<b>Specification Reference:</b>	47CFR15.107 and 47CFR15.109
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart B (Radio Frequency Devices) - Sections 15.107 and 15.109
<b>Specification Reference:</b>	47CFR15.209
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart C (Intentional Radiators) - Section 15.209
<b>Site Registration:</b>	209735
<b>Location of Testing:</b>	RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH.
<b>Test Dates:</b>	13 November 2010 to 18 November 2010

### 2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 15.107(a)	Receiver/Idle Mode AC Conducted Spurious Emissions	✓
Part 15.109	Receiver/Idle Mode Radiated Spurious Emissions	✓
Part 15.225(a)(b)(c)(d)	Transmitter Fundamental Field Strength	✓
Part 15.209(a), 15.225(d)	Transmitter Radiated Spurious Emissions	✓
Part 15.209(a), 15.225(c)(d)	Transmitter Band Edge Radiated Emissions	✓
Part 2.1049	Transmitter 20 dB Bandwidth	✓
Part 15.225(e)	Transmitter Frequency Stability (Temperature & Voltage Variation)	✓
<b>Key to Results</b>		
 = Complied	 = Did not comply	

### 2.3. Methods and Procedures

<b>Reference:</b>	ANSI C63.4 (2009)
<b>Title:</b>	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>Reference:</b>	ANSI C63.10 (2009)
<b>Title:</b>	American National Standard for Testing Unlicensed Wireless Devices

### 2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

### **3. Equipment Under Test (EUT)**

#### **3.1. Identification of Equipment Under Test (EUT)**

<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	001P
<b>IMEI:</b>	004401221005610
<b>Hardware Version Number:</b>	Rev C
<b>Software Version Number:</b>	001PVA13
<b>FCC ID:</b>	UCE210035A

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	Battery
<b>Model Name or Number:</b>	PMBAS1

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	AC Charger
<b>Model Name or Number:</b>	ZTDAA1

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	DC Charger
<b>Model Name or Number:</b>	PMJAA1

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	USB Data cable
<b>Model Name or Number:</b>	ZTFe01

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	Personal Hands-free
<b>Model Name or Number:</b>	ZTCK01

<b>Brand Name:</b>	SoftBank
<b>Description:</b>	Personal Hands-free Converter
<b>Model Name or Number:</b>	PMLAJ1

### **3.2. Description of EUT**

The equipment under test was a dual mode cellular mobile telephone with *Bluetooth*, WLAN and RFID.

### **3.3. Modifications Incorporated in the EUT**

No modifications were applied to the EUT during testing.

### **3.4. Additional Information Related to Testing**

<b>Tested Technology:</b>	RFID	
<b>Category of Equipment:</b>	Transceiver	
<b>Channel Spacing:</b>	Single channel device	
<b>Transmit Frequency Range:</b>	13.56 MHz	
<b>Receive Frequency Range:</b>	13.56 MHz	
<b>Power Supply Requirement:</b>	Nominal	3.7 V
	Minimum	3.4 V
	Maximum	4.2 V
<b>Tested Temperature Range:</b>	Minimum	-20°C
	Maximum	50°C

### **3.5. Support Equipment**

The following support equipment was used to exercise the EUT during testing:

<b>Brand Name:</b>	Not marked or stated
<b>Description:</b>	Micro SD Memory Card
<b>Model Name or Number:</b>	128 MB

<b>Brand Name:</b>	Buffalo
<b>Description:</b>	USB Hub
<b>Model Name or Number:</b>	BSH3U01

<b>Brand Name:</b>	Not marked or stated
<b>Description:</b>	Dummy battery
<b>Model Name or Number:</b>	Not marked or stated

<b>Brand Name:</b>	Sony
<b>Description:</b>	Laptop PC
<b>Model Name or Number:</b>	Vaio PCG-551N
<b>Serial Number:</b>	283506 2 1208763

## **4. Operation and Monitoring of the EUT during Testing**

### **4.1. Operating Modes**

The EUT was tested in the following operating mode(s):

- Receiver/Idle mode
- Constantly transmitting at full power with a modulated carrier in RFID test mode.

### **4.2. Configuration and Peripherals**

The EUT was tested in the following configuration(s):

- The RFID transmitter test mode was enabled by running a proprietary application on the laptop PC supplied by the client.
- Receiver Idle/standby mode radiated spurious emission tests were performed with the AC Charger connected to the EUT as this was found to be the worst case during pre-scans. All accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- Transmitter radiated spurious emission tests were performed with the Personal Hands Free connected to the EUT as this was found to be the worst case during pre-scans. All appropriate accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- As the EUT is not capable of transmitting while charging in RFID test mode, no AC Mains conducted emissions (150 kHz to 30 MHz) tests were performed in transmit mode.

## **5. Measurements, Examinations and Derived Results**

### **5.1. General Comments**

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6: Measurement Uncertainties* for details.

## **5.2. Test Results**

### **5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions**

#### **Test Summary:**

Test Engineer:	Ian Watch	Test Date:	13 November 2010
Test Sample IMEI:	004401221005610		

FCC Part:	15.107(a)
Test Method Used:	As detailed in ANSI C63.10 Section 6.2 referencing ANSI C63.4

#### **Environmental Conditions:**


Temperature (°C):	25
Relative Humidity (%):	25

#### **Results: Quasi Peak**

Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.258000	Neutral	35.8	61.5	25.7	Complied

#### **Note(s):**

1. All other emissions were >30 dB below the applicable limits.
2. All average emissions were >20 dB below the applicable limits.



*Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.*

**5.2.2. Receiver/Idle Mode Radiated Spurious Emissions****Test Summary:**

<b>Test Engineer:</b>	Ian Watch	<b>Test Date:</b>	13 November 2010 / 14 November 2010
<b>Test Sample IMEI:</b>	004401221005610		

<b>FCC Part:</b>	15.109
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Sections 6.3, 6.4 and 6.5 referencing ANSI C63.4
<b>Frequency Range:</b>	9 kHz to 1000 MHz

**Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	24




**Results: Quasi Peak**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
50.369	Vertical	26.1	40.0	13.9	Complied
107.592	Vertical	24.5	43.5	19.0	Complied
458.795	Vertical	28.1	46.0	17.9	Complied

**Note(s):**

1. Limits below 30 MHz are specified at a test distance of 30 metres, whilst below 0.49 MHz they are specified at a test distance of 300 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.
3. Final measurement values include corrections for antenna factor and cable losses.
4. All emissions on the 9 kHz to 150 kHz plot were investigated and found to be radiating from the test site turntable.
5. All other emissions shown on the pre-scan plots were investigated and found to be >20 dB below the applicable limit or below the measurement noise floor.

## Receiver/Idle Mode Radiated Spurious Emissions (continued)



### 5.2.3. Transmitter Fundamental Field Strength

#### Test Summary:

Test Engineer:	Ian Watch	Test Date:	13 November 2010
Test Sample IMEI:	004401221005610		

FCC Part:	15.225(a)(b)(c)(d)
Test Method Used:	ANSI C63.10 Section 6.4

#### Environmental Conditions:


Temperature (°C):	26
Relative Humidity (%):	24

#### Results: Quasi Peak

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit at 30 m (dB $\mu$ V/m)	Margin (dB)	Result
13.56	90° to EUT	-7.1	84.0	91.1	Complied

#### Note(s):

1. The limit is specified at a test distance of 30 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres. A distance extrapolation factor of 40 dB was used.



### **5.2.4. Transmitter Radiated Spurious Emissions**

#### **Test Summary:**

<b>Test Engineer:</b>	Ian Watch	<b>Test Date:</b>	13 November 2010 / 14 November 2010
<b>Test Sample IMEI:</b>	004401221005610		

<b>FCC Part:</b>	15.225(d) & 15.209(a)
<b>Test Method Used:</b>	As detailed in ANSI C63.10 Sections 6.3, 6.4 and 6.5 referencing ANSI C63.4
<b>Frequency Range:</b>	9 kHz to 1000 MHz

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	25
<b>Relative Humidity (%):</b>	27




#### **Results: Quasi Peak**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
67.798	Horizontal	31.2	40.0	8.8	Complied
149.156	Vertical	29.1	43.5	14.4	Complied
718.657	Vertical	34.2	46.0	11.8	Complied
881.404	Vertical	37.2	46.0	8.8	Complied
908.515	Vertical	38.1	46.0	7.9	Complied

#### **Note(s):**

1. Limits below 30 MHz are specified at a test distance of 30 metres, whilst below 0.49 MHz they are specified at a test distance of 300 metres. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).
2. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.
3. Final measurement values include corrections for antenna factor and cable losses.
4. The emission shown at approximately 13.56 MHz is the fundamental.
5. All emissions on the 9 kHz to 150 kHz plot were investigated and found to be radiating from the test site turntable.
6. All other emissions shown on the pre-scan plots were investigated and found to be >20 dB below the applicable limit or below the measurement system noise floor.

## Transmitter Radiated Spurious Emissions (continued)



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying table.

**5.2.5. Transmitter Band Edge Radiated Emissions****Test Summary:**

Test Engineer:	Ian Watch	Test Date:	13 November 2010
Test Sample IMEI:	004401221005610		

FCC Part:	15.225(c)(d) & 15.209(a)
Test Method Used:	As detailed in ANSI C63.10 Section 6.9.2

**Environmental Conditions:**

Temperature (°C):	27
Relative Humidity (%):	25

**Results: Quasi Peak Lower Band Edge**


Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
13.11	-24.3	29.5	53.8	Complied

**Results: Quasi Peak Upper Band Edge**

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
14.01	-24.3	29.5	53.8	Complied

**Note(s):**

1. A transducer factor on the measuring instrument was used to extrapolate the results at 3 metres to a distance of 30 metres where required. A distance extrapolation factor of 40 dB was used.



**5.2.6. Transmitter 20 dB Bandwidth****Test Summary:**

Test Engineer:	Ian Watch	Test Date:	13 November 2010
Test Sample IMEI:	004401221005610		


FCC Part:	2.1049
Test Method Used:	As detailed in ANSI C63.10 Section 6.9.1

**Environmental Conditions:**

Temperature (°C):	25
Relative Humidity (%):	24

**Results:**

20 dB Bandwidth (kHz)	
	37.475



**5.2.7. Transmitter Frequency Stability (Temperature & Voltage Variation)****Test Summary:**

Test Engineer:	Ian Watch	Test Date:	18 November 2010
Test Sample IMEI:	004401221005610		

FCC Part:	15.225(e)
Test Method Used:	As detailed in ANSI C63.10 Section 6.8.1 and 6.8.2

**Environmental Conditions:**

Ambient Temperature (°C):	20
Ambient Relative Humidity (%):	34

**Results: Maximum frequency error of the EUT with variations in ambient temperature**

Temperature (°C)	Time after Start-up			
	0 minutes	2 minutes	5 minutes	10 minutes
-20	13.560099 MHz	13.560097 MHz	13.560095 MHz	13.560093 MHz
20	13.560008 MHz	13.599999 MHz	13.559995 MHz	13.559996 MHz
50	13.559890 MHz	13.559888 MHz	13.559886 MHz	13.559885 MHz

Frequency with Worst Case Deviation (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
13.559885	115	0.000848	0.01	0.009152	Complied

**Results: Maximum frequency error of the EUT with variations in nominal operating voltage at an ambient temperature of 20°C**

Supply Voltage (V)	Nominal Frequency (MHz)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
3.4	13.56	13.559996	4	0.000029	0.01	0.009971	Complied
3.7	13.56	13.560008	8	0.000059	0.01	0.009941	Complied
4.2	13.56	13.559995	5	0.000037	0.01	0.009963	Complied

## **6. Measurement Uncertainty**

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±3.25 dB
20 dB Bandwidth	13 MHz to 14 MHz	95%	±0.92 ppm
Frequency Stability	13 MHz to 14 MHz	95%	±0.92 ppm
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	±3.53 dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	±2.94 dB
Transmitter Fundamental Field Strength	13 MHz to 14 MHz	95%	±3.53 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

## Appendix 1. Test Equipment Used

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
A007	Antenna	Rohde & Schwarz	HFH2-Z2	880 458/020	29 Mar 2011	12
A1069	LISN	Rohde & Schwarz	ESH3-Z5	837469/012	13 Apr 2011	12
A1830	Pulse Limiter	Rhode & Schwarz	ESH3-Z2	100668	01 Mar 2011	12
A288	Antenna	Chase	CBL6111A	1589	05 Sep 2011	12
E0513	Environmental Chamber	TAS	LT600	23900506	Calibrated before use	-
K0001	5m Semi-Anechoic Chamber	Rainford EMC	N/A	N/A	25 Apr 2011	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	05 Sep 2011	12
M1068	Thermometer	Iso-Tech	RS55	93102884	10 Nov 2011	12
M1124	Test Receiver	Rohde & Schwarz	ESI26	100046K	22 Apr 2011	12
M1229	Digital Multimeter	Fluke	179	87640015	15 Jul 2011	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	28 Jun 2011	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	01 Apr 2011	12
M1379	Test Receiver	Rohde & Schwarz	ESIB7	100330	26 Aug 2011	12
S0536	Power Supply	TTI	EL302D	249944	Calibrated before use	-

**NB** In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.