

TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: SoftBank 001P

FCC ID: UCE210035A

To: FCC Part 24: 2010 Subpart E

Test Report Serial No:
RFI-RPT-RP79566JD07A

This Test Report Is Issued Under The Authority
Of Chris Guy, Head of Global Approvals:



| | |
|-----------------------|--|
| Checked By: | A. Henriques |
| Signature: |  |
| Date of Issue: | 24 November 2010 |

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

This page has been left intentionally blank.

Table of Contents

| | |
|--|-----------|
| 1. Customer Information | 4 |
| 2. Summary of Testing | 5 |
| 2.1. General Information | 5 |
| 2.2. Summary of Test Results | 5 |
| 2.3. Methods and Procedures | 5 |
| 2.4. Deviations from the Test Specification | 5 |
| 3. Equipment Under Test (EUT) | 6 |
| 3.1. Identification of Equipment Under Test (EUT) | 6 |
| 3.2. Description of EUT | 7 |
| 3.3. Modifications Incorporated in the EUT | 7 |
| 3.4. Additional Information Related to Testing | 7 |
| 3.5. Support Equipment | 8 |
| 4. Operation and Monitoring of the EUT during Testing | 9 |
| 4.1. Operating Modes | 9 |
| 4.2. Configuration and Peripherals | 9 |
| 5. Measurements, Examinations and Derived Results | 10 |
| 5.1. General Comments | 10 |
| 5.2. Test Results | 11 |
| 5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions | 11 |
| 5.2.2. Receiver/Idle Mode Radiated Spurious Emissions | 12 |
| 5.2.3. Transmitter Output Power (EIRP) | 16 |
| 5.2.4. Transmitter Conducted Output Power | 17 |
| 5.2.5. Transmitter Frequency Stability (Temperature Variation) | 18 |
| 5.2.6. Transmitter Frequency Stability (Voltage Variation) | 20 |
| 5.2.7. Transmitter Occupied Bandwidth | 21 |
| 5.2.8. Transmitter Out of Band Radiated Emissions | 23 |
| 5.2.9. Transmitter Band Edge Radiated Emissions | 26 |
| 6. Measurement Uncertainty | 28 |
| Appendix 1. Test Equipment Used..... | 29 |

1. Customer Information

| | |
|----------------------|--|
| Company Name: | Panasonic Mobile Communications Development of Europe Ltd. |
| Address: | Panasonic House Willoughby Road Bracknell Berkshire RG12 8FP United Kingdom |

2. Summary of Testing

2.1. General Information

| | |
|---------------------------------|---|
| Specification Reference: | 47CFR24 |
| Specification Title: | Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 24 Subpart E (Personal Communication Services) |
| Specification Reference: | 47CFR15.107 and 47CFR15.109 |
| Specification Title: | Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart B (Unintentional Radiators) - Sections 15.107 and 15.109 |
| Site Registration: | 209735 |
| Location of Testing: | RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH. |
| Test Dates: | 13 November 2010 to 18 November 2010 |

2.2. Summary of Test Results

| FCC Reference (47CFR) | Measurement | Result |
|-----------------------|---|--------|
| Part 15.107(a) | Receiver/Idle Mode AC Conducted Spurious Emissions | ✓ |
| Part 15.109 | Receiver/Idle Mode Radiated Spurious Emissions | ✓ |
| Part 24.232 | Transmitter Output Power (EIRP) | ✓ |
| Part 2.1046 | Transmitter Conducted Output Power | Note 1 |
| Part 2.1055/24.235 | Transmitter Frequency Stability (Temperature and Voltage Variation) | ✓ |
| Part 2.1049 | Transmitter Occupied Bandwidth | ✓ |
| Part 2.1053/24.238 | Transmitter Out of Band Radiated Emissions | ✓ |
| Part 2.1053/24.238 | Transmitter Band Edge Radiated Emissions | ✓ |
| Key to Results | | |
| ✓ = Complied | ✗ = Did not comply | |

Note 1: The measurement was performed to support SAR tests.

2.3. Methods and Procedures

| | |
|-------------------|--|
| Reference: | ANSI/TIA-603-C-2004 |
| Title: | Land Mobile Communications Equipment, Measurements and performance Standards |
| Reference: | ANSI C63.4 (2009) |
| Title: | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz. |

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

| | |
|---------------------------------|--|
| Brand Name: | SoftBank |
| Model Name or Number: | 001P |
| IMEI: | 004401221005610 (<i>Radiated sample</i>) |
| Hardware Version Number: | Rev C |
| Software Version Number: | 001PVA13 |
| FCC ID: | UCE210035A |

| | |
|---------------------------------|---|
| Brand Name: | SoftBank |
| Model Name or Number: | 001P |
| IMEI: | 004401221005552 (<i>Conducted RF port sample</i>) |
| Hardware Version Number: | Rev C |
| Software Version Number: | 001PVA13 |
| FCC ID: | UCE210035A |

| | |
|------------------------------|----------|
| Brand Name: | SoftBank |
| Description: | Battery |
| Model Name or Number: | PMBAS1 |

| | |
|------------------------------|------------|
| Brand Name: | SoftBank |
| Description: | AC Charger |
| Model Name or Number: | ZTDA1 |

| | |
|------------------------------|------------|
| Brand Name: | SoftBank |
| Description: | DC Charger |
| Model Name or Number: | PMJAA1 |

| | |
|------------------------------|----------------|
| Brand Name: | SoftBank |
| Description: | USB Data cable |
| Model Name or Number: | ZTAE01 |

| | |
|------------------------------|---------------------|
| Brand Name: | SoftBank |
| Description: | Personal Hands-free |
| Model Name or Number: | ZTCK01 |

| | |
|------------------------------|-------------------------------|
| Brand Name: | SoftBank |
| Description: | Personal Hands-free Converter |
| Model Name or Number: | PMLAJ1 |

3.2. Description of EUT

The equipment under test was a dual mode Cellular Mobile Telephone with Bluetooth, WLAN and RFID.

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

| | | | |
|-------------------------------------|-------------------|-----------------------|--------------------------------|
| Technology Tested: | PCS1900 | | |
| Type of Radio Device: | Transceiver | | |
| Mode: | GSM/GPRS | | |
| Modulation Type: | GMSK | | |
| Channel Spacing: | 200 kHz | | |
| Power Supply Requirement(s): | Nominal | 3.7 V | |
| | Minimum | 3.4 V | |
| | Maximum | 4.2 V | |
| Maximum Output Power (EIRP): | GSM | 27.8 dBm | |
| | GPRS | 26.1 dBm | |
| Transmit Frequency Range: | 1850 to 1910 MHz | | |
| Transmit Channels Tested: | Channel ID | Channel Number | Channel Frequency (MHz) |
| | Bottom | 512 | 1850.2 |
| | Middle | 660 | 1879.8 |
| | Top | 810 | 1909.8 |
| Receive Frequency Range: | 1930 to 1990 MHz | | |
| Receive Channels Tested: | Channel ID | Channel Number | Channel Frequency (MHz) |
| | Bottom | 512 | 1930.2 |
| | Middle | 660 | 1959.8 |
| | Top | 810 | 1989.8 |

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

| | |
|------------------------------|----------------------|
| Brand Name: | Not marked or stated |
| Description: | Micro SD Memory Card |
| Model Name or Number: | 128 MB |

| | |
|------------------------------|---------|
| Brand Name: | Buffalo |
| Description: | USB Hub |
| Model Name or Number: | BSH3U01 |

| | |
|------------------------------|----------------------|
| Brand Name: | Not marked or stated |
| Description: | Dummy battery |
| Model Name or Number: | Not marked or stated |

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

- Receiver/Idle mode.
- Constantly transmitting at full power on bottom, middle and top channels as required.
- Occupied bandwidth, EIRP and band edge tests were performed with the EUT in GSM single timeslot circuit switched and GPRS Multislot Class 10 with the unit transmitting on two timeslots in the uplink.
- Transmitter radiated spurious emissions were checked in all modes during pre-scans. Circuit switched voice was found to be the worst case and all final measurements were performed with the EUT in this mode.

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- The sample with IMEI 004401221005552 was used for frequency stability, occupied bandwidth and conducted power measurements. The sample with IMEI 004401221005610 was used for all other measurements.
- The SDRAM card was present in the EUT during all tests.
- The dummy battery was fitted for frequency stability measurements.
- Idle mode and transmitter mode radiated spurious emissions tests were performed with the AC charger connected to the EUT as this was found to be the worst case during pre-scans. All accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- Connected to a GSM/GPRS system simulator, operating in transceiver mode

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

5.2. Test Results

5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions

Test Summary:

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 13 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |

| | |
|-------------------|---|
| FCC Part: | 15.107(a) |
| Test Method Used: | As detailed in ANSI C63.10 Section 6.2 referencing ANSI C63.4 |

Environmental Conditions:


| | |
|------------------------|----|
| Temperature (°C): | 25 |
| Relative Humidity (%): | 25 |

Results: Quasi Peak

| Frequency (MHz) | Line | Level (dB μ V) | Limit (dB μ V) | Margin (dB) | Result |
|-----------------|---------|--------------------|--------------------|-------------|----------|
| 0.258000 | Neutral | 35.8 | 61.5 | 25.7 | Complied |

Note(s):

1. All other emissions were >30 dB below the applicable limits.
2. All average emissions were >20 dB below the applicable limits



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

5.2.2. Receiver/Idle Mode Radiated Spurious Emissions**Test Summary:**

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 14 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |

| | |
|-------------------|--|
| FCC Part: | 15.109 |
| Test Method Used: | As detailed in ANSI C63.10 Sections 6.3 and 6.5 referencing ANSI C63.4 |
| Frequency Range: | 30 MHz to 1000 MHz |

Environmental Conditions:


| | |
|------------------------|----|
| Temperature (°C): | 27 |
| Relative Humidity (%): | 24 |

Results: Quasi Peak

| Frequency (MHz) | Antenna Polarity | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Result |
|-----------------|------------------|----------------------|----------------------|-------------|----------|
| 50.369 | Vertical | 26.1 | 40.0 | 13.9 | Complied |
| 107.592 | Vertical | 24.5 | 43.5 | 19.0 | Complied |
| 458.795 | Vertical | 28.1 | 46.0 | 17.9 | Complied |

Note(s):

1. The final measured value, for the given emission, in the table above incorporates the calibrated antenna factor and cable loss.
2. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.

Receiver/Idle Mode Radiated Spurious Emissions (continued)

Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Receiver/Idle Mode Radiated Spurious Emissions (continued)**Test Summary:**

| | | | |
|--------------------------|-----------------|-------------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 14 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |

| | |
|--------------------------|--|
| FCC Part: | 15.109 |
| Test Method Used: | As detailed in ANSI C63.10 Sections 6.3 and 6.6 referencing ANSI C63.4 |
| Frequency Range: | 1 GHz to 10 GHz |

Environmental Conditions:

| | |
|-------------------------------|----|
| Temperature (°C): | 23 |
| Relative Humidity (%): | 25 |





Results:

| Frequency (MHz) | Antenna Polarity | Peak Level (dB μ V/m) | Average Limit (dB μ V/m) | Margin (dB) | Result |
|-----------------|------------------|---------------------------|------------------------------|-------------|----------|
| 3933.868 | Vertical | 47.5 | 54.0 | 6.5 | Complied |

Note(s):

1. The final measured value, for the given emission, in the table above incorporates the calibrated antenna factor and cable loss.
2. No spurious emissions were detected above the noise floor of the measuring receiver therefore the highest peak noise floor reading of the measuring receiver was recorded as shown in the table above. The peak level was compared to the average limit as opposed to being compared to the peak limit because this is the more onerous limit.

Receiver/Idle Mode Radiated Spurious Emissions (continued)



5.2.3. Transmitter Output Power (EIRP)**Test Summary:**

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 14 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |

| | |
|-------------------|---|
| FCC Part: | 24.232 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.17.2 |

Environmental Conditions:

| | |
|------------------------|----|
| Temperature (°C): | 23 |
| Relative Humidity (%): | 25 |

Results: GSM Circuit Switched

| Channel | Frequency (MHz) | Antenna Polarity | EIRP (dBm) | Limit (dBm) | Margin (dB) | Result |
|---------|-----------------|------------------|------------|-------------|-------------|----------|
| Bottom | 1850.2 | Vertical | 19.5 | 33.0 | 13.5 | Complied |
| Middle | 1879.8 | Vertical | 23.0 | 33.0 | 10.0 | Complied |
| Top | 1909.8 | Vertical | 27.8 | 33.0 | 5.2 | Complied |

Results: GPRS

| Channel | Frequency (MHz) | Antenna Polarity | EIRP (dBm) | Limit (dBm) | Margin (dB) | Result |
|---------|-----------------|------------------|------------|-------------|-------------|----------|
| Bottom | 1850.2 | Vertical | 17.2 | 33.0 | 15.8 | Complied |
| Middle | 1879.8 | Vertical | 20.9 | 33.0 | 12.1 | Complied |
| Top | 1909.8 | Vertical | 26.1 | 33.0 | 6.9 | Complied |

5.2.4. Transmitter Conducted Output Power

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 16 November 2010 |
| Test Sample IMEI: | 004401221005552 | | |

| | |
|-------------------|---|
| FCC Part: | 2.1046 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.1 referencing FCC CFR Part 2.1046(a) |

Environmental Conditions:

| | |
|------------------------|----|
| Temperature (°C): | 25 |
| Relative Humidity (%): | 23 |

Results: GSM Circuit Switched

| Channel | Frequency (MHz) | Maximum Peak Conducted Power (dBm) | Maximum Average Conducted Power (dBm) |
|---------|-----------------|------------------------------------|---------------------------------------|
| Bottom | 1850.2 | 29.4 | 29.3 |
| Middle | 1879.8 | 29.7 | 29.5 |
| Top | 1909.8 | 29.9 | 29.8 |

Results: GPRS

| Channel | Frequency (MHz) | Maximum Peak Conducted Power (dBm) | Maximum Average Conducted Power (dBm) |
|---------|-----------------|------------------------------------|---------------------------------------|
| Bottom | 1850.2 | 27.4 | 27.3 |
| Middle | 1879.8 | 27.6 | 27.5 |
| Top | 1909.8 | 27.8 | 27.7 |

Note(s):

- Conducted power tests were performed to support SAR tests.

5.2.5. Transmitter Frequency Stability (Temperature Variation)**Test Summary:**

| | | | |
|--------------------------|-----------------|-------------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 16 November 2010 |
| Test Sample IMEI: | 004401221005552 | | |

| | |
|--------------------------|--|
| FCC Part: | 2.1055 & 24.235 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.2 referencing FCC CFR Part 2.1055 |

Environmental Conditions:

| | |
|---------------------------------------|----|
| Ambient Temperature (°C): | 24 |
| Ambient Relative Humidity (%): | 25 |

Results: Bottom Channel (1850.2 MHz)

| Temperature (°C) | Frequency Error (Hz) | Measured Frequency (MHz) | Lower Band Edge Limit (MHz) | Margin (MHz) | Result |
|------------------|----------------------|--------------------------|-----------------------------|--------------|----------|
| -30 | 22 | 1850.199978 | 1850.0 | 0.199978 | Complied |
| -20 | 8 | 1850.200008 | 1850.0 | 0.200008 | Complied |
| -10 | 20 | 1850.200020 | 1850.0 | 0.200020 | Complied |
| 0 | 14 | 1850.200014 | 1850.0 | 0.200014 | Complied |
| 10 | 17 | 1850.199983 | 1850.0 | 0.199983 | Complied |
| 20 | 9 | 1850.199991 | 1850.0 | 0.199991 | Complied |
| 30 | 24 | 1850.199976 | 1850.0 | 0.199976 | Complied |
| 40 | 17 | 1850.199983 | 1850.0 | 0.199983 | Complied |
| 50 | 9 | 1850.199991 | 1850.0 | 0.199991 | Complied |

Results: Top Channel (1909.8 MHz)

| Temperature (°C) | Frequency Error (Hz) | Measured Frequency (MHz) | Upper Band Edge Limit (MHz) | Margin (MHz) | Result |
|------------------|----------------------|--------------------------|-----------------------------|--------------|----------|
| -30 | 33 | 1909.799967 | 1910.0 | 0.200033 | Complied |
| -20 | 17 | 1909.800017 | 1910.0 | 0.199983 | Complied |
| -10 | 27 | 1909.800027 | 1910.0 | 0.199973 | Complied |
| 0 | 17 | 1909.800017 | 1910.0 | 0.199983 | Complied |
| 10 | 16 | 1909.799984 | 1910.0 | 0.200016 | Complied |
| 20 | 19 | 1909.799981 | 1910.0 | 0.200019 | Complied |
| 30 | 28 | 1909.799972 | 1910.0 | 0.200028 | Complied |
| 40 | 29 | 1909.799971 | 1910.0 | 0.200029 | Complied |
| 50 | 20 | 1909.800020 | 1910.0 | 0.199980 | Complied |

Transmitter Frequency Stability (Temperature Variation) (continued)**Note(s):**

1. Temperature was monitored throughout the test with a calibrated digital thermometer.

5.2.6. Transmitter Frequency Stability (Voltage Variation)**Test Summary:**

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 16 November 2010 |
| Test Sample IMEI: | 004401221005552 | | |

| | |
|-------------------|--|
| FCC Part: | 2.1055 & 24.235 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.2 referencing FCC CFR Part 2.1055 |

Environmental Conditions:

| | |
|------------------------|----|
| Temperature (°C): | 25 |
| Relative Humidity (%): | 23 |

Results: Bottom Channel (1850.2 MHz)

| Supply Voltage (V) | Frequency Error (Hz) | Measured Frequency (MHz) | Lower Band Edge Limit (MHz) | Margin (MHz) | Result |
|--------------------|----------------------|--------------------------|-----------------------------|--------------|----------|
| 3.4 | 14 | 1850.199986 | 1850.0 | 0.199986 | Complied |
| 4.2 | 18 | 1850.199982 | 1850.0 | 0.199982 | Complied |

Results: Top Channel (1909.8 MHz)

| Supply Voltage (V) | Frequency Error (Hz) | Measured Frequency (MHz) | Upper Band Edge Limit (MHz) | Margin (MHz) | Result |
|--------------------|----------------------|--------------------------|-----------------------------|--------------|----------|
| 3.4 | 26 | 1909.799974 | 1910.0 | 0.200026 | Complied |
| 4.2 | 17 | 1909.799983 | 1910.0 | 0.200017 | Complied |

Note(s):

1. Voltage was monitored throughout the test with a calibrated digital voltmeter.

5.2.7. Transmitter Occupied Bandwidth**Test Summary:**

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 18 November 2010 |
| Test Sample IMEI: | 004401221005552 | | |

| | |
|-------------------|--|
| FCC Part: | 2.1049 |
| Test Method Used: | As detailed in ANSI C63.4 Section 13.7 referencing FCC CFR Part 2.1049 |

Environmental Conditions:

| | |
|------------------------|----|
| Temperature (°C): | 24 |
| Relative Humidity (%): | 34 |

Results: GSM Circuit Switched

| Channel | Frequency (MHz) | Occupied Bandwidth (kHz) |
|---------|-----------------|--------------------------|
| Middle | 1879.8 | 241.683 |



Results: GPRS

| Channel | Frequency (MHz) | Occupied Bandwidth (kHz) |
|---------|-----------------|--------------------------|
| Middle | 1879.8 | 239.279 |

Note(s):

1. In lieu of the test method detailed in ANSI C63.4 Section 13.7, the 99% occupied bandwidth was measured using the Occupied Bandwidth function of a spectrum analyser.

Transmitter Occupied Bandwidth (continued)



5.2.8. Transmitter Out of Band Radiated Emissions**Test Summary:**

| | | | |
|--------------------------|-----------------|-------------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 17 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |

| | |
|--------------------------|---|
| FCC Part: | 2.1053 & 24.238 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.12 referencing FCC CFR Parts 2.1053 and 24.238 |
| Frequency Range: | 30 MHz to 20 GHz |
| Configuration: | GSM Circuit Switched |

Environmental Conditions:

| | |
|-------------------------------|----|
| Temperature (°C): | 25 |
| Relative Humidity (%): | 22 |

Results: Bottom Channel

| Frequency (MHz) | Peak Level (dBm) | Limit (dBm) | Margin (dB) | Result |
|------------------------|-------------------------|--------------------|--------------------|---------------|
| 3700.466 | -27.8 | -13.0 | 14.8 | Complied |
| 9250.990 | -31.4 | -13.0 | 18.4 | Complied |

Results: Middle Channel

| Frequency (MHz) | Peak Level (dBm) | Limit (dBm) | Margin (dB) | Result |
|------------------------|-------------------------|--------------------|--------------------|---------------|
| 3759.604 | -28.8 | -13.0 | 15.8 | Complied |
| 9399.010 | -26.3 | -13.0 | 13.3 | Complied |





Results: Top Channel

| Frequency (MHz) | Peak Level (dBm) | Limit (dBm) | Margin (dB) | Result |
|------------------------|-------------------------|--------------------|--------------------|---------------|
| 3819.639 | -26.8 | -13.0 | 13.8 | Complied |
| 9549.108 | -30.5 | -13.0 | 17.5 | Complied |




Note(s):

1. The uplink and downlink traffic channels are shown on the 1 GHz to 4 GHz plot at approximately 1909 MHz and 1992 MHz.
2. Final measurements were made using appropriate RF filters and attenuators where required.

Transmitter Out of Band Radiated Emissions (continued)



Transmitter Out of Band Radiated Emissions (continued)



5.2.9. Transmitter Band Edge Radiated Emissions

Test Summary:

| | | | |
|-------------------|-----------------|------------|------------------|
| Test Engineer: | Ian Watch | Test Date: | 18 November 2010 |
| Test Sample IMEI: | 004401221005610 | | |



| | |
|-------------------|---|
| FCC Part: | 2.1053 & 24.238 |
| Test Method Used: | As detailed in ANSI TIA-603-C-2004 Section 2.2.12 referencing FCC CFR Parts 2.1053 and 24.238 |

Environmental Conditions:

| | |
|------------------------|----|
| Temperature (°C): | 24 |
| Relative Humidity (%): | 33 |



Results: GSM Circuit Switched

| Frequency (MHz) | Peak Level (dBm) | Limit (dBm) | Margin (dB) | Result |
|-----------------|------------------|-------------|-------------|----------|
| 1850 | -24.2 | -13.0 | 11.2 | Complied |
| 1910 | -18.3 | -13.0 | 5.3 | Complied |
| 1910.01523 | -17.0 | -13.0 | 4.0 | Complied |



Transmitter Band Edge Radiated Emissions (continued)**Results: GPRS**

| Frequency (MHz) | Peak Level (dBm) | Limit (dBm) | Margin (dB) | Result |
|-----------------|------------------|-------------|-------------|----------|
| 1850 | -27.2 | -13.0 | 14.2 | Complied |
| 1910 | -20.8 | -13.0 | 7.8 | Complied |
| 1910.01914 | -19.0 | -13.0 | 6.0 | Complied |



6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

| Measurement Type | Range | Confidence Level (%) | Calculated Uncertainty |
|---|--------------------|----------------------|------------------------|
| AC Conducted Spurious Emissions | 0.15 MHz to 30 MHz | 95% | ±3.25 dB |
| Effective Isotropic Radiated Power (EIRP) | 1850 to 1910 MHz | 95% | ±2.94 dB |
| Conducted Output Power | 1850 to 1910 MHz | 95% | ±0.27 dB |
| Frequency Stability | 1850 to 1910 MHz | 95% | ±0.92 ppm |
| Occupied Bandwidth | 1850 to 1910 MHz | 95% | ±0.92 ppm |
| Radiated Spurious Emissions | 30 MHz to 20 GHz | 95% | ±2.94 dB |

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

Appendix 1. Test Equipment Used

| RFI No. | Instrument | Manufacturer | Type No. | Serial No. | Date Calibration Due | Cal. Interval (Months) |
|---------|---------------------|-----------------|-----------|------------|-----------------------|------------------------|
| A1069 | LISN | Rohde & Schwarz | ESH3-Z5 | 837469/012 | 13 Apr 2011 | 12 |
| A1396 | Attenuator | Huber + Suhner | 757987 | 6810.17.B | 06 Jul 2011 | 12 |
| A1415 | Directional Coupler | Atlantic | 422057-1 | 306 | Calibrated before use | - |
| A1534 | Pre Amplifier | Hewlett Packard | 8449B | 3008A00405 | 06 Jun 2011 | 12 |
| A1818 | Antenna | EMCO | 3115 | 00075692 | 05 Sep 2011 | 12 |
| A1830 | Pulse Limiter | Rhode & Schwarz | ESH3-Z2 | 100668 | 01 Mar 2011 | 12 |
| A1975 | High Pass Filter | AtlanTecRF | AFH-03000 | 090424010 | 22 Jan 2011 | 12 |
| A244 | Attenuator | Schaffner | 6820-17-B | None | Calibrated before use | - |
| A253 | Antenna | Flann Microwave | 12240-20 | 128 | 05 Sep 2011 | 12 |
| A254 | Antenna | Flann Microwave | 14240-20 | 139 | 05 Sep 2011 | 12 |
| A255 | Antenna | Flann Microwave | 16240-20 | 519 | 05 Sep 2011 | 12 |
| A256 | Antenna | Flann Microwave | 18240-20 | 400 | 05 Sep 2011 | 12 |
| A288 | Antenna | Chase | CBL6111A | 1589 | 05 Sep 2011 | 12 |
| A436 | Antenna | Flann Microwave | 20240-20 | 330 | 05 Sep 2011 | 12 |
| K0002 | 3m RSE Chamber | Rainford EMC | N/A | N/A | 05 Sep 2011 | 12 |
| L1005 | Comms Test Set | Rohde & Schwarz | CMU200 | 116284 | 29 Jan 2011 | 12 |
| M1068 | Thermometer | Iso-Tech | RS55 | 93102884 | 10 Nov 2011 | 12 |
| M1124 | Test Receiver | Rohde & Schwarz | ESI26 | 100046K | 22 Apr 2011 | 12 |
| M1229 | Digital Multimeter | Fluke | 179 | 87640015 | 15 Jul 2011 | 12 |
| M1263 | Test Receiver | Rohde & Schwarz | ESIB7 | 100265 | 28 Jun 2011 | 12 |
| S0520 | Power Supply | GW instek | GPC-3030 | E835141 | Calibrated before use | - |

NB In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.