on 2.0 Issue Date: 05 July 2011

Appendix 5. Validation of System

Prior to the assessment, the system was verified in the flat region of the phantom. A 900MHz, 1900MHz and a 2450MHz dipole was used. A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of $\pm 5\%$ for the 900MHz, 1900MHz and a 2450 MHz dipole.

The applicable verification normalised to 1 Watt.

Date: 27/05/2011	
Validation Dipole and Serial	Number: D900V2; SN: 185

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
		23.0 °C	22.8 °C	ε _r	41.50	41.13	-0.90	5.00
Head 900	900			σ	0.97	0.93	-3.96	5.00
	900			1g SAR	11.00	10.68	-2.91	5.00
				10g SAR	7.06	6.92	-1.98	5.00

Date: 28/05/2011

Validation Dipole and Serial Number: D900V2; SN: 185

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
		23.0	22.3	ε _r	55.0	52.69	-4.20	5.00
Body 900	900			σ	1.05	1.05	0.21	5.00
	°C	°C	1g SAR	11.00	11.24	2.18	5.00	
				10g SAR	7.16	7.28	1.68	5.00

Date: 29/05/2011

Validation Dipole and Serial Number: D1900V2; SN: 540

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
		23.0 °C	22.3 ℃	ε _r	40.00	38.30	-4.25	5.00
Head 1900	1000			σ	1.40	1.41	1.01	5.00
	1900			1g SAR	40.30	41.20	2.23	5.00
				10g SAR	21.00	21.16	0.76	5.00

Page: 154 of 160 RFI Global Services Ltd.

Issue Date: 05 July 2011

Validation of System (Conti

Date: 30/05/2011

Validation Dipole and Serial Number: D1900V2; SN: 540

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
		22.1 °C	ε _r	53.30	51.63	-3.13	5.00	
Body 1900	23.0 °C		σ	1.52	1.59	4.88	5.00	
			1g SAR	40.70	42.40	4.18	5.00	
				10g SAR	21.60	21.80	0.93	5.00

Date: 31/05/2011

Validation Dipole and Serial Number: D2450V2; SN: 725

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)	
					ε _r 39.	39.20	38.29	-2.32	5.00
Head 2450	23.0 °C	22.1 °C	σ	1.80	1.83	1.90	5.00		
			1g SAR	52.90	54.77	3.54	5.00		
				10g SAR	24.70	25.29	2.40	5.00	

Date: 01/06/2011

Validation Dipole and Serial Number: D2450V2; SN: 725

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
		23.0 °C	21.9 °C	ε _r	52.70	50.50	-4.18	5.00
Body 2450	2450			σ	1.95	2.02	3.57	5.00
	2430			1g SAR	51.90	50.80	-2.12	5.00
				10g SAR	24.10	23.52	-2.41	5.00

Page: 155 of 160 RFI Global Services Ltd.

Issue Date: 05 July 2011

Appendix 6. Simulated Tissues

The body mixture consists of water and glycol. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

	Frequency
Ingredient	835/850/900 MHz Head
De-Ionized Water	52.87
Polysorbate 20 (Tween 20)	46.10
Salt	1.03

	Frequency
Ingredient	835/850/900 MHz Body
De-Ionized Water	71.30
Polysorbate 20 (Tween 20)	28.00
Salt	0.70

Ingredient	Frequency
	1800/1900 MHz Head
De-Ionized Water	55.40
Polysorbate 20 (Tween 20)	44.22
Salt	0.38

Ingredient	Frequency
	1800/1900 MHz Body
De-Ionized Water	71.50
Polysorbate 20 (Tween 20)	28.00
Salt	0.50

Page: 156 of 160 RFI Global Services Ltd.

Issue Date: 05 July 2011

Simulated Tissues (Continued)

Ingredient	Frequency
	2450 MHz Head
De-Ionized Water	55.75
Polysorbate 20 (Tween 20)	45.25

Ingredient	Frequency
	2450 MHz Body
De-Ionized Water	71.70
Polysorbate 20 (Tween 20)	28.00
Salt	0.30

Page: 157 of 160 RFI Global Services Ltd.

rsion 2.0 Issue Date: 05 July 2011

Appendix 7. DASY4 System Details

A.7.1. DASY4 SAR Measurement System

RFI Global Services Ltd, SAR measurement facility utilises the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the SAM phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller; teach pendant (Joystick), and remote control. This is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. The data acquisition electronics (DAE) performs signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection etc. The DAE is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilises a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching mulitplexer, a fast 16bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

Page: 158 of 160 RFI Global Services Ltd.

Serial No: RFI/SAR/RP81531JD08A V2.0 Issue Date: 05 July 2011

A.7.2. DASY4 SAR System Specifications			
Robot System			
Positioner:	Stäubli Unimation Corp. Robot Model: RX90L		
Repeatability:	0.025 mm		
No. of Axis:	6		
Serial Number:	F00/SD89A1/A/01		
Reach:	1185 mm		
Payload:	3.5 kg		
Control Unit:	CS7		
Programming Language:	V+		
Data Acquisition Electronic (DAE) System			
Serial Number:	DAE3 SN:450		
PC Controller			
PC:	Dell Precision 340		
Operating System:	Windows 2000		
Data Card:	DASY4 Measurement Server		
Serial Number:	1080		
Data Converter			
Features:	Signal Amplifier, multiplexer, A/D converted and control logic.		
Software:	DASY4 Software		
Connecting Lines:	Optical downlink for data and status info. Optical uplink for commands and clock.		
PC Interface Card			
Function:	24 bit (64 MHz) DSP for real time processing Link to DAE3 16 nit A/D converter for surface detection system serial link to robot direct emergency stop output for robot.		

Page: 159 of 160 RFI Global Services Ltd.

DASY4 SAR System Specifications (Continued)		
E-field Probe		
Model:	EX3DV3	
Serial No:	3508	
Construction:	Triangular core	
Frequency:	10 MHz to >6 GHz	
Linearity:	±0.2 dB (30 MHz to 6 GHz)	
Probe Length (mm):	330	
Probe Diameter (mm):	12	
Tip Length (mm):	20	
Tip Diameter (mm):	2.5	
Sensor X Offset (mm):	1	
Sensor Y Offset (mm):	1	
Sensor Z Offset (mm):	1	
Phantom		
Phantom:	SAM Phantom	
Shell Material:	Fibreglass	
Thickness:	2.0 ±0.1 mm	

Page: 160 of 160 RFI Global Services Ltd.