

Note: This report is issued subject to TÜV SÜD PSB Corporation's "Terms and Conditions Governing Technical Services".
The terms and conditions governing the issue of this report are set out as attached within this report.

FORMAL REPORT ON TESTING IN ACCORDANCE WITH
FCC Parts 2, 15 & 24 : 2006
OF A
MOBILE DATA TERMINAL
[Model : W738P and W738G]
[FCC ID : UCW17W738V2]

TEST FACILITY TÜV SÜD PSB Corporation Pte Ltd,
Telecoms & EMC, Testing Group,
1 Science Park Drive, Singapore 118221

FCC REG. NO. 90937 (3m & 10m OATS)
99142 (10m Anechoic Chamber)
871638 (5m Anechoic Chamber)
325572 (10m Anechoic Chamber)

IND. CANADA REG. NO. IC 4257 (3m and 10m Anechoic Chambers)

PREPARED FOR Inforwave Pte Ltd
600 Sin Ming Avenue
4th Floor
Singapore 575733

Tel : (65) 6210 6317 Fax : (65) 6483 0388

JOB NUMBER 53S062804

TEST PERIOD 30 Oct 2006 – 01 Nov 2006

PREPARED BY

Quek Keng Huat
Associate Engineer

APPROVED BY

Lim Cher Hwee
Assistant Vice President



LA-2001-0212-A
LA-2001-0213-F
LA-2001-0214-E
LA-2001-0215-B
LA-2001-0216-G
LA-2001-0217-G
LA-2006-0355-C

The results reported herein have been performed in accordance with the laboratory's terms of accreditation under the Singapore Accreditation Council - Singapore Laboratory Accreditation Scheme. Tests/Calibrations marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our laboratory.

TABLE OF CONTENTS

TEST SUMMARY

PRODUCT DESCRIPTION

SUPPORTING EQUIPMENT DESCRIPTION

EUT OPERATING CONDITIONS

RF OUTPUT POWER TEST

OUT OF BAND EMISSION TEST

BAND EDGE COMPLIANCE (RADIATED) TEST

RECEIVER SPURIOUS EMISSION TEST

MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

ANNEX A

- EUT PHOTOGRAPHS / DIAGRAMS

ANNEX B

- FCC LABEL & POSITION

ANNEX C

- USER MANUAL, TECHNICAL
DESCRIPTION, BLOCK & CIRCUIT
DIAGRAMS

TEST SUMMARY

The product was tested in accordance with the customer's specifications.

Test Results Summary

Test Standard	Description	Pass / Fail
FCC Part 24: 2006		
15.107(a)	Conducted Emissions	Not Applicable *See Note 3
24.232(b), 2.1046	RF Power Output	Pass
24.238(a), 2.1051	Out of Band Emissions	Pass
24.238(a)	Band Edge Compliance (Radiated)	Pass
15.109	Receiver Spurious Emissions	Pass
1.1310	Maximum Permissible Exposure	Pass

Notes

- Three channels as listed below, which respectively represent the lower, middle and upper channels of the Equipment Under Test (EUT) were chosen and tested. For each channel, the EUT was configured to operate in the test mode.

<u>Transmit Channel</u>	<u>Frequency (MHz)</u>
Channel 512	1850.2
Channel 661	1880.0
Channel 810	1909.8
- All test measurement procedures are according to ANSI C63.4: 2003.
- The Equipment Under Test (EUT) is a battery operated device and contains no provision for public utility connections.
- All the measurements in FCC Part 24 were done based on radiated measurements.
- The EUT is a Class B device when in non-transmitting state and meets the FCC Part15B Class B requirements.
- The RF module of the Equipment Under Test (EUT) is a qualified RF module, which bears the FCC ID: QIPMC56. As such, only limited tests as mentioned above were evaluated.

Modifications

- No modifications were made.

PRODUCT DESCRIPTION

Description	: The Equipment Under Test (EUT) is a MOBILE DATA TERMINAL .
Manufacturer	: E-smart Distribution Pte Ltd 17 Kallang Junction #04-03 Esmart Centre Singapore 339274
	TTM Manufacturing Sdn Bhd 11 Jalan Angkasa Mas 5 Kawasan Perindustrian Tebrau II 81100 Johor Bahru Malaysia
Model Number	: W738P & W738G
Serial Number	: 738-P-YYMM-XXXX5, 0412-00001
Microprocessor	: Intel PXA255
Operating Frequency	: 900MHz & 1800MHz (GSM/GPRS)
Clock / Oscillator Frequency	: 3.68MHz, 400MHz
Port / Connectors	: Refer to manufacturers' user manual / operating manual.
Rated Input Power	: 12VDC
Accessories	: Refer to manufacturers' user manual / operating manual.

SUPPORTING EQUIPMENT DESCRIPTION

The EUT was tested as a stand-alone unit without any supporting equipment.

EUT OPERATING CONDITIONS

FCC Parts 2, 15 and 24
1. RF Output Power
2. Out of Band Emission
3. Band Edge Compliance (Radiated)
4. Receiver Spurious Emission
5. Maximum Permissible Exposure
The EUT was exercised by operating in continuous loopback mode with maximum transmission at lower, middle and upper channels one at a time. The R&S CMU200 was used as a PCS1900 base station.

RF OUTPUT POWER TEST

FCC Part 24.232(b) RF Output Power Limits

The EUT shows compliance to the requirements of this section, which states the mobile/portable stations are limited to 2 atts EIRP peak power and the equipment must employ means to limits the power to the minimum necessary for successful communication.

FCC Parts 2.1046 and 24.232(b) RF Output Power Test Instrumentation

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz-26.5GHz) – ESMI3	ESMI	829214/005 829550/004	04 Jul 2007
EMCO Horn Antenna – H14	3115	0003-6087	19 May 2007
EMCO Horn Antenna – H15	3115	0003-6088	19 May 2007
Weinschel Corp 10dB Attenuator	47-10-43	BD8406	19 May 2007
Agilent Signal Generator	83620B	3844A01337	24 Jan 2007

RF OUTPUT POWER TEST

FCC Parts 2.1046 and 24.232(b) RF Output Power Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant antenna was set at the required test distance away from the EUT and supporting equipment boundary.

FCC Parts 2.1046 and 24.232(b) RF Output Power Test Method

1. The EUT was set to transmit at the maximum power at the lower channel with the modulation on at normal test condition.
2. The receiving antenna (test antenna) was set at vertical polarization with the height of 1m.
3. With the spectrum analyser was set to max hold enabled (peak detector mode), the level of the operating frequency (carrier emission) was recorded. For EUT which is a portable device, the carrier emission was carried out by rotating the EUT through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission.
4. The test antenna was then raised or lowered through the specified range of heights (1m – 4m) until a maximum signal level was detected on the test receiver.
5. The EUT was then rotated through 360° in the horizontal plane until the maximum signal was received. The maximum received signal level was recorded as A (in dBm).
6. The EUT was replaced with the substitution antenna with the antenna input was connected to the signal generator via a 10dB attenuator (if required).
7. The signal generator was set to the found carrier frequency. The output level of the signal generator was adjusted until the test receiver was at least 20dB above the level when the signal generator was switched off.
8. The test antenna was raised and lowered through the specified range of heights (1m – 4m) until the maximum signal level was received on the test receiver.
9. The substitution antenna was rotated until the maximum level was detected on the test receiver.
10. The output level of the signal generator was adjusted until the received signal level at the test receiver was equal to the level recorded in step 5 (A dBm). The signal generator output level was recorded as B (in dBm).
11. The spurious emission level, P (e.i.r.p) was computed as followed:

P (e.i.r.p)	=	B – C – D + E
where	C	= cable loss between the signal generator and the substitution
	D	= attenuation level if attenuator is used
	E	= substitution antenna gain
12. The steps 2 to 11 were repeated with the receiving antenna was set to horizontal polarization.
13. Comparison was made on both measured results with vertical and horizontal polarizations. The highest value out of vertical and horizontal polarizations was recorded.
14. The steps 1 to 13 were repeated with the EUT was set to operate at the middle and upper channels respectively.

RF OUTPUT POWER TEST



RF Output Power Test Setup (Front View)



RF Output Power Test Setup (Rear View)

RF OUTPUT POWER TEST

FCC Parts 2.1046 and 24.232(b) RF Output Power Results

Operating Mode	PCS1900 Transmit	Temperature	20°C
Test Input Power	110VAC 60Hz	Relative Humidity	55%
Test Distance	3m	Atmospheric Pressure	1030mbar
Tested By			Xu Quanqiang

Frequency (MHz)	Amplitude (dBW)	Limit (dBW)	Channel
1850.2	-14.9	3	512
1880.0	-14.5	3	661
1909.8	-14.3	3	810

Notes

1. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:
>1GHz
RBW: 1MHz VBW: 1MHz
2. RF Output Power Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25GHz is ±4.3dB (for EUTs < 0.5m X 0.5m X 0.5m).

OUT OF BAND EMISSION TEST

FCC Part 24.238(a) Out of Band Emission Limits

The EUT shows compliance to the requirements of this section, which states the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power, P by a factor of at least $43 + 10\log(P)$ dB.

FCC Parts 2.1051 and 24.238(a) Out of Band Emission Test Instrumentation

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz-26.5GHz) – ESMI3	ESMI	829214/005 829550/004	04 Jul 2007
Schaffner Pre-Amplifier	CPA9231A	3422	01 Apr 2007
MITEQ Preamplifier (0.1-26.5GHz) – PA4	NSP2650-N	604879	07 Nov 2006
Schaffner Bilog Antenna – BL4	CBL6112B	2593	12 May 2007
EMCO Horn Antenna – H14	3115	0003-6087	19 May 2007
EMCO Horn Antenna – H15	3115	0003-6088	19 May 2007
Agilent Signal Generator	83620B	3844A01337	24 Jan 2007
K&L Microwave Variable Bandstop Filter	3TNF-1000/2000/N/N	436	04 Aug 2007

OUT OF BAND EMISSION TEST

FCC Parts 2.1051 and 24.238(a) Out of Band Emission Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant antenna was set at the required test distance away from the EUT and supporting equipment boundary.

FCC Parts 2.1051 and 24.238(a) Out of Band Emission Test Method

1. The EUT was set to transmit at the maximum power at the lower channel with the modulation on at normal test condition.
2. The receiving antenna (test antenna) was set at vertical polarization with the height of 1m.
3. With the spectrum analyser was set to max hold enabled (peak detector mode), the emissions outside the operating frequency range (spurious emissions) were searched and recorded. For EUT which is a portable device, the spurious emission search was carried out by rotating the EUT through three orthogonal axes to determine which attitude and equipment arrangement produces worst emissions.
4. For each spurious emission found, the test antenna was raised or lowered through the specified range of heights (1m – 4m) until a maximum signal level was detected on the test receiver.
5. The EUT was then rotated through 360° in the horizontal plane until the maximum signal was received. The maximum received signal level was recorded as A (in dBm).
6. The EUT was replaced with the substitution antenna with the antenna input was connected to the signal generator via a 10dB attenuator (if required).
7. The signal generator was set to the found spurious frequency. The output level of the signal generator was adjusted until the test receiver was at least 20dB above the level when the signal generator was switched off.
8. The test antenna was raised and lowered through the specified range of heights (1m – 4m) until the maximum signal level was received on the test receiver.
9. The substitution antenna was rotated until the maximum level was detected on the test receiver.
10. The output level of the signal generator was adjusted until the received signal level at the test receiver was equal to the level recorded in step 5 (A dBm). The signal generator output level was recorded as B (in dBm).
11. The spurious emission level, P (e.i.r.p) was computed as followed:
$$P \text{ (e.i.r.p)} = B - C - D + E$$

where C = cable loss between the signal generator and the substitution
 D = attenuation level if attenuator is used
 E = substitution antenna gain
12. The steps 2 to 11 were repeated with the receiving antenna was set to horizontal polarization.
13. Comparison was made on both measured results with vertical and horizontal polarizations. The highest value out of vertical and horizontal polarizations was recorded.
14. The steps 2 to 13 were repeated until all the spurious emissions (up to 10th harmonics of the carrier frequency) were measured.
15. The steps 1 to 14 were repeated with the EUT was set to operate at the middle and upper channels respectively.

OUT OF BAND EMISSION TEST



Out of Band Emissions Test Setup (Front View)



Out of Band Emissions Test Setup (Rear View)

OUT OF BAND EMISSION TEST

FCC Parts 2.1051 and 24.238(a) Out of Band Emission Results

Operating Mode	PCS1900 Transmit	Temperature	24°C
Test Input Power	110VAC 60Hz	Relative Humidity	58%
Test Distance	3m	Atmospheric Pressure	1030mbar
		Tested By	Lucas Beh

Lower Channel (Channel 512) Carrier Power: -8.7dBW (21.3dBm)

Frequency (MHz)	Amplitude (dBW)	Limit (dBc)	Actual Attenuation Below Carrier (dBc)
3700.4	-51.0	-34.3	-42.3
5550.6	-67.0	-34.3	-58.3
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

Middle Channel (Channel 661) Carrier Power: -9.2dBW (20.8dBm)

Frequency (MHz)	Amplitude (dBW)	Limit (dBc)	Actual Attenuation Below Carrier (dBc)
3760.0	-52.0	-33.8	-42.8
5640.0	-67.0	-33.8	-57.8
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

Upper Channel (Channel 810) Carrier Power: -10.0dBW (20.0dBm)

Frequency (MHz)	Amplitude (dBW)	Limit (dBc)	Actual Attenuation Below Carrier (dBc)
3819.6	-52.0	-33.0	-42.0
5729.4	-66.0	-33.0	-56.0
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

OUT OF BAND EMISSION TEST

Notes

1. All possible modes of operation were investigated. Only the worst case emissions measured. All other emissions were relatively insignificant.
2. "--" indicates no emissions were found and shows compliance to the limits.
3. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:
30MHz - 1GHz
RBW: 120kHz VBW: 1MHz
>1GHz
RBW: 1MHz VBW: 1MHz
4. The upper frequency of radiated emission investigations was according to requirements stated in Section 15.33(a) for intentional radiators & Section 15.33(b) for unintentional radiators.
5. Out of Band Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25GHz is $\pm 4.3\text{dB}$ (for EUTs $< 0.5\text{m} \times 0.5\text{m} \times 0.5\text{m}$).

BAND EDGE COMPLIANCE (RADIATED) TEST

FCC Part 24.238(a) Band Edge Compliance (Radiated) Limits

The EUT shows compliance to the requirements of this section, which states the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power, P by a factor of at least $43 + 10\log(P)$ dB.

FCC Part 24.238(a) Band Edge Compliance (Radiated) Test Instrumentation

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz-26.5GHz) – ESMI3	ESMI	829214/005 829550/004	04 Jul 2007
EMCO Horn Antenna – H14	3115	0003-6087	19 May 2007
Weinschel Corp 10dB Attenuator	47-10-43	BD8406	19 May 2007
Agilent Signal Generator	83620B	3844A01337	24 Jan 2007

BAND EDGE COMPLIANCE (RADIATED) TEST


FCC Part 24.238(a) Out of Band Emission Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant antenna was set at the required test distance away from the EUT and supporting equipment boundary.

FCC Part 24.238(a) Out of Band Emission Test Method

1. The EUT was set to transmit at the maximum power at the lower channel with the modulation on at normal test condition.
2. The frequency span of the spectrum analyser was set to wide enough to capture the lower band edge of the transmission band and any spurious emissions at the band edge.
3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected. The band edge spurious emissions plot was plotted.
4. The EUT was set to transmit at the maximum power at the upper channel with the modulation on at normal test condition.
5. The steps 2 to 3 were repeated with the frequency span of the spectrum analyser was set to wide enough to capture the upper band edge frequency of the transmission band and any spurious emissions at the band-edge.

BAND EDGE COMPLIANCE (RADIATED) TEST



Band Edge Compliance (Radiated) Test Setup (Front View)



Band Edge Compliance (Radiated) Test Setup (Rear View)

BAND EDGE COMPLIANCE (RADIATED) TEST

FCC Part 24.238(a) Band Edge Compliance (Radiated) Results

Operating Mode	PCS1900 Transmit	Temperature	20°C
Test Input Power	110VAC 60Hz	Relative Humidity	55%
Test Distance	3m	Atmospheric Pressure	1030mbar
Attached Plots	3 - 4	Tested By	Xu Quanqiang



No significant signal was found and they were below the specified limit.

Notes

1. Refer to Plots 1 and 2 for lower and upper channels 26dB bandwidth.
2. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings (at least 1% of the 26dB of the channel under evaluation):
RBW: 100kHz VBW: 100kHz


BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (26dB Bandwidth)




BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots



Plot 3 – Lower Band Edge



Plot 4 – Upper Band Edge



RECEIVER SPURIOUS EMISSION TEST

FCC Part 15.109 Receiver Spurious Emission Limits (Class B)

Frequency Range (MHz)	Quasi-Peak Limit Values (dB μ V/m) @ 3m
30 - 88	40.0
88 - 216	43.5
216 - 960	46.0
Above 960	54.0*

* Above 1GHz, average detector was used. A peak limit of 20dB above the average limit does apply.

FCC Part 15.109 Receiver Spurious Emission Test Instrumentation

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz-26.5GHz) – ESMI3	ESMI	829214/005 829550/004	04 Jul 2007
Schaffner Pre-Amplifier	CPA9231A	3422	01 Apr 2007
MITEQ Preamplifier (0.1-26.5GHz) – PA4	NSP2650-N	604879	07 Nov 2006
Schaffner Bilog Antenna –BL4	CBL6112B	2593	12 May 2007
EMCO Horn Antenna – H14	3115	0003-6087	19 May 2007
K&L Microwave Variable Bandstop Filter	3TNF-1000/2000/N/N	436	04 Aug 2007

RECEIVER SPURIOUS EMISSION TEST

FCC Part 15.109 Receiver Spurious Emission Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard as shown in the setup photos.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.

FCC Part 15.109 Receiver Spurious Emission Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A prescan was carried out to pick the worst emission frequencies from the EUT. For EUT which is a portable device, the prescan was carried out by rotating the EUT through three orthogonal axes to determine which attitude and equipment arrangement produces such emissions.
3. The test was carried out at the selected frequency points obtained from the prescan in step 2. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
4. A Quasi-peak measurement was made for that frequency point if it was less than or equal to 1GHz. For frequency point that above 1GHz, both Peak and Average measurements were carried out.
5. Steps 3 and 4 were repeated for the next frequency point, until all selected frequency points were measured.
6. The frequency range covered was from 30MHz to 10th harmonic of the highest frequency used or generated by the EUT, using the Bi-log antenna for frequencies from 30MHz up to 3GHz, and the Horn antenna above 3GHz.

Sample Calculation Example

At 300 MHz

Q-P limit (Class B) = 70.8 μ V/m = 37.0 dB μ V/m

Log-periodic antenna factor & cable loss at 300 MHz = 18.5 dB

Q-P reading obtained directly from EMI Receiver = 31.0 dB μ V/m
(Calibrated level including antenna factors & cable losses)

Therefore, Q-P margin = 31.0 - 37.0 = -6.0

i.e. **6 dB below Q-P limit**

RECEIVER SPURIOUS EMISSION TEST



Receiver Spurious Emissions Test Setup (Front View)



Receiver Spurious Emissions Test Setup (Rear View)

RECEIVER SPURIOUS EMISSION TEST

FCC Part 15.109 Receiver Spurious Emission Results

Operating Mode	PCS 1900 Receiving	Temperature	23°C
Test Input Power	110V 60Hz	Relative Humidity	55%
Test Distance	3m	Atmospheric Pressure	1030mbar
Class	B	Tested By	Thor Wen Lei

Emissions ranging from 30MHz – 1GHz

Frequency (MHz)	Q-P Value (dB μ V/m)	Q-P Margin (dB)	Azimuth (Degrees)	Height (cm)	Polarisation (H/V)
235.1670	40.7	-5.3	359	101	H
268.7631	39.6	-6.4	47	101	H
335.9600	39.6	-6.4	40	101	H
398.0900	39.9	-6.1	359	101	H
431.9621	41.5	-4.5	328	101	V
895.7281	42.5	-3.5	25	100	V

Emissions above 1GHz

Frequency (GHz)	Peak Value (dB μ V/m)	Average Value (dB μ V/m)	Average Margin (dB)	Azimuth (Degrees)	Height (cm)	Pol (H/V)	Channel
3.7596	73.9	52.4	-1.6	78	101	H	512
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Notes

1. All possible modes of operation were investigated. Only the worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "–ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:
30MHz - 1GHz
RBW: 120kHz VBW: 1MHz
>1GHz
RBW: 1MHz VBW: 1MHz
4. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25.0GHz (QP only @ 3m & 10m) is ± 4.3 dB (for EUTs $< 0.5m \times 0.5m \times 0.5m$).

MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

FCC Part 1.1310 Maximum Permissible Exposure (MPE) Limits

The EUT shows compliance to the requirements of this section, which states the MPE limits for general population / uncontrolled exposure are as shown below:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (min)
0.3 - 1.34	614	1.63	100 ^{Note 2}	30
1.34 - 30	824 / f	2.19 / f	180 / f ² ^{Note 2}	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f / 1500	30
1500 - 100000	-	-	1.0	30
Notes				
1. f = frequency in MHz				
2. Plane wave equivalent power density				

FCC Part 1.1310 Maximum Permissible Exposure (MPE) Test Instrumentation

Instrument	Model	S/No	Cal Due Date
PMM 8053 Portable Field Meter	8053	0220J10308	16 Apr 2007
PMM Electric and Magnetic Field Analyzer	EHP-50A	1311L10515	16 Apr 2007

FCC Part 1.1310 Maximum Permissible Exposure (MPE) Test Setup

1. The EUT and supporting equipment were set up as shown on the setup photo.
2. The relevant field probe was positioned at least 20cm away from the EUT and supporting equipment boundary.

FCC Part 1.1310 Maximum Permissible Exposure (MPE) Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was first carried out at one of the positions / sides of the EUT.
3. Power density measurement (mW/cm²) was made using the field meter set to the required averaging time.
4. Steps 2 and 3 were repeated for the next position and its associate EUT operating mode, until all possible positions and modes were measured.

Sample Calculation Example

At 2400 MHz, limit = 1.0 mW/cm²

Power density reading obtained directly from field meter = 0.3 mW/cm² averaged over the required 30 minutes.

Therefore, margin = 0.3 – 1.0 = -0.7 mW/cm² i.e. **0.7 mW/cm² below limit**

MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST



Maximum Permissible Exposure (MPE) Test Setup

MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

FCC Part 1.1310 Maximum Permissible Exposure (MPE) Results

Test Input Power	110V 60Hz	Temperature	20°C
Test Distance	20cm	Relative Humidity	55%
		Atmospheric Pressure	1030mbar
		Tested By	Xu Quanqiang

Channel	Channel Frequency (GHz)	Power Density Value (mW/cm ²)	Margin (mW/cm ²)	Averaging Time (min)	Limit (mW/cm ²)
512	1850.2	0.0050	-0.9950	30	1.0
661	1880.0	0.0044	-0.9956	30	1.0
810	1909.8	0.0043	-0.9957	30	1.0

Notes

1. All possible modes of operation were investigated. Only the worst case highest radiation levels were measured. Measurements were taken at the required averaging time. All other radiation levels were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 0.1MHz – 3GHz is ±15% .

This Report is issued under the following conditions:

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, a report shall contain only technical results. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB Corporation approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB Corporation in any way "guarantees" the later performance of the product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB Corporation therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through TÜV SÜD PSB Corporation, unless the Client has authorised TÜV SÜD PSB Corporation in writing to do so.
6. TÜV SÜD PSB Corporation may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with TÜV SÜD PSB Corporation and the Client shall, upon payment of TÜV SÜD PSB Corporation's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that TÜV SÜD PSB Corporation may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB Corporation has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB Corporation or to the report or results furnished by TÜV SÜD PSB Corporation in any advertisements or sales promotion.
10. Unless otherwise stated, the tests are carried out in TÜV SÜD PSB Corporation Pte Ltd, No.1 Science Park Drive Singapore 118221.

October 2006

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

ANNEX A

EUT PHOTOGRAPHS / DIAGRAMS

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P



Front View




Rear View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




Internal View – Top Cover

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




Internal View – Bottom Cover

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




Main-Board - Component Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P



Main-Board - PCB Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




LCD Display – Front View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




LCD Display - Rear View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




LCD Display - Component Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738P




LCD Display - Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Sub-Board - PCB Component Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Sub-Board - PCB Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A


EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



RF Module

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



Front View




Rear View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Internal View - Top Cover

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Internal View – Bottom Cover

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Main-Board - Component Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



Main-Board - Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




LCD Display – Front View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




LCD Display - Rear View

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A


EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




LCD Display - Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




Sub-Board - PCB Component Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



Sub-Board - PCB Trace Side

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G




RF Module

EUT PHOTOGRAPHS / DIAGRAMS

ANNEX A

EUT PHOTOGRAPHS FOR MOBILE DATA TERMINAL MODEL – W738G



RF Module



FCC LABEL & POSITION

ANNEX B

ANNEX B

FCC LABEL & POSITION

FCC LABEL & POSITION

ANNEX B

Labelling requirements per Section 2.925 & 15.19

The label shown will be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time of purchase.



Sample Label



Physical Location of FCC Label on EUT

**USER MANUAL TECHNICAL DESCRIPTION BLOCK
& CIRCUIT DIAGRAMS**

ANNEX C

ANNEX C

**USER MANUAL
TECHNICAL DESCRIPTION
BLOCK & CIRCUIT DIAGRAMS**

(Please refer to manufacturer for details)