



Lab Code: 200707-0



## FCC PART 15.247


# TEST REPORT

For

# Lorex Technology Inc.

250 Royal Crest Court, Markham, Ontario, L3R 3S1, Canada

**FCC ID: UCZ-MC2004**

<b>Report Type:</b> Original Report	<b>Product Type:</b> 2.4 GHz Video Baby Moniotr (Camera Unit)
<b>Test Engineer:</b> <u>Ares Liu</u> 	
<b>Report Number:</b> <u>R1DG111209002-00</u>	
<b>Report Date:</b> <u>2012-01-06</u>	
<b>Reviewed By:</b> <u>EMC Engineer</u> 	
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\* or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk ★ (Rev.2)

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS.....</b>	<b>8</b>
<b>FCC §15.247 (i) &amp; §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>9</b>
STANDARD APPLICABLE .....	9
TEST DATA .....	9
<b>FCC §15.203 – ANTENNA REQUIREMENT .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) - CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY .....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE .....	12
TEST RESULTS SUMMARY.....	12
TEST DATA .....	12
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
MEASUREMENT UNCERTAINTY .....	15
EUT SETUP .....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST PROCEDURE .....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	16
TEST RESULTS SUMMARY .....	17
TEST DATA .....	17
<b>FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....</b>	<b>20</b>
APPLICABLE STANDARD .....	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST PROCEDURE .....	20
TEST DATA .....	20

<b>FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING .....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST PROCEDURE .....	23
TEST DATA .....	23
<b>FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>26</b>
APPLICABLE STANDARD .....	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST PROCEDURE .....	26
TEST DATA .....	26
<b>FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>28</b>
APPLICABLE STANDARD .....	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST PROCEDURE .....	28
TEST DATA .....	28
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST PROCEDURE .....	31
TEST DATA .....	31
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>34</b>
APPLICABLE STANDARD .....	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST PROCEDURE .....	34
TEST DATA .....	35

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Lorex Technology Inc.*'s product, model number: *MC2004 (FCC ID: UCZ-MC2004)* (the "EUT") in this report was a camera unit of *2.4 GHz Wireless Color Camera*, which was measured approximately: 12 cm (L) x7.2 cm (W) x 3 cm (H), rated input voltage: DC 5V from adapter.

Adapter Information: Switching Adapter

Model: S04-003-0050-00600

Input: 100-240V~50/60Hz 0.1A Max.

Output: DC 5.0 V 600mA

*\* All measurement and test data in this report was gathered from production sample serial number: WB01100100001 (Assigned by applicant). The EUT was received on 2011-12-09.*

### Objective

This report is prepared on behalf of *Lorex Technology Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

The part of a system with FCC ID: UCZ-WL2004.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration


The system was configured for testing in an engineering mode which was selected by manufacturer.

### EUT Exercise Software

No Exercise Software.

### Equipment Modifications

Added copper sheet, please see the below photos




### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lorex	2.4 GHz Wireless Color Camera	WL2004	N/A

### External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded Detachable DC Power Cable	1.8	EUT	Adapter DC Port

**Block Diagram of Test Setup**

**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

## FCC §15.247 (i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Standard Applicable

According to FCC subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Test Data

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally **numeric** gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2404	0	1	13.91	24.603	20	0.004897	1.0

**Result:** Compliance, the device meets the MPE at 20 cm distance.

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has a monopole antenna permanently soldered to main board, the gain was 0 dBi, which fully in accordance to section 15.203, please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) - CONDUCTED EMISSIONS

### Applicable Standard


FCC §15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is  $\pm 2.4$  dB (k=2, 95% level of confidence).

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<b><u>Frequency Range</u></b>	<b><u>IF B/W</u></b>
150 kHz – 30 MHz	9 kHz

## Test Equipment List and Details

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the [FCC Part 15.207](#), with the worst margin reading of:

**12.69 dB at 0.330 MHz in the Neutral conducted mode**

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Ares Liu on 2011-12-16.*


*Test Mode: Transmitting*

**AC 120 V, 60 Hz, Line:**



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.310	28.70	0.02	51.43	22.73	Ave.
0.310	37.41	0.02	61.43	24.02	QP
1.455	21.47	0.01	46.00	24.53	Ave.
1.025	20.87	0.01	46.00	25.13	Ave.
1.455	30.44	0.01	56.00	25.56	QP
4.760	20.20	0.03	46.00	25.80	Ave.
1.035	29.35	0.01	56.00	26.65	QP
27.120	22.96	0.07	50.00	27.04	Ave.
0.445	30.13	0.01	57.57	27.44	QP
4.815	28.52	0.03	56.00	27.48	QP
0.445	16.88	0.01	47.57	30.69	Ave.
27.120	26.29	0.07	60.00	33.71	QP

## AC 120V, 60 Hz, Neutral:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.330	38.17	0.02	50.86	12.69	Ave.
1.910	28.36	0.01	46.00	17.64	Ave.
1.040	28.24	0.01	46.00	17.76	Ave.
0.655	28.20	0.01	46.00	17.80	Ave.
0.330	41.19	0.02	60.86	19.67	QP
1.040	32.70	0.01	56.00	23.30	QP
0.660	32.48	0.01	56.00	23.52	QP
1.920	32.09	0.01	56.00	23.91	QP
5.030	25.93	0.03	50.00	24.07	Ave.
27.120	21.71	0.07	50.00	28.29	Ave.
27.120	27.22	0.07	60.00	32.78	QP
5.005	22.18	0.03	60.00	37.82	QP

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d), §15.209 and §15.205.

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB (k=2, 95% level of confidence).

### EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<b>Frequency Range</b>	<b>RBW</b>	<b>Video B/W</b>	<b>Detector</b>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

## Test Equipment List and Details

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Mini-circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Electro-Mechanics	Horn Antenna	3116	9510-2270	2011-10-11	2012-10-10
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

For the radiated emissions test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

**0.10 dB at 4936 MHz** in the **Horizontal** polarization at High channel

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Ares Liu on 2011-12-31.*

*Test Mode: Transmitting*

### 1) 30 MHz – 1 GHz:

Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Polarity (H/V)	Correction Factor (dB)	FCC Limit (dB $\mu$ V/m)	Margin (dB)
614.61	36.66	V	1.29	46	9.34
899.12	34.78	H	4.63	46	11.22
524.7	34.06	V	-0.38	46	11.94
283.84	33.34	H	-5.07	46	12.66
899.12	32.09	V	4.63	46	13.91
609.62	31.69	H	1.82	46	14.31
524.7	31.35	H	-0.38	46	14.65
283.84	30.55	V	-5.07	46	15.45

## 2)1 – 25 GHz:

Indicated		Detector (PK/Ave.)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	S.A. Reading (dBmV)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBmV/m)	Limit (dBmV/m)	Margin (dB)	Comment
Low Channel (2404 MHz)										
2404	68.25	PK	H	29.1	3.9	0	101.25	/	/	Fund.
2404	54.15	Ave.	H	29.1	3.9	0	87.15	/	/	Fund.
2404	72.44	PK	V	29.1	3.9	0	105.44	/	/	Fund.
2404	58.47	Ave.	V	29.1	3.9	0	91.47	/	/	Funda.
7212	13.21	Ave.	H	37.7	7.6	7	51.51	54	2.49*	harmonic
2388.9	38.47	PK	H	29.1	3.9	0	71.47	74	2.53*	spurious
7212	12.99	Ave.	V	37.7	7.6	7	51.29	54	2.71*	harmonic
4808	20.68	Ave.	H	32.1	5.8	7.4	51.18	54	2.82*	harmonic
7212	31.71	PK	H	37.7	7.6	7	70.01	74	3.99*	harmonic
4808	19.5	Ave.	V	32.1	5.8	7.4	50	54	4.00*	harmonic
7212	31.67	PK	V	37.7	7.6	7	69.97	74	4.03	harmonic
2389.8	36.9	PK	H	29.1	3.9	0	69.9	74	4.10	spurious
2388.9	14.25	Ave.	H	29.1	3.9	0	47.25	54	6.75	spurious
2389.8	13.4	Ave.	H	29.1	3.9	0	46.4	54	7.60	spurious
4808	33.81	PK	H	32.1	5.8	7.4	64.31	74	9.69	harmonic
4808	33.46	PK	V	32.1	5.8	7.4	63.96	74	10.04	harmonic
Middle Channel (2436 MHz)										
2436	68.21	PK	H	29.1	3.9	0	101.21	/	/	Fund.
2436	54.99	Ave.	H	29.1	3.9	0	87.99	/	/	Fund.
2436	70.58	PK	V	29.1	3.9	0	103.58	/	/	Fund.
2436	58.47	Ave.	V	29.1	3.9	0	91.47	/	/	Fund.
4872	22.8	Ave.	H	32.2	5.8	7.3	53.5	54	0.50*	harmonic
7308	12.87	Ave.	V	37.9	7.6	7.2	51.17	54	2.83*	harmonic
7308	32.59	PK	H	37.9	7.6	7.2	70.89	74	3.11*	harmonic
7308	12.56	Ave.	H	37.9	7.6	7.2	50.86	54	3.14*	harmonic
7308	31.85	PK	V	37.9	7.6	7.2	70.15	74	3.85*	harmonic
4872	18.34	Ave.	V	32.2	5.8	7.3	49.04	54	4.96	harmonic
4872	35.45	PK	H	32.2	5.8	7.3	66.15	74	7.85	harmonic
4872	32.92	PK	V	32.2	5.8	7.3	63.62	74	10.38	harmonic

Indicated		Detector (PK/Ave.)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	S.A. Reading (dBmV)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBmV/m)	Limit (dBmV/m)	Margin (dB)	Comment
High Channel (2468 MHz)										
2468	73.95	PK	H	29.7	3.9	0	102.98	/	/	Fund.
2468	60.99	Ave.	H	29.7	3.9	0	89.74	/	/	Fund.
2468	76.65	PK	V	29.7	3.9	0	104.94	/	/	Fund.
2468	63.17	Ave.	V	29.7	3.9	0	92.01	/	/	Funda.
4936	22.8	Ave.	H	32.5	5.8	7.2	53.9	54	0.10*	harmonic
4936	22.26	Ave.	V	32.5	5.8	7.2	53.36	54	0.64*	harmonic
7404	33.81	PK	H	38.5	7.6	7.3	72.61	74	1.39*	harmonic
7404	33.21	PK	V	38.5	7.6	7.3	72.01	74	1.99*	harmonic
2483.8	37.88	PK	V	29.7	3.9	0	71.48	74	2.52*	spurious
7404	12.36	Ave.	H	38.5	7.6	7.3	51.16	54	2.84*	harmonic
7404	12.05	Ave.	V	38.5	7.6	7.3	50.85	54	3.15*	harmonic
2483.5	36.87	PK	V	29.7	3.9	0	70.47	74	3.53*	spurious
2483.5	14.21	Ave.	V	29.7	3.9	0	47.81	54	6.19	spurious
4936	36.33	PK	H	32.5	5.8	7.2	67.43	74	6.57	harmonic
4936	36.18	PK	V	32.5	5.8	7.2	67.28	74	6.72	harmonic
2483.8	13.48	Ave.	V	29.7	3.9	0	47.08	54	6.92	spurious

\*Within measurement uncertainty.

## FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Set the EUT in Operating mode, spectrum Bandwidth was set at 10 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

\* The testing was performed by Ares Liu on 2012-01-04.


**Test Result:** Compliance.

Please refer to following tables and plots

*Test Mode: Transmitting*


Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result	
Low Channel	2404	2.008	1.44	Pass	
Adjacency Channel	2406				
Mid Channel	2436		1.44		
Adjacency Channel	2438				
High Channel	2468		1.44		
Adjacency Channel	2466				

### Low Channel




Date: 4.JAN.2012 22:52:18

### Middle Channel



Date: 4.JAN.2012 22:54:25

### High Channel



Date: 4.JAN.2012 22:55:41

## FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\* The testing was performed by Ares Liu on 2012-01-04.


**Test Result:** Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
Low	2404	2.10
Middle	2436	2.16
High	2468	2.12


### Low Channel



Date: 4.JAN.2012 19:32:21

**Middle Channel**

Date: 4.JAN.2012 20:04:54

**High Channel**

Date: 4.JAN.2012 21:26:17

## FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

The testing was performed by Ares Liu on 2012-01-04.


**Test Result:** Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.50	33	$\geq 15$

### Number of Hopping Channels



Date: 4.JAN.2012 22:50:26

**FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= Time slot length \* hope rate/ number of hopping channels \* hopping NO.\*0.4 s

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Ares Liu on 2012-01-04.*


**Test Result:** Compliance.

Please refer to following tables and plots


*Test Mode: Transmitting*

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
Low	0.129	0.0516	0.4	Pass
Middle	0.13	0.052	0.4	Pass
High	0.132	0.0528	0.4	Pass
<i>Note: Dwell time = (Pulse time/1000)*(1000//33)*33*0.4S</i>				


### Low Channel



Date: 4.JAN.2012 22:59:07

**Middle Channel**

Date: 4.JAN.2012 22:59:46

**High Channel**

Date: 4.JAN.2012 23:00:15

## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\* The testing was performed by Ares Liu on 2012-01-04.


**Test Result:** Compliance.

*Test Mode: Transmitting*


*Please refer to the following table and plots:*

Frequency (MHz)	Conducted Output Power		FCC Limit (mW)
	(dBm)	(mW)	
2404	13.91	24.603	100
2436	13.21	20.941	100
2468	13.21	20.941	100


### Low Channel



Date: 4.JAN.2012 19:33:41

**Middle Channel**

Date: 4.JAN.2012 20:06:21

**High Channel**

Date: 4.JAN.2012 21:24:40

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in Operating mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\*The testing was performed by Ares Liu on 2012-01-04.


Test Result: Compliance.

Test Mode: Transmitting


Please refer to the following table and plots:

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Delta Limit (dBc)
2390.000	59.30	20
2483.500	55.20	20

### Band Edge: Left Side



Date: 4.JAN.2012 19:37:38

**Band Edge: Right Side**

Date: 4.JAN.2012 21:29:38

**\*\*\*\*\* END OF REPORT \*\*\*\*\***