



FCC PART 15.247

TEST REPORT

For

Lorex Technology Inc

250 Royal Crest Court, Markham, Ontario, L3R 3S1, Canada

FCC ID: UCZM2251

Report Type: Original Report	Product Type: Digital FHSS Device (Monitor Unit)
Test Engineer: <u>August He</u>	
Report Number: <u>RSZ140425002-00B</u>	
Report Date: <u>2014-04-29</u>	
Reviewed By: <u>RF Leader</u>	
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1093- RF Exposure	8
FCC §15.203 – ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	14
APPLICABLE STANDARD	14
MEASUREMENT UNCERTAINTY	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
TEST EQUIPMENT LIST AND DETAILS.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.247(a) (1)-CHANNEL SEPARATION	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA	19
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22

TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST DATA	25
FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	27
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA	30
FCC §15.247(d) - BAND EDGES	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
PRODUCT SIMILARITY DECLARATION LETTER	35

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Lorex Technology Inc*'s product, model number: *LB2251 (FCC ID: UCZM2251)* (the "EUT") in this report was a monitor unit of Digital FHSS Device, named as *2.4G video baby monitor* by the applicant, which was measured approximately: 16.0 cm (L) x 8.4 cm (W) x 2.5 cm (H), rated with input voltage: 3.7V Li-ion battery or DC 6.0V from adapter.

Adapter Information: AC ADAPTER

Model: 5E-AD060080-U

Input: AC 120V~240V, 50/60Hz, 0.15A

Output: DC 6V, 0.8A

Note: the monitor unit of model LB2251 and LB251 is electrically identical; they share the same PCB layout and schematic, the only difference among them is the model number for purpose of market.

** All measurement and test data in this report was gathered from production sample serial number: 1404169 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-04-25.*

Objective

This report is prepared on behalf of *Lorex Technology Inc* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 submission of camera unit with FCC ID: UCZC5410 has been granted on 02/04/2013.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode which was selected by manufacturer.

EUT Exercise Software

No exercise software was used.

Equipment Modifications


No modification was made to the EUT tested.

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding DC Power Cable	1.8	EUT	Adapter

Block Diagram of Test Setup

For Conducted emission test at main port:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b)(1), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1093- RF Exposure

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

The SAR data please refer to the SAR report, report No.: RSZ140425002-20.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one integrated antenna arrangement, which was permanently attached and the antenna gain is 2.0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	Transient limitator	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	--	--

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the [FCC Part 15.207](#), with the worst margin reading of:

15.0 dB at 0.343070 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cisp}$$

in BACL., $U_{(Lm)}$ is less than U_{cisp} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.

Test Mode: Charging & Transmitting


AC 120 V, 60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.343070	44.1	19.5	59.1	15.0	QP
0.343070	34.1	19.5	49.1	15.0	Ave.
0.294500	30.9	19.4	50.4	19.5	Ave.
1.137170	26.3	19.5	46.0	19.7	Ave.
0.687650	25.8	19.6	46.0	20.2	Ave.
0.648310	25.6	19.6	46.0	20.4	Ave.
0.648310	35.1	19.6	56.0	20.9	QP
0.687650	34.2	19.6	56.0	21.8	QP
1.137170	33.2	19.5	56.0	22.8	QP
0.294500	37.2	19.4	60.4	23.2	QP
0.864830	31.2	19.5	56.0	24.8	QP
0.864830	21.1	19.5	46.0	24.9	Ave.

AC 120V, 60 Hz, Neutral:

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.644190	30.7	19.6	46.0	15.3	Ave.
1.101350	30.3	19.5	46.0	15.7	Ave.
0.644190	39.9	19.6	56.0	16.1	QP
0.573510	29.8	19.6	46.0	16.2	Ave.
0.683710	29.7	19.6	46.0	16.3	Ave.
0.683710	39.4	19.6	56.0	16.6	QP
1.146950	29.4	19.5	46.0	16.6	Ave.
1.491470	29.1	19.5	46.0	16.9	Ave.
0.573510	38.6	19.6	56.0	17.4	QP
1.101350	38.4	19.5	56.0	17.6	QP
1.491470	37.3	19.5	56.0	18.7	QP
1.146950	36.7	19.5	56.0	19.3	QP

Note:

- 1) Corrected Amplitude = Reading + Correction Factor
- 2) Correction Factor = LISN/ISN VDF (Voltage Division Factor) + Cable Loss
The corrected factor has been input into the transducer of the test software.
- 3) Margin = Limit – Corrected Amplitude
- 4) *Within measurement uncertainty

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz. And the uncertainty will not be taken into consideration for the test data recorded in the report

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz to 1GHz and peak and Average detection modes for frequencies above 1GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-03	2015-04-03
Sunol Sciences	Horn Antenna	DRH-118	A052304	2013-11-30	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2013-08-03	2014-08-03
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

7.59 dB at 2483.6 MHz in the **Horizontal** polarization

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

in BACL., $U_{(Lm)}$ is less than $+ U_{\text{cispr}}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.

30 MHz -25 GHz:*Test Mode: Transmitting*

Frequency (MHz)	Receiver		Turn table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBuV/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel(2410.875 MHz)									
126.5	39.19	QP	209	2.0	V	-13.0	26.19	46	19.81
2410.9	96.46	PK	52	1.8	H	6.13	102.59	/	/
2410.9	90.53	Ave.	52	1.8	H	6.13	96.66	/	/
2410.9	95.31	PK	360	1.1	V	6.13	101.44	/	/
2410.9	90.56	Ave.	360	1.1	V	6.13	96.69	/	/
2362.0	35.13	PK	12	1.5	V	5.48	40.61	74	33.39
2362.0	21.05	Ave.	12	1.5	V	5.48	26.53	54	27.47
2380.1	39.06	PK	283	1.8	H	5.48	44.54	74	29.46
2380.1	28.97	Ave.	283	1.8	H	5.48	34.45	54	19.55
2483.7	35.80	PK	85	2.3	H	7.21	43.01	74	30.99
2483.7	21.94	Ave.	85	2.3	H	7.21	29.15	54	24.85
4821.8	37.01	PK	133	1.3	H	12.44	49.45	74	24.55
4821.8	22.07	Ave.	133	1.3	H	12.44	34.51	54	19.49
7232.6	34.91	PK	243	1.1	V	17.06	51.97	74	22.03
7232.6	20.23	Ave.	243	1.1	V	17.06	37.29	54	16.71
9643.5	35.64	PK	296	1.1	V	19.28	54.92	74	19.08
9643.5	19.98	Ave.	296	1.1	V	19.28	39.26	54	14.74
Middle Channel(2441.25 MHz)									
126.5	38.19	QP	47	2.4	H	-13.0	25.19	46	20.81
2441.3	90.84	PK	26	1.3	H	6.13	106.97	/	/
2441.3	82.77	Ave.	26	1.3	H	6.13	98.90	/	/
2441.3	90.74	PK	7	1.5	V	6.13	106.87	/	/
2441.3	82.93	Ave.	7	1.5	V	6.13	99.06	/	/
2378.4	37.98	PK	279	1.8	V	5.48	43.46	74	30.54
2378.4	27.51	Ave.	279	1.8	V	5.48	32.99	54	21.01
2483.5	43.03	PK	231	1.3	H	7.21	50.24	74	23.76
2483.5	34.66	Ave.	231	1.3	H	7.21	41.87	54	12.13
2497.3	36.54	PK	180	1.3	H	7.21	43.75	74	30.25
2497.3	24.99	Ave.	180	1.3	H	7.21	32.2	54	21.80
4882.5	36.30	PK	251	2.5	H	12.4	48.7	74	25.30
4882.5	21.82	Ave.	251	2.5	H	12.4	34.22	54	19.78
7323.8	34.67	PK	266	1.1	V	16.49	51.16	74	22.84
7323.8	20.32	Ave.	266	1.1	V	16.49	36.81	54	17.19
9765.0	35.52	PK	142	2.1	V	19.4	54.92	74	19.08
9765.0	19.85	Ave.	142	2.1	V	19.4	39.25	54	14.75

Frequency (MHz)	Receiver		Turn table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBuV/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.e.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel(2471.625 MHz)									
126.5	39.38	QP	248	1.1	H	-13.0	26.38	46	19.62
2471.6	101.30	PK	151	1.3	H	7.21	108.51	/	/
2471.6	93.85	Ave.	151	1.3	H	7.21	101.06	/	/
2471.6	100.89	PK	176	1.4	V	7.21	108.10	/	/
2471.6	92.13	Ave.	176	1.4	V	7.21	99.34	/	/
2377.9	36.55	PK	330	2.0	V	5.48	42.03	74	31.97
2377.9	27.93	Ave.	330	2.0	V	5.48	33.41	54	20.59
2483.6	48.49	PK	188	1.2	H	7.21	55.70	74	18.30
2483.6	39.20	Ave.	188	1.2	H	7.21	46.41	54	7.59
2491.0	38.11	PK	17	1.8	H	7.21	45.32	74	28.68
2491.0	28.63	Ave.	17	1.8	H	7.21	35.84	54	18.16
4943.3	36.46	PK	117	1.4	H	12.46	48.92	74	25.08
4943.3	22.90	Ave.	117	1.4	H	12.46	35.36	54	18.64
7414.9	34.71	PK	43	1.9	H	15.91	50.62	74	23.38
7414.9	21.55	Ave.	43	1.9	H	15.91	37.46	54	16.54
9886.5	34.59	PK	208	2.4	V	19.39	53.98	74	20.02
9886.5	19.40	Ave.	208	2.4	V	19.39	38.79	54	15.21

Note:

1. Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor
2. Corrected Amplitude = Corrected Factor + Receiver Reading
3. Margin = Limit- Corrected Amplitude

FCC §15.247(a) (1)-CHANNEL SEPARATION

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in operating mode, RBW was set at 100 kHz, $VBW \geq 3RBW$ maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.

Test Result: Compliance.


Please refer to following tables and plots



Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	\geq Limit (MHz)
Low	2410.875	3.367	2.426
Adjacent	2414.25		
Middle	2441.25	3.353	2.437
Adjacent	2444.625		
High	2471.625	3.423	2.437
Adjacent	2468.25		

Note: limit =2/3 of 20 dB bandwidth

Low Channel



Middle Channel**High Channel**

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
3. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.


Test Result: Compliance.



Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
Low	2410.875	3.639
Middle	2441.250	3.655
High	2471.625	3.655

Low Channel



Middle Channel**High Channel**

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400 ~ 2483.50	19	≥ 15

Number of Hopping Channels



FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; spectrum span was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= Pulse time (ms) * hope rate/ number of hopping channels * hopping No.*0.4 s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-28.

Test Result: Compliance.


Please refer to following tables and plots



Test Mode: Transmitting

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
Low	0.136	0.0388	0.4	Pass
Middle	0.134	0.0383	0.4	Pass
High	0.136	0.0388	0.4	Pass

Note: Dwell time=Pulse time (ms) \times (714/19) \times 19 \times 0.4 S
Hopping rate = 714 times per second

Low Channel



Middle Channel**High Channel**

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions



Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by August He on 2014-04-28.

Test Result: Compliance.

Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Conducted output power (dBm)	Conducted Output Power (mW)	Limit (mW)
Low	2410.875	9.46	8.83	125
Middle	2441.250	9.98	9.95	125
High	2471.625	10.40	10.96	125

Low Channel**Middle Channel**

High Channel

FCC §15.247(d) - BAND EDGES

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
3. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions



Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by August He on 2014-04-29.

Test Result: Compliance.

Test Mode: Transmitting

Please refer to follow plots:

Band Edge: Left Side**Band Edge: Right Side**

PRODUCT SIMILARITY DECLARATION LETTER

Lorex Technology Inc
250 Royal Crest Court Markham, Ontario L3R 3S1 Canada
Tel: 905 946 8589 Fax: 905 947 0138

2014-04-28

Product Similarity Declaration Letter

To Whom It May Concern,

We, Lorex Technology Inc. hereby declare that our product 2.4G video baby monitor, the model LB2251, LB251, LB2251AC1 and LB2251AC1B are electrically identical, they have the same PCB layout and schematic, the only difference is the model number for the purpose of market.

Model Number	Description
LB2251/LB251	1 camera + 1 monitor
LB2251AC1/LB2251AC1B	1 camera

Model LB2251 was tested by BACL.

Please contact me if you have any question.

Niles Kanapathipillai
Director Quality Assurance

***** END OF REPORT *****