



**DIGITAL EMC CO., LTD.**  
 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080  
 Tel: +82-31-321-2664 Fax: +82-31-321-1664  
<http://www.digitalemc.com>

## CERTIFICATION OF COMPLIANCE

**Dream Technology Co., Ltd.**

2F, Uniqest Bldg., 271-2, Seohyeon-dong, Bundang-gu  
 seongnam-si, Korea

Dates of Tests: August 28 ~ September 05, 2008

Test Report S/N: DR50110809F

Test Site : DIGITAL EMC CO., LTD.

FCC ID

**UD5QL200**

APPLICANT

**Dream Technology Co., Ltd.**

<b>FCC Equipment Class</b>	<b>:</b> Part 15 Spread Spectrum Transmitter(DSS)
<b>Device name</b>	<b>:</b> Bluetooth Mono Headset
<b>Manufacturer</b>	<b>:</b> Dream Technology Co., Ltd.
<b>FCC ID</b>	<b>:</b> UD5QL200
<b>Model name</b>	<b>:</b> QL200
<b>Test Device Serial number</b>	<b>:</b> Identical prototype
<b>FCC Rule Part(s)</b>	<b>:</b> FCC Part 15.247 Subpart C ANSI C63.4-2003
<b>Frequency Range</b>	<b>:</b> 2402 ~ 2480 MHz
<b>Max. Output power</b>	<b>:</b> 3.09 dBm Conducted
<b>Data of issue</b>	<b>:</b> September 09, 2008

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



NVLAP LAB CODE 200559-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION -----	3
2. INFORMATION ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 TRANSMITTER REQUIREMENTS -----	6
3.2.1 CARRIER FREQUENCY SEPARATION -----	6
3.2.2 NUMBER OF HOPPING FREQUENCIES -----	8
3.2.3 20 dB BANDWIDTH -----	11
3.2.4 TIME OF OCCUPANCY (Dwell Time) -----	14
3.2.5 PEAK OUTPUT POWER -----	17
3.2.6 CONDUCTED SPURIOUS EMISSIONS -----	20
3.2.7 RADIATED EMISSIONS -----	29
3.2.8 AC LINE CONDUCTED EMISSIONS -----	35
APPENDIX TEST EQUIPMENT FOR TESTS -----	38

## 1. General information

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

<http://www.digitalemc.com> E-mail : [Harveysung@digitalemc.com](mailto:Harveysung@digitalemc.com)

Tel: +82-31-321-2664 Fax: +82-31-321-1664

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the

“General requirements for the competent of calibration and testing laboratory”.

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200559-0.

**Test operator: engineer**



September 09, 2008

D.C.Cha

Data

Name

Signature

**Report Reviewed By: manager**



September 09, 2008

Harvey Sung

Data

Name

Signature

**Ordering party:**

Company name	:	Dream Technology Co., Ltd.
Address	:	2F, Uniqest Bldg., 271-2, Seohyeon-dong, Bundang-gu
City/town	:	Seongnam-si
Country	:	Korea
Date of order	:	August 18, 2008

## 2. Information about test item

UD5QL200

### 2.1 Equipment information

Equipment model no.	QL200
Equipment serial no.	Identical prototype
Type of equipment	Bluetooth Mono Headset
Frequency band	2402 ~ 2480 MHz
Type of Modulation	GFSK
Spread Spectrum	Frequency Hopping
Channel Spacing	1.0 MHz
Type of antenna	Chip Antenna

- This device does not have EDR function.

### 2.2 Tested frequency

Frequency	TX	RX
Low frequency	2402MHz	2402MHz
Middle frequency	2441MHz	2441MHz
High frequency	2480MHz	2480MHz

### 2.3 Tested environment

Temperature	: 15 ~ 35 (°C)
Relative humidity content	: 20 ~ 75 %
Air pressure	: 86 ~ 103 kPa
Details of power supply	: 3.7 V DC

### 2.4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Adapter	DT C-100	N/A	ShenZhen Bayang Industry Co., Ltd

### 2.5 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing

-> None

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit (Using in 2400 ~ 2483.5MHz)	Test Condition	Status (note 1)	
<b>I. Test Items</b>					
15.247(a)	Carrier Frequency Separation	>= 20dB BW or >= Two-Thirds of the 20dB BW	Conducted	C	
	Number of Hopping Frequencies	>= 15 hops		C	
	20 dB Bandwidth	None		C	
	Dwell Time	=< 0.4 seconds		C	
15.247(b)	Transmitter Output Power	=< 1Watt , if CHs >= 75 Others =<0.125W	Conducted	C	
15.247(c)	Band-edge /Conducted	The radiated emission to any 100 kHz of outband shall be at least 20dB below the highest inband spectral density.		C	
	Conducted Spurious Emissions			C	
15.205 15.209	Radiated Emissions	FCC 15.209 Limits	Radiated	C	
15.207	AC Conducted Emissions	EN 55022	AC Line Conducted	C	
Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable					

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003, DA00-705

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz Sweep = auto

VBW = 30 kHz Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency of marker #1 (MHz)	Frequency of marker #2 (MHz)	Test Results	
		Carrier Frequency Separation (MHz)	Result
2441.012	2442.014	1.002	Comply

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

## Carrier Frequency Separation



### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Frequency range 1: Start = 2389.5MHz, Stop = 2414.5 MHz

2: Start = 2414.5MHz, Stop = 2439.5 MHz

3: Start = 2439.5MHz, Stop = 2464.5 MHz

4: Start = 2464.5MHz, Stop = 2489.5 MHz

RBW = 300 kHz (1% of the span or more) Sweep = auto

VBW = 300 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold Span = 25MHz

#### Measurement Data: Comply

<b>Total number of Hopping Channels</b>	79
---	----

- See next pages for actual measured spectrum plots.



#### Minimum Standard:

At least 15 hopes
-------------------



#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## Number of Hopping Frequencies



## Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 10 kHz (1% of the 20dB bandwidth or more) Sweep = auto

VBW = 10 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (MHz)	Result
2402	1	0.940	Comply
2441	40	0.945	Comply
2480	79	0.935	Comply

- See next pages for actual measured spectrum plots.



#### Minimum Standard:

None
------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## 20 dB Bandwidth



## 20 dB Bandwidth



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

**Measurement Data:** See next pages for actual measured spectrum plots.

Packet Type	Burst On Time (ms)	Period (ms)	Number of hopping Channels	DWELL TIME (s)	Result
DH 1	0.399	1.251	79	0.128	Comply
DH 3	1.652	2.499	79	0.264	Comply
DH 5	2.900	3.750	79	0.309	Comply



Note : Each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event. DWELL TIME=(0.4 x Number of hopping Channels) x Burst On time / (period x Number of hopping Channels)


#### Minimum Standard:

No greater than 0.4 seconds

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Time of Occupancy for Packet Type DH 1Time of Occupancy for Packet Type DH 3

Time of Occupancy for Packet Type DH 5

### 3.2.5 Peak Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Sweep = auto

#### Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	1	<b>3.09</b>	<b>2.037</b>	<b>Comply</b>
2441	40	<b>2.82</b>	<b>1.914</b>	<b>Comply</b>
2480	79	<b>3.03</b>	<b>2.009</b>	<b>Comply</b>



- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: <b>1 Watt</b> . For all other frequency hopping systems in the 2400-2483.5 MHz band: <b>0.125 Watts</b>
--------------------------	--


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## Peak Output Power



## Peak Output Power



### 3.2.6 Conducted Spurious Emissions

## Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Detector function = peak

### Measurement Data: **Comply**


See next pages for actual measured spectrum plots

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------


## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



## Low band with hopping disabled




## Low band with hopping enabled




## Low channel spurious





## Low channel spurious




## Mid channel ref




## Mid channel spurious




## Mid channel spurious





## High band with hopping disabled



## High band with hopping enabled



## High channel spurious



### 3.2.7 Radiated Emissions

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 120 kHz ( 30MHz ~ 1 GHz)

VBW ≥ RBW (Peak)

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

VBW = 10Hz (Average)

Trace = max hold

Sweep = auto

#### Measurement Data: **Comply**

- Refer to the next page.

**Note. : Marker 1's emissions of the low band edge test plots are emissions from WIMAX downlink signal in Korea. So it's not an emission from this device.**


#### Minimum Standard: FCC Part 15.205 (a), 15.205(b), 15.209(a) and (b)

#### Limit : FCC P15.209(a)


Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.


## Restricted Band Edge: Low Channel (Peak, Horizontal)




## Restricted Band Edge: Low Channel (Average, Horizontal)




## Restricted Band Edge: Low Channel (Peak, Vertical)




## Restricted Band Edge: Low Channel (Average, Vertical)




## Restricted Band Edge: High Channel (Peak, Horizontal)




## Restricted Band Edge: High Channel (Average, Horizontal)



## Restricted Band Edge: High Channel (Peak, Vertical)



## Restricted Band Edge: High Channel (Average, Vertical)



## Harmonic and other emissions Measurement Data: Fundamental Frequency = 2402MHz

Frequency (MHz)	ANT Pol	Reading(dBuV)			T.F (dB)	Result(dBuV/m)			Limit(dBuV/m)			Margin(dB)		
		QP	PK	AV		QP	PK	AV	QP	PK	AV	QP	PK	AV
4804	Hor	-	51.11	42.10	7.19	-	58.30	49.29	-	74.00	54.00	-	15.70	4.71
4804	Ver	-	52.71	44.27	7.19	-	59.90	51.46	-	74.00	54.00	-	14.10	2.54
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

## Harmonic and other emissions Measurement Data: Fundamental Frequency = 2441MHz

Frequency (MHz)	ANT Pol	Reading(dBuV)			T.F (dB)	Result(dBuV/m)			Limit(dBuV/m)			Margin(dB)		
		QP	PK	AV		QP	PK	AV	QP	PK	AV	QP	PK	AV
4882	Hor	-	50.56	39.49	7.48	-	58.04	46.97	-	74.00	54.00	-	15.96	7.03
4882	Ver	-	52.75	42.63	7.48	-	60.23	50.11	-	74.00	54.00	-	13.77	3.89
-	-	-	-	-	-					-	-	-	-	-

## Harmonic and other emissions Measurement Data: Fundamental Frequency = 2480MHz

Frequency (MHz)	ANT Pol	Reading(dBuV)			T.F (dB)	Result(dBuV/m)			Limit(dBuV/m)			Margin(dB)		
		QP	PK	AV		QP	PK	AV	QP	PK	AV	QP	PK	AV
4960	Hor	-	50.42	38.93	7.89	-	58.31	46.82	-	74.00	54.00	-	15.69	7.18
4960	Ver	-	52.43	42.01	7.89	-	60.32	49.90	-	74.00	54.00	-	13.68	4.10
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

**Note.**

1. No other spurious and harmonic emissions were detected at a level greater than 20dB below limit.
2. If peak result meet AV limit, AV measurement is omitted.
3. Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

### 3.2.8 AC Line Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak and average detector mode with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

**Measurement Data:** **Comply** (See next pages for actual measured spectrum plots.)

**Note : When this device is in the charging mode, the Bluetooth function is disabled.**

**So the conducted emission test was performed in charging mode without transmitting.**

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

#### Measurement Setup






Figure 2: Measurement setup for AC Conducted Emission

### - Conducted Emission Graph -



**-Conducted Emission List -**

\*\*\*\*\* DIGITAL EMC \*\*\*\*\*  
 <<CONDUCTED EMISSION>>

28 August, 2008 08:56

Standard : Part 15  
 Manufacturer : dreamtech  
 Model : QL200  
 Operator : D. C. Cha  
 AC Power : 120V 60Hz  
 Temp, Humidity : 23'C 52%  
 Remark1 : IDLE  
 Remark2 :  
 Remark3 :  
 :

## Final Result

## --- N Phase ---

No.	Frequency	Reading		c.f.	Result		Result		Limit		Margin		Remark
		QP	AV		QP	[dB(µV)]	AV	QP	[dB(µV)]	AV	QP	[dB]	
1	0.153	24.6	14.9	0.1	24.7	15.0	65.8	55.8	41.1	40.8			
2	0.204	28.8	20.5	0.1	28.9	20.6	63.4	53.4	34.5	32.8			
3	0.238	34.7	25.5	0.1	34.8	25.6	62.2	52.2	27.4	26.6			
4	0.323	19.2	0.0	0.1	19.3	0.0	59.6	49.6	40.3	0.0			
5	0.423	37.4	21.8	0.1	37.5	21.9	57.4	47.4	19.9	25.5			
6	0.484	36.6	22.8	0.1	36.7	22.4	56.3	46.3	19.6	23.9			
7	2.065	29.1	14.4	0.3	29.4	14.7	56.0	46.0	26.6	31.3			

## --- L1 Phase ---

No.	Frequency	Reading		c.f.	Result		Result		Limit		Margin		Remark
		QP	AV		QP	[dB(µV)]	AV	QP	[dB(µV)]	AV	QP	[dB]	
1	0.434	40.4	23.4	0.2	40.6	23.6	57.2	47.2	16.6	23.6			
2	0.178	35.7	23.0	0.2	35.9	23.2	64.6	54.6	23.7	31.4			
3	0.235	35.7	24.4	0.2	35.9	24.6	62.3	52.3	26.4	27.7			
4	0.296	34.2	22.6	0.2	34.4	22.8	60.4	50.4	26.0	27.6			
5	0.363	32.3	20.6	0.2	32.5	20.8	58.7	48.7	26.2	27.9			
6	2.154	29.0	17.0	0.4	29.4	17.4	56.0	46.0	26.6	28.6			
7	1.430	32.2	17.7	0.2	32.5	18.0	56.0	46.0	23.5	28.0			
8	0.604	30.0	16.0	0.3	30.3	16.3	56.0	46.0	26.7	29.7			

## **APPENDIX**

### **TEST EQUIPMENT FOR TESTS**

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment.

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	Next.Due.Date (dd/mm/yy)	S/N
01	Spectrum Analyzer	Agilent	E4404B	21/03/08	21/03/09	US41061134
02	Spectrum Analyzer	Agilent	E4440A	15/11/07	15/11/08	MY45304199
03	Spectrum Analyzer	H.P	8563E	09/10/07	09/10/09	3551A04634
04	Spectrum Analyzer	H.P	8591E	26/04/08	26/04/09	3649A05889
05	EMI TEST RECEIVER	R&S	ESU	11/01/08	11/01/09	100014
06	EMI TEST RECEIVER	R&S	ESCI	13/05/08	13/05/09	100364
07	Power Meter	H.P	EMP-442A	10/07/08	10/07/09	GB37170413
08	Power Sensor	H.P	8481A	14/07/08	14/07/09	3318A96566
09	Power Divider	Agilent	11636B	07/12/07	07/12/08	56471
10	Signal Generator	Rohde Schwarz	SMR20	02/04/08	02/04/09	101251
11	Signal Generator	H.P	ESG-3000A	09/07/08	09/07/09	US37230529
12	Vector Signal Generator	Rohde Schwarz	SMJ100A	17/01/08	17/01/09	100148
13	Audio Analyzer	H.P	8903B	09/07/08	09/07/09	3011A09448
14	Modulation Analyzer	H.P	8901B	1807/08	18/07/09	3028A03029
15	Oscilloscope	Tektronix	TDS3052	02/11/07	02/11/08	B016821
16	8960 Series 10 Wireless Comms. Test Set	Agilent	E5515C	31/07/07	31/07/09	GB43461134
17	Universal Radio communication Tester	Rohde Schwarz	CMU 200	02/04/08	02/04/09	107631
18	Bluetooth Tester	TESCOM	TC-3000A	01/08/08	01/08/09	3000A4A0121
19	Power Splitter	WEINSCHEL	1593	05/10/07	05/10/08	332
20	Power Splitter	Anritsu	K241B	19/10/07	19/10/08	020611
21	BAND Reject Filter	Microwave Circuits	N0308372	18/10/07	18/10/08	3125-01DC0312
22	BAND Reject Filter	Wainwright	WRCG1750	18/10/07	18/10/08	SN2
23	AC Power supply	DAEKWANG	5KVA	20/03/08	20/03/09	N/A
24	DC Power Supply	H.P	6622A	20/03/08	20/03/09	465487
25	DC Power Supply	HP	6633A	20/03/08	20/03/09	3524A06634
26	HORN ANT	ETS	3115	13/06/08	13/06/09	6419
27	HORN ANT	ETS	3115	09/10/07	09/10/08	21097
28	HORN ANT	A.H.Systems	SAS-574	13/06/08	13/06/09	154
29	HORN ANT	A.H.Systems	SAS-574	13/06/08	13/06/09	155
30	Dipole Antenna	Schwarzbeck	VHA9103	19/12/07	19/12/08	2116

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	Next.Due.Date (dd/mm/yy)	S/N
31	Dipole Antenna	Schwarzbeck	VHA9103	19/12/07	19/12/08	2117
32	Dipole Antenna	Schwarzbeck	UHA9105	20/12/07	20/12/08	2261
33	Dipole Antenna	Schwarzbeck	UHA9105	20/12/07	20/12/08	2262
34	TEMP & HUMIDITY Chamber	JISCO	J-RHC2	02/10/07	02/10/08	021031
35	Log Periodic Antenna	Schwarzbeck	UHALP9108A1	01/10/07	01/10/08	1098
36	Biconical Antenna	Schwarzbeck	VHA9103	01/10/07	01/10/08	2233
37	Digital Multimeter	H.P	34401A	20/03/08	20/03/09	3146A13475
38	Attenuator (10dB)	WEINSCHEL	23-10-34	05/10/07	05/10/08	BP4386
39	Attenuator (10dB)	WEINSCHEL	23-10-34	30/01/08	30/01/09	BP4387
40	High-Pass Filter	ANRITSU	MP526D	08/10/07	08/10/08	MP27756
41	Attenuator (3dB)	Agilent	8491B	01/08/08	01/08/09	MY39260700
42	20dB Attenuator	Aeroflex/Weinschel	86-20-11	25/10/07	25/10/08	432
43	10dB Attenuator	Aeroflex/Weinschel	86-10-11	25/10/07	25/10/08	446
44	10dB Attenuator	Aeroflex/Weinschel	86-10-11	25/10/07	25/10/08	408
45	Type N Coaxial CIRCULATOR	NOVA MICROWAVE	0088CAN	11/07/08	11/07/09	788
46	Type N Coaxial CIRCULATOR	NOVA MICROWAVE	0185CAN	11/07/08	11/07/09	790
47	Type N Coaxial CIRCULATOR	NOVA MICROWAVE	0215CAN	11/07/08	11/07/09	112
48	Amplifier (25dB)	Agilent	8447D	21/05/08	21/05/09	2944A10144
49	Amplifier (30dB)	Agilent	8449B	25/10/07	25/10/08	3008A01590
50	Amplifier (22dB)	H.P	8447E	27/02/08	27/02/09	2945A02865
51	Attenuator (20dB)	Aeroflex/Weinschel	86-20-11	25/10/07	25/10/08	432
52	Attenuator (10dB)	Aeroflex/Weinschel	86-10-11	25/10/07	25/10/08	446
53	Attenuator (10dB)	Aeroflex/Weinschel	86-10-11	25/10/07	25/10/08	408
54	Position Controller	TOKIN	5901T	N/A	N/A	14173
55	Driver	TOKIN	5902T2	N/A	N/A	14174
56	LISN	Kyorits	KNW-407	04/08/08	04/08/09	8-317-8
57	LISN	Kyorits	KNW-242	06/10/07	06/10/08	8-654-15
58	CVCF	NF Electronic	4400	N/A	N/A	344536 4420064
59	Software	ToYo EMI	EP5/RE	N/A	N/A	Ver 2.0.800
60	Software	ToYo EMI	EP5/CE	N/A	N/A	Ver 2.0.801
61	Software	AUDIX	e3	N/A	N/A	Ver 3.0
62	Software	Agilent	Benchlink	N/A	N/A	A.01.09 021211